ISO/IEC 23001-11:2019 (E)

Information technology — MPEG systems technologies — Part 11: Energy-efficient media consumption (green metadata)

Contents

Foreword

Introduction

1 Scope

2 Normative references

3 Terms, definitions, symbols, abbreviated terms and conventions

3.1 Terms and definitions
3.2 Symbols and abbreviated terms
3.3 Conventions
3.3.1 Arithmetic operators
3.3.2 Mathematical functions

4 Functional architecture

4.1 Description of the functional architecture
4.2 Definition of components in the functional architecture

5 Decoder power reduction

5.1 General
5.2 Complexity metrics for decoder-power reduction
5.2.1 General
5.2.2 Syntax
5.2.3 Signalling
5.2.4 Semantics
5.2.4.1 AVC semantics
5.2.4.2 HEVC semantics
5.3 Interactive signalling for remote decoder-power reduction
5.3.1 General
5.3.2 Syntax
5.3.3 Signalling
5.3.4 Semantics

6 Display power reduction using display adaptation

6.1 General
6.2 Syntax
6.2.1 Systems without a signalling mechanism from the receiver to the transmitter
6.2.2 Systems with a signalling mechanism from the receiver to the transmitter
6.3 Signalling
6.3.1 General
6.3.2 Systems without a signalling mechanism from the receiver to the transmitter
6.3.3 Systems with a signalling mechanism from the receiver to the transmitter
6.4 Semantics

7 Energy-efficient media selection

7.1 General
7.2 Syntax
7.3 Signalling
7.4 Semantics
7.4.1 Decoder-power indication metadata semantics
7.4.2 Display-power indication metadata semantics

8 Metrics for quality recovery after low-power encoding

8.1 General
8.2 Syntax
8.3 Signalling
8.4 Semantics

9 Conformance and reference software

Annex A (normative) Supplemental enhancement information (SEI) syntax

A.1 Syntax and semantics of green metadata SEI message carried in AVC NAL units
A.1.1 General
A.1.2 Syntax
A.1.3 Semantics
A.2 Syntax and semantics of green metadata SEI message carried in HEVC NAL units
A.2.1 General
A.2.2 Syntax
A.2.3 Semantics

Annex B (informative) Implementation guidelines for the usage of green metadata

B.1 Codec dynamic voltage frequency scaling for decoder-power reduction
B.1.1 General
B.1.2 Derivation of the complexity metrics
B.1.2.1 Deriving the worst-case, largest value for MaxNumSixTapFilteringsPic(i)
B.1.2.2 Deriving the worst-case, largest value for MaxNumAlphaPointDeblockingInstancesPic(i)

B.1.3 Example usage of C-DVFS metadata
B.2 Display adaptation
B.2.1 General
B.2.2 Example usage of display-adaptation metadata
B.2.2.1 General
B.2.2.2 Example usage of display-adaptation metadata for contrast enhancement
B.2.2.3 Preventing flicker arising from control latency
B.2.2.4 Metadata for DA on displays with control-frequency limitations
B.2.2.5 DA metadata to prevent flicker from large variations
B.3 Energy-efficient media selection in adaptive streaming
B.3.1 General
B.3.2 Green metadata production and transmission at the server side
B.3.3 Use of green metadata at the client
B.4 Interactive signalling for remote decoder-power reduction
B.4.1 General
B.4.2 Decoding operations reduction request computation and transmission
B.4.3 Use of decoding operations reduction request
B.5 Cross-segment decoding for quality recovery after low-power encoding
B.5.1 General
B.5.2 Green metadata usage

Annex C (normative) Conformance and reference software

C.1 Complexity metrics for decoder-power reduction
C.1.1 Conformance test vectors
C.1.2 Reference software
C.2 Display-power reduction using display adaptation
C.2.1 Conformance test vectors
C.2.2 Reference software
C.3 Energy-efficient media selection
C.3.1 Conformance test vectors
C.3.2 Reference software
C.4 Metrics for quality recovery after low-power encoding
C.4.1 Conformance test vectors
C.4.2 Reference software

Page count: 66