

ISO/IEC 24770-5:2019 (E)

Information technology — Real-time locating system (RTLS) device performance test methods — Part 5: Test methods for chirp spread spectrum (CSS) air interface

Contents

| | |
|---------|--|
| | Foreword |
| | Introduction |
| 1 | Scope |
| 2 | Normative references |
| 3 | Terms, definitions, and abbreviated terms |
| 3.1 | Terms and definitions |
| 3.2 | Abbreviated terms |
| 4 | General |
| 4.1 | Performance requirements |
| 4.1.1 | Overview |
| 4.1.2 | Location accuracy |
| 4.1.3 | Tag capacity |
| 4.1.4 | Location latency |
| 4.1.5 | Tag orientation |
| 4.1.6 | System range and packet error rates |
| 4.2 | Default conditions applicable to the test methods |
| 4.2.1 | Overview |
| 4.2.2 | Test environment |
| 4.2.3 | Default tolerance |
| 4.2.4 | System logging |
| 5 | Performance tests for ISO/IEC 24730-5 |
| 5.1 | System locate performance |
| 5.1.1 | Test overview |
| 5.1.2 | Test objective |
| 5.1.3 | Test setup |
| 5.1.4 | Test procedure |
| 5.1.5 | Test measurements and requirements |
| 5.1.5.1 | Location accuracy |
| 5.1.5.2 | Location reporting latency |
| 5.1.5.3 | Tag capacity |
| 5.1.5.4 | Tag orientation |
| 5.1.6 | Test report |
| 5.2 | Tests for CSS tag to reader air interface using default blink mode |
| 5.2.1 | Test objective |
| 5.2.2 | Test setup |
| 5.2.3 | Test procedure |
| 5.2.4 | Test measurements and requirements |
| 5.2.4.1 | Packet error rate |
| 5.2.4.2 | Tag range |
| 5.2.4.3 | Tag orientation |
| 5.2.5 | Test report |
| 5.3 | Tests for CSS tag to reader air interface using two-way-ranging |
| 5.3.1 | Overview |
| 5.3.2 | Test objective |
| 5.3.3 | Test setup |
| 5.3.4 | Test procedure |

- 5.3.5 Test measurements and requirements**
- 5.3.5.1 Ranging success rate**
- 5.3.5.2 Ranging range**
- 5.3.5.3 Ranging accuracy**
- 5.3.5.4 Orientation**

Page count: 9