ISO/IEC/IEEE 8802-1Q:2020-08 (E)

Telecommunications and exchange between information technology systems - Requirements for local and metropolitan area networks - Part 1Q: Bridges and bridged networks

Contents

1. Overview 61

1.1 Scope 61
1.2 Purpose 61
1.3 Introduction 62

2. Normative references 69

3. Definitions 73

4. Abbreviations 95

5. Conformance 101

5.1 Requirements terminology 101
5.2 Conformant components and equipment 101
5.3 Protocol Implementation Conformance Statement (PICS) 102
5.4 VLAN Bridge component requirements 102
5.4.1 VLAN Bridge component options 103
5.4.2 Multiple VLAN Registration Protocol (MVRP) requirements 108
5.4.3 VLAN Bridge requirements for congestion notification 108
5.4.4 Multiple Stream Registration Protocol (MSRP) requirements 109
5.4.5 Shortest Path Bridging (SPB) operation (optional) 109
5.4.6 Path Control and Reservation (PCR) (optional) 110
5.5 C-VLAN component conformance 111
5.5.1 C-VLAN component options 111
5.6 S-VLAN component conformance 111
5.6.1 S-VLAN component options 112
5.6.2 S-VLAN component requirements for Provider Backbone Bridge Traffic Engineering (PBB-TE) 112
5.6.3 S-VLAN component requirements for PBB-TE IPS 112
5.6.4 S-VLAN component requirements for ECMP with flow filtering 113
5.7 I-component conformance 113
5.7.1 I-component options 113
5.8 B-component conformance 113
5.8.1 B-component options 114
5.8.2 B-component requirements for PBB-TE 114
5.8.3 B-component requirements for PBB-TE IPS 114
5.8.4 B-component requirements for ECMP with flow filtering 115
5.9 C-VLAN Bridge conformance 115
5.9.1 C-VLAN Bridge options 115
5.10 Provider Bridge conformance 115
5.10.1 S-VLAN Bridge conformance 115
5.10.2 Provider Edge Bridge conformance 116
5.11 System requirements for Priority-based Flow Control (PFC) 116
5.12 Backbone Edge Bridge (BEB) conformance 116
5.12.1 BEB requirements for PBB-TE 117
5.13 MAC Bridge component requirements 117
5.13.1 MAC Bridge component options 117
5.14 MAC Bridge conformance 118
5.14.1 MAC Bridge options 118
5.15 TPMR component conformance 118

5.15.1 TPMR component options ... 119
5.16 TPMR conformance ... 119
5.16.1 TPMR options ... 119
5.17 T-component conformance ... 119
5.17.1 T-component options ... 120
5.18 End station requirements for MMRP, MVRP, and MSRP ... 120
5.18.1 MMRP requirements and options ... 120
5.18.2 MVRP requirements and options ... 121
5.18.3 MSRP requirements and options ... 121
5.19 VLAN-aware end station requirements for CFM ... 122
5.20 End station requirements—FQTSS ... 122
5.21 End station requirements for congestion notification ... 123
5.22 MAC-specific bridging methods ... 123
5.23 EVB Bridge requirements ... 123
5.24 EVB station requirements ... 124
5.24.1 Edge relay (ER) requirements ... 125
5.25 End station requirements—enhancements for scheduled traffic ... 126
5.26 End station requirements—enhancements for frame preemption ... 126
5.27 End-station requirements—PSFP ... 127
5.28 End station requirements—Cyclic queuing and forwarding ... 127

6. Support of the MAC Service ... 128

6.1 Basic architectural concepts and terms ... 129
6.2 Provision of the MAC Service ... 129
6.2.1 Point-to-point, multipoint-to-multipoint, and rooted-multipoint connectivity ... 130
6.3 Support of the MAC Service ... 130
6.4 Preservation of the MAC Service ... 131
6.5 Quality of service (QoS) maintenance ... 131
6.5.1 Service availability ... 131
6.5.2 Frame loss ... 132
6.5.3 Frame misordering ... 132
6.5.4 Frame duplication ... 133
6.5.5 Transit delay ... 134
6.5.6 Frame lifetime ... 135
6.5.7 Undetected frame error rate ... 135
6.5.8 Maximum Service Data Unit Size ... 135
6.5.9 Priority ... 135
6.5.10 Throughput ... 136
6.6 Internal Sublayer Service (ISS) ... 137
6.7 Support of the ISS by specific MAC procedures ... 137
6.7.1 Support of the ISS by IEEE Std 802.3 (Ethernet) ... 137
6.7.2 Frame preemption ... 137
6.8 Enhanced Internal Sublayer Service (EISS) ... 138
6.8.1 Service primitives ... 138
6.8.2 Status parameters ... 139
6.8.3 Point-to-point parameters ... 139
6.8.4 Control primitives and parameters ... 139
6.9 Support of the EISS ... 140
6.9.1 Data indications ... 141
6.9.2 Data requests ... 142
6.9.3 Priority Code Point encoding ... 142
6.9.4 Regenerating priority ... 144
6.10 Support of the ISS/EISS by PIPs ... 145

6.10.1 Data indications 147
6.10.2 Data requests 148
6.10.3 Priority Code Point encoding 148
6.11 Support of the EISS by CBPs 149
6.11.1 Data indications 150
6.11.2 Data requests 151
6.11.3 Priority Code Point decoding 152
6.11.4 Regenerating priority 152
6.12 Protocol VLAN classification 152
6.12.1 Protocol Templates 154
6.12.2 Protocol Group Identifiers 154
6.12.3 Protocol Group Database 154
6.13 Support of the ISS for attachment to a PBN 155
6.13.1 Data requests 156
6.13.2 Data indications 157
6.14 Support of the ISS within a system 157
6.15 Support of the ISS by additional technologies 157
6.16 Filtering services in Bridged Networks 158
6.16.1 Purpose(s) of filtering service provision 158
6.16.2 Goals of filtering service provision 158
6.16.3 Users of filtering services 159
6.16.4 Basis of service 159
6.16.5 Categories of service 159
6.16.6 Service configuration 159
6.16.7 Service definition for Extended Filtering Services 160
6.17 EISS Multiplex Entity 161
6.18 Backbone Service Instance Multiplex Entity 162
6.18.1 Demultiplexing direction 163
6.18.2 Multiplexing direction 164
6.18.3 Priority Code Point encoding 165
6.18.4 Status parameters 165
6.19 TESI Multiplex Entity 165
6.20 Support of the ISS with signaled priority 166
6.20.1 Data indications 167
6.20.2 Data requests 167
6.21 Infrastructure Segment Multiplex Entity 167
6.22 PDU and protocol discrimination and media 169

7. Principles of Virtual Bridged Network operation 170

7.1 Network overview 170
7.2 Use of VLANs 171
7.3 Active topology 171
7.4 VLAN topology 172
7.5 Locating end stations 173
7.6 Ingress, forwarding, and egress rules 174

8. Principles of Bridge operation 175

8.1 Bridge operation 175
8.1.1 Relay 175
8.1.2 Filtering and relaying information 176
8.1.3 Duplicate frame prevention 176
8.1.4 Traffic segregation 176
8.1.5 Traffic reduction 177

8.1.6 Traffic expediting 177
8.1.7 Conversion of frame formats 177
8.2 Bridge architecture 178
8.3 Model of operation 180
8.4 Active topologies, learning, and forwarding 184
8.5 Bridge Port Transmit and Receive 185
8.5.1 Bridge Port connectivity 185
8.5.2 TPMR Port connectivity 186
8.5.3 Support of Higher Layer Entities 187
8.6 The Forwarding Process 187
8.6.1 Active topology enforcement 188
8.6.2 Ingress filtering 190
8.6.3 Frame filtering 190
8.6.4 Egress filtering 193
8.6.5 Flow classification and metering 193
8.6.6 Queuing frames 197
8.6.7 Queue management 199
8.6.8 Transmission selection 199
8.6.9 Scheduled traffic state machines 205
8.6.10 Stream gate control state machines 213
8.7 The Learning Process 215
8.7.1 Default filtering utility criteria 215
8.7.2 Enhanced filtering utility criteria 216
8.7.3 Ageing of Dynamic Filtering Entries 216
8.8 The Filtering Database (FDB) 217
8.8.1 Static Filtering Entries 220
8.8.2 Static VLAN Registration Entries 221
8.8.3 Dynamic Filtering Entries 221
8.8.4 MAC Address Registration Entries 222
8.8.5 Dynamic VLAN Registration Entries 223
8.8.6 Default Group filtering behavior 223
8.8.7 Dynamic Reservation Entries 224
8.8.8 Allocation of VIDs to FIDs 225
8.8.9 Querying the FDB 225
8.8.10 Determination of the member set for a VID 229
8.8.11 Permanent Database 230
8.8.12 Connection_Identifier 230
8.9 MST, SPB, and ESP configuration information 230
8.9.1 MST Configuration Table 231
8.9.2 MST configuration identification 231
8.9.3 FID to MSTI Allocation Table 232
8.9.4 SPT Configuration Identification 232
8.10 Spanning Tree Protocol Entity 233
8.11 MRP entities 233
8.12 Bridge Management Entity 233
8.13 Addressing 233
8.13.1 End stations 233
8.13.2 Bridge Ports 234
8.13.3 Use of LLC by Spanning Tree Protocol Entities 234
8.13.4 Reserved MAC addresses 234
8.13.5 Group MAC addresses for spanning tree entity 235
8.13.6 Group MAC addresses for MRP Applications 237
8.13.7 Bridge Management Entities 237
8.13.8 Unique identification of a Bridge 237

8.13.9 Points of attachment and connectivity for Higher Layer Entities 238
8.13.10 VLAN attachment and connectivity for Higher Layer Entities 241
8.13.11 CFM entities 242

9. Tagged frame format 244

9.1 Purpose of tagging 244
9.2 Representation and encoding of tag fields 244
9.3 Tag format 245
9.4 TPID formats 245
9.5 Tag Protocol identification 245
9.6 VLAN Tag Control Information (TCI) 246
9.7 Backbone Service Instance Tag Control Information (I-TAG TCI) 247

10. Multiple Registration Protocol (MRP) and Multiple MAC Registration Protocol (MMRP) 249

10.1 MRP overview 249
10.2 MRP architecture 252
10.3 MRP Attribute Propagation (MAP) 253
10.3.1 MAP Context 254
10.4 Requirements to be met by MRP 255
10.5 Requirements for interoperability between MRP Participants 256
10.6 Protocol operation 257
10.7 Protocol specification 261
10.7.1 Notational conventions and abbreviations 262
10.7.2 Registrar Administrative Controls 264
10.7.3 Applicant Administrative Controls 264
10.7.4 Protocol timers 264
10.7.5 Protocol event definitions 265
10.7.6 Protocol Action definitions 268
10.7.7 Applicant state machine 270
10.7.8 Registrar state machine 271
10.7.9 LeaveAll state machine 271
10.7.10 PeriodicTransmission state machine 272
10.7.11 Timer values 272
10.7.12 Operational reporting and statistics 273
10.7.13 Interoperability considerations 273
10.8 Structure and encoding of Multiple Registration Protocol Data Units (MRPDUs) 274
10.8.1 Structure 274
10.8.2 Encoding of MRPDU parameters 276
10.8.3 Packing and parsing MRPDUs 279
10.9 Multiple MAC Registration Protocol (MMRP)—Purpose 281
10.10 Model of operation 282
10.10.1 Propagation of Group Membership information 283
10.10.2 Propagation of Group service requirement information 284
10.10.3 Source pruning 284
10.10.4 Use of Group service requirement registration by end stations 284
10.11 Default Group filtering behavior and MMRP propagation 284
10.12 Definition of the MMRP application 286
10.12.1 Definition of MRP elements 286
10.12.2 Provision and support of Extended Filtering Services 288
10.12.3 Use of “new” declaration capability 290
10.12.4 Attribute value support requirements 290
10.12.5 Registrar Administrative Controls 290

11. VLAN topology management 291

11.1 Static and dynamic VLAN configuration 291
11.2 Multiple VLAN Registration Protocol (MVRP) 292
11.2.1 MVRP overview 292
11.2.2 VLAN registration service definition 294
11.2.3 Definition of the MVRP application 295
11.2.4 VID translation table 298
11.2.5 Use of “new” declaration capability 298
11.2.6 New-Only Participant and Registrar Administrative Controls 298
11.2.7 Attribute value support requirements 298

12. Bridge management 299

12.1 Management functions 299
12.1.1 Configuration Management 299
12.1.2 Fault Management 300
12.1.3 Performance Management 300
12.1.4 Security Management 300
12.1.5 Accounting Management 300
12.2 VLAN Bridge objects 300
12.3 Data types 301
12.4 Bridge Management Entity 302
12.4.1 Bridge Configuration 302
12.4.2 Port configuration 305
12.5 MAC entities 307
12.5.1 ISS Port Number table managed object (optional) 307
12.6 Forwarding process 307
12.6.1 The Port Counters 307
12.6.2 Priority handling 308
12.6.3 Traffic Class Table 316
12.7 Filtering Database (FDB) 317
12.7.1 The Filtering Database object 317
12.7.2 A Static Filtering Entry object 318
12.7.3 A Dynamic Filtering Entry object 318
12.7.4 A MAC Address Registration Entry object 318
12.7.5 A VLAN Registration Entry object 319
12.7.6 Permanent Database object 319
12.7.7 General FDB operations 320
12.8 Bridge Protocol Entity 321
12.8.1 The Protocol Entity 322
12.8.2 Bridge Port 325
12.9 MRP Entities 329
12.9.1 The MRP Timer object 329
12.9.2 The MRP Attribute Type object 330
12.9.3 Periodic state machine objects 331
12.10 Bridge VLAN managed objects 331
12.10.1 Bridge VLAN Configuration managed object 332
12.10.2 VLAN Configuration managed object 337
12.10.3 The VID to FID allocation managed object 338
12.11 MMRP entities 341
12.11.1 MMRP Configuration managed object 341
12.12 MST configuration entities 342
12.12.1 The MSTI List 342
12.12.2 The FID to MSTID Allocation Table 344

12.12.3 The MST Configuration Table 345
12.13 Provider Bridge management 346
12.13.1 Provider Bridge Port Type managed object 348
12.13.2 Customer Edge Port Configuration managed object 349
12.13.3 Remote Customer Access Port Configuration managed object 352
12.14 CFM entities 354
12.14.1 Maintenance Domain list managed object 355
12.14.2 CFM Stack managed object 356
12.14.3 Default MD Level managed object 357
12.14.4 Configuration Error List managed object 358
12.14.5 Maintenance Domain managed object 358
12.14.6 Maintenance Association managed object 361
12.14.7 Maintenance association Endpoint managed object 364
12.15 Backbone Core Bridge (BCB) management 371
12.16 Backbone Edge Bridge (BEB) management 371
12.16.1 BEB configuration managed object 372
12.16.2 BEB/PB/VLAN Bridge Port configuration managed object 376
12.16.3 VIP configuration managed object 377
12.16.4 PIP configuration managed object 378
12.16.5 CBP Configuration managed object 384
12.17 DDCFM entities 387
12.17.1 DDCFM Stack managed object 387
12.17.2 Reflection Responder managed object 388
12.17.3 RFM Receiver managed object 391
12.17.4 Decapsulator Responder managed object 392
12.17.5 SFM Originator managed object 395
12.18 PBB-TE Protection Switching managed objects 398
12.18.1 TE protection group list managed object 398
12.18.2 TE protection group managed object 399
12.19 TPMR managed objects 401
12.19.1 TPMR management entity 402
12.19.2 MAC and PHY entities 404
12.19.3 Forwarding Process 404
12.19.4 MAC Status Propagation Entity (MSPE) 409
12.20 Management entities for FQTSS 411
12.20.1 The Bandwidth Availability Parameter Table 411
12.20.2 The Transmission Selection Algorithm Table 412
12.20.3 The Priority Regeneration Override Table 412
12.21 Congestion Notification managed objects 412
12.21.1 CN component managed object 413
12.21.2 CN component priority managed object 413
12.21.3 CN Port priority managed object 414
12.21.4 Congestion Point managed object 415
12.21.5 Reaction Point port priority managed object 416
12.21.6 Reaction Point group managed object 416
12.22 Stream Reservation Protocol (SRP) entities 417
12.22.1 SRP Bridge Base Table 417
12.22.2 SRP Bridge Port Table 417
12.22.3 SRP Latency Parameter Table 418
12.22.4 SRP Stream Table 418
12.22.5 SRP Reservations Table 419
12.23 Priority-based Flow Control objects 419
12.24 1:1 PBB-TE IPS managed objects 420
12.24.1 IPG list managed object 420

12.24.2 IPG managed object 422
12.25 Shortest Path Bridging managed objects 424
12.25.1 The SPB System managed object 425
12.25.2 The SPB MTID Static managed object 428
12.25.3 The SPB Topology Instance Dynamic managed object 429
12.25.4 The SPB ECT Static Entry managed object 430
12.25.5 The SPB ECT Dynamic Entry managed object 431
12.25.6 The SPB Adjacency Static Entry managed object 432
12.25.7 The SPB Adjacency Dynamic Entry managed object 433
12.25.8 The SPBM BSI Static Entry managed object 434
12.25.9 The SPB Topology Node Table managed object 435
12.25.10 The SPB Topology ECT Table managed object 436
12.25.11 The SPB Topology Edge Table managed object 436
12.25.12 The SPBM Topology Service Table managed object 437
12.25.13 The SPBV Topology Service Table managed object 438
12.25.14 The ECMP ECT Static Entry managed object 439
12.26 Edge Virtual Bridging (EVB) management 440
12.26.1 EVB system base table 444
12.26.2 SBP table entry 445
12.26.3 VSI table entry 446
12.26.4 S-channel configuration and management 448
12.26.5 ER management 450
12.27 Edge Control Protocol (ECP) management 451
12.27.1 ECP table entry 451
12.28 Path Control and Reservation (PCR) management 451
12.28.1 The PCR ECT Static Entry managed object 452
12.28.2 The PCR Topology ECT Table managed object 455
12.29 Managed objects for scheduled traffic 455
12.29.1 The Gate Parameter Table 455
12.29.2 Timing points for scheduled traffic 458
12.30 Managed objects for frame preemption 459
12.30.1 Frame Preemption Parameter table 459
12.31 Managed objects for per-stream filtering and policing 460
12.31.1 The Stream Parameter Table 460
12.31.2 The Stream Filter Instance Table 461
12.31.3 The Stream Gate Instance Table 463
12.31.4 The Flow Meter Instance Table 466

13. Spanning tree protocols 467

13.1 Protocol design requirements 468
13.2 Protocol support requirements 469
13.2.1 MSTP support requirements 469
13.2.2 SPB support requirements 469
13.3 Protocol design goals 470
13.4 RSTP overview 470
13.4.1 Computation of the active topology 471
13.4.2 Example topologies 472
13.5 MSTP overview 475
13.5.1 Example topologies 476
13.5.2 Relationship of MSTP to RSTP 479
13.5.3 Modeling an MST or SPT Region as a single Bridge 479
13.6 SPB overview 480
13.7 Compatibility and interoperability 481

13.7.1 Designated Port selection 481
13.7.2 Force Protocol Version 481
13.8 MST Configuration Identifier (MCID) 482
13.9 Spanning tree priority vectors 483
13.10 CIST Priority Vector calculations 485
13.11 MST Priority Vector calculations 487
13.12 Port Role assignments 489
13.13 Stable connectivity 490
13.14 Communicating spanning tree information 491
13.15 Changing spanning tree information 492
13.16 Changing Port States with RSTP or MSTP 493
13.16.1 Subtree connectivity and priority vectors 494
13.16.2 Root Port transition to Forwarding 494
13.16.3 Designated Port transition to Forwarding 494
13.16.4 Master Port transition to Forwarding 496
13.17 Changing Port States with SPB 498
13.17.1 Agreement Digest 500
13.18 Managing spanning tree topologies 501
13.19 Updating learned station location information 502
13.20 Managing reconfiguration 504
13.21 Partial and disputed connectivity 505
13.22 In-service upgrades 505
13.23 Fragile Bridges 507
13.24 Spanning tree protocol state machines 507
13.25 State machine timers 509
13.25.1 edgeDelayWhile 510
13.25.2 fdWhile 510
13.25.3 helloWhen 510
13.25.4 mdelayWhile 510
13.25.5 rbWhile 510
13.25.6 rcvdInfoWhile 510
13.25.7 rrWhile 511
13.25.8 tcDetected 511
13.25.9 tcWhile 511
13.25.10 pseudoInfoHelloWhen 511
13.26 Per Bridge variables 511
13.26.1 agreementDigest 512
13.26.2 BridgeIdentifier 512
13.26.3 BridgePriority 512
13.26.4 BridgeTimes 512
13.26.5 ForceProtocolVersion 513
13.26.6 MigrateTime 513
13.26.7 MstConfigId 513
13.26.8 AuxMstConfigId 513
13.26.9 rootPortId 513
13.26.10 rootPriority 513
13.26.11 rootTimes 513
13.26.12 TxHoldCount 513
13.27 Per port variables 513
13.27.1 AdminEdge 516
13.27.2 ageingTime 516
13.27.3 agree 516
13.27.4 agreed 516
13.27.5 agreedAbove 516

13.27.6 agreedDigest 516
13.27.7 agreedDigestValid 516
13.27.8 agreeDigest 516
13.27.9 agreeDigestValid 516
13.27.10 agreedMisorder 517
13.27.11 agreedN 517
13.27.12 agreedND 517
13.27.13 agreedPriority 517
13.27.14 agreedTopology 517
13.27.15 agreementOutstanding 517
13.27.16 agreeN 517
13.27.17 agreeND 517
13.27.18 AutoEdge 517
13.27.19 AutoIsolate 518
13.27.20 designatedPriority 518
13.27.21 designatedTimes 518
13.27.22 disputed 518
13.27.23 enableBPDUrx 518
13.27.24 enableBPDUtx 518
13.27.25 ExternalPortPathCost 518
13.27.26 isL2gp 518
13.27.27 isolate 519
13.27.28 fdbFlush 519
13.27.29 forward 519
13.27.30 forwarding 519
13.27.31 infoInternal 519
13.27.32 infoIs 519
13.27.33 InternalPortPathCost 519
13.27.34 learn 520
13.27.35 learning 520
13.27.36 master 520
13.27.37 mastered 520
13.27.38 mcheck 520
13.27.39 msgPriority 520
13.27.40 msgTimes 520
13.27.41 neighbourPriority 521
13.27.42 newInfo 521
13.27.43 newInfoMsti 521
13.27.44 operEdge 521
13.27.45 portEnabled 521
13.27.46 portId 521
13.27.47 portPriority 521
13.27.48 portTimes 522
13.27.49 proposed 522
13.27.50 proposing 522
13.27.51 pseudoRootId 522
13.27.52 rcvdBPDU 522
13.27.53 rcvdInfo 522
13.27.54 rcvdInternal 522
13.27.55 rcvdMsg 522
13.27.56 rcvdRSTP 522
13.27.57 rcvdSTP 522
13.27.58 rcvdTc 522
13.27.59 rcvdTcAck 522

13.27.60 rcvdTcn 523
13.27.61 reRoot 523
13.27.62 reselect 523
13.27.63 restrictedDomainRole 523
13.27.64 restrictedRole 523
13.27.65 restrictedTcn 523
13.27.66 role 523
13.27.67 selected 523
13.27.68 selectedRole 523
13.27.69 sendRSTP 524
13.27.70 sync 524
13.27.71 synced 524
13.27.72 tcAck 524
13.27.73 tcProp 524
13.27.74 tick 524
13.27.75 txCount 524
13.27.76 updtInfo 524
13.28 State machine conditions and parameters 524
13.28.1 allSptAgree 525
13.28.2 allSynced 525
13.28.3 allTransmitReady 525
13.28.4 BestAgreementPriority 525
13.28.5 cist 525
13.28.6 cistRootPort 525
13.28.7 cistDesignatedPort 526
13.28.8 EdgeDelay 526
13.28.9 forwardDelay 526
13.28.10 FwdDelay 526
13.28.11 HelloTime 526
13.28.12 MaxAge 526
13.28.13 msti 526
13.28.14 mstiDesignatedOrTCpropagatingRootPort 526
13.28.15 mstiMasterPort 526
13.28.16 operPointToPoint 526
13.28.17 rcvdAnyMsg 526
13.28.18 rcvdCistMsg 526
13.28.19 rcvdMstiMsg 527
13.28.20 reRooted 527
13.28.21 rstpVersion 527
13.28.22 spt 527
13.28.23 stpVersion 527
13.28.24 updtCistInfo 527
13.28.25 updtMstiInfo 527
13.29 State machine procedures 527
13.29.1 betterorsameInfo(newInfoIs) 528
13.29.2 clearAllRcvdMsgs() 528
13.29.3 clearReselectTree() 528
13.29.4 disableForwarding() 529
13.29.5 disableLearning() 529
13.29.6 enableForwarding() 529
13.29.7 enableLearning() 529
13.29.8 fromSameRegion() 529
13.29.9 newTcDetected() 529
13.29.10 newTcWhile() 529

13.29.11 pseudoRcvMsgs() 530
13.29.12 rcvInfo() 530
13.29.13 rcvMsgs() 531
13.29.14 rcvAgreements() 531
13.29.15 recordAgreement() 531
13.29.16 recordDispute() 532
13.29.17 recordMastered() 532
13.29.18 recordPriority() 532
13.29.19 recordProposal() 532
13.29.20 recordTimes() 532
13.29.21 setReRootTree() 533
13.29.22 setSelectedTree() 533
13.29.23 setSyncTree() 533
13.29.24 setTcFlags() 533
13.29.25 setTcPropTree() 533
13.29.26 syncMaster() 533
13.29.27 txConfig() 533
13.29.28 txRstp() 534
13.29.29 txTcn() 534
13.29.30 updtAgreement() 534
13.29.31 updtBPDUVersion() 535
13.29.32 updtDigest() 535
13.29.33 updtRcvdInfoWhile() 536
13.29.34 updtRolesTree() 537
13.29.35 uptRolesDisabledTree() 538
13.30 The Port Timers state machine 538
13.31 Port Receive state machine 539
13.32 Port Protocol Migration state machine 540
13.33 Bridge Detection state machine 540
13.34 Port Transmit state machine 541
13.35 Port Information state machine 542
13.36 Port Role Selection state machine 543
13.37 Port Role Transitions state machine 543
13.38 Port State Transition state machine 548
13.38.1 Port State transitions for the CIST and MSTIs 549
13.38.2 Port State transitions for SPTs 549
13.39 Topology Change state machine 550
13.40 Layer 2 Gateway Port Receive state machine 551
13.41 CEP spanning tree operation 551
13.41.1 PEP operPointToPointMAC and operEdge 551
13.41.2 updtRolesTree() 552
13.41.3 setReRootTree(), setSyncTree(), setTcPropTree() 552
13.41.4 allSynced, reRooted 552
13.41.5 Configuration parameters 552
13.42 Virtual Instance Port (VIP) spanning tree operation 553

14. Encoding of Bridge Protocol Data Units (BPDUs) 554

14.1 BPDU Structure 554
14.1.1 Transmission and representation of octets 554
14.1.2 Common BPDU fields 554
14.2 Encoding of parameter types 556
14.2.1 Encoding of Protocol Identifiers 556
14.2.2 Encoding of Protocol Version Identifiers 556

14.2.3 Encoding of BPDU types ... 556
14.2.4 Encoding of flags ... 556
14.2.5 Encoding of Bridge Identifiers ... 556
14.2.6 Encoding of External Root Path Cost and Internal Root Path Cost ... 557
14.2.7 Encoding of Port Identifiers ... 557
14.2.8 Encoding of Timer Values ... 557
14.2.9 Encoding of Port Role values ... 557
14.2.10 Encoding of Length Values ... 558
14.2.11 Encoding of Hop Counts ... 558
14.3 Transmission of BPDUs ... 558
14.4 Encoding and decoding of STP Configuration, RST, MST, and SPT BPDUs ... 558
14.4.1 MSTI Configuration Messages ... 560
14.5 Validation of received BPDUs ... 561
14.6 Validation and interoperability ... 562

15. Support of the MAC Service by PBNs ... 563

15.1 Service transparency ... 563
15.2 Customer service interfaces ... 564
15.3 Port-based service interface ... 564
15.4 C-tagged service interface ... 565
15.5 S-tagged service interface ... 566
15.6 Remote customer service interfaces (RCSIs) ... 567
15.7 Service instance segregation ... 570
15.8 Service instance selection and identification ... 570
15.9 Service priority selection ... 571
15.10 Service access protection ... 571

16. Principles of Provider Bridged Network (PBN) operation ... 572

16.1 PBN overview ... 572
16.2 Provider Bridged Network (PBN) ... 573
16.3 Service instance connectivity ... 576
16.4 Service provider learning of customer end station addresses ... 577
16.5 Detection of connectivity loops through attached networks ... 577
16.6 Network management ... 578

17. Management Information Base (MIB) ... 579

17.1 Internet Standard Management Framework ... 579
17.2 Structure of the MIB ... 579
17.2.1 Structure of the IEEE8021-TC-MIB ... 580
17.2.2 Structure of the IEEE8021-BRIDGE-MIB ... 582
17.2.3 Structure of the IEEE8021-SPANNING-TREE MIB ... 586
17.2.4 Structure of the IEEE8021-Q-BRIDGE-MIB ... 589
17.2.5 Structure of the IEEE8021-PB-MIB ... 594
17.2.6 Structure of the IEEE8021-MSTP-MIB ... 596
17.2.7 Structure of the IEEE8021-CFM-MIB ... 599
17.2.8 Structure of the IEEE8021-PBB-MIB ... 605
17.2.9 Structure of the IEEE8021-DDCFM-MIBs ... 607
17.2.10 Structure of the IEEE8021-PBBTE-MIB ... 610
17.2.11 Structure of the TPMR MIB ... 612
17.2.12 Structure of the IEEE8021-FQTSS-MIB ... 614
17.2.13 Structure of the Congestion Notification MIB ... 615
17.2.14 Structure of the IEEE8021-SRP-MIB ... 617

17.2.15 Structure of the MVRP extension MIB 619
17.2.16 Structure of the MIRP MIB 619
17.2.17 Structure of the PFC MIB 620
17.2.18 Structure of the IEEE80221-TEIPS MIB 620
17.2.19 Structure of the IEEE8021-SPB-MIB 622
17.2.20 Structure of the IEEE8021-EVB-MIB 626
17.2.21 Structure of the IEEE8021-ECMP-MIB 630
17.2.22 Structure of the IEEE8021-ST-MIB 631
17.2.23 Structure of the IEEE8021-Preemption-MIB 632
17.2.24 Structure of the IEEE8021-PSFP-MIB 633
17.3 Relationship to other MIBs 636
17.3.1 Relationship of the IEEE8021-TC-MIB to other MIB modules 636
17.3.2 Relationship of the IEEE8021-BRIDGE-MIB to other MIB modules 636
17.3.3 Relationship of the IEEE8021-RSTP MIB to other MIB modules 639
17.3.4 Relationship of the IEEE8021-Q-BRIDGE-MIB to other MIB modules 639
17.3.5 Relationship of the IEEE8021-PB-BRIDGE MIB to other MIB modules 641
17.3.6 Relationship of the IEEE8021-MSTP-MIB to other MIB modules 641
17.3.7 Relationship of the IEEE8021-CFM-MIB to other MIB modules 641
17.3.8 Relationship of the IEEE8021-PBB-MIB to other MIB modules 642
17.3.9 Relationship of the IEEE8021-DDCFM to other MIB modules 643
17.3.10 Relationship of the IEEE8021-PBBTE-MIB to other MIB modules 643
17.3.11 Relationship of the TPMR MIB to other MIB modules 644
17.3.12 Relationship of the IEEE8021-FQTSS-MIB to other MIB modules 644
17.3.13 Relationship of the IEEE802-CN-MIB to other MIB modules 644
17.3.14 Relationship of the IEEE8021-SRP-MIB to other MIB modules 645
17.3.15 Relationship of the IEEE8021-MVRPX-MIB to other MIB modules 645
17.3.16 Relationship of the IEEE8021-MIRP-MIB to other MIB modules 645
17.3.17 Relationship of the PFC MIB to other MIB modules 645
17.3.18 Relationship of the IEEE8021-TEIPS-MIB to other MIB modules 646
17.3.19 Relationship of the of the IEEE8021-SPB-MIB to other MIB modules 646
17.3.20 Relationship of the IEEE8021-EVB-MIB to other MIB modules 646
17.3.21 Relationship of the of the IEEE8021-ECMP-MIB to other MIB modules 646
17.3.22 Relationship of the PCR MIB to other MIB modules 646
17.3.23 Relationship of the IEEE8021-ST-MIB to other MIBs 646
17.3.24 Relationship of the IEEE8021-Preemption-MIB to other MIBs 647
17.3.25 Relationship of IEEE8021-PSFP-MIB to other MIBs 647
17.4 Security considerations 647
17.4.1 Security considerations of the IEEE8021-TC-MIB 647
17.4.2 Security considerations of the IEEE8021-BRIDGE-MIB 647
17.4.3 Security considerations of the IEEE8021-SPANNING-TREE MIB 648
17.4.4 Security considerations of the IEEE8021-Q-BRIDGE-MIB 649
17.4.5 Security considerations of the IEEE8021-PB-MIB 650
17.4.6 Security considerations of the IEEE8021-MSTP-MIB 650
17.4.7 Security considerations of the IEEE8021-CFM-MIB 651
17.4.8 Security considerations of the IEEE8021-PBB-MIB 653
17.4.9 Security considerations of the IEEE8021-DDCFM-MIB 653
17.4.10 Security considerations of the IEEE8021-PBBTE-MIB 654
17.4.11 Security considerations of the TPMR MIB 655
17.4.12 Security considerations of the IEEE8021-FQTSS-MIB 655
17.4.13 Security considerations of the Congestion Notification MIB 656
17.4.14 Security considerations of the IEEE8021-SRP-MIB 657
17.4.15 Security considerations of the IEEE8021-MVRPX-MIB 658
17.4.16 Security considerations of the IEEE8021-MIRP-MIB 658
17.4.17 Security considerations for the PFC MIB 659

17.4.18 Security considerations of the IEEE8021-TEIPS-MIB 659
17.4.19 Security considerations of the IEEE8021-SPB-MIB 659
17.4.20 Security considerations of the IEEE8021-EVB-MIB 660
17.4.21 Security considerations of the IEEE8021-ECMP-MIB 661
17.4.22 Security considerations of the PCR MIB 662
17.4.23 Security considerations of the IEEE8021-ST-MIB 662
17.4.24 Security considerations of the IEEE8021-Preemption-MIB 663
17.4.25 Security considerations of the IEEE8021-PSFP-MIB 663
17.5 Dynamic component and Port creation 665
17.5.1 Overview of the dynamically created Bridge entities 665
17.5.2 Component creation 666
17.5.3 Port creation 667
17.6 MIB operations for service interface configuration 677
17.6.1 Provisioning PBN service interfaces 677
17.6.2 Provisioning Backbone Bridged Network service interfaces 680
17.7 MIB modules, ... 686
17.7.1 Definitions for the IEEE8021-TC-MIB module 686
17.7.2 Definitions for the IEEE8021-BRIDGE-MIB module 697
17.7.3 Definitions for the IEEE8021-SPANNING-TREE-MIB module 737
17.7.4 Definitions for the IEEE8021-Q-BRIDGE-MIB module 755
17.7.5 Definitions for the IEEE8021-PB-MIB module 801
17.7.6 Definitions for the IEEE8021-MSTP-MIB module 819
17.7.7 Definitions for the CFM MIB modules 848
17.7.8 Definitions for the IEEE8021-PBB-MIB module 931
17.7.9 Definitions for the IEEE8021-DDCFM-MIB module 954
17.7.10 Definitions for the IEEE8021-PBBTE-MIB module 972
17.7.11 Definitions for the IEEE8021-TPMR-MIB module 989
17.7.12 Definitions for the IEEE8021-FQTSS-MIB module 1003
17.7.13 Definitions for the IEEE8021-CN-MIB module 1014
17.7.14 Definitions for the IEEE8021-SRP-MIB module 1050
17.7.15 Definitions for the IEEE8021-MVRPX-MIB module 1066
17.7.16 Definitions for the IEEE8021-MIRP-MIB module 1071
17.7.17 Definitions for the IEEE8021-PFC-MIB module 1077
17.7.18 Definitions for the IEEE8021-TEIPS-V2-MIB module 1081
17.7.19 Definitions for the IEEE8021-SPB-MIB module 1096
17.7.20 Definitions for the IEEE8021-EVB-MIB module 1140
17.7.21 Definitions for the IEEE8021-ECMP-MIB module 1169
17.7.22 Definitions for the IEEE8021-ST-MIB module 1177
17.7.23 Definitions for the IEEE8021-Preemption-MIB module 1190
17.7.24 Definitions for the IEEE8021-PSFP-MIB module 1196

18. Principles of Connectivity Fault Management operation 1220

18.1 Maintenance Domains and DoSAPs 1221
18.2 Service instances and MAs 1223
18.3 Maintenance Domain Levels 1224

19. CFM entity operation 1228

19.1 Maintenance Points (MPs) 1228
19.2 MA Endpoints (MEPs) 1229
19.2.1 MEP identification 1229
19.2.2 MEP functions 1230
19.2.3 MEP architecture 1230
19.2.4 MP Type Demultiplexer 1232

19.2.5 MP Multiplexer 1232
19.2.6 MP Level Demultiplexer 1232
19.2.7 MP OpCode Demultiplexer 1232
19.2.8 MEP Continuity Check Receiver 1233
19.2.9 MEP Continuity Check Initiator 1233
19.2.10 MP Loopback Responder 1234
19.2.11 MEP Loopback Initiator 1234
19.2.12 MEP Linktrace Initiator 1234
19.2.13 MEP LTI SAP 1234
19.2.14 MEP Linktrace SAP 1234
19.2.15 MEP CCM Database 1234
19.2.16 MEP Fault Notification Generator 1234
19.2.17 MEP Decapsulator Responder (DR) 1235
19.2.18 MEP RFM Receiver 1235
19.3 MIP Half Function 1235
19.3.1 MHF identification 1235
19.3.2 MHF functions 1235
19.3.3 MHF architecture 1236
19.3.4 MHF Level Demultiplexer 1236
19.3.5 MHF Type Demultiplexer 1236
19.3.6 MHF OpCode Demultiplexer 1236
19.3.7 MHF Multiplexer 1236
19.3.8 MHF Loopback Responder 1236
19.3.9 MHF Continuity Check Receiver 1237
19.3.10 MIP CCM Database 1237
19.3.11 MHF Linktrace SAP 1238
19.3.12 MHF DR 1238
19.3.13 MHF RFM Receiver 1238
19.4 MP addressing 1238
19.5 Linktrace Output Multiplexer (LOM) 1239
19.6 Linktrace Responder 1239

20. CFM protocols 1241

20.1 Continuity Check protocol 1242
20.1.1 MAC status reporting in the CCM 1244
20.1.2 Defects and Fault Alarms 1244
20.1.3 CCM reception 1245
20.2 Loopback protocol 1245
20.2.1 LBM transmission 1246
20.2.2 LBM reception and LBR transmission 1246
20.2.3 LBR reception 1247
20.3 Linktrace protocol 1247
20.3.1 LTM origination 1248
20.3.2 LTM reception, forwarding, and replying 1249
20.3.3 LTR reception 1250
20.4 CFM state machines 1251
20.5 CFM state machine timers 1251
20.5.1 LTFwhile 1253
20.5.2 CCIwhile 1253
20.5.3 errorCCMwhile 1253
20.5.4 xconCCMwhile 1253
20.5.5 LBIwhile 1253
20.5.6 FNGwhile 1253

20.5.7 mmCCMwhile 1253
20.5.8 mmLocwhile 1253
20.5.9 mmFNGwhile 1253
20.5.10 rMEPwhile 1253
20.6 CFM procedures 1254
20.6.1 CCMtime() 1254
20.7 Maintenance Domain variable 1254
20.7.1 mdLevel 1254
20.8 MA variables 1254
20.8.1 CCMinterval 1254
20.9 MEP variables 1254
20.9.1 MEPactive 1255
20.9.2 enableRmepDefect 1255
20.9.3 MAdefectIndication 1256
20.9.4 allRMEPsDead 1256
20.9.5 lowestAlarmPri 1256
20.9.6 presentRDI 1256
20.9.7 MEPprimaryVID 1256
20.9.8 presentTraffic 1256
20.9.9 presentmmLoc 1256
20.9.10 ISpresentTraffic 1257
20.9.11 ISpresentmmLoc 1257
20.9.12 EpMEP 1257
20.10 MEP Continuity Check Initiator variables 1257
20.10.1 CCIenabled 1257
20.10.2 CCIsentCCMs 1257
20.10.3 MACstatusChanged 1257
20.10.4 Npaths 1257
20.10.5 flowHash[ ] 1258
20.10.6 pathN 1258
20.10.7 CCMcnt 1258
20.11 MEP Continuity Check Initiator procedures 1258
20.11.1 xmitCCM() 1258
20.12 MEP Continuity Check Initiator state machine 1259
20.13 MHF Continuity Check Receiver variables 1260
20.13.1 MHFrecvdCCM 1260
20.13.2 MHFCCMPDU 1260
20.14 MHF Continuity Check Receiver procedures 1260
20.14.1 MHFprocessCCM() 1260
20.15 MHF Continuity Check Receiver state machine 1260
20.16 MEP Continuity Check Receiver variables 1261
20.16.1 CCMreceivedEqual 1261
20.16.2 CCMequalPDU 1261
20.16.3 CCMreceivedLow 1261
20.16.4 CCMlowPDU 1261
20.16.5 recvdMacAddress 1261
20.16.6 recvdRDI 1261
20.16.7 recvdInterval 1262
20.16.8 recvdPortState 1262
20.16.9 recvdInterfaceStatus 1262
20.16.10 recvdSenderId 1262
20.16.11 recvdFrame 1262
20.16.12 CCMsequenceErrors 1262
20.16.13 rcvdTrafficBit 1262

20.17 MEP Continuity Check Receiver procedures 1262
20.17.1 MEPprocessEqualCCM() 1263
20.17.2 MEPprocessLowCCM() 1263
20.18 MEP Continuity Check Receiver state machine 1264
20.19 Remote MEP variables 1264
20.19.1 rMEPCCMdefect 1264
20.19.2 rMEPlastRDI and rMEPlastRDI[i] 1264
20.19.3 rMEPlastPortState 1265
20.19.4 rMEPlastInterfaceStatus 1265
20.19.5 rMEPlastSenderId 1265
20.19.6 rCCMreceived 1265
20.19.7 rMEPmacAddress 1265
20.19.8 rMEPportStatusDefect 1265
20.19.9 rMEPinterfaceStatusDefect 1265
20.19.10 lastPathN 1265
20.20 Remote MEP state machine 1266
20.21 Remote MEP Error variables 1267
20.21.1 errorCCMreceived 1267
20.21.2 errorCCMlastFailure 1267
20.21.3 errorCCMdefect 1267
20.22 Remote MEP Error state machine 1267
20.23 MEP Cross Connect variables 1268
20.23.1 xconCCMreceived 1268
20.23.2 xconCCMlastFailure 1268
20.23.3 xconCCMdefect 1268
20.24 MEP Cross Connect state machine 1268
20.25 MEP Mismatch variables 1269
20.25.1 mmCCMreceived 1269
20.25.2 mmCCMdefect 1269
20.25.3 mmCCMTime 1269
20.25.4 disableLocdefect 1269
20.25.5 mmLocdefect 1269
20.26 MEP Mismatch state machines 1270
20.27 MP Loopback Responder variables 1271
20.27.1 LBMreceived 1271
20.27.2 LBMPDU 1271
20.28 MP Loopback Responder procedures 1271
20.28.1 ProcessLBM() 1271
20.28.2 xmitLBR() 1272
20.29 MP Loopback Responder state machine 1272
20.30 MEP Loopback Initiator variables 1273
20.30.1 LBMsToSend 1273
20.30.2 nextLBMtransID 1273
20.30.3 expectedLBRtransID 1273
20.30.4 LBIactive 1273
20.30.5 xmitReady 1273
20.30.6 LBRreceived 1273
20.30.7 LBRPDU 1273
20.31 MEP Loopback Initiator transmit procedures 1274
20.31.1 xmitLBM() 1274
20.32 MEP Loopback Initiator transmit state machine 1275
20.33 MEP Loopback Initiator receive procedures 1275
20.33.1 ProcessLBR() 1275
20.34 MEP Loopback Initiator receive state machine 1276

20.35 MEP Fault Notification Generator variables 1276
20.35.1 fngPriority 1276
20.35.2 fngDefect 1277
20.35.3 fngAlarmTime 1277
20.35.4 fngResetTime 1277
20.35.5 someRMEPCCMdefect 1277
20.35.6 someMACstatusDefect 1277
20.35.7 someRDIdefect 1277
20.35.8 highestDefectPri 1277
20.35.9 highestDefect 1277
20.36 MEP Fault Notification Generator procedures 1278
20.36.1 xmitFaultAlarm() 1278
20.37 MEP Fault Notification Generator state machine 1278
20.38 MEP Mismatch Fault Notification Generator variables 1279
20.38.1 mfngAllowed 1279
20.38.2 mmdefectIndication 1279
20.38.3 mfngAlarmTime 1279
20.38.4 mfngResetTime 1279
20.39 MEP Mismatch Fault Notification Generator procedures 1279
20.39.1 xmitFaultAlarm() 1279
20.40 MEP Mismatch Fault Notification Generator state machine 1280
20.41 MEP Linktrace Initiator variables 1280
20.41.1 nextLTMtransID 1280
20.41.2 ltmReplyList 1281
20.42 MEP Linktrace Initiator procedures 1283
20.42.1 xmitLTM() 1283
20.43 MEP Linktrace Initiator receive variables 1284
20.43.1 LTRreceived 1284
20.43.2 LTRPDU 1284
20.44 MEP Linktrace Initiator receive procedures 1284
20.44.1 ProcessLTR() 1284
20.45 MEP Linktrace Initiator receive state machine 1285
20.46 Linktrace Responder variables 1285
20.46.1 nPendingLTRs 1285
20.46.2 LTMreceived 1285
20.46.3 LTMPDU 1285
20.47 LTM Receiver procedures 1286
20.47.1 ProcessLTM() 1286
20.47.2 clearPendingLTRs() 1290
20.47.3 ForwardLTM() 1290
20.47.4 enqueLTR() 1291
20.48 LTM Receiver state machine 1292
20.49 LTR Transmitter procedure 1293
20.49.1 xmitOldestLTR() 1293
20.50 LTR Transmitter state machine 1293
20.51 CFM PDU validation and versioning 1294
20.51.1 Goals of CFM PDU versioning 1294
20.51.2 PDU transmission 1294
20.51.3 PDU validation 1294
20.51.4 Validation pass 1295
20.51.5 Execution pass 1296
20.51.6 Future extensions 1296
20.52 PDU identification 1297
20.53 Use of transaction IDs and sequence numbers 1297

21. Encoding of CFM PDUs 1299

21.1 Structure, representation, and encoding 1299
21.2 CFM encapsulation 1299
21.3 CFM request and indication parameters 1300
21.3.1 destination_address parameter 1300
21.3.2 source_address parameter 1300
21.4 Common CFM Header 1300
21.4.1 MD Level 1300
21.4.2 Version 1300
21.4.3 OpCode 1301
21.4.4 Flags 1301
21.4.5 First TLV Offset 1302
21.5 TLV format 1302
21.5.1 General format for CFM TLVs 1302
21.5.2 Organization-Specific TLV 1303
21.5.3 Sender ID TLV 1304
21.5.4 Port Status TLV 1305
21.5.5 Interface Status TLV 1306
21.5.6 Data TLV 1307
21.5.7 End TLV 1307
21.6 CCM format 1307
21.6.1 Flags 1308
21.6.2 First TLV Offset 1309
21.6.3 Sequence Number 1309
21.6.4 Maintenance association Endpoint Identifier 1309
21.6.5 Maintenance Association Identifier 1309
21.6.6 Defined by ITU-T Y.1731 (02/2008) 1312
21.6.7 Optional CCM TLVs 1312
21.7 LBM and LBR formats 1312
21.7.1 Flags 1312
21.7.2 First TLV Offset 1313
21.7.3 Loopback Transaction Identifier 1313
21.7.4 Additional LBM/LBR TLVs 1313
21.7.5 PBB-TE MIP TLV 1314
21.8 LTM format 1315
21.8.1 Flags 1315
21.8.2 First TLV Offset 1315
21.8.3 LTM Transaction Identifier 1315
21.8.4 LTM TTL 1316
21.8.5 Original MAC Address 1316
21.8.6 Target MAC Address 1316
21.8.7 Additional LTM TLVs 1316
21.8.8 LTM Egress Identifier TLV 1316
21.9 LTR format 1317
21.9.1 Flags 1317
21.9.2 First TLV Offset 1318
21.9.3 LTR Transaction Identifier 1318
21.9.4 Reply TTL 1318
21.9.5 Relay Action 1318
21.9.6 Additional LTR TLVs 1318
21.9.7 LTR Egress Identifier TLV 1319
21.9.8 Reply Ingress TLV 1319
21.9.9 Reply Egress TLV 1321

22. CFM in systems 1323

22.1 CFM shims in Bridges 1323
22.1.1 Preliminary positioning of MPs 1323
22.1.2 CFM and the Forwarding Process 1324
22.1.3 Up/Down separation of MPs 1326
22.1.4 Service instances over multiple Bridges 1328
22.1.5 Multiple VID service instances 1330
22.1.6 Untagged CFM PDUs 1330
22.1.7 MPs and non-VLAN-aware Bridges 1330
22.1.8 MPs and other standards 1331
22.1.9 CFM and IEEE 802.3 OAM 1333
22.2 Maintenance Entity creation 1333
22.2.1 Creating Maintenance Domains and MAs 1334
22.2.2 Creating MEPs 1334
22.2.3 Creating MIPs 1336
22.2.4 CFM configuration errors 1337
22.3 MPs, Ports, and MD Level assignment 1338
22.4 Stations and CFM 1338
22.5 Scalability of CFM 1339
22.6 CFM in Provider Bridges 1340
22.6.1 MPs and C-VLAN components 1340
22.6.2 Maintenance C-VLAN on a Port-based service interface 1341
22.6.3 Maintenance C-VLAN on a C-tagged service interface 1342
22.6.4 MPs and Port-mapping S-VLAN components 1342
22.7 Management Port MEPs and CFM in the enterprise environment 1344
22.8 Implementing CFM on Bridges that implement earlier revisions of IEEE Std 802.1Q 1346

23. MAC status propagation 1347

23.1 Model of operation 1348
23.1.1 MAC Status Shim (MSS) 1349
23.1.2 Relationship of CFM to the MSS 1350
23.2 MAC Status Protocol (MSP) overview 1350
23.3 MSP state machines 1355
23.4 State machine timers 1356
23.4.1 linkNotifyWhen 1356
23.4.2 linkNotifyWhile 1356
23.4.3 macNotifyWhile 1356
23.4.4 macRecoverWhile 1356
23.5 MSP performance parameters 1356
23.5.1 LinkNotify 1357
23.5.2 LinkNotifyWait 1357
23.5.3 LinkNotifyRetry 1357
23.5.4 MACNotify 1357
23.5.5 MACNotifyTime 1357
23.5.6 MACRecoverTime 1357
23.6 State machine variables 1357
23.6.1 BEGIN 1357
23.6.2 addConfirmed 1357
23.6.3 disableMAC 1357
23.6.4 disabledMAC 1357
23.6.5 disableMSS 1358
23.6.6 lossConfirmed 1358
23.6.7 macOperational 1358

23.6.8 mssOperational ... 1358
23.6.9 prop ... 1358
23.6.10 rxAck ... 1358
23.6.11 rxAdd ... 1358
23.6.12 rxAddConfirm ... 1358
23.6.13 rxLoss ... 1358
23.6.14 rxLossConfirm ... 1358
23.6.15 txAck ... 1358
23.6.16 txAdd ... 1358
23.6.17 txAddConfirm ... 1359
23.6.18 txLoss ... 1359
23.6.19 txLossConfirm ... 1359
23.7 State machine procedures ... 1359
23.8 Status Transition state machine (STM) ... 1359
23.9 Status Notification state machine (SNM) ... 1360
23.10 Receive Process ... 1360
23.11 Transmit Process ... 1360
23.12 Management of MSP ... 1360
23.13 MSPDU transmission, addressing, and protocol identification ... 1361
23.13.1 Destination MAC Address ... 1361
23.13.2 Source MAC Address ... 1361
23.13.3 Priority ... 1362
23.13.4 EtherType use and encoding ... 1362
23.14 Representation and encoding of octets ... 1362
23.15 MSPDU structure ... 1362
23.15.1 Protocol Version ... 1362
23.15.2 Packet Type ... 1363
23.16 Validation of received MSPDUs ... 1363
23.17 Other MSP participants ... 1363

24. Bridge performance ... 1364

24.1 Guaranteed Port Filtering Rate ... 1364
24.2 Guaranteed Bridge Relaying Rate ... 1364
24.3 RSTP performance requirements ... 1364

25. Support of the MAC Service by PBBNs ... 1366

25.1 Service transparency ... 1368
25.2 Customer service interface ... 1368
25.3 Port-based service interface ... 1369
25.4 S-tagged service interface ... 1370
25.5 I-tagged service interface ... 1372
25.6 Service instance segregation ... 1374
25.7 Service instance selection and identification ... 1374
25.8 Service priority and drop eligibility selection ... 1375
25.9 Service access protection ... 1375
25.9.1 Class II redundant LANs access protection ... 1377
25.9.2 Class III simple redundant LANs and nodes access protection ... 1378
25.10 Support of the MAC Service by a PBB-TE Region ... 1379
25.10.1 Provisioning TESIs ... 1380
25.10.2 ESP forwarding behavior ... 1381
25.11 Transparent service interface ... 1382

26. Principles of Provider Backbone Bridged Network (PBBN) operation 1384

26.1 PBBN overview 1384
26.2 PBBN example 1385
26.3 B-VLAN connectivity 1387
26.4 Backbone addressing 1388
26.4.1 Learning individual backbone addresses at a PIP 1389
26.4.2 Translating backbone destination addresses at a CBP 1389
26.4.3 Backbone addressing considerations for CFM MPs 1390
26.5 Detection of connectivity loops through attached networks 1390
26.6 Scaling of PBBs 1390
26.6.1 Hierarchal PBBNs 1391
26.6.2 Peer PBBNs 1391
26.7 Network management 1391
26.8 CFM in PBBs 1392
26.8.1 CFM over Port-based and S-tagged service interfaces 1397
26.8.2 CFM over I-tagged Service Interfaces 1398
26.8.3 CFM over hierarchal E-NNI 1398
26.8.4 CFM over peer E-NNI 1398
26.9 CFM in a PBB-TE Region 1399
26.9.1 Addressing PBB-TE MEPs 1399
26.9.2 TESI identification 1400
26.9.3 PBB-TE MEP placement in a Bridge Port 1400
26.9.4 PBB-TE MIP placement in a Bridge Port 1400
26.9.5 TESI Maintenance Domains 1400
26.9.6 PBB-TE enhancements of the CFM protocols 1401
26.9.7 Addressing Infrastructure Segment MEPs 1403
26.9.8 Infrastructure Segment identification 1403
26.9.9 Infrastructure Segment MEP placement in a Bridge Port 1404
26.9.10 Infrastructure Segment Maintenance Domains 1404
26.9.11 IPS extensions to Continuity Check operation 1404
26.10 Protection switching for point-to-point TESIs 1406
26.10.1 Introduction 1406
26.10.2 1:1 point-to-point TESI protection switching 1407
26.10.3 Protection Switching state machines 1410
26.11 IPS in PBB-TE Region 1415
26.11.1 Infrastructure Segment monitoring 1416
26.11.2 1:1 IPS 1417
26.11.3 IPS Control entity 1420
26.11.4 1:1 IPS state machines 1421
26.11.5 M:1 IPS 1421
26.12 Mismatch defect 1427
26.13 Signaling VLAN registrations among I-components 1428

27. Shortest Path Bridging (SPB) 1429

27.1 Protocol design requirements 1431
27.2 Protocol support 1432
27.3 Protocol design goals 1433
27.4 ISIS-SPB VLAN configuration 1433
27.4.1 SPT Region and ISIS-SPB adjacency determination 1434
27.5 ISIS-SPB information 1436
27.6 Calculating CIST connectivity 1437
27.7 Connectivity between regions in the same domain 1438
27.8 Calculating SPT connectivity 1438

27.8.1 ISIS-SPB overload ... 1439
27.9 Loop prevention ... 1439
27.10 SPVID and SPSourceID allocation ... 1439
27.11 Allocation of VIDs to FIDs ... 1441
27.12 SPBV SPVID translation ... 1442
27.13 VLAN topology management ... 1442
27.14 Individual addresses and SPBM ... 1443
27.14.1 Loop mitigation ... 1444
27.14.2 Loop prevention ... 1444
27.15 SPBM group addressing ... 1445
27.16 Backbone service instance topology management ... 1447
27.17 Equal cost shortest paths, ECTs, and load spreading ... 1447
27.18 Connectivity Fault Management for SPBM ... 1448
27.18.1 SPBM MA types ... 1448
27.18.2 SPBM MEP placement in a Bridge Port ... 1448
27.18.3 SPBM MIP placement in a Bridge Port ... 1449
27.18.4 SPBM modifications of the CFM protocols ... 1449
27.19 Using SPBV and SPBM modes ... 1451
27.19.1 Shortest Path Bridging—VID ... 1451
27.19.2 Shortest Path Bridging—MAC ... 1452
27.20 Security considerations ... 1454

28. ISIS-SPB Link State Protocol ... 1455

28.1 ISIS-SPB control plane MAC ... 1455
28.2 Formation and maintenance of ISIS-SPB adjacencies ... 1456
28.3 Loop prevention ... 1457
28.4 The Agreement Digest ... 1457
28.4.1 Agreement Digest Format Identifier ... 1458
28.4.2 Agreement Digest Format Capabilities ... 1458
28.4.3 Agreement Digest Convention Identifier ... 1458
28.4.4 Agreement Digest Convention Capabilities ... 1459
28.4.5 Agreement Digest Edge Count ... 1459
28.4.6 The Computed Topology Digest ... 1459
28.5 Symmetric shortest path tie breaking ... 1460
28.6 Symmetric ECT framework ... 1461
28.7 Symmetric ECT ... 1462
28.8 Symmetric ECT Algorithm details ... 1463
28.9 ECT Migration ... 1464
28.9.1 Use of a new ECT Algorithm in SPBV ... 1465
28.9.2 Use of a new ECT Algorithm in SPBM ... 1465
28.10 MAC address registration ... 1466
28.11 Circuit IDs and Port Identifiers ... 1467
28.12 ISIS-SPB TLVs ... 1467
28.12.1 MT-Capability TLV ... 1468
28.12.2 SPB MCID sub-TLV ... 1468
28.12.3 SPB Digest sub-TLV ... 1469
28.12.4 SPB Base VLAN-Identifiers sub-TLV ... 1469
28.12.5 SPB Instance sub-TLV ... 1471
28.12.6 SPB Instance Opaque ECT Algorithm sub-TLV ... 1473
28.12.7 SPB Link Metric sub-TLV ... 1474
28.12.8 SPB Adjacency Opaque ECT Algorithm sub-TLV ... 1475
28.12.9 SPBV MAC address sub-TLV ... 1476
28.12.10 SPBM Service Identifier and Unicast Address (ISID-ADDR) sub-TLV ... 1477

29. DDCFM operations and protocols 1480

29.1 Principles of DDCFM operation 1480
29.1.1 Data-driven and data-dependent faults (DDFs) 1480
29.1.2 Basic principle to diagnose and isolate DDFs 1480
29.2 DDCFM Entity operation 1483
29.2.1 DDCFM implementation 1483
29.2.2 FPT RR 1484
29.2.3 RR-related parameters 1485
29.2.4 Reflection Target and RFM Receiver 1486
29.2.5 RPT-related parameters 1486
29.2.6 Decapsulator Responder (DR) 1487
29.2.7 SFM Originator 1488
29.3 DDCFM protocols 1488
29.3.1 RR variables 1488
29.3.2 RR Filter procedures 1490
29.3.3 RR Encapsulation procedures 1491
29.3.4 RR Transmit procedure 1492
29.3.5 RR-related state machines 1493
29.3.6 RFM Receiver variables 1495
29.3.7 RFM Receiver procedure 1495
29.3.8 DR variables 1496
29.3.9 DR procedures 1497
29.3.10 Decapsulator Responder state machine 1498
29.4 Encoding of DDCFM PDUs 1498
29.4.1 RFM and SFM Header 1498
29.4.2 RFM format 1499
29.4.3 SFM format 1500

30. Principles of congestion notification 1502

30.1 Congestion notification design requirements 1502
30.2 Quantized Congestion Notification protocol (QCN) 1504
30.2.1 The CP algorithm 1505
30.2.2 Basic RP algorithm 1506
30.2.3 RP algorithm with timer 1507
30.3 Congestion Controlled Flow (CCF) 1508
30.4 Congestion Notification Priority Value (CNPV) 1509
30.5 Congestion Notification tag (CN-TAG) 1509
30.6 Congestion Notification Domain (CND) 1509
30.7 Multicast data 1510
30.8 Congestion notification and additional tags 1510

31. Congestion notification entity operation 1512

31.1 Congestion-aware Bridge Forwarding Process 1512
31.1.1 Congestion Point (CP) 1513
31.1.2 CP ingress multiplexer 1513
31.2 Congestion-aware end station functions 1513
31.2.1 Output flow segregation 1514
31.2.2 Per-CNPV station function 1515
31.2.3 Flow Select Database 1517
31.2.4 Flow multiplexer 1517
31.2.5 CNM demultiplexer 1517
31.2.6 Input flow segregation 1517

31.2.7 End station input queue 1518
31.2.8 Reception selection 1518

32. Congestion notification protocol 1519

32.1 CND operations 1519
32.1.1 CND defense 1519
32.1.2 Automatic CND recognition 1521
32.1.3 Variables controlling CND defense 1521
32.2 CN component variables 1522
32.2.1 cngMasterEnable 1523
32.2.2 cngCnmTransmitPriority 1523
32.2.3 cngDiscardedFrames 1523
32.2.4 cngErroredPortList 1523
32.3 Congestion notification per-CNPV variables 1523
32.3.1 cncpDefModeChoice 1523
32.3.2 cncpAlternatePriority 1524
32.3.3 cncpAutoAltPri 1524
32.3.4 cncpAdminDefenseMode 1524
32.3.5 cncpCreation 1524
32.3.6 cncpLldpInstanceChoice 1524
32.3.7 cncpLldpInstanceSelector 1524
32.4 CND defense per-Port per-CNPV variables 1525
32.4.1 cnpdDefModeChoice 1525
32.4.2 cnpdAdminDefenseMode 1525
32.4.3 cnpdAutoDefenseMode 1526
32.4.4 cnpdLldpInstanceChoice 1526
32.4.5 cnpdLldpInstanceSelector 1526
32.4.6 cnpdAlternatePriority 1526
32.4.7 cnpdXmitCnpvCapable 1526
32.4.8 cnpdXmitReady 1526
32.4.9 cncpDoesEdge 1527
32.4.10 cnpdAcceptsCnTag 1527
32.4.11 cnpdRcvdCnpv 1527
32.4.12 cnpdRcvdReady 1527
32.4.13 cnpdIsAdminDefMode 1527
32.4.14 cnpdDefenseMode 1528
32.5 CND defense procedures 1528
32.5.1 DisableCnpvRemapping() 1528
32.5.2 TurnOnCnDefenses() 1528
32.5.3 TurnOffCnDefenses() 1528
32.6 CND defense state machine 1528
32.7 Congestion notification protocol 1529
32.8 CP variables 1530
32.8.1 cpMacAddress 1531
32.8.2 cpId 1531
32.8.3 cpQSp 1531
32.8.4 cpQLen 1531
32.8.5 cpQLenOld 1531
32.8.6 cpW 1531
32.8.7 cpQOffset 1531
32.8.8 cpQDelta 1531
32.8.9 cpFb 1531
32.8.10 cpEnqued 1532

32.8.11 cpSampleBase ... 1532
32.8.12 cpDiscardedFrames ... 1532
32.8.13 cpTransmittedFrames ... 1532
32.8.14 cpTransmittedCnms ... 1532
32.8.15 cpMinHeaderOctets ... 1532
32.9 CP procedures ... 1532
32.9.1 Random ... 1532
32.9.2 NewCpSampleBase() ... 1532
32.9.3 EM_UNITDATA.request (parameters) ... 1533
32.9.4 GenerateCnmPdu() ... 1533
32.10 RP per-Port per-CNPV variables ... 1534
32.10.1 rpppMaxRps ... 1534
32.10.2 rpppCreatedRps ... 1534
32.10.3 rpppRpCentiseconds ... 1535
32.11 RP group variables ... 1535
32.11.1 rpgEnable ... 1535
32.11.2 rpgTimeReset ... 1535
32.11.3 rpgByteReset ... 1535
32.11.4 rpgThreshold ... 1536
32.11.5 rpgMaxRate ... 1536
32.11.6 rpgAiRate ... 1536
32.11.7 rpgHaiRate ... 1536
32.11.8 rpgGd ... 1536
32.11.9 rpgMinDecFac ... 1536
32.11.10 rpgMinRate ... 1536
32.12 RP timer ... 1536
32.12.1 RpWhile ... 1537
32.13 RP variables ... 1537
32.13.1 rpEnabled ... 1537
32.13.2 rpByteCount ... 1537
32.13.3 rpByteStage ... 1537
32.13.4 rpTimeStage ... 1537
32.13.5 rpTargetRate ... 1537
32.13.6 rpCurrentRate ... 1538
32.13.7 rpFreeze ... 1538
32.13.8 rpLimiterRate ... 1538
32.13.9 rpFb ... 1538
32.14 RP procedures ... 1538
32.14.1 ResetCnm ... 1538
32.14.2 TestRpTerminate ... 1539
32.14.3 TransmitDataFrame ... 1539
32.14.4 ReceiveCnm ... 1539
32.14.5 ProcessCnm ... 1540
32.14.6 AdjustRates ... 1540
32.15 RP rate control state machine ... 1540
32.16 Congestion notification and encapsulation interworking function ... 1542

33. Encoding of congestion notification PDUs ... 1544

33.1 Structure, representation, and encoding ... 1544
33.2 CN-TAG format ... 1544
33.2.1 Flow Identifier ... 1545
33.3 Congestion Notification Message (CNM) ... 1545
33.4 Congestion Notification Message PDU format ... 1545

33.4.1 Version ... 1545
33.4.2 ReservedV ... 1546
33.4.3 Quantized Feedback ... 1546
33.4.4 Congestion Point Identifier ... 1546
33.4.5 cnmQOffset ... 1546
33.4.6 cnmQDelta ... 1547
33.4.7 Encapsulated priority ... 1547
33.4.8 Encapsulated destination MAC address ... 1547
33.4.9 Encapsulated MSDU length ... 1547
33.4.10 Encapsulated MSDU ... 1547
33.4.11 CNM Validation ... 1547

34. Forwarding and Queuing Enhancements for time-sensitive streams (FQTSS) ... 1548

34.1 Overview ... 1548
34.2 Detection of SRP domains ... 1548
34.3 The bandwidth availability parameters ... 1549
34.3.1 Relationships among bandwidth availability parameters ... 1549
34.3.2 Bandwidth availability parameter management ... 1550
34.4 Deriving actual bandwidth requirements from the size of the MSDU ... 1550
34.5 Mapping priorities to traffic classes for time-sensitive streams ... 1551
34.6 End station behavior ... 1553
34.6.1 Talker behavior ... 1553
34.6.2 Listener behavior ... 1554

35. Stream Reservation Protocol (SRP) ... 1555

35.1 Multiple Stream Registration Protocol (MSRP) ... 1556
35.1.1 MSRP and Shared Media ... 1557
35.1.2 Behavior of end stations ... 1557
35.1.3 Behavior of Bridges ... 1559
35.1.4 SRP domains and status parameters ... 1559
35.2 Definition of the MSRP application ... 1559
35.2.1 Definition of internal state variables ... 1560
35.2.2 Definition of MRP elements ... 1562
35.2.3 Provision and support of Stream registration service ... 1572
35.2.4 MSRP Attribute Propagation ... 1576
35.2.5 Operational reporting and statistics ... 1581
35.2.6 Encoding ... 1581
35.2.7 Attribute value support requirements ... 1582

36. Priority-based Flow Control (PFC) ... 1583

36.1 PFC operation ... 1583
36.1.1 Overview ... 1583
36.1.2 PFC primitives ... 1584
36.1.3 Detailed specification of PFC operation ... 1585
36.2 PFC-aware system queue functions ... 1586
36.2.1 PFC Initiator ... 1587
36.2.2 PFC Receiver ... 1587

37. Enhanced Transmission Selection (ETS) ... 1589

37.1 Overview ... 1589
37.1.1 Relationship to other transmission selection algorithms ... 1589
37.2 ETS configuration parameters ... 1589

37.3 ETS algorithm ... 1589
37.4 Legacy configuration ... 1590

38. Data Center Bridging eXchange protocol (DCBX) ... 1591

38.1 Overview ... 1591
38.2 Goals ... 1591
38.3 Types of DCBX attributes ... 1591
38.3.1 Informational attributes ... 1591
38.4 DCBX and LLDP ... 1592
38.4.1 Asymmetric attribute passing ... 1592
38.4.2 Symmetric attribute passing ... 1593

39. Multiple I-SID Registration Protocol (MIRP) ... 1595

39.1 MIRP overview ... 1595
39.1.1 Behavior of I-components ... 1597
39.1.2 Behavior of B-components ... 1597
39.2 Definition of the MIRP application ... 1597
39.2.1 Definition of MRP elements ... 1597
39.2.2 Alternate MIRP model for B-components ... 1600
39.2.3 Use of “new” declaration capability ... 1602
39.2.4 Attribute value support requirements ... 1602
39.2.5 MRP Message filtering ... 1602

40. Edge Virtual Bridging (EVB) ... 1603

40.1 EVB architecture without S-channels ... 1604
40.2 EVB architecture with S-channels ... 1605
40.3 Asymmetric EVB architecture without S-channels ... 1607
40.4 EVB status parameters ... 1609
40.4.1 EVBMode = Not supported ... 1609
40.4.2 EVBMode = EVB Bridge ... 1609
40.4.3 EVBMode = EVB station ... 1609

41. VSI Discovery and Configuration Protocol (VDP) ... 1610

41.1 VSI manager ID TLV definition ... 1610
41.1.1 TLV type ... 1610
41.1.2 TLV information string length ... 1610
41.1.3 VSI Manager ID ... 1611
41.2 VDP association TLV definitions ... 1611
41.2.1 TLV type ... 1611
41.2.2 TLV information string length ... 1612
41.2.3 Status ... 1612
41.2.4 VSI Type ID (VTID) ... 1613
41.2.5 VSI Type Version ... 1613
41.2.6 VSIID format ... 1613
41.2.7 VSIID ... 1613
41.2.8 Filter Info format ... 1614
41.2.9 Filter Info field ... 1614
41.2.10 VDP TLV type and Status semantics ... 1617
41.3 Organizationally defined TLV definitions ... 1618
41.3.1 TLV type ... 1618
41.3.2 TLV information string length ... 1618
41.3.3 Organizationally unique identifier (OUI) or Company ID (CID) ... 1618

41.3.4 Organizationally defined information ... 1618
41.4 Validation rules for VDP TLVs ... 1618
41.5 VDP state machines ... 1619
41.5.1 State machine conventions ... 1619
41.5.2 Bridge VDP state machine ... 1619
41.5.3 Station VDP state machine ... 1620
41.5.4 VDP state machine timers ... 1621
41.5.5 VDP state machine variables and parameters ... 1621
41.5.6 Command-Response TLV field references in state machines ... 1624
41.5.7 VDP state machine procedures ... 1624

42. S-Channel Discovery and Configuration Protocol (CDCP) ... 1626

42.1 CDCP discovery and configuration ... 1626
42.2 CDCP state machine overview ... 1626
42.3 CDCP configuration state machine ... 1627
42.4 CDCP configuration variables ... 1629
42.4.1 AdminChnCap ... 1629
42.4.2 AdminRole ... 1629
42.4.3 AdminSVIDWants ... 1629
42.4.4 LastLocalSVIDPool ... 1629
42.4.5 LastRemoteSVIDList ... 1629
42.4.6 LastSVIDWants ... 1629
42.4.7 LocalSVIDPool ... 1629
42.4.8 OperChnCap ... 1629
42.4.9 OperRole ... 1630
42.4.10 OperSVIDList ... 1630
42.4.11 RemoteChnCap ... 1630
42.4.12 RemoteRole ... 1630
42.4.13 RemoteSVIDList ... 1630
42.4.14 schState ... 1630
42.5 CDCP configuration procedures ... 1630
42.5.1 SetSVIDRequest (OperRole, AdminSVIDWants, OperSVIDList) ... 1630
42.5.2 RxSVIDConfig (OperSVIDList, LastRemoteSVIDList) ... 1631
42.5.3 TxSVIDConfig (OperChnCap, RemoteChnCap, LastLocalSVIDPool, RemoteSVIDList, OperSVIDList) ... 1631

43. Edge Control Protocol (ECP) ... 1632

43.1 ECP operation ... 1632
43.2 Edge Control Sublayer Service (ECSS) ... 1633
43.3 ECP state machines ... 1633
43.3.1 State machine conventions ... 1633
43.3.2 Overview ... 1633
43.3.3 Edge Control Protocol Data Unit (ECPDU) ... 1634
43.3.4 ECP transmit state machine ... 1635
43.3.5 ECP receive state machine ... 1636
43.3.6 ECP state machine timers ... 1636
43.3.7 ECP state machine variables and parameters ... 1637
43.3.8 ECP state machine procedures ... 1638

44. Equal Cost Multiple Paths (ECMP) ... 1639

44.1 SPBM ECMP ... 1639
44.1.1 ECMP Operation ... 1639

44.1.2 ECMP ECT Algorithm 1640
44.1.3 Loop prevention for ECMP 1642
44.2 Support for Flow Filtering 1642
44.2.1 Flow filtering tag (F-TAG) 1643
44.2.2 F-TAG processing 1644
44.2.3 Forwarding process extension for flow filtering 1645
44.2.4 TTL Loop mitigation 1646
44.2.5 CFM for ECMP with flow filtering 1646
44.2.6 Operation with selective support for flow filtering 1648

45. Path Control and Reservation (PCR) 1649

45.1 Explicit trees 1649
45.1.1 Tree structures 1653
45.1.2 Explicit ECT Algorithms 1654
45.1.3 ISIS-PCR VLAN configuration 1656
45.1.4 Use of VIDs for strict explicit trees 1660
45.1.5 MAC addresses and ISIS-PCR 1661
45.1.6 Filtering Database entries for explicit trees 1661
45.1.7 ISIS-PCR support 1662
45.1.8 Attributes for path computation 1662
45.1.9 Topology sub-TLV 1664
45.1.10 Hop sub-TLV 1667
45.1.11 Administrative Group sub-TLV 1670
45.1.12 Bandwidth Constraint sub-TLV 1670
45.2 Reservation 1671
45.2.1 Bandwidth Assignment sub-TLV 1671
45.2.2 Timestamp sub-TLV 1673
45.2.3 Precedence ordering 1673
45.3 Redundancy 1673
45.3.1 Loop-free alternates for unicast data flows 1674
45.3.2 Static redundant trees 1674
45.3.3 Maximally Redundant Trees (MRTs) 1675
45.3.4 MRTs with centralized GADAG computation 1678

Annex A (normative) PICS proforma—Bridge implementations 1682

Annex B (normative) PICS proforma—End station implementations 1748

Annex C (normative) Designated MSRP Node (DMN) Implementations 1763

Annex D (normative) IEEE 802.1 Organizationally Specific TLVs 1780

Annex E (normative) Notational conventions used in state diagrams 1896

Annex F (informative) Shared and Independent VLAN Learning (SVL and IVL) 1898

Annex G (informative) MAC method-dependent aspects of VLAN support 1907

Annex H (informative) Interoperability considerations 1911

Annex I (informative) Priority and drop precedence 1917

Annex J (informative) CFM protocol design and use 1925

Annex K (informative) TPMR use cases 1933

Annex L (informative) Operation of the credit-based shaper algorithm 1938

Annex M (normative) Support for PFC in link layers without MAC Control 1955

Annex N (informative) Buffer requirements for PFC 1956

Annex O (informative) Preserving the integrity of FCS fields in MAC Bridges 1961

Annex P (informative) Frame duplication and misordering 1968

Annex Q (informative) Traffic scheduling 1971

Annex R (informative) Preemption and IEEE 802.1AE MAC Security 1975

Annex S (informative) Preemption and scheduled traffic 1977

Annex T (informative) Cyclic queuing and forwarding 1980

Annex U (informative) Bibliography 1988

Figures

Figure 6-1—Internal organization of the MAC sublayer 128
Figure 6-2—Provider Instance Ports (PIPs) 146
Figure 6-3—B-Component CBP 149
Figure 6-4—Example of operation of Port-and-Protocol-based classification 153
Figure 6-5—Service access priority selection 155
Figure 6-6—Two back-to-back EISS Multiplex Entities 161
Figure 6-7—Two back-to-back Backbone Service Instance Multiplex Entities 162
Figure 6-8—Backbone Service Instance Multiplex Entities with example CFM shims 163
Figure 6-9—Two back-to-back Up and Down TESI Multiplex Entities 165
Figure 6-10—Supporting the ISS with signaled priority 167
Figure 6-11—Two back-to-back Up and Down Infrastructure Segment Multiplex Entities 168
Figure 7-1—VLAN Bridging overview 170
Figure 8-1—A Bridged Network 176
Figure 8-2—VLAN Bridge architecture 178
Figure 8-3—MAC Bridge architecture 179
Figure 8-4—Relaying MAC frames 181
Figure 8-5—Observation of network traffic 181
Figure 8-6—Operation of Spanning Tree Protocol Entity 182
Figure 8-7—Operation of MRP 182
Figure 8-8—Management Port transmission and reception 183
Figure 8-9—Infrastructure Segment MEP placement in a PNP 183
Figure 8-10—Bridge Port Transmit and Receive 186
Figure 8-11—TPMR Port Transmit and Receive 186
Figure 8-12—Forwarding process functions 188
Figure 8-13—Per-stream filtering and policing 194
Figure 8-14—Transmission selection with gates 203
Figure 8-15—Scheduled traffic state machines—overview and relationships 206
Figure 8-16—Cycle Timer state machine 206
Figure 8-17—List Execute state machine 208
Figure 8-18—List Config state machine 209
Figure 8-19—Logical points of attachment of the Higher Layer and Relay Entities 238
Figure 8-20—Effect of control information on the forwarding path 238
Figure 8-21—Per-Port points of attachment 239
Figure 8-22—Single point of attachment—relay permitted 239
Figure 8-23—Single point of attachment—relay not permitted 240
Figure 8-24—Effect of Port State 240
Figure 8-25—Controlled and Uncontrolled Port connectivity 241
Figure 8-26—Ingress/egress control information in the forwarding path 241
Figure 9-1—VLAN TCI format 246
Figure 9-2—I-TAG TCI format 247
Figure 10-1—Example—Attribute value propagation from one station 250
Figure 10-2—Example—Attribute value propagation from two stations 251
Figure 10-3—Example—Registrations as pointers to the sources of declarations 251
Figure 10-4—MRP architecture 253
Figure 10-5—Format of the major components of an MRPDU 276
Figure 10-6—Operation of MMRP for a single VLAN Context 282
Figure 10-7—Example Directed Graph 283
Figure 10-8—Example of MMRP propagation in a VLAN Context 285
Figure 11-1—Operation of MVRP 293
Figure 12-1—Relationships among CFM managed objects 354
Figure 12-2—Relationship among BEB managed objects 371

Figure 12-3—SPB managed objects (MOs) 425
Figure 12-4—Relationships among EVB Bridge managed objects 441
Figure 12-5—Relationship among EVB station managed objects 442
Figure 12-6—Timing points for scheduled traffic 458
Figure 12-7—Timing points for PSFP 465
Figure 13-1—Diagrammatic conventions for spanning tree topologies 472
Figure 13-2—Physical topology and active topology 473
Figure 13-3—Port Roles and Port States 473
Figure 13-4—A Backup Port 474
Figure 13-5—“Ring Backbone” example 474
Figure 13-6—An MST Bridge network 476
Figure 13-7—CIST Priority Vectors, Port Roles, and MST Regions 477
Figure 13-8—MSTI Active Topology in Region 2 478
Figure 13-9—CIST and MSTI active topologies in Region 1 of the example network 491
Figure 13-10—Agreements and Proposals 495
Figure 13-11—CIST and MSTI Active Topologies in Region 2 of Figure 13-6 496
Figure 13-12—Enhanced Agreements 497
Figure 13-13—Spanning tree protocol state machines—overview and relationships 508
Figure 13-14—MSTP overview notation 509
Figure 13-15—Port Timers state machine 539
Figure 13-16—Port Receive state machine 539
Figure 13-17—Port Protocol Migration state machine 540
Figure 13-18—Bridge Detection state machine 540
Figure 13-19—Port Transmit state machine 541
Figure 13-20—Port Information state machine 542
Figure 13-21—Port Role Selection state machine 543
Figure 13-22—Disabled Port role transitions 544
Figure 13-23—Port Role Transitions state machine—MasterPort 545
Figure 13-24—Port Role Transitions state machine—RootPort 546
Figure 13-25—Port Role Transitions state machine—DesignatedPort 547
Figure 13-26—Port Role Transitions state machine—AlternatePort and BackupPort 548
Figure 13-27—Port State Transition state machine 548
Figure 13-28—Topology Change state machine 550
Figure 13-29—L2 Gateway Port Receive state machine 551
Figure 14-1—RST, MST, SPT, and STP Configuration BPDU format 555
Figure 14-2—STP TCN BPDU format 555
Figure 14-3—MSTI Configuration Message parameters and format 560
Figure 15-1—Internal organization of the MAC sublayer in a PBN 563
Figure 15-2—Port-based service interface to a PBN 564
Figure 15-3—Port-based service interface to a PBN 565
Figure 15-4—C-tagged service interface to a PBN 565
Figure 15-5—C-tagged service interface to a PBN 565
Figure 15-6—Customer Edge Ports (CEPs) 566
Figure 15-7—S-tagged service interface to a PBN 566
Figure 15-8—S-tagged interface to a PBN 567
Figure 15-9—RCSIs to a PBN 567
Figure 15-10—Remote Customer Access Ports (RCAPs) 568
Figure 15-11—C-tagged RCSI to a PBN 569
Figure 15-12—Port-based RCSI to a PBN 569
Figure 15-13—Provider Network Port (PNP) interface 570
Figure 16-1—PBN with interface examples 573
Figure 16-2—Examples of remote customer service access via a second PBN 575
Figure 16-3—Access service separation and “Hairpin Switching” 576
Figure 17-1—C-VLAN component internal LAN managed system 638

Figure 17-2—I/B-component internal LAN managed system 643
Figure 18-1—One Maintenance Domain: operator's view 1222
Figure 18-2—One service instance: operator's view 1223
Figure 18-3—One service instance: customer's view 1223
Figure 18-4—MEP and MIP Symbols 1224
Figure 18-5—MAs: one service instance in a provider network 1225
Figure 18-6—MAs: Expansion of Figure 18-5 1226
Figure 18-7—MEPs, MIPs, and MD Levels 1227
Figure 19-1—CFM Protocol shims 1228
Figure 19-2—MA Endpoint (MEP) 1231
Figure 19-3—MIP Half Function (MHF) 1237
Figure 19-4—LOM shim 1239
Figure 19-5—LOM architecture 1239
Figure 20-1—MEP state machines—overview and relationships 1252
Figure 20-2—MEP Continuity Check Initiator state machine 1259
Figure 20-3—MHF Continuity Check Receiver state machine 1260
Figure 20-4—MEP Continuity Check Receiver state machine 1264
Figure 20-5—Remote MEP state machine 1266
Figure 20-6—Remote MEP Error state machine 1267
Figure 20-7—MEP Cross Connect state machine 1268
Figure 20-8—MEP Traffic Field Mismatch state machine 1270
Figure 20-9—MEP Local Mismatch state machine 1270
Figure 20-10—MP Loopback Responder state machine 1272
Figure 20-11—MEP Loopback Initiator transmit state machine 1275
Figure 20-12—MEP Loopback Initiator receive state machine 1276
Figure 20-13—MEP Fault Notification Generator state machine 1278
Figure 20-14—MEP Mismatch Fault Notification Generator state machine 1280
Figure 20-15—MEP Linktrace Initiator receive state machine 1285
Figure 20-16—Linktrace Responder, MEPs, MHFs, and LOMs 1287
Figure 20-17—LTM Receiver state machine 1292
Figure 20-18—LTR Transmitter state machine 1293
Figure 22-1—MEPs and MIPs distinguished by VID (incomplete picture) 1324
Figure 22-2—Alternate view of Forwarding process 1325
Figure 22-3—Combining per-VLAN MPs into two shims 1326
Figure 22-4—More complete picture of MP placement in a Bridge Port 1327
Figure 22-5—Service instance spanning two Bridges protected by Up MPs 1329
Figure 22-6—Service instance spanning two Bridges protected by Down MPs 1329
Figure 22-7—MP placement in a non-VLAN-aware Bridge Port 1331
Figure 22-8—MP placement relative to other standards 1332
Figure 22-9—Creating MEPs and MIPs 1335
Figure 22-10—CFM in a Provider Edge Bridge C-tagged service interface 1341
Figure 22-11—CFM in a Provider Edge Bridge C-tagged RCSI 1343
Figure 22-12—Up MEPs in a Management Port 1344
Figure 22-13—CFM in the enterprise environment 1345
Figure 22-14—CFM on a Bridge that implements IEEE Std 802.1Q-2005 1346
Figure 23-1—TPMR connecting two Bridge Ports 1347
Figure 23-2—TPMR chain connecting Bridge Ports 1347
Figure 23-3—MSSs and the MSPE 1349
Figure 23-4—Adding connectivity 1351
Figure 23-5—Losing connectivity 1352
Figure 23-6—TPMR recovery 1353
Figure 23-7—Notification from one end of the link to the other 1354
Figure 23-8—Immediate MAC status notification at the end of a link 1354
Figure 23-9—MSPE state machine overview 1355

Figure 23-10—Status Transition state machine (STM) 1359
Figure 23-11—Status Notification state machine (SNM) 1360
Figure 23-12—MSPDU structure 1362
Figure 25-1—Internal organization of the MAC sublayer in a PBBN 1366
Figure 25-2—PBB terminology 1367
Figure 25-3—Customer service interface types 1368
Figure 25-4—Port-based service interface 1369
Figure 25-5—Port-based interface equipment 1370
Figure 25-6—Encapsulated service frames at ISS 1371
Figure 25-7—S-tagged service interface 1371
Figure 25-8—S-tagged service interface equipment 1372
Figure 25-9—I-tagged service interface 1373
Figure 25-10—I-tagged service interface equipment 1373
Figure 25-11—S-tagged and Port-based service interface access classifications 1376
Figure 25-12—I-tagged service interface access protection classifications 1377
Figure 25-13—Internal organization of the MAC sublayer in a PBB-TE Region 1379
Figure 25-14—PBB-TE Region 1381
Figure 25-15—Transparent service interface 1383
Figure 25-16—Transparent service interface equipment 1383
Figure 26-1—PBBN example 1385
Figure 26-2—CFM shim model 1392
Figure 26-3—CFM example applied to a Port-based and S-tagged service interface 1393
Figure 26-4—CFM example applied to an I-tagged Service Interface 1394
Figure 26-5—CFM example applied to a hierarchal E-NNI, CBP-PIP Demarc 1395
Figure 26-6—CFM example applied to a peer E-NNI, CBP-PIP 1396
Figure 26-7—Independent ESPs using the same ESP-DAs and ESP-VIDs 1400
Figure 26-8—PBB-TE MEP placement in a CBP 1401
Figure 26-9—Independent Infrastructure Segments distinguished by SMP-SA 1404
Figure 26-10—Infrastructure Segment MEP placement in a PNP 1405
Figure 26-11—Protection switching architecture 1406
Figure 26-12—PBB-TE point-to-point protection switching 1408
Figure 26-13—Mapping data traffic to the protection entity 1409
Figure 26-14—Relationships of the Protection switching state machines—overview 1410
Figure 26-15—Hold-off state machine 1414
Figure 26-16—Clear Manual Switch state machine 1414
Figure 26-17—Service Mapping state machine 1415
Figure 26-18—Segment terminology and properties 1416
Figure 26-19—Infrastructure Segment monitoring 1417
Figure 26-20—Working Segment and Protection Segment 1417
Figure 26-21—Nested IPGs 1418
Figure 26-22—IPS Control entity 1420
Figure 26-23—M:1 IPS 1422
Figure 26-24—M:1 IPS state machines 1423
Figure 26-25—M:1 Hold-off state machine 1426
Figure 26-26—Protection Segment Selection state machine 1427
Figure 27-1—Configuring VLAN support in an SPT Region (example) 1434
Figure 27-2—SPBM group MAC address—general format 1445
Figure 27-3—SPBM group MAC addresses—source rooted SPT 1446
Figure 27-4—SPBM group MAC addresses—shared tree 1446
Figure 27-5—SPBM MEP placement in a CBP 1449
Figure 27-6—SPBV campus network example 1451
Figure 27-7—SPT Bridge Network using SPBM example 1453
Figure 28-1—Agreement Digest field format 1458
Figure 28-2—MT-Capability TLV 1468

Figure 28-3—SPB MCID sub-TLV 1468
Figure 28-4—SPB Digest sub-TLV 1469
Figure 28-5—SPB Base VLAN-Identifiers sub-TLV 1470
Figure 28-6—SPB Instance sub-TLV 1471
Figure 28-7—SPB Instance Opaque ECT-ALGORITHM sub-TLV 1473
Figure 28-8—ECMP ECT-ALGORITHM sub-TLV 1474
Figure 28-9—SPB Link Metric sub-TLV 1474
Figure 28-10—SPB Adjacency Opaque ECT-ALGORITHM sub-TLV 1475
Figure 28-11—SPBV MAC Address sub-TLV 1476
Figure 28-12—SPBM Service Identifier and Unicast Address sub-TLV 1477
Figure 29-1—Forward path test (FPT) 1481
Figure 29-2—Return path test (RPT) 1482
Figure 29-3—Combination of FPT and RPT 1483
Figure 29-4—Detailed functions of RR 1484
Figure 29-5—RFM Receiver on an non-MP 1487
Figure 29-6—Return Path DR 1488
Figure 29-7—RR Filter state machine 1493
Figure 29-8—RR Encapsulation state machine 1494
Figure 29-9—RR Transmit state machine 1494
Figure 29-10—RFM Receiver state machine 1496
Figure 29-11—Decapsulator Responder state machine 1498
Figure 30-1—Congestion detection in QCN CP 1505
Figure 30-2—Sampling (reflection) probability in QCN CP as a function of |Fb| 1505
Figure 30-3—QCN RP operation 1506
Figure 30-4—Byte Counter and Timer interaction with Rate Limiter 1508
Figure 30-5—CP–RP peering in VLAN Bridged Network 1510
Figure 30-6—CP–RP peering in PBBN 1511
Figure 31-1—CPs and congestion-aware queues in a Bridge 1512
Figure 31-2—Congestion-aware queue functions in an end station 1514
Figure 31-3—Per-CNPV station function 1516
Figure 32-1—CND defense state machine 1529
Figure 32-2—RP rate control state machine 1541
Figure 32-3—CP–RP peering in any hierarchical Bridged Network 1542
Figure 34-1—Queuing model for a Talker station 1553
Figure 35-1—Operation of MSRP 1556
Figure 35-2—Format of the components of the reservation FirstValue fields 1566
Figure 35-3—Format of the components of the Domain FirstValue 1571
Figure 36-1—PFC peering 1583
Figure 36-2—PFC Receiver state diagram for priority n 1585
Figure 36-3—PFC-aware system queue functions 1587
Figure 36-4—PFC-aware system queue functions with Link Aggregation 1588
Figure 38-1—DCBX Asymmetric state machine 1593
Figure 38-2—Symmetric state machine 1594
Figure 39-1—Operation of MIRP in an I-component 1596
Figure 39-2—Operation of MIRP in a B-component 1596
Figure 39-3—Alternate model for MIRP in a B-component 1601
Figure 40-1—EVB architecture overview 1603
Figure 40-2—EVB architecture without S-channels 1605
Figure 40-3—EVB archichtecture with S-channel 1605
Figure 40-4—EVB components and internal LANs with S-channels 1606
Figure 40-5—EVB architecture without S-channels, with EVB Bridge S-VLAN component 1608
Figure 40-6—EVB architecture without S-channels, with EVB station S-VLAN component 1608
Figure 41-1—VSI manager ID TLV 1610
Figure 41-2—VDP association TLV 1611

Figure 41-3—VID Filter Info format 1615
Figure 41-4—MAC/VID filter format 1615
Figure 41-5—GroupID/VID filter format 1616
Figure 41-6—GroupID/MAC/VID filter format 1616
Figure 41-7—Organizationally defined TLV 1618
Figure 41-8—Bridge VDP state machine 1619
Figure 41-9—Station VDP state machine 1620
Figure 42-1—CDCP state machine—Station role 1627
Figure 42-2—CDCP state machine—Bridge role 1628
Figure 43-1—Example ECP exchange 1632
Figure 43-2—ECPDU structure 1634
Figure 43-3—ECP transmit state machine 1635
Figure 43-4—ECP receive state machine 1636
Figure 44-1—Flow FilteringTCI format 1643
Figure 44-2—SPBM VID MEP and ECMP path MEP placement in a CBP 1647
Figure 45-1—An SPT Region controlled by a single PCE 1650
Figure 45-2—An SPT Region controlled by multiple PCEs 1651
Figure 45-3—The use of the SPB Instance sub-TLV for MRT 1659
Figure 45-4—Shared Risk Link Group (SRLG) TLV 1663
Figure 45-5—Topology sub-TLV 1664
Figure 45-6—A strict tree and its descriptor Topology sub-TLV 1665
Figure 45-7—Topology sub-TLV of a loose tree 1666
Figure 45-8—Hop sub-TLV 1667
Figure 45-9—Administrative Group sub-TLV 1670
Figure 45-10—Bandwidth Constraint sub-TLV 1671
Figure 45-11—Bandwidth Assignment sub-TLV 1672
Figure 45-12—Timestamp sub-TLV 1673
Figure 45-13—A GADAG and its descriptor Topology sub-TLV 1679
Figure 45-14—MRT-Blue and MRT-Red for MRT Root 55 1679
Figure 45-15—A GADAG for a topology with multiple blocks 1680
Figure C-1—CSN backbone 1763
Figure C-2—Bridge's CSN model for bandwidth reservation 1764
Figure C-3—Talker MSRPDU flow 1765
Figure C-4—Listener MSRPDU flow 1765
Figure C-5—IEEE DMN Device Attribute IE 1767
Figure C-6—DMN Confirmation Transaction 1769
Figure C-7—Bandwidth reservation—bridge model for IEEE 802.11 BSS (STA downstream Port) 1772
Figure C-8—Bandwidth reservation—bridge model for IEEE 802.11 BSS (STA upstream Port) 1772
Figure C-9—Bandwidth reservation—bridge model for IEEE 802.11 BSS (direct link setup) 1773
Figure C-10—MSRP/IEEE 802.11 query flows 1773
Figure C-11—MSRP/802.11 Talker STA to Listener STA reservation flows 1774
Figure C-12—MSRP/802.11 "Bridged" Listener to Talker STA reservation flows 1775
Figure C-13—MSRP/802.11 Listener STA to "Bridged" Talker reservation flows 1775
Figure D-1—Port VLAN ID TLV format 1781
Figure D-2—Port And Protocol VLAN ID TLV format 1781
Figure D-3—VLAN Name TLV format 1782
Figure D-4—Protocol Identity TLV format 1783
Figure D-5—VID Usage Digest TLV format 1784
Figure D-6—Management VID TLV format 1784
Figure D-7—Congestion Notification TLV format 1785
Figure D-8—ETS Configuration TLV format 1786
Figure D-9—ETS Recommendation TLV format 1788
Figure D-10—Priority-based Flow Control Configuration TLV format 1789
Figure D-11—Application Priority TLV format 1790

Figure D-12—EVB TLV format 1792
Figure D-13—CDCP TLV structure 1795
Figure D-14—Application VLAN TLV format 1797
Figure F-1—Connecting independent VLANs—1 1899
Figure F-2—Connecting independent VLANs—2 1900
Figure F-3—Duplicate MAC addresses 1900
Figure F-4—Asymmetric VID use: “multi-netted server” 1901
Figure F-5—Asymmetric VLAN use: “Rooted-Multipoint” 1903
Figure F-6—Rooted-Multipoint with tagged interfaces 1904
Figure F-7—SPBV VLAN Shared Learning and VID Translation 1905
Figure G-1— Example of IEEE 802.3 MAC frame format..... 1907
Figure G-2—Methods for Bridge access to IEEE 802.11 and PMPN media: example 1910
Figure H-1—Static filtering inconsistency 1913
Figure H-2—Interoperability with MAC Bridges: example 1 1914
Figure H-3—Interoperability with MAC Bridges: example 2 1915
Figure H-4—Interoperability between Port-based and Port-and-Protocol-based classification 1916
Figure J-1—Up MPs in a CFM Port 1930
Figure K-1—TPMR as UNI demarcation device 1933
Figure K-2—TPMRs with aggregated links 1934
Figure K-3—Multiple TPMRs 1934
Figure K-4—Recovery at the end of a chain 1935
Figure K-5—Near simultaneous recoveries 1936
Figure K-6—Near simultaneous failure and recovery 1936
Figure K-7—Loss with quick recovery 1937
Figure L-1—Credit-based shaper operation—no conflicting traffic 1940
Figure L-2—Credit-based shaper operation–conflicting traffic 1941
Figure L-3—Credit-based shaper operation—burst traffic 1942
Figure L-4—Interference and latency 1946
Figure L-5—Burst behavior and credit 1946
Figure L-6—Fan-in scenario 1950
Figure L-7—Permanent delay scenario 1951
Figure L-8—Building up buffer occupancy—1 1952
Figure L-9—Building up buffer occupancy—2 1952
Figure L-10—Building up buffer occupancy—3 1952
Figure L-11—Building up buffer occupancy—4 1953
Figure M-1—PFC PDU format 1955
Figure N-1—PFC delays 1956
Figure N-2—Delay model 1957
Figure N-3—Worst-case delay 1958
Figure O-1—Converting a CRC to an FCS 1963
Figure O-2—Detection Lossless Circuit 1963
Figure O-3—Field change adjustment 1965
Figure O-4—Field insertion adjustment 1966
Figure P-1—Frame duplication scenario 1969
Figure P-2—Frame misordering scenario 1970
Figure Q-1—Establishing a guard band 1972
Figure Q-2—Using gate operations 1973
Figure T-1—Example PSFP configuration for QCF 1983
Figure T-2—Traffic scheduling example for CQF 1984
Figure T-3—Example PSFP configuration with two values of T 1985
Figure T-4—Traffic scheduling example with two values of T 1985
Figure T-5—Interleaving example—factor of 2 1986

Tables

Table 6-1—Bridge transit delay 135
Table 6-2—Priority Code Point encoding 143
Table 6-3—Priority Code Point decoding 143
Table 6-4—Priority regeneration 144
Table 6-5—Default SRP domain boundary port priority regeneration override values 145
Table 6-6—Service Access Priority 156
Table 6-7—Encapsulated Addresses EtherType 163
Table 8-1—C-VLAN and MAC Bridge component Reserved addresses 191
Table 8-2—S-VLAN component Reserved addresses 192
Table 8-3—TPMR component Reserved addresses 192
Table 8-4—Stream gate control operations 197
Table 8-5—Recommended priority to traffic class mappings 198
Table 8-6—Transmission selection algorithm identifiers 200
Table 8-7—Gate operations 204
Table 8-8—Scheduled Traffic and PSFP procedures/variables 213
Table 8-9—Ageing time parameter value 216
Table 8-10—Combining Static and Dynamic Filtering Entries for an individual MAC address 226
Table 8-11—Combining Static Filtering Entry and MAC Address Registration Entry for "All Group Addresses" and "All Unregistered Group Addresses" 227
Table 8-12—Forwarding or Filtering for specific group MAC addresses 228
Table 8-13—Forwarding or Filtering with Dynamic Reservation Entries 229
Table 8-14—Determination of whether a Port is in a VID's member set 229
Table 8-15—Standard LLC address assignment 234
Table 8-16—ISIS-SPB reserved addresses 236
Table 8-17—ISIS-SPB Recommended Address Usage 236
Table 8-18—CCM group destination MAC addresses 243
Table 8-19—LTM group destination MAC addresses 243
Table 9-1—IEEE 802.1Q™ EtherType allocations 246
Table 9-2—Reserved VID values 246
Table 9-3—Reserved I-SID values 248
Table 10-1—MRP application addresses 256
Table 10-2—MRP EtherType values 257
Table 10-3—Applicant state table 270
Table 10-4—Registrar state table 271
Table 10-5—LeaveAll state table 272
Table 10-6—PeriodicTransmission state table 272
Table 10-7—MRP timer parameter values 273
Table 12-1—Component table entry managed object 304
Table 12-2—Port table entry 306
Table 12-3—ISS Port Number table entry 307
Table 12-4—Bandwidth Availability Parameter Table row elements 411
Table 12-5—Transmission Selection Algorithm Table row elements 412
Table 12-6—Priority Regeneration Override Table row elements 412
Table 12-7—CN component managed object row elements 413
Table 12-8—CN component priority managed object row elements 414
Table 12-9—CN Port priority managed object row elements 415
Table 12-10—Congestion Point managed object row elements 415
Table 12-11—Reaction Point port priority managed object row elements 416
Table 12-12—Reaction Point group managed object row elements 416
Table 12-13—SRP Bridge Base Table row elements 417
Table 12-14—SRP Bridge Port Table row elements 418

Table 12-15—SRP Latency Parameter Table row elements 418
Table 12-16—SRP Stream Table row elements 418
Table 12-17—SRP Reservations Table row elements 419
Table 12-18—Priority-based Flow Control objects 420
Table 12-19—EVB system base table 444
Table 12-20—EVB system parameter defaults 445
Table 12-21—SBP table entry 446
Table 12-22—VSI table entry 446
Table 12-23—VSI MAC/VLAN table entry 447
Table 12-24—UAP table entry 448
Table 12-25—UAP table entry parameters 449
Table 12-26—S-channel interface table entry 449
Table 12-27—URP table entry 450
Table 12-28—ECP table entry 451
Table 12-29—The Gate Parameter Table 456
Table 12-30—Frame Preemption Parameter table 459
Table 12-31—The Stream Parameter Table 461
Table 12-32—Stream Filter Instance Table 461
Table 12-33—The Stream Gate Instance Table 463
Table 12-34—The Flow Meter Instance Table 466
Table 13-1—Configuration Digest Signature Key 482
Table 13-2—Sample Configuration Digest Signature Keys 483
Table 13-3—Bridge and Port Priority values 501
Table 13-4—Port Path Cost values 502
Table 13-5—Timer and related parameter values 510
Table 17-1—Structure of the MIB modules 579
Table 17-2—IEEE8021-TC-MIB structure 581
Table 17-3—IEEE8021-BRIDGE-MIB structure and relationship to IETF RFC 4188 and this standard 582
Table 17-4—IEEE 802.1D objects not in the IEEE8021-BRIDGE-MIB 586
Table 17-5—IEEE8021-SPANNING-TREE MIB structure and relationship to IETF RFC 4318 and this standard 586
Table 17-6—Clause 12 objects not in the IEEE8021-SPANNING-TREE MIB 588
Table 17-7—IEEE8021-QBRIDGE MIB structure and relationship to IETF RFC 4363 and this standard 589
Table 17-8—Clause 12 management not in IEEE8021-Q-BRIDGE-MIB 594
Table 17-9—IEEE8021-PB-MIB structure and relationship to this standard 594
Table 17-10—IEEE8021-MSTP-MIB structure and relationship to this standard 596
Table 17-11—IEEE8021-CFM-MIB correspondence between variables, managed objects, and MIB objects 599
Table 17-12—IEEE8021-CFM-V2-MIB correspondence between variables, managed objects, and MIB objects 603
Table 17-13—IEEE8021-PBB-MIB structure and relationship to this standard 605
Table 17-14—IEEE8021-DDCFM-MIB structure and relationship to this standard 608
Table 17-15—IEEE8021-PBBTE-MIB Structure and relationship to this standard 610
Table 17-16—Example of ieee8021PbbTeTeSiEspTable 611
Table 17-17—IEEE8021-TPMR-MIB Structure and relationship to this standard 613
Table 17-18—FQTSS MIB structure and object cross reference 614
Table 17-19—Variables, managed object tables, and MIB objects 615
Table 17-20—SRP MIB structure and object cross reference 617
Table 17-21—IEEE8021-MVRPX-MIB structure and relationship to this standard 619
Table 17-22—IEEE8021-MIRP-MIB structure and relationship to this standard 619
Table 17-23—Variables, managed object tables, and MIB objects 620
Table 17-24—IEEE8021-TEIPS MIB structure and relationship to this standard 620

Table 17-25—IEEE8021-SPB-MIB structure and relationship to this standard 622
Table 17-26—EVB MIB structure and object cross reference 626
Table 17-27—IEEE8021-ECMP-MIB structure and relationship to this standard 630
Table 17-28—IEEE8021-ST-MIB structure and relationship to this standard 631
Table 17-29—IEEE8021-Preemption-MIB Structure and relationship to this standard 632
Table 17-30—IEEE8021-PSFP-MIB Structure and relationship to this standard 633
Table 17-31—PBB-TE required MIB compliances 644
Table 17-32—Sensitive managed objects: tables and notifications 652
Table 17-33—Sensitive managed objects: variables in dot1agCfmMdTable 652
Table 17-34—Sensitive managed objects (of DDCFM): tables and notifications 654
Table 17-35—Sensitive managed objects (of DDCFM) for read 654
Table 17-36—Sensitive managed objects (of EVB): tables and notifications 661
Table 17-37—Sensitive managed objects (of EVB) for read 661
Table 17-38—Provider Bridge service interface parameters 677
Table 17-39—PBB service interface parameters 681
Table 19-1—Actions taken by MP OpCode Demultiplexers 1233
Table 19-2—SAP use for LTMs and LTRs 1240
Table 20-1—Fault Alarm defects and priorities 1245
Table 20-2—Deriving enableRmepDefect and Port Status TLV in a Bridge 1255
Table 21-1—CFM PDU Encapsulation EtherType 1299
Table 21-2—Common CFM Header format 1301
Table 21-3—OpCode Field range assignments 1301
Table 21-4—TLV format 1302
Table 21-5—Type Field values 1302
Table 21-6—Organization-Specific TLV format 1303
Table 21-7—Sender ID TLV format 1304
Table 21-8—Port Status TLV format 1306
Table 21-9—Port Status TLV values 1306
Table 21-10—Interface Status TLV format 1306
Table 21-11— Interface Status TLV values 1306
Table 21-12—Data TLV format 1307
Table 21-13—End TLV format 1307
Table 21-14—CCM format 1308
Table 21-15—CCM Interval field encoding 1309
Table 21-16—CCM Maintenance Association Identifier field format: Maintenance Domain present 1310
Table 21-17—CCM Maintenance Association Identifier field format: Maintenance Domain not present 1310
Table 21-18—Maintenance Domain Name Format 1311
Table 21-19—Short MA Name Format 1312
Table 21-20—LBM and LBR formats 1313
Table 21-21—PBB-TE MIP TLV format 1314
Table 21-22—LTM format 1315
Table 21-23—LTM Flags field 1315
Table 21-24—LTM Egress Identifier TLV format 1317
Table 21-25—LTR format 1317
Table 21-26—LTR Flags field 1317
Table 21-27—Relay Action field values 1318
Table 21-28—LTR Egress Identifier TLV format 1319
Table 21-29—Reply Ingress TLV format 1319
Table 21-30—Ingress Action field values 1320
Table 21-31—Reply Egress TLV format 1321
Table 21-32—Egress Action field values 1321
Table 22-1—MEP creation 1335
Table 22-2—MIP creation 1336

Table 22-3—Bandwidth required for CCMs for 1 MA 1339
Table 22-4—Bandwidth required for CCMs for 1000 MAs 1340
Table 23-1—Time sequence diagram symbols 1350
Table 23-2—MSP performance parameters 1356
Table 23-3—MSP EtherType assignment 1362
Table 23-4—MSP Packet Types 1363
Table 24-1—Transmission and reception delays 1365
Table 26-1—Backbone Service Instance Group address OUI 1388
Table 26-2—Protection Requests Hierarchy 1411
Table 27-1—Allocation of VIDs to FIDs and FIDs to MSTIDs in an SPT Region (example) 1434
Table 28-1—Bridge Priority Masking 1463
Table 29-1—RFM format 1499
Table 29-2—SFM format 1500
Table 32-1—LLDP instance selection managed object overrides 1522
Table 32-2—CND defense mode selection managed object overrides 1522
Table 32-3—Determining cnpdIsAdminDefMode and cnpdDefenseMode 1528
Table 32-4—Correspondence of QCN and CCF message fields 1530
Table 32-5—NewCpSampleBase() return value as a function of cpFb 1533
Table 33-1—CN-TAG Encapsulation 1545
Table 33-2—CNM Encapsulation 1545
Table 33-3—Congestion Notification Message PDU 1546
Table 34-1—Recommended priority to traffic class mappings for SR classes A and B 1552
Table 34-2—Recommended priority to traffic class mappings for SR class B only 1552
Table 35-1—AttributeType Values 1563
Table 35-2—AttributeLength Values 1563
Table 35-3—FourPackedEvent Values 1564
Table 35-4—MSRP FirstValue NumberOfValues example 1565
Table 35-5—TSpec components examples 1568
Table 35-6—Reservation Failure Codes 1570
Table 35-7—SR class ID 1572
Table 35-8—Summary of Talker primitives 1573
Table 35-9—Summary of Listener primitives 1574
Table 35-10—Talker attribute propagation per port 1578
Table 35-11—Incoming Listener attribute propagation per port 1579
Table 35-12—Updating Dynamic Reservation Entries 1580
Table 35-13—Updating operIdleSlope(N) 1580
Table 35-14—Listener Declaration Type Summation 1580
Table 41-1—VDP TLV types 1611
Table 41-2—Flag values in VDP requests 1612
Table 41-3—Error types in VDP responses 1612
Table 41-4—Flag values in VDP responses 1613
Table 41-5—VSIID format values 1613
Table 41-6—Filter Info format values 1614
Table 43-1—ECP subtypes 1634
Table 44-1—ECMP ECT-ALGORITHM values 1642
Table 44-2—F-TAG EtherType 1643
Table 45-1—ECT-ALGORITHM values for explicit trees 1654
Table 45-2—Bridge Priority Masking for the LT and LTS ECT Algorithms 1655
Table 45-3—Hop sub-TLV flags 1668
Table C-1—SRP to MoCA PQoS Transaction mapping 1770
Table C-2—SRP TSpec to MoCA TSPEC mapping 1771
Table C-3—SRP StreamID to MoCA PQoS Flow transaction mapping 1771
Table C-4—SRP to MLME QoS Services mapping 1777
Table C-5—EDCA-AC for AV Streams 1778

Table C-6—HCCA for AV Streams 1779
Table D-1—IEEE 802.1 Organizationally Specific TLVs 1780
Table D-2—Port and protocol capability/status 1782
Table D-3—Priority assignment table 1786
Table D-4—Traffic class bandwidth assignment table 1787
Table D-5—TSA Assignment Table 1787
Table D-6—PFC Enable bit vector 1790
Table D-7—Application Priority Table Entry format 1791
Table D-8—Sel field values 1791
Table D-9—RRSAT flag values and meanings 1793
Table D-10—EVB Mode values 1794
Table D-11—Application VLAN Table Entry format 1797
Table D-12—Sel field values 1798
Table D-13—IEEE 802.1 extension MIB object group conformance requirements 1803
Table D-14—IEEE 802.1/LLDP extension MIB object cross reference 1804
Table E-1—State machine symbols 1897
Table I-1—Traffic type to traffic class mapping 1918
Table I-2—Traffic type acronyms 1920
Table I-3—Defining traffic types 1921
Table I-4—Defining traffic types—Credit-based shaper support of SR class B only 1922
Table I-5—Defining traffic types—Credit-based shaper support of SR classes A and B 1922
Table I-6—Priority Code Point encoding 1924
Table I-7—Priority Code Point decoding 1924
Table J-1—Provider MD Level allocation 1926
Table J-2—IEEE / ITU-T terminology differences 1926
Table N-1—IEEE 802.3 Interface Delays 1959