

ISO/IEC/IEEE 8802-1Q:2020-08 (E)

Telecommunications and exchange between information technology systems - Requirements for local and metropolitan area networks - Part 1Q: Bridges and bridged networks

Contents

| | | |
|--------|--|-----|
| 1. | Overview..... | 61 |
| 1.1 | Scope..... | 61 |
| 1.2 | Purpose..... | 61 |
| 1.3 | Introduction..... | 62 |
| 2. | Normative references..... | 69 |
| 3. | Definitions..... | 73 |
| 4. | Abbreviations..... | 95 |
| 5. | Conformance..... | 101 |
| 5.1 | Requirements terminology..... | 101 |
| 5.2 | Conformant components and equipment..... | 101 |
| 5.3 | Protocol Implementation Conformance Statement (PICS)..... | 102 |
| 5.4 | VLAN Bridge component requirements..... | 102 |
| 5.4.1 | VLAN Bridge component options..... | 103 |
| 5.4.2 | Multiple VLAN Registration Protocol (MVRP) requirements..... | 108 |
| 5.4.3 | VLAN Bridge requirements for congestion notification..... | 108 |
| 5.4.4 | Multiple Stream Registration Protocol (MSRP) requirements..... | 109 |
| 5.4.5 | Shortest Path Bridging (SPB) operation (optional)..... | 109 |
| 5.4.6 | Path Control and Reservation (PCR) (optional)..... | 110 |
| 5.5 | C-VLAN component conformance..... | 111 |
| 5.5.1 | C-VLAN component options..... | 111 |
| 5.6 | S-VLAN component conformance..... | 111 |
| 5.6.1 | S-VLAN component options..... | 112 |
| 5.6.2 | S-VLAN component requirements for Provider Backbone Bridge Traffic Engineering (PBB-TE)..... | 112 |
| 5.6.3 | S-VLAN component requirements for PBB-TE IPS..... | 112 |
| 5.6.4 | S-VLAN component requirements for ECMP with flow filtering..... | 113 |
| 5.7 | I-component conformance..... | 113 |
| 5.7.1 | I-component options..... | 113 |
| 5.8 | B-component conformance..... | 113 |
| 5.8.1 | B-component options..... | 114 |
| 5.8.2 | B-component requirements for PBB-TE..... | 114 |
| 5.8.3 | B-component requirements for PBB-TE IPS..... | 114 |
| 5.8.4 | B-component requirements for ECMP with flow filtering..... | 115 |
| 5.9 | C-VLAN Bridge conformance..... | 115 |
| 5.9.1 | C-VLAN Bridge options..... | 115 |
| 5.10 | Provider Bridge conformance..... | 115 |
| 5.10.1 | S-VLAN Bridge conformance..... | 115 |
| 5.10.2 | Provider Edge Bridge conformance..... | 116 |
| 5.11 | System requirements for Priority-based Flow Control (PFC)..... | 116 |
| 5.12 | Backbone Edge Bridge (BEB) conformance..... | 116 |
| 5.12.1 | BEB requirements for PBB-TE..... | 117 |
| 5.13 | MAC Bridge component requirements..... | 117 |
| 5.13.1 | MAC Bridge component options..... | 117 |
| 5.14 | MAC Bridge conformance..... | 118 |
| 5.14.1 | MAC Bridge options..... | 118 |
| 5.15 | TPMR component conformance..... | 118 |

| | | |
|--------|--|-----|
| 5.15.1 | TPMR component options | 119 |
| 5.16 | TPMR conformance..... | 119 |
| 5.16.1 | TPMR options | 119 |
| 5.17 | T-component conformance | 119 |
| 5.17.1 | T-component options | 120 |
| 5.18 | End station requirements for MMRP, MVRP, and MSRP | 120 |
| 5.18.1 | MMRP requirements and options | 120 |
| 5.18.2 | MVRP requirements and options | 121 |
| 5.18.3 | MSRP requirements and options | 121 |
| 5.19 | VLAN-aware end station requirements for CFM | 122 |
| 5.20 | End station requirements—FQTSS | 122 |
| 5.21 | End station requirements for congestion notification | 123 |
| 5.22 | MAC-specific bridging methods | 123 |
| 5.23 | EVB Bridge requirements..... | 123 |
| 5.24 | EVB station requirements..... | 124 |
| 5.24.1 | Edge relay (ER) requirements | 125 |
| 5.25 | End station requirements—enhancements for scheduled traffic | 126 |
| 5.26 | End station requirements—enhancements for frame preemption..... | 126 |
| 5.27 | End-station requirements—PSFP | 127 |
| 5.28 | End station requirements—Cyclic queuing and forwarding..... | 127 |
| 6. | Support of the MAC Service | 128 |
| 6.1 | Basic architectural concepts and terms..... | 129 |
| 6.2 | Provision of the MAC Service..... | 129 |
| 6.2.1 | Point-to-point, multipoint-to-multipoint, and rooted-multipoint connectivity ... | 130 |
| 6.3 | Support of the MAC Service | 130 |
| 6.4 | Preservation of the MAC Service | 131 |
| 6.5 | Quality of service (QoS) maintenance..... | 131 |
| 6.5.1 | Service availability | 131 |
| 6.5.2 | Frame loss | 132 |
| 6.5.3 | Frame misordering | 132 |
| 6.5.4 | Frame duplication | 133 |
| 6.5.5 | Transit delay | 134 |
| 6.5.6 | Frame lifetime | 135 |
| 6.5.7 | Undetected frame error rate | 135 |
| 6.5.8 | Maximum Service Data Unit Size | 135 |
| 6.5.9 | Priority | 135 |
| 6.5.10 | Throughput | 136 |
| 6.6 | Internal Sublayer Service (ISS) | 137 |
| 6.7 | Support of the ISS by specific MAC procedures..... | 137 |
| 6.7.1 | Support of the ISS by IEEE Std 802.3 (Ethernet) | 137 |
| 6.7.2 | Frame preemption | 137 |
| 6.8 | Enhanced Internal Sublayer Service (EISS) | 138 |
| 6.8.1 | Service primitives | 138 |
| 6.8.2 | Status parameters | 139 |
| 6.8.3 | Point-to-point parameters | 139 |
| 6.8.4 | Control primitives and parameters | 139 |
| 6.9 | Support of the EISS | 140 |
| 6.9.1 | Data indications | 141 |
| 6.9.2 | Data requests | 142 |
| 6.9.3 | Priority Code Point encoding | 142 |
| 6.9.4 | Regenerating priority | 144 |
| 6.10 | Support of the ISS/EISS by PIPs | 145 |

| | | |
|--------|--|-----|
| 6.10.1 | Data indications | 147 |
| 6.10.2 | Data requests | 148 |
| 6.10.3 | Priority Code Point encoding | 148 |
| 6.11 | Support of the EISS by CBPs | 149 |
| 6.11.1 | Data indications | 150 |
| 6.11.2 | Data requests | 151 |
| 6.11.3 | Priority Code Point decoding | 152 |
| 6.11.4 | Regenerating priority | 152 |
| 6.12 | Protocol VLAN classification..... | 152 |
| 6.12.1 | Protocol Templates | 154 |
| 6.12.2 | Protocol Group Identifiers | 154 |
| 6.12.3 | Protocol Group Database | 154 |
| 6.13 | Support of the ISS for attachment to a PBN..... | 155 |
| 6.13.1 | Data requests | 156 |
| 6.13.2 | Data indications | 157 |
| 6.14 | Support of the ISS within a system..... | 157 |
| 6.15 | Support of the ISS by additional technologies..... | 157 |
| 6.16 | Filtering services in Bridged Networks | 158 |
| 6.16.1 | Purpose(s) of filtering service provision | 158 |
| 6.16.2 | Goals of filtering service provision | 158 |
| 6.16.3 | Users of filtering services | 159 |
| 6.16.4 | Basis of service | 159 |
| 6.16.5 | Categories of service | 159 |
| 6.16.6 | Service configuration | 159 |
| 6.16.7 | Service definition for Extended Filtering Services | 160 |
| 6.17 | EISS Multiplex Entity..... | 161 |
| 6.18 | Backbone Service Instance Multiplex Entity..... | 162 |
| 6.18.1 | Demultiplexing direction | 163 |
| 6.18.2 | Multiplexing direction | 164 |
| 6.18.3 | Priority Code Point encoding | 165 |
| 6.18.4 | Status parameters | 165 |
| 6.19 | TESI Multiplex Entity | 165 |
| 6.20 | Support of the ISS with signaled priority | 166 |
| 6.20.1 | Data indications | 167 |
| 6.20.2 | Data requests | 167 |
| 6.21 | Infrastructure Segment Multiplex Entity..... | 167 |
| 6.22 | PDU and protocol discrimination and media | 169 |
| 7. | Principles of Virtual Bridged Network operation..... | 170 |
| 7.1 | Network overview..... | 170 |
| 7.2 | Use of VLANs | 171 |
| 7.3 | Active topology..... | 171 |
| 7.4 | VLAN topology | 172 |
| 7.5 | Locating end stations | 173 |
| 7.6 | Ingress, forwarding, and egress rules..... | 174 |
| 8. | Principles of Bridge operation | 175 |
| 8.1 | Bridge operation | 175 |
| 8.1.1 | Relay | 175 |
| 8.1.2 | Filtering and relaying information | 176 |
| 8.1.3 | Duplicate frame prevention | 176 |
| 8.1.4 | Traffic segregation | 176 |
| 8.1.5 | Traffic reduction | 177 |

| | | |
|--------|---|-----|
| 8.1.6 | Traffic expediting | 177 |
| 8.1.7 | Conversion of frame formats | 177 |
| 8.2 | Bridge architecture..... | 178 |
| 8.3 | Model of operation..... | 180 |
| 8.4 | Active topologies, learning, and forwarding | 184 |
| 8.5 | Bridge Port Transmit and Receive..... | 185 |
| 8.5.1 | Bridge Port connectivity | 185 |
| 8.5.2 | TPMR Port connectivity | 186 |
| 8.5.3 | Support of Higher Layer Entities | 187 |
| 8.6 | The Forwarding Process | 187 |
| 8.6.1 | Active topology enforcement | 188 |
| 8.6.2 | Ingress filtering | 190 |
| 8.6.3 | Frame filtering | 190 |
| 8.6.4 | Egress filtering | 193 |
| 8.6.5 | Flow classification and metering | 193 |
| 8.6.6 | Queuing frames | 197 |
| 8.6.7 | Queue management | 199 |
| 8.6.8 | Transmission selection | 199 |
| 8.6.9 | Scheduled traffic state machines | 205 |
| 8.6.10 | Stream gate control state machines | 213 |
| 8.7 | The Learning Process..... | 215 |
| 8.7.1 | Default filtering utility criteria | 215 |
| 8.7.2 | Enhanced filtering utility criteria | 216 |
| 8.7.3 | Ageing of Dynamic Filtering Entries | 216 |
| 8.8 | The Filtering Database (FDB) | 217 |
| 8.8.1 | Static Filtering Entries | 220 |
| 8.8.2 | Static VLAN Registration Entries | 221 |
| 8.8.3 | Dynamic Filtering Entries | 221 |
| 8.8.4 | MAC Address Registration Entries | 222 |
| 8.8.5 | Dynamic VLAN Registration Entries | 223 |
| 8.8.6 | Default Group filtering behavior | 223 |
| 8.8.7 | Dynamic Reservation Entries | 224 |
| 8.8.8 | Allocation of VIDs to FIDs | 225 |
| 8.8.9 | Querying the FDB | 225 |
| 8.8.10 | Determination of the member set for a VID | 229 |
| 8.8.11 | Permanent Database | 230 |
| 8.8.12 | Connection_Identifier | 230 |
| 8.9 | MST, SPB, and ESP configuration information | 230 |
| 8.9.1 | MST Configuration Table | 231 |
| 8.9.2 | MST configuration identification | 231 |
| 8.9.3 | FID to MSTI Allocation Table | 232 |
| 8.9.4 | SPT Configuration Identification | 232 |
| 8.10 | Spanning Tree Protocol Entity..... | 233 |
| 8.11 | MRP entities | 233 |
| 8.12 | Bridge Management Entity..... | 233 |
| 8.13 | Addressing | 233 |
| 8.13.1 | End stations | 233 |
| 8.13.2 | Bridge Ports | 234 |
| 8.13.3 | Use of LLC by Spanning Tree Protocol Entities | 234 |
| 8.13.4 | Reserved MAC addresses | 234 |
| 8.13.5 | Group MAC addresses for spanning tree entity | 235 |
| 8.13.6 | Group MAC addresses for MRP Applications | 237 |
| 8.13.7 | Bridge Management Entities | 237 |
| 8.13.8 | Unique identification of a Bridge | 237 |

| | | |
|---------|--|-----|
| 8.13.9 | Points of attachment and connectivity for Higher Layer Entities | 238 |
| 8.13.10 | VLAN attachment and connectivity for Higher Layer Entities | 241 |
| 8.13.11 | CFM entities | 242 |
| 9. | Tagged frame format | 244 |
| 9.1 | Purpose of tagging | 244 |
| 9.2 | Representation and encoding of tag fields | 244 |
| 9.3 | Tag format..... | 245 |
| 9.4 | TPID formats | 245 |
| 9.5 | Tag Protocol identification | 245 |
| 9.6 | VLAN Tag Control Information (TCI)..... | 246 |
| 9.7 | Backbone Service Instance Tag Control Information (I-TAG TCI)..... | 247 |
| 10. | Multiple Registration Protocol (MRP) and Multiple MAC Registration Protocol (MMRP) | 249 |
| 10.1 | MRP overview | 249 |
| 10.2 | MRP architecture | 252 |
| 10.3 | MRP Attribute Propagation (MAP)..... | 253 |
| 10.3.1 | MAP Context | 254 |
| 10.4 | Requirements to be met by MRP..... | 255 |
| 10.5 | Requirements for interoperability between MRP Participants | 256 |
| 10.6 | Protocol operation..... | 257 |
| 10.7 | Protocol specification | 261 |
| 10.7.1 | Notational conventions and abbreviations | 262 |
| 10.7.2 | Registrar Administrative Controls | 264 |
| 10.7.3 | Applicant Administrative Controls | 264 |
| 10.7.4 | Protocol timers | 264 |
| 10.7.5 | Protocol event definitions | 265 |
| 10.7.6 | Protocol Action definitions | 268 |
| 10.7.7 | Applicant state machine | 270 |
| 10.7.8 | Registrar state machine | 271 |
| 10.7.9 | LeaveAll state machine | 271 |
| 10.7.10 | PeriodicTransmission state machine | 272 |
| 10.7.11 | Timer values | 272 |
| 10.7.12 | Operational reporting and statistics | 273 |
| 10.7.13 | Interoperability considerations | 273 |
| 10.8 | Structure and encoding of Multiple Registration Protocol Data Units (MRPDUs) | 274 |
| 10.8.1 | Structure | 274 |
| 10.8.2 | Encoding of MRPDU parameters | 276 |
| 10.8.3 | Packing and parsing MRPDUs | 279 |
| 10.9 | Multiple MAC Registration Protocol (MMRP)—Purpose..... | 281 |
| 10.10 | Model of operation..... | 282 |
| 10.10.1 | Propagation of Group Membership information | 283 |
| 10.10.2 | Propagation of Group service requirement information | 284 |
| 10.10.3 | Source pruning | 284 |
| 10.10.4 | Use of Group service requirement registration by end stations | 284 |
| 10.11 | Default Group filtering behavior and MMRP propagation | 284 |
| 10.12 | Definition of the MMRP application..... | 286 |
| 10.12.1 | Definition of MRP elements | 286 |
| 10.12.2 | Provision and support of Extended Filtering Services | 288 |
| 10.12.3 | Use of “new” declaration capability | 290 |
| 10.12.4 | Attribute value support requirements | 290 |
| 10.12.5 | Registrar Administrative Controls | 290 |

| | | |
|---------|--|-----|
| 11. | VLAN topology management..... | 291 |
| 11.1 | Static and dynamic VLAN configuration | 291 |
| 11.2 | Multiple VLAN Registration Protocol (MVRP) | 292 |
| 11.2.1 | MVRP overview | 292 |
| 11.2.2 | VLAN registration service definition | 294 |
| 11.2.3 | Definition of the MVRP application | 295 |
| 11.2.4 | VID translation table | 298 |
| 11.2.5 | Use of “new” declaration capability | 298 |
| 11.2.6 | New-Only Participant and Registrar Administrative Controls | 298 |
| 11.2.7 | Attribute value support requirements | 298 |
| 12. | Bridge management | 299 |
| 12.1 | Management functions..... | 299 |
| 12.1.1 | Configuration Management | 299 |
| 12.1.2 | Fault Management | 300 |
| 12.1.3 | Performance Management | 300 |
| 12.1.4 | Security Management | 300 |
| 12.1.5 | Accounting Management | 300 |
| 12.2 | VLAN Bridge objects | 300 |
| 12.3 | Data types | 301 |
| 12.4 | Bridge Management Entity | 302 |
| 12.4.1 | Bridge Configuration | 302 |
| 12.4.2 | Port configuration | 305 |
| 12.5 | MAC entities..... | 307 |
| 12.5.1 | ISS Port Number table managed object (optional) | 307 |
| 12.6 | Forwarding process..... | 307 |
| 12.6.1 | The Port Counters | 307 |
| 12.6.2 | Priority handling | 308 |
| 12.6.3 | Traffic Class Table | 316 |
| 12.7 | Filtering Database (FDB)..... | 317 |
| 12.7.1 | The Filtering Database object | 317 |
| 12.7.2 | A Static Filtering Entry object | 318 |
| 12.7.3 | A Dynamic Filtering Entry object | 318 |
| 12.7.4 | A MAC Address Registration Entry object | 318 |
| 12.7.5 | A VLAN Registration Entry object | 319 |
| 12.7.6 | Permanent Database object | 319 |
| 12.7.7 | General FDB operations | 320 |
| 12.8 | Bridge Protocol Entity | 321 |
| 12.8.1 | The Protocol Entity | 322 |
| 12.8.2 | Bridge Port | 325 |
| 12.9 | MRP Entities..... | 329 |
| 12.9.1 | The MRP Timer object | 329 |
| 12.9.2 | The MRP Attribute Type object | 330 |
| 12.9.3 | Periodic state machine objects | 331 |
| 12.10 | Bridge VLAN managed objects..... | 331 |
| 12.10.1 | Bridge VLAN Configuration managed object | 332 |
| 12.10.2 | VLAN Configuration managed object | 337 |
| 12.10.3 | The VID to FID allocation managed object | 338 |
| 12.11 | MMRP entities..... | 341 |
| 12.11.1 | MMRP Configuration managed object | 341 |
| 12.12 | MST configuration entities | 342 |
| 12.12.1 | The MSTI List | 342 |
| 12.12.2 | The FID to MSTID Allocation Table | 344 |

| | | |
|---------|--|-----|
| 12.12.3 | The MST Configuration Table | 345 |
| 12.13 | Provider Bridge management | 346 |
| 12.13.1 | Provider Bridge Port Type managed object | 348 |
| 12.13.2 | Customer Edge Port Configuration managed object | 349 |
| 12.13.3 | Remote Customer Access Port Configuration managed object | 352 |
| 12.14 | CFM entities | 354 |
| 12.14.1 | Maintenance Domain list managed object | 355 |
| 12.14.2 | CFM Stack managed object | 356 |
| 12.14.3 | Default MD Level managed object | 357 |
| 12.14.4 | Configuration Error List managed object | 358 |
| 12.14.5 | Maintenance Domain managed object | 358 |
| 12.14.6 | Maintenance Association managed object | 361 |
| 12.14.7 | Maintenance association Endpoint managed object | 364 |
| 12.15 | Backbone Core Bridge (BCB) management..... | 371 |
| 12.16 | Backbone Edge Bridge (BEB) management | 371 |
| 12.16.1 | BEB configuration managed object | 372 |
| 12.16.2 | BEB/PB/VLAN Bridge Port configuration managed object | 376 |
| 12.16.3 | VIP configuration managed object | 377 |
| 12.16.4 | PIP configuration managed object | 378 |
| 12.16.5 | CBP Configuration managed object | 384 |
| 12.17 | DDCFM entities..... | 387 |
| 12.17.1 | DDCFM Stack managed object | 387 |
| 12.17.2 | Reflection Responder managed object | 388 |
| 12.17.3 | RFM Receiver managed object | 391 |
| 12.17.4 | Decapsulator Responder managed object | 392 |
| 12.17.5 | SFM Originator managed object | 395 |
| 12.18 | PBB-TE Protection Switching managed objects | 398 |
| 12.18.1 | TE protection group list managed object | 398 |
| 12.18.2 | TE protection group managed object | 399 |
| 12.19 | TPMR managed objects..... | 401 |
| 12.19.1 | TPMR management entity | 402 |
| 12.19.2 | MAC and PHY entities | 404 |
| 12.19.3 | Forwarding Process | 404 |
| 12.19.4 | MAC Status Propagation Entity (MSPE) | 409 |
| 12.20 | Management entities for FQTSS | 411 |
| 12.20.1 | The Bandwidth Availability Parameter Table | 411 |
| 12.20.2 | The Transmission Selection Algorithm Table | 412 |
| 12.20.3 | The Priority Regeneration Override Table | 412 |
| 12.21 | Congestion Notification managed objects | 412 |
| 12.21.1 | CN component managed object | 413 |
| 12.21.2 | CN component priority managed object | 413 |
| 12.21.3 | CN Port priority managed object | 414 |
| 12.21.4 | Congestion Point managed object | 415 |
| 12.21.5 | Reaction Point port priority managed object | 416 |
| 12.21.6 | Reaction Point group managed object | 416 |
| 12.22 | Stream Reservation Protocol (SRP) entities | 417 |
| 12.22.1 | SRP Bridge Base Table | 417 |
| 12.22.2 | SRP Bridge Port Table | 417 |
| 12.22.3 | SRP Latency Parameter Table | 418 |
| 12.22.4 | SRP Stream Table | 418 |
| 12.22.5 | SRP Reservations Table | 419 |
| 12.23 | Priority-based Flow Control objects..... | 419 |
| 12.24 | 1:1 PBB-TE IPS managed objects..... | 420 |
| 12.24.1 | IPG list managed object | 420 |

| | | |
|----------|--|-----|
| 12.24.2 | IPG managed object | 422 |
| 12.25 | Shortest Path Bridging managed objects | 424 |
| 12.25.1 | The SPB System managed object | 425 |
| 12.25.2 | The SPB MTID Static managed object | 428 |
| 12.25.3 | The SPB Topology Instance Dynamic managed object | 429 |
| 12.25.4 | The SPB ECT Static Entry managed object | 430 |
| 12.25.5 | The SPB ECT Dynamic Entry managed object | 431 |
| 12.25.6 | The SPB Adjacency Static Entry managed object | 432 |
| 12.25.7 | The SPB Adjacency Dynamic Entry managed object | 433 |
| 12.25.8 | The SPBM BSI Static Entry managed object | 434 |
| 12.25.9 | The SPB Topology Node Table managed object | 435 |
| 12.25.10 | The SPB Topology ECT Table managed object | 436 |
| 12.25.11 | The SPB Topology Edge Table managed object | 436 |
| 12.25.12 | The SPBM Topology Service Table managed object | 437 |
| 12.25.13 | The SPBV Topology Service Table managed object | 438 |
| 12.25.14 | The ECMP ECT Static Entry managed object | 439 |
| 12.26 | Edge Virtual Bridging (EVB) management..... | 440 |
| 12.26.1 | EVB system base table | 444 |
| 12.26.2 | SBP table entry | 445 |
| 12.26.3 | VSI table entry | 446 |
| 12.26.4 | S-channel configuration and management | 448 |
| 12.26.5 | ER management | 450 |
| 12.27 | Edge Control Protocol (ECP) management..... | 451 |
| 12.27.1 | ECP table entry | 451 |
| 12.28 | Path Control and Reservation (PCR) management..... | 451 |
| 12.28.1 | The PCR ECT Static Entry managed object | 452 |
| 12.28.2 | The PCR Topology ECT Table managed object | 455 |
| 12.29 | Managed objects for scheduled traffic..... | 455 |
| 12.29.1 | The Gate Parameter Table | 455 |
| 12.29.2 | Timing points for scheduled traffic | 458 |
| 12.30 | Managed objects for frame preemption | 459 |
| 12.30.1 | Frame Preemption Parameter table | 459 |
| 12.31 | Managed objects for per-stream filtering and policing..... | 460 |
| 12.31.1 | The Stream Parameter Table | 460 |
| 12.31.2 | The Stream Filter Instance Table | 461 |
| 12.31.3 | The Stream Gate Instance Table | 463 |
| 12.31.4 | The Flow Meter Instance Table | 466 |
| 13. | Spanning tree protocols | 467 |
| 13.1 | Protocol design requirements..... | 468 |
| 13.2 | Protocol support requirements | 469 |
| 13.2.1 | MSTP support requirements | 469 |
| 13.2.2 | SPB support requirements | 469 |
| 13.3 | Protocol design goals | 470 |
| 13.4 | RSTP overview | 470 |
| 13.4.1 | Computation of the active topology | 471 |
| 13.4.2 | Example topologies | 472 |
| 13.5 | MSTP overview | 475 |
| 13.5.1 | Example topologies | 476 |
| 13.5.2 | Relationship of MSTP to RSTP | 479 |
| 13.5.3 | Modeling an MST or SPT Region as a single Bridge | 479 |
| 13.6 | SPB overview | 480 |
| 13.7 | Compatibility and interoperability..... | 481 |

| | | |
|----------|---|-----|
| 13.7.1 | Designated Port selection | 481 |
| 13.7.2 | Force Protocol Version | 481 |
| 13.8 | MST Configuration Identifier (MCID)..... | 482 |
| 13.9 | Spanning tree priority vectors..... | 483 |
| 13.10 | CIST Priority Vector calculations..... | 485 |
| 13.11 | MST Priority Vector calculations..... | 487 |
| 13.12 | Port Role assignments..... | 489 |
| 13.13 | Stable connectivity..... | 490 |
| 13.14 | Communicating spanning tree information | 491 |
| 13.15 | Changing spanning tree information..... | 492 |
| 13.16 | Changing Port States with RSTP or MSTP | 493 |
| 13.16.1 | Subtree connectivity and priority vectors | 494 |
| 13.16.2 | Root Port transition to Forwarding | 494 |
| 13.16.3 | Designated Port transition to Forwarding | 494 |
| 13.16.4 | Master Port transition to Forwarding | 496 |
| 13.17 | Changing Port States with SPB | 498 |
| 13.17.1 | Agreement Digest | 500 |
| 13.18 | Managing spanning tree topologies | 501 |
| 13.19 | Updating learned station location information | 502 |
| 13.20 | Managing reconfiguration..... | 504 |
| 13.21 | Partial and disputed connectivity..... | 505 |
| 13.22 | In-service upgrades | 505 |
| 13.23 | Fragile Bridges..... | 507 |
| 13.24 | Spanning tree protocol state machines..... | 507 |
| 13.25 | State machine timers | 509 |
| 13.25.1 | edgeDelayWhile | 510 |
| 13.25.2 | fdWhile | 510 |
| 13.25.3 | helloWhen | 510 |
| 13.25.4 | mdelayWhile | 510 |
| 13.25.5 | rbWhile | 510 |
| 13.25.6 | rcvdInfoWhile | 510 |
| 13.25.7 | rrWhile | 511 |
| 13.25.8 | tcDetected | 511 |
| 13.25.9 | tcWhile | 511 |
| 13.25.10 | pseudoInfoHelloWhen | 511 |
| 13.26 | Per Bridge variables..... | 511 |
| 13.26.1 | agreementDigest | 512 |
| 13.26.2 | BridgeIdentifier | 512 |
| 13.26.3 | BridgePriority | 512 |
| 13.26.4 | BridgeTimes | 512 |
| 13.26.5 | ForceProtocolVersion | 513 |
| 13.26.6 | MigrateTime | 513 |
| 13.26.7 | MstConfigId | 513 |
| 13.26.8 | AuxMstConfigId | 513 |
| 13.26.9 | rootPortId | 513 |
| 13.26.10 | rootPriority | 513 |
| 13.26.11 | rootTimes | 513 |
| 13.26.12 | TxHoldCount | 513 |
| 13.27 | Per port variables | 513 |
| 13.27.1 | AdminEdge | 516 |
| 13.27.2 | ageingTime | 516 |
| 13.27.3 | agree | 516 |
| 13.27.4 | agreed | 516 |
| 13.27.5 | agreedAbove | 516 |

| | | |
|----------|----------------------|-----|
| 13.27.6 | agreedDigest | 516 |
| 13.27.7 | agreedDigestValid | 516 |
| 13.27.8 | agreeDigest | 516 |
| 13.27.9 | agreeDigestValid | 516 |
| 13.27.10 | agreedMisorder | 517 |
| 13.27.11 | agreedN | 517 |
| 13.27.12 | agreedND | 517 |
| 13.27.13 | agreedPriority | 517 |
| 13.27.14 | agreedTopology | 517 |
| 13.27.15 | agreementOutstanding | 517 |
| 13.27.16 | agreeN | 517 |
| 13.27.17 | agreeND | 517 |
| 13.27.18 | AutoEdge | 517 |
| 13.27.19 | AutoIsolate | 518 |
| 13.27.20 | designatedPriority | 518 |
| 13.27.21 | designatedTimes | 518 |
| 13.27.22 | disputed | 518 |
| 13.27.23 | enableBPDUrx | 518 |
| 13.27.24 | enableBPDUtx | 518 |
| 13.27.25 | ExternalPortPathCost | 518 |
| 13.27.26 | isL2gp | 518 |
| 13.27.27 | isolate | 519 |
| 13.27.28 | fdbFlush | 519 |
| 13.27.29 | forward | 519 |
| 13.27.30 | forwarding | 519 |
| 13.27.31 | infoInternal | 519 |
| 13.27.32 | infols | 519 |
| 13.27.33 | InternalPortPathCost | 519 |
| 13.27.34 | learn | 520 |
| 13.27.35 | learning | 520 |
| 13.27.36 | master | 520 |
| 13.27.37 | mastered | 520 |
| 13.27.38 | mcheck | 520 |
| 13.27.39 | msgPriority | 520 |
| 13.27.40 | msgTimes | 520 |
| 13.27.41 | neighbourPriority | 521 |
| 13.27.42 | newInfo | 521 |
| 13.27.43 | newInfoMsti | 521 |
| 13.27.44 | operEdge | 521 |
| 13.27.45 | portEnabled | 521 |
| 13.27.46 | portId | 521 |
| 13.27.47 | portPriority | 521 |
| 13.27.48 | portTimes | 522 |
| 13.27.49 | proposed | 522 |
| 13.27.50 | proposing | 522 |
| 13.27.51 | pseudoRootId | 522 |
| 13.27.52 | rcvdBPDU | 522 |
| 13.27.53 | rcvdInfo | 522 |
| 13.27.54 | rcvdInternal | 522 |
| 13.27.55 | rcvdMsg | 522 |
| 13.27.56 | rcvdRSTP | 522 |
| 13.27.57 | rcvdSTP | 522 |
| 13.27.58 | rcvdTc | 522 |
| 13.27.59 | rcvdTcAck | 522 |

| | | |
|----------|---|-----|
| 13.27.60 | rcvdTcn | 523 |
| 13.27.61 | reRoot | 523 |
| 13.27.62 | reselect | 523 |
| 13.27.63 | restrictedDomainRole | 523 |
| 13.27.64 | restrictedRole | 523 |
| 13.27.65 | restrictedTcn | 523 |
| 13.27.66 | role | 523 |
| 13.27.67 | selected | 523 |
| 13.27.68 | selectedRole | 523 |
| 13.27.69 | sendRSTP | 524 |
| 13.27.70 | sync | 524 |
| 13.27.71 | synced | 524 |
| 13.27.72 | tcAck | 524 |
| 13.27.73 | tcProp | 524 |
| 13.27.74 | tick | 524 |
| 13.27.75 | txCount | 524 |
| 13.27.76 | updtInfo | 524 |
| 13.28 | State machine conditions and parameters | 524 |
| 13.28.1 | allSptAgree | 525 |
| 13.28.2 | allSynced | 525 |
| 13.28.3 | allTransmitReady | 525 |
| 13.28.4 | BestAgreementPriority | 525 |
| 13.28.5 | cist | 525 |
| 13.28.6 | cistRootPort | 525 |
| 13.28.7 | cistDesignatedPort | 526 |
| 13.28.8 | EdgeDelay | 526 |
| 13.28.9 | forwardDelay | 526 |
| 13.28.10 | FwdDelay | 526 |
| 13.28.11 | HelloTime | 526 |
| 13.28.12 | MaxAge | 526 |
| 13.28.13 | msti | 526 |
| 13.28.14 | mstiDesignatedOrTCpropagatingRootPort | 526 |
| 13.28.15 | mstiMasterPort | 526 |
| 13.28.16 | operPointToPoint | 526 |
| 13.28.17 | rcvdAnyMsg | 526 |
| 13.28.18 | rcvdCistMsg | 526 |
| 13.28.19 | rcvdMstiMsg | 527 |
| 13.28.20 | reRooted | 527 |
| 13.28.21 | rstpVersion | 527 |
| 13.28.22 | spt | 527 |
| 13.28.23 | stpVersion | 527 |
| 13.28.24 | updtCistInfo | 527 |
| 13.28.25 | updtMstiInfo | 527 |
| 13.29 | State machine procedures | 527 |
| 13.29.1 | betterorsameInfo(newInfoIs) | 528 |
| 13.29.2 | clearAllRcvdMsgs() | 528 |
| 13.29.3 | clearReselectTree() | 528 |
| 13.29.4 | disableForwarding() | 529 |
| 13.29.5 | disableLearning() | 529 |
| 13.29.6 | enableForwarding() | 529 |
| 13.29.7 | enableLearning() | 529 |
| 13.29.8 | fromSameRegion() | 529 |
| 13.29.9 | newTcDetected() | 529 |
| 13.29.10 | newTcWhile() | 529 |

| | | |
|----------|---|-----|
| 13.29.11 | pseudoRcvMsgs() | 530 |
| 13.29.12 | revInfo() | 530 |
| 13.29.13 | rcvMsgs() | 531 |
| 13.29.14 | rcvAgreements() | 531 |
| 13.29.15 | recordAgreement() | 531 |
| 13.29.16 | recordDispute() | 532 |
| 13.29.17 | recordMastered() | 532 |
| 13.29.18 | recordPriority() | 532 |
| 13.29.19 | recordProposal() | 532 |
| 13.29.20 | recordTimes() | 532 |
| 13.29.21 | setReRootTree() | 533 |
| 13.29.22 | setSelectedTree() | 533 |
| 13.29.23 | setSyncTree() | 533 |
| 13.29.24 | setTcFlags() | 533 |
| 13.29.25 | setTcPropTree() | 533 |
| 13.29.26 | syncMaster() | 533 |
| 13.29.27 | txConfig() | 533 |
| 13.29.28 | txRstp() | 534 |
| 13.29.29 | txTcn() | 534 |
| 13.29.30 | updtAgreement() | 534 |
| 13.29.31 | updtBPDUVersion() | 535 |
| 13.29.32 | updtDigest() | 535 |
| 13.29.33 | updtRcvdInfoWhile() | 536 |
| 13.29.34 | updtRolesTree() | 537 |
| 13.29.35 | uptRolesDisabledTree() | 538 |
| 13.30 | The Port Timers state machine | 538 |
| 13.31 | Port Receive state machine | 539 |
| 13.32 | Port Protocol Migration state machine | 540 |
| 13.33 | Bridge Detection state machine | 540 |
| 13.34 | Port Transmit state machine | 541 |
| 13.35 | Port Information state machine | 542 |
| 13.36 | Port Role Selection state machine | 543 |
| 13.37 | Port Role Transitions state machine | 543 |
| 13.38 | Port State Transition state machine | 548 |
| 13.38.1 | Port State transitions for the CIST and MSTIs | 549 |
| 13.38.2 | Port State transitions for SPTs | 549 |
| 13.39 | Topology Change state machine | 550 |
| 13.40 | Layer 2 Gateway Port Receive state machine | 551 |
| 13.41 | CEP spanning tree operation | 551 |
| 13.41.1 | PEP operPointToPointMAC and operEdge | 551 |
| 13.41.2 | updtRolesTree() | 552 |
| 13.41.3 | setReRootTree(), setSyncTree(), setTcPropTree() | 552 |
| 13.41.4 | allSynced, reRooted | 552 |
| 13.41.5 | Configuration parameters | 552 |
| 13.42 | Virtual Instance Port (VIP) spanning tree operation | 553 |
| 14. | Encoding of Bridge Protocol Data Units (BPDUs) | 554 |
| 14.1 | BPDUs Structure | 554 |
| 14.1.1 | Transmission and representation of octets | 554 |
| 14.1.2 | Common BPDUs fields | 554 |
| 14.2 | Encoding of parameter types | 556 |
| 14.2.1 | Encoding of Protocol Identifiers | 556 |
| 14.2.2 | Encoding of Protocol Version Identifiers | 556 |

| | | |
|---------|--|-----|
| 14.2.3 | Encoding of BPDU types | 556 |
| 14.2.4 | Encoding of flags | 556 |
| 14.2.5 | Encoding of Bridge Identifiers | 556 |
| 14.2.6 | Encoding of External Root Path Cost and Internal Root Path Cost | 557 |
| 14.2.7 | Encoding of Port Identifiers | 557 |
| 14.2.8 | Encoding of Timer Values | 557 |
| 14.2.9 | Encoding of Port Role values | 557 |
| 14.2.10 | Encoding of Length Values | 558 |
| 14.2.11 | Encoding of Hop Counts | 558 |
| 14.3 | Transmission of BPDUs | 558 |
| 14.4 | Encoding and decoding of STP Configuration, RST, MST, and SPT BPDUs..... | 558 |
| 14.4.1 | MSTI Configuration Messages | 560 |
| 14.5 | Validation of received BPDUs | 561 |
| 14.6 | Validation and interoperability | 562 |
| 15. | Support of the MAC Service by PBNs | 563 |
| 15.1 | Service transparency | 563 |
| 15.2 | Customer service interfaces | 564 |
| 15.3 | Port-based service interface | 564 |
| 15.4 | C-tagged service interface | 565 |
| 15.5 | S-tagged service interface..... | 566 |
| 15.6 | Remote customer service interfaces (RCSIs) | 567 |
| 15.7 | Service instance segregation..... | 570 |
| 15.8 | Service instance selection and identification | 570 |
| 15.9 | Service priority selection | 571 |
| 15.10 | Service access protection | 571 |
| 16. | Principles of Provider Bridged Network (PBN) operation..... | 572 |
| 16.1 | PBN overview..... | 572 |
| 16.2 | Provider Bridged Network (PBN) | 573 |
| 16.3 | Service instance connectivity..... | 576 |
| 16.4 | Service provider learning of customer end station addresses..... | 577 |
| 16.5 | Detection of connectivity loops through attached networks..... | 577 |
| 16.6 | Network management | 578 |
| 17. | Management Information Base (MIB) | 579 |
| 17.1 | Internet Standard Management Framework | 579 |
| 17.2 | Structure of the MIB | 579 |
| 17.2.1 | Structure of the IEEE8021-TC-MIB | 580 |
| 17.2.2 | Structure of the IEEE8021-BRIDGE-MIB | 582 |
| 17.2.3 | Structure of the IEEE8021-SPANNING-TREE MIB | 586 |
| 17.2.4 | Structure of the IEEE8021-Q-BRIDGE-MIB | 589 |
| 17.2.5 | Structure of the IEEE8021-PB-MIB | 594 |
| 17.2.6 | Structure of the IEEE8021-MSTP-MIB | 596 |
| 17.2.7 | Structure of the IEEE8021-CFM-MIB | 599 |
| 17.2.8 | Structure of the IEEE8021-PBB-MIB | 605 |
| 17.2.9 | Structure of the IEEE8021-DDCFM-MIBs | 607 |
| 17.2.10 | Structure of the IEEE8021-PBBTE-MIB | 610 |
| 17.2.11 | Structure of the TPMR MIB | 612 |
| 17.2.12 | Structure of the IEEE8021-FQTSS-MIB | 614 |
| 17.2.13 | Structure of the Congestion Notification MIB | 615 |
| 17.2.14 | Structure of the IEEE8021-SRP-MIB | 617 |

| | | |
|---------|---|-----|
| 17.2.15 | Structure of the MVRP extension MIB | 619 |
| 17.2.16 | Structure of the MIRP MIB | 619 |
| 17.2.17 | Structure of the PFC MIB | 620 |
| 17.2.18 | Structure of the IEEE80221-TEIPS MIB | 620 |
| 17.2.19 | Structure of the IEEE8021-SPB-MIB | 622 |
| 17.2.20 | Structure of the IEEE8021-EVB-MIB | 626 |
| 17.2.21 | Structure of the IEEE8021-ECMP-MIB | 630 |
| 17.2.22 | Structure of the IEEE8021-ST-MIB | 631 |
| 17.2.23 | Structure of the IEEE8021-Preemption-MIB | 632 |
| 17.2.24 | Structure of the IEEE8021-PSFP-MIB | 633 |
| 17.3 | Relationship to other MIBs..... | 636 |
| 17.3.1 | Relationship of the IEEE8021-TC-MIB to other MIB modules | 636 |
| 17.3.2 | Relationship of the IEEE8021-BRIDGE-MIB to other MIB modules | 636 |
| 17.3.3 | Relationship of the IEEE8021-RSTP MIB to other MIB modules | 639 |
| 17.3.4 | Relationship of the IEEE8021-Q-BRIDGE-MIB to other MIB modules | 639 |
| 17.3.5 | Relationship of the IEEE8021-PB-BRIDGE MIB to other MIB modules | 641 |
| 17.3.6 | Relationship of the IEEE8021-MSTP-MIB to other MIB modules | 641 |
| 17.3.7 | Relationship of the IEEE8021-CFM-MIB to other MIB modules | 641 |
| 17.3.8 | Relationship of the IEEE8021-PBB-MIB to other MIB modules | 642 |
| 17.3.9 | Relationship of the IEEE8021-DDCFM to other MIB modules | 643 |
| 17.3.10 | Relationship of the IEEE8021-PBBTE-MIB to other MIB modules | 643 |
| 17.3.11 | Relationship of the TPMR MIB to other MIB modules | 644 |
| 17.3.12 | Relationship of the IEEE8021-FQTSS-MIB to other MIB modules | 644 |
| 17.3.13 | Relationship of the IEEE802-CN-MIB to other MIB modules | 644 |
| 17.3.14 | Relationship of the IEEE8021-SRP-MIB to other MIB modules | 645 |
| 17.3.15 | Relationship of the IEEE8021-MVRPX-MIB to other MIB modules | 645 |
| 17.3.16 | Relationship of the IEEE8021-MIRP-MIB to other MIB modules | 645 |
| 17.3.17 | Relationship of the PFC MIB to other MIB modules | 645 |
| 17.3.18 | Relationship of the IEEE8021-TEIPS-MIB to other MIB modules | 646 |
| 17.3.19 | Relationship of the of the IEEE8021-SPB-MIB to other MIB modules | 646 |
| 17.3.20 | Relationship of the IEEE8021-EVB-MIB to other MIB modules | 646 |
| 17.3.21 | Relationship of the of the IEEE8021-ECMP-MIB to other MIB modules | 646 |
| 17.3.22 | Relationship of the PCR MIB to other MIB modules | 646 |
| 17.3.23 | Relationship of the IEEE8021-ST-MIB to other MIBs | 646 |
| 17.3.24 | Relationship of the IEEE8021-Preemption-MIB to other MIBs | 647 |
| 17.3.25 | Relationship of IEEE8021-PSFP-MIB to other MIBs | 647 |
| 17.4 | Security considerations | 647 |
| 17.4.1 | Security considerations of the IEEE8021-TC-MIB | 647 |
| 17.4.2 | Security considerations of the IEEE8021-BRIDGE-MIB | 647 |
| 17.4.3 | Security considerations of the IEEE8021-SPANNING-TREE MIB | 648 |
| 17.4.4 | Security considerations of the IEEE8021-Q-BRIDGE-MIB | 649 |
| 17.4.5 | Security considerations of the IEEE8021-PB-MIB | 650 |
| 17.4.6 | Security considerations of the IEEE8021-MSTP-MIB | 650 |
| 17.4.7 | Security considerations of the IEEE8021-CFM-MIB | 651 |
| 17.4.8 | Security considerations of the IEEE8021-PBB-MIB | 653 |
| 17.4.9 | Security considerations of the IEEE8021-DDCFM-MIB | 653 |
| 17.4.10 | Security considerations of the IEEE8021-PBBTE-MIB | 654 |
| 17.4.11 | Security considerations of the TPMR MIB | 655 |
| 17.4.12 | Security considerations of the IEEE8021-FQTSS-MIB | 655 |
| 17.4.13 | Security considerations of the Congestion Notification MIB | 656 |
| 17.4.14 | Security considerations of the IEEE8021-SRP-MIB | 657 |
| 17.4.15 | Security considerations of the IEEE8021-MVRPX-MIB | 658 |
| 17.4.16 | Security considerations of the IEEE8021-MIRP-MIB | 658 |
| 17.4.17 | Security considerations for the PFC MIB | 659 |

| | | |
|---------|--|------|
| 17.4.18 | Security considerations of the IEEE8021-TEIPS-MIB | 659 |
| 17.4.19 | Security considerations of the IEEE8021-SPB-MIB | 659 |
| 17.4.20 | Security considerations of the IEEE8021-EVB-MIB | 660 |
| 17.4.21 | Security considerations of the IEEE8021-ECMP-MIB | 661 |
| 17.4.22 | Security considerations of the PCR MIB | 662 |
| 17.4.23 | Security considerations of the IEEE8021-ST-MIB | 662 |
| 17.4.24 | Security considerations of the IEEE8021-Preemption-MIB | 663 |
| 17.4.25 | Security considerations of the IEEE8021-PSFP-MIB | 663 |
| 17.5 | Dynamic component and Port creation..... | 665 |
| 17.5.1 | Overview of the dynamically created Bridge entities | 665 |
| 17.5.2 | Component creation | 666 |
| 17.5.3 | Port creation | 667 |
| 17.6 | MIB operations for service interface configuration..... | 677 |
| 17.6.1 | Provisioning PBN service interfaces | 677 |
| 17.6.2 | Provisioning Backbone Bridged Network service interfaces | 680 |
| 17.7 | MIB modules, | 686 |
| 17.7.1 | Definitions for the IEEE8021-TC-MIB module | 686 |
| 17.7.2 | Definitions for the IEEE8021-BRIDGE-MIB module | 697 |
| 17.7.3 | Definitions for the IEEE8021-SPANNING-TREE-MIB module | 737 |
| 17.7.4 | Definitions for the IEEE8021-Q-BRIDGE-MIB module | 755 |
| 17.7.5 | Definitions for the IEEE8021-PB-MIB module | 801 |
| 17.7.6 | Definitions for the IEEE8021-MSTP-MIB module | 819 |
| 17.7.7 | Definitions for the CFM MIB modules | 848 |
| 17.7.8 | Definitions for the IEEE8021-PBB-MIB module | 931 |
| 17.7.9 | Definitions for the IEEE8021-DDCFM-MIB module | 954 |
| 17.7.10 | Definitions for the IEEE8021-PBBTE-MIB module | 972 |
| 17.7.11 | Definitions for the IEEE8021-TPMR-MIB module | 989 |
| 17.7.12 | Definitions for the IEEE8021-FQTSS-MIB module | 1003 |
| 17.7.13 | Definitions for the IEEE8021-CN-MIB module | 1014 |
| 17.7.14 | Definitions for the IEEE8021-SRP-MIB module | 1050 |
| 17.7.15 | Definitions for the IEEE8021-MVRPX-MIB module | 1066 |
| 17.7.16 | Definitions for the IEEE8021-MIRP-MIB module | 1071 |
| 17.7.17 | Definitions for the IEEE8021-PFC-MIB module | 1077 |
| 17.7.18 | Definitions for the IEEE8021-TEIPS-V2-MIB module | 1081 |
| 17.7.19 | Definitions for the IEEE8021-SPB-MIB module | 1096 |
| 17.7.20 | Definitions for the IEEE8021-EVB-MIB module | 1140 |
| 17.7.21 | Definitions for the IEEE8021-ECMP-MIB module | 1169 |
| 17.7.22 | Definitions for the IEEE8021-ST-MIB module | 1177 |
| 17.7.23 | Definitions for the IEEE8021-Preemption-MIB module | 1190 |
| 17.7.24 | Definitions for the IEEE8021-PSFP-MIB module | 1196 |
| 18. | Principles of Connectivity Fault Management operation | 1220 |
| 18.1 | Maintenance Domains and DoSAPs..... | 1221 |
| 18.2 | Service instances and MAs | 1223 |
| 18.3 | Maintenance Domain Levels | 1224 |
| 19. | CFM entity operation..... | 1228 |
| 19.1 | Maintenance Points (MPs)..... | 1228 |
| 19.2 | MA Endpoints (MEPs) | 1229 |
| 19.2.1 | MEP identification | 1229 |
| 19.2.2 | MEP functions | 1230 |
| 19.2.3 | MEP architecture | 1230 |
| 19.2.4 | MP Type Demultiplexer | 1232 |

| | | |
|---------|---|------|
| 19.2.5 | MP Multiplexer | 1232 |
| 19.2.6 | MP Level Demultiplexer | 1232 |
| 19.2.7 | MP OpCode Demultiplexer | 1232 |
| 19.2.8 | MEP Continuity Check Receiver | 1233 |
| 19.2.9 | MEP Continuity Check Initiator | 1233 |
| 19.2.10 | MP Loopback Responder | 1234 |
| 19.2.11 | MEP Loopback Initiator | 1234 |
| 19.2.12 | MEP Linktrace Initiator | 1234 |
| 19.2.13 | MEP LTI SAP | 1234 |
| 19.2.14 | MEP Linktrace SAP | 1234 |
| 19.2.15 | MEP CCM Database | 1234 |
| 19.2.16 | MEP Fault Notification Generator | 1234 |
| 19.2.17 | MEP Decapsulator Responder (DR) | 1235 |
| 19.2.18 | MEP RFM Receiver | 1235 |
| 19.3 | MIP Half Function | 1235 |
| 19.3.1 | MHF identification | 1235 |
| 19.3.2 | MHF functions | 1235 |
| 19.3.3 | MHF architecture | 1236 |
| 19.3.4 | MHF Level Demultiplexer | 1236 |
| 19.3.5 | MHF Type Demultiplexer | 1236 |
| 19.3.6 | MHF OpCode Demultiplexer | 1236 |
| 19.3.7 | MHF Multiplexer | 1236 |
| 19.3.8 | MHF Loopback Responder | 1236 |
| 19.3.9 | MHF Continuity Check Receiver | 1237 |
| 19.3.10 | MIP CCM Database | 1237 |
| 19.3.11 | MHF Linktrace SAP | 1238 |
| 19.3.12 | MHF DR | 1238 |
| 19.3.13 | MHF RFM Receiver | 1238 |
| 19.4 | MP addressing..... | 1238 |
| 19.5 | Linktrace Output Multiplexer (LOM)..... | 1239 |
| 19.6 | Linktrace Responder | 1239 |
| 20. | CFM protocols | 1241 |
| 20.1 | Continuity Check protocol | 1242 |
| 20.1.1 | MAC status reporting in the CCM | 1244 |
| 20.1.2 | Defects and Fault Alarms | 1244 |
| 20.1.3 | CCM reception | 1245 |
| 20.2 | Loopback protocol | 1245 |
| 20.2.1 | LBM transmission | 1246 |
| 20.2.2 | LBM reception and LBR transmission | 1246 |
| 20.2.3 | LBR reception | 1247 |
| 20.3 | Linktrace protocol | 1247 |
| 20.3.1 | LTM origination | 1248 |
| 20.3.2 | LTM reception, forwarding, and replying | 1249 |
| 20.3.3 | LTR reception | 1250 |
| 20.4 | CFM state machines | 1251 |
| 20.5 | CFM state machine timers | 1251 |
| 20.5.1 | LTFwhile | 1253 |
| 20.5.2 | CCIwhile | 1253 |
| 20.5.3 | errorCCMwhile | 1253 |
| 20.5.4 | xconCCMwhile | 1253 |
| 20.5.5 | LBIwhile | 1253 |
| 20.5.6 | FNGwhile | 1253 |

| | | |
|----------|--|------|
| 20.5.7 | mmCCMwhile | 1253 |
| 20.5.8 | mmLocwhile | 1253 |
| 20.5.9 | mmFNGwhile | 1253 |
| 20.5.10 | rMEPwhile | 1253 |
| 20.6 | CFM procedures | 1254 |
| 20.6.1 | CCMtime() | 1254 |
| 20.7 | Maintenance Domain variable | 1254 |
| 20.7.1 | mdLevel | 1254 |
| 20.8 | MA variables | 1254 |
| 20.8.1 | CCMinterval | 1254 |
| 20.9 | MEP variables | 1254 |
| 20.9.1 | MEPactive | 1255 |
| 20.9.2 | enableRmepDefect | 1255 |
| 20.9.3 | MAdefectIndication | 1256 |
| 20.9.4 | allRMEPsDead | 1256 |
| 20.9.5 | lowestAlarmPri | 1256 |
| 20.9.6 | presentRDI | 1256 |
| 20.9.7 | MEPprimaryVID | 1256 |
| 20.9.8 | presentTraffic | 1256 |
| 20.9.9 | presentmmLoc | 1256 |
| 20.9.10 | ISpresentTraffic | 1257 |
| 20.9.11 | ISpresentmmLoc | 1257 |
| 20.9.12 | EpMEP | 1257 |
| 20.10 | MEP Continuity Check Initiator variables | 1257 |
| 20.10.1 | CCIenabled | 1257 |
| 20.10.2 | CCIsentCCMs | 1257 |
| 20.10.3 | MACstatusChanged | 1257 |
| 20.10.4 | Npaths | 1257 |
| 20.10.5 | flowHash[] | 1258 |
| 20.10.6 | pathN | 1258 |
| 20.10.7 | CCMent | 1258 |
| 20.11 | MEP Continuity Check Initiator procedures | 1258 |
| 20.11.1 | xmitCCM() | 1258 |
| 20.12 | MEP Continuity Check Initiator state machine | 1259 |
| 20.13 | MHF Continuity Check Receiver variables | 1260 |
| 20.13.1 | MHFrecvdCCM | 1260 |
| 20.13.2 | MHFCCMPDU | 1260 |
| 20.14 | MHF Continuity Check Receiver procedures | 1260 |
| 20.14.1 | MHFprocessCCM() | 1260 |
| 20.15 | MHF Continuity Check Receiver state machine | 1260 |
| 20.16 | MEP Continuity Check Receiver variables | 1261 |
| 20.16.1 | CCMreceivedEqual | 1261 |
| 20.16.2 | CCMequalPDU | 1261 |
| 20.16.3 | CCMreceivedLow | 1261 |
| 20.16.4 | CCMlowPDU | 1261 |
| 20.16.5 | recvdMacAddress | 1261 |
| 20.16.6 | recvdRDI | 1261 |
| 20.16.7 | recvdInterval | 1262 |
| 20.16.8 | recvdPortState | 1262 |
| 20.16.9 | recvdInterfaceStatus | 1262 |
| 20.16.10 | recvdSenderId | 1262 |
| 20.16.11 | recvdFrame | 1262 |
| 20.16.12 | CCMsequenceErrors | 1262 |
| 20.16.13 | recvdTrafficBit | 1262 |

| | | |
|----------|---|------|
| 20.17 | MEP Continuity Check Receiver procedures | 1262 |
| 20.17.1 | MEPprocessEqualCCM() | 1263 |
| 20.17.2 | MEPprocessLowCCM() | 1263 |
| 20.18 | MEP Continuity Check Receiver state machine | 1264 |
| 20.19 | Remote MEP variables | 1264 |
| 20.19.1 | rMEPCCMdefect | 1264 |
| 20.19.2 | rMEPlastRDI and rMEPlastRDI[i] | 1264 |
| 20.19.3 | rMEPlastPortState | 1265 |
| 20.19.4 | rMEPlastInterfaceStatus | 1265 |
| 20.19.5 | rMEPlastSenderId | 1265 |
| 20.19.6 | rCCMreceived | 1265 |
| 20.19.7 | rMEPmacAddress | 1265 |
| 20.19.8 | rMEPportStatusDefect | 1265 |
| 20.19.9 | rMEPinterfaceStatusDefect | 1265 |
| 20.19.10 | lastPathN | 1265 |
| 20.20 | Remote MEP state machine | 1266 |
| 20.21 | Remote MEP Error variables | 1267 |
| 20.21.1 | errorCCMreceived | 1267 |
| 20.21.2 | errorCCMlastFailure | 1267 |
| 20.21.3 | errorCCMdefect | 1267 |
| 20.22 | Remote MEP Error state machine | 1267 |
| 20.23 | MEP Cross Connect variables | 1268 |
| 20.23.1 | xconCCMreceived | 1268 |
| 20.23.2 | xconCCMlastFailure | 1268 |
| 20.23.3 | xconCCMdefect | 1268 |
| 20.24 | MEP Cross Connect state machine | 1268 |
| 20.25 | MEP Mismatch variables | 1269 |
| 20.25.1 | mmCCMreceived | 1269 |
| 20.25.2 | mmCCMdefect | 1269 |
| 20.25.3 | mmCCMTime | 1269 |
| 20.25.4 | disableLocdefect | 1269 |
| 20.25.5 | mmLocdefect | 1269 |
| 20.26 | MEP Mismatch state machines | 1270 |
| 20.27 | MP Loopback Responder variables | 1271 |
| 20.27.1 | LBMreceived | 1271 |
| 20.27.2 | LBMPPDU | 1271 |
| 20.28 | MP Loopback Responder procedures | 1271 |
| 20.28.1 | ProcessLBM() | 1271 |
| 20.28.2 | xmitLBR() | 1272 |
| 20.29 | MP Loopback Responder state machine | 1272 |
| 20.30 | MEP Loopback Initiator variables | 1273 |
| 20.30.1 | LBMstoSend | 1273 |
| 20.30.2 | nextLBMtransID | 1273 |
| 20.30.3 | expectedLBRtransID | 1273 |
| 20.30.4 | LBIactive | 1273 |
| 20.30.5 | xmitReady | 1273 |
| 20.30.6 | LBRreceived | 1273 |
| 20.30.7 | LBRPDU | 1273 |
| 20.31 | MEP Loopback Initiator transmit procedures | 1274 |
| 20.31.1 | xmitLBM() | 1274 |
| 20.32 | MEP Loopback Initiator transmit state machine | 1275 |
| 20.33 | MEP Loopback Initiator receive procedures | 1275 |
| 20.33.1 | ProcessLBR() | 1275 |
| 20.34 | MEP Loopback Initiator receive state machine | 1276 |

| | | |
|---------|---|------|
| 20.35 | MEP Fault Notification Generator variables | 1276 |
| 20.35.1 | fngPriority | 1276 |
| 20.35.2 | fngDefect | 1277 |
| 20.35.3 | fngAlarmTime | 1277 |
| 20.35.4 | fngResetTime | 1277 |
| 20.35.5 | someRMEPCCMdefect | 1277 |
| 20.35.6 | someMACstatusDefect | 1277 |
| 20.35.7 | someRDId defect | 1277 |
| 20.35.8 | highestDefectPri | 1277 |
| 20.35.9 | highestDefect | 1277 |
| 20.36 | MEP Fault Notification Generator procedures | 1278 |
| 20.36.1 | xmitFaultAlarm() | 1278 |
| 20.37 | MEP Fault Notification Generator state machine | 1278 |
| 20.38 | MEP Mismatch Fault Notification Generator variables | 1279 |
| 20.38.1 | mfngAllowed | 1279 |
| 20.38.2 | mmdefectIndication | 1279 |
| 20.38.3 | mfngAlarmTime | 1279 |
| 20.38.4 | mfngResetTime | 1279 |
| 20.39 | MEP Mismatch Fault Notification Generator procedures | 1279 |
| 20.39.1 | xmitFaultAlarm() | 1279 |
| 20.40 | MEP Mismatch Fault Notification Generator state machine | 1280 |
| 20.41 | MEP Linktrace Initiator variables | 1280 |
| 20.41.1 | nextLTMtransID | 1280 |
| 20.41.2 | ltmReplyList | 1281 |
| 20.42 | MEP Linktrace Initiator procedures | 1283 |
| 20.42.1 | xmitLTM() | 1283 |
| 20.43 | MEP Linktrace Initiator receive variables | 1284 |
| 20.43.1 | LTRreceived | 1284 |
| 20.43.2 | LTRPDU | 1284 |
| 20.44 | MEP Linktrace Initiator receive procedures | 1284 |
| 20.44.1 | ProcessLTR() | 1284 |
| 20.45 | MEP Linktrace Initiator receive state machine | 1285 |
| 20.46 | Linktrace Responder variables | 1285 |
| 20.46.1 | nPendingLTRs | 1285 |
| 20.46.2 | LTMreceived | 1285 |
| 20.46.3 | LTMPDU | 1285 |
| 20.47 | LTM Receiver procedures | 1286 |
| 20.47.1 | ProcessLTM() | 1286 |
| 20.47.2 | clearPendingLTRs() | 1290 |
| 20.47.3 | ForwardLTM() | 1290 |
| 20.47.4 | enqueLTR() | 1291 |
| 20.48 | LTM Receiver state machine | 1292 |
| 20.49 | LTR Transmitter procedure | 1293 |
| 20.49.1 | xmitOldestLTR() | 1293 |
| 20.50 | LTR Transmitter state machine | 1293 |
| 20.51 | CFM PDU validation and versioning | 1294 |
| 20.51.1 | Goals of CFM PDU versioning | 1294 |
| 20.51.2 | PDU transmission | 1294 |
| 20.51.3 | PDU validation | 1294 |
| 20.51.4 | Validation pass | 1295 |
| 20.51.5 | Execution pass | 1296 |
| 20.51.6 | Future extensions | 1296 |
| 20.52 | PDU identification | 1297 |
| 20.53 | Use of transaction IDs and sequence numbers | 1297 |

| | | |
|--------|---|------|
| 21. | Encoding of CFM PDUs | 1299 |
| 21.1 | Structure, representation, and encoding | 1299 |
| 21.2 | CFM encapsulation | 1299 |
| 21.3 | CFM request and indication parameters | 1300 |
| 21.3.1 | destination_address parameter | 1300 |
| 21.3.2 | source_address parameter | 1300 |
| 21.4 | Common CFM Header | 1300 |
| 21.4.1 | MD Level | 1300 |
| 21.4.2 | Version | 1300 |
| 21.4.3 | OpCode | 1301 |
| 21.4.4 | Flags | 1301 |
| 21.4.5 | First TLV Offset | 1302 |
| 21.5 | TLV format | 1302 |
| 21.5.1 | General format for CFM TLVs | 1302 |
| 21.5.2 | Organization-Specific TLV | 1303 |
| 21.5.3 | Sender ID TLV | 1304 |
| 21.5.4 | Port Status TLV | 1305 |
| 21.5.5 | Interface Status TLV | 1306 |
| 21.5.6 | Data TLV | 1307 |
| 21.5.7 | End TLV | 1307 |
| 21.6 | CCM format | 1307 |
| 21.6.1 | Flags | 1308 |
| 21.6.2 | First TLV Offset | 1309 |
| 21.6.3 | Sequence Number | 1309 |
| 21.6.4 | Maintenance association Endpoint Identifier | 1309 |
| 21.6.5 | Maintenance Association Identifier | 1309 |
| 21.6.6 | Defined by ITU-T Y.1731 (02/2008) | 1312 |
| 21.6.7 | Optional CCM TLVs | 1312 |
| 21.7 | LBM and LBR formats | 1312 |
| 21.7.1 | Flags | 1312 |
| 21.7.2 | First TLV Offset | 1313 |
| 21.7.3 | Loopback Transaction Identifier | 1313 |
| 21.7.4 | Additional LBM/LBR TLVs | 1313 |
| 21.7.5 | PBB-TE MIP TLV | 1314 |
| 21.8 | LTM format | 1315 |
| 21.8.1 | Flags | 1315 |
| 21.8.2 | First TLV Offset | 1315 |
| 21.8.3 | LTM Transaction Identifier | 1315 |
| 21.8.4 | LTM TTL | 1316 |
| 21.8.5 | Original MAC Address | 1316 |
| 21.8.6 | Target MAC Address | 1316 |
| 21.8.7 | Additional LTM TLVs | 1316 |
| 21.8.8 | LTM Egress Identifier TLV | 1316 |
| 21.9 | LTR format | 1317 |
| 21.9.1 | Flags | 1317 |
| 21.9.2 | First TLV Offset | 1318 |
| 21.9.3 | LTR Transaction Identifier | 1318 |
| 21.9.4 | Reply TTL | 1318 |
| 21.9.5 | Relay Action | 1318 |
| 21.9.6 | Additional LTR TLVs | 1318 |
| 21.9.7 | LTR Egress Identifier TLV | 1319 |
| 21.9.8 | Reply Ingress TLV | 1319 |
| 21.9.9 | Reply Egress TLV | 1321 |

| | | |
|--------|--|------|
| 22. | CFM in systems | 1323 |
| 22.1 | CFM shims in Bridges | 1323 |
| 22.1.1 | Preliminary positioning of MPs | 1323 |
| 22.1.2 | CFM and the Forwarding Process | 1324 |
| 22.1.3 | Up/Down separation of MPs | 1326 |
| 22.1.4 | Service instances over multiple Bridges | 1328 |
| 22.1.5 | Multiple VID service instances | 1330 |
| 22.1.6 | Untagged CFM PDUs | 1330 |
| 22.1.7 | MPs and non-VLAN-aware Bridges | 1330 |
| 22.1.8 | MPs and other standards | 1331 |
| 22.1.9 | CFM and IEEE 802.3 OAM | 1333 |
| 22.2 | Maintenance Entity creation | 1333 |
| 22.2.1 | Creating Maintenance Domains and MAs | 1334 |
| 22.2.2 | Creating MEPs | 1334 |
| 22.2.3 | Creating MIPs | 1336 |
| 22.2.4 | CFM configuration errors | 1337 |
| 22.3 | MPs, Ports, and MD Level assignment..... | 1338 |
| 22.4 | Stations and CFM | 1338 |
| 22.5 | Scalability of CFM..... | 1339 |
| 22.6 | CFM in Provider Bridges..... | 1340 |
| 22.6.1 | MPs and C-VLAN components | 1340 |
| 22.6.2 | Maintenance C-VLAN on a Port-based service interface | 1341 |
| 22.6.3 | Maintenance C-VLAN on a C-tagged service interface | 1342 |
| 22.6.4 | MPs and Port-mapping S-VLAN components | 1342 |
| 22.7 | Management Port MEPs and CFM in the enterprise environment..... | 1344 |
| 22.8 | Implementing CFM on Bridges that implement earlier revisions of IEEE Std 802.1Q | 1346 |
| 23. | MAC status propagation | 1347 |
| 23.1 | Model of operation..... | 1348 |
| 23.1.1 | MAC Status Shim (MSS) | 1349 |
| 23.1.2 | Relationship of CFM to the MSS | 1350 |
| 23.2 | MAC Status Protocol (MSP) overview | 1350 |
| 23.3 | MSP state machines | 1355 |
| 23.4 | State machine timers | 1356 |
| 23.4.1 | linkNotifyWhen | 1356 |
| 23.4.2 | linkNotifyWhile | 1356 |
| 23.4.3 | macNotifyWhile | 1356 |
| 23.4.4 | macRecoverWhile | 1356 |
| 23.5 | MSP performance parameters..... | 1356 |
| 23.5.1 | LinkNotify | 1357 |
| 23.5.2 | LinkNotifyWait | 1357 |
| 23.5.3 | LinkNotifyRetry | 1357 |
| 23.5.4 | MACNotify | 1357 |
| 23.5.5 | MACNotifyTime | 1357 |
| 23.5.6 | MACRecoverTime | 1357 |
| 23.6 | State machine variables | 1357 |
| 23.6.1 | BEGIN | 1357 |
| 23.6.2 | addConfirmed | 1357 |
| 23.6.3 | disableMAC | 1357 |
| 23.6.4 | disabledMAC | 1357 |
| 23.6.5 | disableMSS | 1358 |
| 23.6.6 | lossConfirmed | 1358 |
| 23.6.7 | macOperational | 1358 |

| | | |
|---------|---|------|
| 23.6.8 | mssOperational | 1358 |
| 23.6.9 | prop | 1358 |
| 23.6.10 | rxAck | 1358 |
| 23.6.11 | rxAdd | 1358 |
| 23.6.12 | rxAddConfirm | 1358 |
| 23.6.13 | rxLoss | 1358 |
| 23.6.14 | rxLossConfirm | 1358 |
| 23.6.15 | txAck | 1358 |
| 23.6.16 | txAdd | 1358 |
| 23.6.17 | txAddConfirm | 1359 |
| 23.6.18 | txLoss | 1359 |
| 23.6.19 | txLossConfirm | 1359 |
| 23.7 | State machine procedures | 1359 |
| 23.8 | Status Transition state machine (STM) | 1359 |
| 23.9 | Status Notification state machine (SNM) | 1360 |
| 23.10 | Receive Process | 1360 |
| 23.11 | Transmit Process | 1360 |
| 23.12 | Management of MSP | 1360 |
| 23.13 | MSPDU transmission, addressing, and protocol identification | 1361 |
| 23.13.1 | Destination MAC Address | 1361 |
| 23.13.2 | Source MAC Address | 1361 |
| 23.13.3 | Priority | 1362 |
| 23.13.4 | EtherType use and encoding | 1362 |
| 23.14 | Representation and encoding of octets | 1362 |
| 23.15 | MSPDU structure | 1362 |
| 23.15.1 | Protocol Version | 1362 |
| 23.15.2 | Packet Type | 1363 |
| 23.16 | Validation of received MSPDUs | 1363 |
| 23.17 | Other MSP participants | 1363 |
| 24. | Bridge performance | 1364 |
| 24.1 | Guaranteed Port Filtering Rate | 1364 |
| 24.2 | Guaranteed Bridge Relaying Rate | 1364 |
| 24.3 | RSTP performance requirements | 1364 |
| 25. | Support of the MAC Service by PBBNs | 1366 |
| 25.1 | Service transparency | 1368 |
| 25.2 | Customer service interface | 1368 |
| 25.3 | Port-based service interface | 1369 |
| 25.4 | S-tagged service interface | 1370 |
| 25.5 | I-tagged service interface | 1372 |
| 25.6 | Service instance segregation | 1374 |
| 25.7 | Service instance selection and identification | 1374 |
| 25.8 | Service priority and drop eligibility selection | 1375 |
| 25.9 | Service access protection | 1375 |
| 25.9.1 | Class II redundant LANs access protection | 1377 |
| 25.9.2 | Class III simple redundant LANs and nodes access protection | 1378 |
| 25.10 | Support of the MAC Service by a PBB-TE Region | 1379 |
| 25.10.1 | Provisioning TESIS | 1380 |
| 25.10.2 | ESP forwarding behavior | 1381 |
| 25.11 | Transparent service interface | 1382 |

| | | |
|---------|--|------|
| 26. | Principles of Provider Backbone Bridged Network (PBBN) operation | 1384 |
| 26.1 | PBBN overview | 1384 |
| 26.2 | PBBN example | 1385 |
| 26.3 | B-VLAN connectivity..... | 1387 |
| 26.4 | Backbone addressing | 1388 |
| 26.4.1 | Learning individual backbone addresses at a PIP | 1389 |
| 26.4.2 | Translating backbone destination addresses at a CBP | 1389 |
| 26.4.3 | Backbone addressing considerations for CFM MPs | 1390 |
| 26.5 | Detection of connectivity loops through attached networks..... | 1390 |
| 26.6 | Scaling of PBBs | 1390 |
| 26.6.1 | Hierarchal PBBNs | 1391 |
| 26.6.2 | Peer PBBNs | 1391 |
| 26.7 | Network management | 1391 |
| 26.8 | CFM in PBBs..... | 1392 |
| 26.8.1 | CFM over Port-based and S-tagged service interfaces | 1397 |
| 26.8.2 | CFM over I-tagged Service Interfaces | 1398 |
| 26.8.3 | CFM over hierarchal E-NNI | 1398 |
| 26.8.4 | CFM over peer E-NNI | 1398 |
| 26.9 | CFM in a PBB-TE Region..... | 1399 |
| 26.9.1 | Addressing PBB-TE MEPs | 1399 |
| 26.9.2 | TESI identification | 1400 |
| 26.9.3 | PBB-TE MEP placement in a Bridge Port | 1400 |
| 26.9.4 | PBB-TE MIP placement in a Bridge Port | 1400 |
| 26.9.5 | TESI Maintenance Domains | 1400 |
| 26.9.6 | PBB-TE enhancements of the CFM protocols | 1401 |
| 26.9.7 | Addressing Infrastructure Segment MEPs | 1403 |
| 26.9.8 | Infrastructure Segment identification | 1403 |
| 26.9.9 | Infrastructure Segment MEP placement in a Bridge Port | 1404 |
| 26.9.10 | Infrastructure Segment Maintenance Domains | 1404 |
| 26.9.11 | IPS extensions to Continuity Check operation | 1404 |
| 26.10 | Protection switching for point-to-point TESIs..... | 1406 |
| 26.10.1 | Introduction | 1406 |
| 26.10.2 | 1:1 point-to-point TESI protection switching | 1407 |
| 26.10.3 | Protection Switching state machines | 1410 |
| 26.11 | IPS in PBB-TE Region | 1415 |
| 26.11.1 | Infrastructure Segment monitoring | 1416 |
| 26.11.2 | 1:1 IPS | 1417 |
| 26.11.3 | IPS Control entity | 1420 |
| 26.11.4 | 1:1 IPS state machines | 1421 |
| 26.11.5 | M:1 IPS | 1421 |
| 26.12 | Mismatch defect..... | 1427 |
| 26.13 | Signaling VLAN registrations among I-components | 1428 |
| 27. | Shortest Path Bridging (SPB) | 1429 |
| 27.1 | Protocol design requirements..... | 1431 |
| 27.2 | Protocol support..... | 1432 |
| 27.3 | Protocol design goals | 1433 |
| 27.4 | ISIS-SPB VLAN configuration | 1433 |
| 27.4.1 | SPT Region and ISIS-SPB adjacency determination | 1434 |
| 27.5 | ISIS-SPB information | 1436 |
| 27.6 | Calculating CIST connectivity..... | 1437 |
| 27.7 | Connectivity between regions in the same domain | 1438 |
| 27.8 | Calculating SPT connectivity | 1438 |

| | | |
|----------|---|------|
| 27.8.1 | ISIS-SPB overload | 1439 |
| 27.9 | Loop prevention..... | 1439 |
| 27.10 | SPVID and SPSourceID allocation..... | 1439 |
| 27.11 | Allocation of VIDs to FIDs | 1441 |
| 27.12 | SPBV SPVID translation | 1442 |
| 27.13 | VLAN topology management..... | 1442 |
| 27.14 | Individual addresses and SPBM | 1443 |
| 27.14.1 | Loop mitigation | 1444 |
| 27.14.2 | Loop prevention | 1444 |
| 27.15 | SPBM group addressing | 1445 |
| 27.16 | Backbone service instance topology management | 1447 |
| 27.17 | Equal cost shortest paths, ECTs, and load spreading | 1447 |
| 27.18 | Connectivity Fault Management for SPBM | 1448 |
| 27.18.1 | SPBM MA types | 1448 |
| 27.18.2 | SPBM MEP placement in a Bridge Port | 1448 |
| 27.18.3 | SPBM MIP placement in a Bridge Port | 1449 |
| 27.18.4 | SPBM modifications of the CFM protocols | 1449 |
| 27.19 | Using SPBV and SPBM modes | 1451 |
| 27.19.1 | Shortest Path Bridging—VID | 1451 |
| 27.19.2 | Shortest Path Bridging—MAC | 1452 |
| 27.20 | Security considerations | 1454 |
| 28. | ISIS-SPB Link State Protocol..... | 1455 |
| 28.1 | ISIS-SPB control plane MAC..... | 1455 |
| 28.2 | Formation and maintenance of ISIS-SPB adjacencies | 1456 |
| 28.3 | Loop prevention..... | 1457 |
| 28.4 | The Agreement Digest..... | 1457 |
| 28.4.1 | Agreement Digest Format Identifier | 1458 |
| 28.4.2 | Agreement Digest Format Capabilities | 1458 |
| 28.4.3 | Agreement Digest Convention Identifier | 1458 |
| 28.4.4 | Agreement Digest Convention Capabilities | 1459 |
| 28.4.5 | Agreement Digest Edge Count | 1459 |
| 28.4.6 | The Computed Topology Digest | 1459 |
| 28.5 | Symmetric shortest path tie breaking..... | 1460 |
| 28.6 | Symmetric ECT framework..... | 1461 |
| 28.7 | Symmetric ECT | 1462 |
| 28.8 | Symmetric ECT Algorithm details | 1463 |
| 28.9 | ECT Migration..... | 1464 |
| 28.9.1 | Use of a new ECT Algorithm in SPBV | 1465 |
| 28.9.2 | Use of a new ECT Algorithm in SPBM | 1465 |
| 28.10 | MAC address registration | 1466 |
| 28.11 | Circuit IDs and Port Identifiers..... | 1467 |
| 28.12 | ISIS-SPB TLVs..... | 1467 |
| 28.12.1 | MT-Capability TLV | 1468 |
| 28.12.2 | SPB MCID sub-TLV | 1468 |
| 28.12.3 | SPB Digest sub-TLV | 1469 |
| 28.12.4 | SPB Base VLAN-Identifiers sub-TLV | 1469 |
| 28.12.5 | SPB Instance sub-TLV | 1471 |
| 28.12.6 | SPB Instance Opaque ECT Algorithm sub-TLV | 1473 |
| 28.12.7 | SPB Link Metric sub-TLV | 1474 |
| 28.12.8 | SPB Adjacency Opaque ECT Algorithm sub-TLV | 1475 |
| 28.12.9 | SPBV MAC address sub-TLV | 1476 |
| 28.12.10 | SPBM Service Identifier and Unicast Address (ISID-ADDR) sub-TLV | 1477 |

| | | |
|---------|--|------|
| 29. | DDCFM operations and protocols..... | 1480 |
| 29.1 | Principles of DDCFM operation..... | 1480 |
| 29.1.1 | Data-driven and data-dependent faults (DDFs) | 1480 |
| 29.1.2 | Basic principle to diagnose and isolate DDFs | 1480 |
| 29.2 | DDCFM Entity operation | 1483 |
| 29.2.1 | DDCFM implementation | 1483 |
| 29.2.2 | FPT RR | 1484 |
| 29.2.3 | RR-related parameters | 1485 |
| 29.2.4 | Reflection Target and RFM Receiver | 1486 |
| 29.2.5 | RPT-related parameters | 1486 |
| 29.2.6 | Decapsulator Responder (DR) | 1487 |
| 29.2.7 | SFM Originator | 1488 |
| 29.3 | DDCFM protocols | 1488 |
| 29.3.1 | RR variables | 1488 |
| 29.3.2 | RR Filter procedures | 1490 |
| 29.3.3 | RR Encapsulation procedures | 1491 |
| 29.3.4 | RR Transmit procedure | 1492 |
| 29.3.5 | RR-related state machines | 1493 |
| 29.3.6 | RFM Receiver variables | 1495 |
| 29.3.7 | RFM Receiver procedure | 1495 |
| 29.3.8 | DR variables | 1496 |
| 29.3.9 | DR procedures | 1497 |
| 29.3.10 | Decapsulator Responder state machine | 1498 |
| 29.4 | Encoding of DDCFM PDUs..... | 1498 |
| 29.4.1 | RFM and SFM Header | 1498 |
| 29.4.2 | RFM format | 1499 |
| 29.4.3 | SFM format | 1500 |
| 30. | Principles of congestion notification | 1502 |
| 30.1 | Congestion notification design requirements | 1502 |
| 30.2 | Quantized Congestion Notification protocol (QCN) | 1504 |
| 30.2.1 | The CP algorithm | 1505 |
| 30.2.2 | Basic RP algorithm | 1506 |
| 30.2.3 | RP algorithm with timer | 1507 |
| 30.3 | Congestion Controlled Flow (CCF) | 1508 |
| 30.4 | Congestion Notification Priority Value (CNPV) | 1509 |
| 30.5 | Congestion Notification tag (CN-TAG) | 1509 |
| 30.6 | Congestion Notification Domain (CND) | 1509 |
| 30.7 | Multicast data | 1510 |
| 30.8 | Congestion notification and additional tags | 1510 |
| 31. | Congestion notification entity operation | 1512 |
| 31.1 | Congestion-aware Bridge Forwarding Process | 1512 |
| 31.1.1 | Congestion Point (CP) | 1513 |
| 31.1.2 | CP ingress multiplexer | 1513 |
| 31.2 | Congestion-aware end station functions | 1513 |
| 31.2.1 | Output flow segregation | 1514 |
| 31.2.2 | Per-CNPV station function | 1515 |
| 31.2.3 | Flow Select Database | 1517 |
| 31.2.4 | Flow multiplexer | 1517 |
| 31.2.5 | CNM demultiplexer | 1517 |
| 31.2.6 | Input flow segregation | 1517 |

| | | |
|---------|--|------|
| 31.2.7 | End station input queue | 1518 |
| 31.2.8 | Reception selection | 1518 |
| 32. | Congestion notification protocol | 1519 |
| 32.1 | CND operations | 1519 |
| 32.1.1 | CND defense | 1519 |
| 32.1.2 | Automatic CND recognition | 1521 |
| 32.1.3 | Variables controlling CND defense | 1521 |
| 32.2 | CN component variables | 1522 |
| 32.2.1 | cngMasterEnable | 1523 |
| 32.2.2 | cngCnmTransmitPriority | 1523 |
| 32.2.3 | cngDiscardedFrames | 1523 |
| 32.2.4 | cngErroredPortList | 1523 |
| 32.3 | Congestion notification per-CNPV variables | 1523 |
| 32.3.1 | cncpDefModeChoice | 1523 |
| 32.3.2 | cncpAlternatePriority | 1524 |
| 32.3.3 | cncpAutoAltPri | 1524 |
| 32.3.4 | cncpAdminDefenseMode | 1524 |
| 32.3.5 | cncpCreation | 1524 |
| 32.3.6 | cncpLdpInstanceChoice | 1524 |
| 32.3.7 | cncpLdpInstanceSelector | 1524 |
| 32.4 | CND defense per-Port per-CNPV variables | 1525 |
| 32.4.1 | cnpdDefModeChoice | 1525 |
| 32.4.2 | cnpdAdminDefenseMode | 1525 |
| 32.4.3 | cnpdAutoDefenseMode | 1526 |
| 32.4.4 | cnpdLdpInstanceChoice | 1526 |
| 32.4.5 | cnpdLdpInstanceSelector | 1526 |
| 32.4.6 | cnpdAlternatePriority | 1526 |
| 32.4.7 | cnpdXmitCnpvCapable | 1526 |
| 32.4.8 | cnpdXmitReady | 1526 |
| 32.4.9 | cncpDoesEdge | 1527 |
| 32.4.10 | cnpdAcceptsCnTag | 1527 |
| 32.4.11 | cnpdRcvdCnpv | 1527 |
| 32.4.12 | cnpdRcvdReady | 1527 |
| 32.4.13 | cnpdIsAdminDefMode | 1527 |
| 32.4.14 | cnpdDefenseMode | 1528 |
| 32.5 | CND defense procedures | 1528 |
| 32.5.1 | DisableCnpvRemapping() | 1528 |
| 32.5.2 | TurnOnCnDefenses() | 1528 |
| 32.5.3 | TurnOffCnDefenses() | 1528 |
| 32.6 | CND defense state machine | 1528 |
| 32.7 | Congestion notification protocol | 1529 |
| 32.8 | CP variables | 1530 |
| 32.8.1 | cpMacAddress | 1531 |
| 32.8.2 | cpId | 1531 |
| 32.8.3 | cpQSp | 1531 |
| 32.8.4 | cpQLen | 1531 |
| 32.8.5 | cpQLenOld | 1531 |
| 32.8.6 | cpW | 1531 |
| 32.8.7 | cpQOffset | 1531 |
| 32.8.8 | cpQDelta | 1531 |
| 32.8.9 | cpFb | 1531 |
| 32.8.10 | cpEnqued | 1532 |

| | | |
|----------|---|------|
| 32.8.11 | cpSampleBase | 1532 |
| 32.8.12 | cpDiscardedFrames | 1532 |
| 32.8.13 | cpTransmittedFrames | 1532 |
| 32.8.14 | cpTransmittedCnms | 1532 |
| 32.8.15 | cpMinHeaderOctets | 1532 |
| 32.9 | CP procedures | 1532 |
| 32.9.1 | Random | 1532 |
| 32.9.2 | NewCpSampleBase() | 1532 |
| 32.9.3 | EM_UNITDATA.request (parameters) | 1533 |
| 32.9.4 | GenerateCnmPdu() | 1533 |
| 32.10 | RP per-Port per-CNPV variables | 1534 |
| 32.10.1 | rpppMaxRps | 1534 |
| 32.10.2 | rpppCreatedRps | 1534 |
| 32.10.3 | rpppRpCentiseconds | 1535 |
| 32.11 | RP group variables | 1535 |
| 32.11.1 | rpgEnable | 1535 |
| 32.11.2 | rpgTimeReset | 1535 |
| 32.11.3 | rpgByteReset | 1535 |
| 32.11.4 | rpgThreshold | 1536 |
| 32.11.5 | rpgMaxRate | 1536 |
| 32.11.6 | rpgAiRate | 1536 |
| 32.11.7 | rpgHaiRate | 1536 |
| 32.11.8 | rpgGd | 1536 |
| 32.11.9 | rpgMinDecFac | 1536 |
| 32.11.10 | rpgMinRate | 1536 |
| 32.12 | RP timer | 1536 |
| 32.12.1 | RpWhile | 1537 |
| 32.13 | RP variables | 1537 |
| 32.13.1 | rpEnabled | 1537 |
| 32.13.2 | rpByteCount | 1537 |
| 32.13.3 | rpByteStage | 1537 |
| 32.13.4 | rpTimeStage | 1537 |
| 32.13.5 | rpTargetRate | 1537 |
| 32.13.6 | rpCurrentRate | 1538 |
| 32.13.7 | rpFreeze | 1538 |
| 32.13.8 | rpLimiterRate | 1538 |
| 32.13.9 | rpFb | 1538 |
| 32.14 | RP procedures | 1538 |
| 32.14.1 | ResetCnm | 1538 |
| 32.14.2 | TestRpTerminate | 1539 |
| 32.14.3 | TransmitDataFrame | 1539 |
| 32.14.4 | ReceiveCnm | 1539 |
| 32.14.5 | ProcessCnm | 1540 |
| 32.14.6 | AdjustRates | 1540 |
| 32.15 | RP rate control state machine | 1540 |
| 32.16 | Congestion notification and encapsulation interworking function | 1542 |
| 33. | Encoding of congestion notification PDUs | 1544 |
| 33.1 | Structure, representation, and encoding | 1544 |
| 33.2 | CN-TAG format | 1544 |
| 33.2.1 | Flow Identifier | 1545 |
| 33.3 | Congestion Notification Message (CNM) | 1545 |
| 33.4 | Congestion Notification Message PDU format | 1545 |

| | | |
|---------|---|------|
| 33.4.1 | Version | 1545 |
| 33.4.2 | ReservedV | 1546 |
| 33.4.3 | Quantized Feedback | 1546 |
| 33.4.4 | Congestion Point Identifier | 1546 |
| 33.4.5 | cnmQOffset | 1546 |
| 33.4.6 | cnmQDelta | 1547 |
| 33.4.7 | Encapsulated priority | 1547 |
| 33.4.8 | Encapsulated destination MAC address | 1547 |
| 33.4.9 | Encapsulated MSDU length | 1547 |
| 33.4.10 | Encapsulated MSDU | 1547 |
| 33.4.11 | CNM Validation | 1547 |
| 34. | Forwarding and Queuing Enhancements for time-sensitive streams (FQTSS)..... | 1548 |
| 34.1 | Overview..... | 1548 |
| 34.2 | Detection of SRP domains | 1548 |
| 34.3 | The bandwidth availability parameters..... | 1549 |
| 34.3.1 | Relationships among bandwidth availability parameters | 1549 |
| 34.3.2 | Bandwidth availability parameter management | 1550 |
| 34.4 | Deriving actual bandwidth requirements from the size of the MSDU | 1550 |
| 34.5 | Mapping priorities to traffic classes for time-sensitive streams | 1551 |
| 34.6 | End station behavior | 1553 |
| 34.6.1 | Talker behavior | 1553 |
| 34.6.2 | Listener behavior | 1554 |
| 35. | Stream Reservation Protocol (SRP)..... | 1555 |
| 35.1 | Multiple Stream Registration Protocol (MSRP)..... | 1556 |
| 35.1.1 | MSRP and Shared Media | 1557 |
| 35.1.2 | Behavior of end stations | 1557 |
| 35.1.3 | Behavior of Bridges | 1559 |
| 35.1.4 | SRP domains and status parameters | 1559 |
| 35.2 | Definition of the MSRP application..... | 1559 |
| 35.2.1 | Definition of internal state variables | 1560 |
| 35.2.2 | Definition of MRP elements | 1562 |
| 35.2.3 | Provision and support of Stream registration service | 1572 |
| 35.2.4 | MSRP Attribute Propagation | 1576 |
| 35.2.5 | Operational reporting and statistics | 1581 |
| 35.2.6 | Encoding | 1581 |
| 35.2.7 | Attribute value support requirements | 1582 |
| 36. | Priority-based Flow Control (PFC) | 1583 |
| 36.1 | PFC operation | 1583 |
| 36.1.1 | Overview | 1583 |
| 36.1.2 | PFC primitives | 1584 |
| 36.1.3 | Detailed specification of PFC operation | 1585 |
| 36.2 | PFC-aware system queue functions | 1586 |
| 36.2.1 | PFC Initiator | 1587 |
| 36.2.2 | PFC Receiver | 1587 |
| 37. | Enhanced Transmission Selection (ETS) | 1589 |
| 37.1 | Overview..... | 1589 |
| 37.1.1 | Relationship to other transmission selection algorithms | 1589 |
| 37.2 | ETS configuration parameters | 1589 |

| | | |
|---------|---|------|
| 37.3 | ETS algorithm..... | 1589 |
| 37.4 | Legacy configuration..... | 1590 |
| 38. | Data Center Bridging eXchange protocol (DCBX)..... | 1591 |
| 38.1 | Overview..... | 1591 |
| 38.2 | Goals..... | 1591 |
| 38.3 | Types of DCBX attributes..... | 1591 |
| 38.3.1 | Informational attributes..... | 1591 |
| 38.4 | DCBX and LLDP..... | 1592 |
| 38.4.1 | Asymmetric attribute passing..... | 1592 |
| 38.4.2 | Symmetric attribute passing..... | 1593 |
| 39. | Multiple I-SID Registration Protocol (MIRP)..... | 1595 |
| 39.1 | MIRP overview..... | 1595 |
| 39.1.1 | Behavior of I-components..... | 1597 |
| 39.1.2 | Behavior of B-components..... | 1597 |
| 39.2 | Definition of the MIRP application..... | 1597 |
| 39.2.1 | Definition of MRP elements..... | 1597 |
| 39.2.2 | Alternate MIRP model for B-components..... | 1600 |
| 39.2.3 | Use of “new” declaration capability..... | 1602 |
| 39.2.4 | Attribute value support requirements..... | 1602 |
| 39.2.5 | MRP Message filtering..... | 1602 |
| 40. | Edge Virtual Bridging (EVB)..... | 1603 |
| 40.1 | EVB architecture without S-channels..... | 1604 |
| 40.2 | EVB architecture with S-channels..... | 1605 |
| 40.3 | Asymmetric EVB architecture without S-channels..... | 1607 |
| 40.4 | EVB status parameters..... | 1609 |
| 40.4.1 | EVBMode = Not supported..... | 1609 |
| 40.4.2 | EVBMode = EVB Bridge..... | 1609 |
| 40.4.3 | EVBMode = EVB station..... | 1609 |
| 41. | VSI Discovery and Configuration Protocol (VDP)..... | 1610 |
| 41.1 | VSI manager ID TLV definition..... | 1610 |
| 41.1.1 | TLV type..... | 1610 |
| 41.1.2 | TLV information string length..... | 1610 |
| 41.1.3 | VSI Manager ID..... | 1611 |
| 41.2 | VDP association TLV definitions..... | 1611 |
| 41.2.1 | TLV type..... | 1611 |
| 41.2.2 | TLV information string length..... | 1612 |
| 41.2.3 | Status..... | 1612 |
| 41.2.4 | VSI Type ID (VTID)..... | 1613 |
| 41.2.5 | VSI Type Version..... | 1613 |
| 41.2.6 | VSIID format..... | 1613 |
| 41.2.7 | VSIID..... | 1613 |
| 41.2.8 | Filter Info format..... | 1614 |
| 41.2.9 | Filter Info field..... | 1614 |
| 41.2.10 | VDP TLV type and Status semantics..... | 1617 |
| 41.3 | Organizationally defined TLV definitions..... | 1618 |
| 41.3.1 | TLV type..... | 1618 |
| 41.3.2 | TLV information string length..... | 1618 |
| 41.3.3 | Organizationally unique identifier (OUI) or Company ID (CID)..... | 1618 |

| | | |
|---------|--|------|
| 41.3.4 | Organizational information | 1618 |
| 41.4 | Validation rules for VDP TLVs | 1618 |
| 41.5 | VDP state machines | 1619 |
| 41.5.1 | State machine conventions | 1619 |
| 41.5.2 | Bridge VDP state machine | 1619 |
| 41.5.3 | Station VDP state machine | 1620 |
| 41.5.4 | VDP state machine timers | 1621 |
| 41.5.5 | VDP state machine variables and parameters | 1621 |
| 41.5.6 | Command-Response TLV field references in state machines | 1624 |
| 41.5.7 | VDP state machine procedures | 1624 |
| 42. | S-Channel Discovery and Configuration Protocol (CDCP) | 1626 |
| 42.1 | CDCP discovery and configuration | 1626 |
| 42.2 | CDCP state machine overview | 1626 |
| 42.3 | CDCP configuration state machine | 1627 |
| 42.4 | CDCP configuration variables | 1629 |
| 42.4.1 | AdminChnCap | 1629 |
| 42.4.2 | AdminRole | 1629 |
| 42.4.3 | AdminSVIDWants | 1629 |
| 42.4.4 | LastLocalSVIDPool | 1629 |
| 42.4.5 | LastRemoteSVIDList | 1629 |
| 42.4.6 | LastSVIDWants | 1629 |
| 42.4.7 | LocalSVIDPool | 1629 |
| 42.4.8 | OperChnCap | 1629 |
| 42.4.9 | OperRole | 1630 |
| 42.4.10 | OperSVIDList | 1630 |
| 42.4.11 | RemoteChnCap | 1630 |
| 42.4.12 | RemoteRole | 1630 |
| 42.4.13 | RemoteSVIDList | 1630 |
| 42.4.14 | schState | 1630 |
| 42.5 | CDCP configuration procedures | 1630 |
| 42.5.1 | SetSVIDRequest (OperRole, AdminSVIDWants, OperSVIDList) | 1630 |
| 42.5.2 | RxSVIDConfig (OperSVIDList, LastRemoteSVIDList) | 1631 |
| 42.5.3 | TxSVIDConfig (OperChnCap, RemoteChnCap, LastLocalSVIDPool, RemoteSVIDList, OperSVIDList) | 1631 |
| 43. | Edge Control Protocol (ECP) | 1632 |
| 43.1 | ECP operation | 1632 |
| 43.2 | Edge Control Sublayer Service (ECSS) | 1633 |
| 43.3 | ECP state machines | 1633 |
| 43.3.1 | State machine conventions | 1633 |
| 43.3.2 | Overview | 1633 |
| 43.3.3 | Edge Control Protocol Data Unit (ECPDU) | 1634 |
| 43.3.4 | ECP transmit state machine | 1635 |
| 43.3.5 | ECP receive state machine | 1636 |
| 43.3.6 | ECP state machine timers | 1636 |
| 43.3.7 | ECP state machine variables and parameters | 1637 |
| 43.3.8 | ECP state machine procedures | 1638 |
| 44. | Equal Cost Multiple Paths (ECMP) | 1639 |
| 44.1 | SPBM ECMP | 1639 |
| 44.1.1 | ECMP Operation | 1639 |

| | | |
|-----------------------|---|------|
| 44.1.2 | ECMP ECT Algorithm | 1640 |
| 44.1.3 | Loop prevention for ECMP | 1642 |
| 44.2 | Support for Flow Filtering | 1642 |
| 44.2.1 | Flow filtering tag (F-TAG) | 1643 |
| 44.2.2 | F-TAG processing | 1644 |
| 44.2.3 | Forwarding process extension for flow filtering | 1645 |
| 44.2.4 | TTL Loop mitigation | 1646 |
| 44.2.5 | CFM for ECMP with flow filtering | 1646 |
| 44.2.6 | Operation with selective support for flow filtering | 1648 |
| 45. | Path Control and Reservation (PCR) | 1649 |
| 45.1 | Explicit trees | 1649 |
| 45.1.1 | Tree structures | 1653 |
| 45.1.2 | Explicit ECT Algorithms | 1654 |
| 45.1.3 | ISIS-PCR VLAN configuration | 1656 |
| 45.1.4 | Use of VIDs for strict explicit trees | 1660 |
| 45.1.5 | MAC addresses and ISIS-PCR | 1661 |
| 45.1.6 | Filtering Database entries for explicit trees | 1661 |
| 45.1.7 | ISIS-PCR support | 1662 |
| 45.1.8 | Attributes for path computation | 1662 |
| 45.1.9 | Topology sub-TLV | 1664 |
| 45.1.10 | Hop sub-TLV | 1667 |
| 45.1.11 | Administrative Group sub-TLV | 1670 |
| 45.1.12 | Bandwidth Constraint sub-TLV | 1670 |
| 45.2 | Reservation | 1671 |
| 45.2.1 | Bandwidth Assignment sub-TLV | 1671 |
| 45.2.2 | Timestamp sub-TLV | 1673 |
| 45.2.3 | Precedence ordering | 1673 |
| 45.3 | Redundancy | 1673 |
| 45.3.1 | Loop-free alternates for unicast data flows | 1674 |
| 45.3.2 | Static redundant trees | 1674 |
| 45.3.3 | Maximally Redundant Trees (MRTs) | 1675 |
| 45.3.4 | MRTs with centralized GADAG computation | 1678 |
| Annex A (normative) | PICS proforma—Bridge implementations | 1682 |
| Annex B (normative) | PICS proforma—End station implementations | 1748 |
| Annex C (normative) | Designated MSRP Node (DMN) Implementations | 1763 |
| Annex D (normative) | IEEE 802.1 Organizationally Specific TLVs | 1780 |
| Annex E (normative) | Notational conventions used in state diagrams | 1896 |
| Annex F (informative) | Shared and Independent VLAN Learning (SVL and IVL) | 1898 |
| Annex G (informative) | MAC method-dependent aspects of VLAN support..... | 1907 |
| Annex H (informative) | Interoperability considerations..... | 1911 |
| Annex I (informative) | Priority and drop precedence..... | 1917 |
| Annex J (informative) | CFM protocol design and use..... | 1925 |

| | |
|---|------|
| Annex K (informative) TPMR use cases | 1933 |
| Annex L (informative) Operation of the credit-based shaper algorithm | 1938 |
| Annex M (normative) Support for PFC in link layers without MAC Control | 1955 |
| Annex N (informative) Buffer requirements for PFC | 1956 |
| Annex O (informative) Preserving the integrity of FCS fields in MAC Bridges | 1961 |
| Annex P (informative) Frame duplication and misordering | 1968 |
| Annex Q (informative) Traffic scheduling | 1971 |
| Annex R (informative) Preemption and IEEE 802.1AE MAC Security | 1975 |
| Annex S (informative) Preemption and scheduled traffic | 1977 |
| Annex T (informative) Cyclic queuing and forwarding | 1980 |
| Annex U (informative) Bibliography | 1988 |

Figures

| | |
|--|-----|
| Figure 6-1—Internal organization of the MAC sublayer | 128 |
| Figure 6-2—Provider Instance Ports (PIPs) | 146 |
| Figure 6-3—B-Component CBP | 149 |
| Figure 6-4—Example of operation of Port-and-Protocol-based classification | 153 |
| Figure 6-5—Service access priority selection | 155 |
| Figure 6-6—Two back-to-back EISS Multiplex Entities | 161 |
| Figure 6-7—Two back-to-back Backbone Service Instance Multiplex Entities | 162 |
| Figure 6-8—Backbone Service Instance Multiplex Entities with example CFM shims | 163 |
| Figure 6-9—Two back-to-back Up and Down TESI Multiplex Entities | 165 |
| Figure 6-10—Supporting the ISS with signaled priority | 167 |
| Figure 6-11—Two back-to-back Up and Down Infrastructure Segment Multiplex Entities | 168 |
| Figure 7-1—VLAN Bridging overview | 170 |
| Figure 8-1—A Bridged Network | 176 |
| Figure 8-2—VLAN Bridge architecture | 178 |
| Figure 8-3—MAC Bridge architecture | 179 |
| Figure 8-4—Relaying MAC frames | 181 |
| Figure 8-5—Observation of network traffic | 181 |
| Figure 8-6—Operation of Spanning Tree Protocol Entity | 182 |
| Figure 8-7—Operation of MRP | 182 |
| Figure 8-8—Management Port transmission and reception | 183 |
| Figure 8-9—Infrastructure Segment MEP placement in a PNP | 183 |
| Figure 8-10—Bridge Port Transmit and Receive | 186 |
| Figure 8-11—TPMR Port Transmit and Receive | 186 |
| Figure 8-12—Forwarding process functions | 188 |
| Figure 8-13—Per-stream filtering and policing | 194 |
| Figure 8-14—Transmission selection with gates | 203 |
| Figure 8-15—Scheduled traffic state machines—overview and relationships | 206 |
| Figure 8-16—Cycle Timer state machine | 206 |
| Figure 8-17—List Execute state machine | 208 |
| Figure 8-18—List Config state machine | 209 |
| Figure 8-19—Logical points of attachment of the Higher Layer and Relay Entities | 238 |
| Figure 8-20—Effect of control information on the forwarding path | 238 |
| Figure 8-21—Per-Port points of attachment | 239 |
| Figure 8-22—Single point of attachment—relay permitted | 239 |
| Figure 8-23—Single point of attachment—relay not permitted | 240 |
| Figure 8-24—Effect of Port State | 240 |
| Figure 8-25—Controlled and Uncontrolled Port connectivity | 241 |
| Figure 8-26—Ingress/egress control information in the forwarding path | 241 |
| Figure 9-1—VLAN TCI format | 246 |
| Figure 9-2—I-TAG TCI format | 247 |
| Figure 10-1—Example—Attribute value propagation from one station | 250 |
| Figure 10-2—Example—Attribute value propagation from two stations | 251 |
| Figure 10-3—Example—Registrations as pointers to the sources of declarations | 251 |
| Figure 10-4—MRP architecture | 253 |
| Figure 10-5—Format of the major components of an MRPDU | 276 |
| Figure 10-6—Operation of MMRP for a single VLAN Context | 282 |
| Figure 10-7—Example Directed Graph | 283 |
| Figure 10-8—Example of MMRP propagation in a VLAN Context | 285 |
| Figure 11-1—Operation of MVRP | 293 |
| Figure 12-1—Relationships among CFM managed objects | 354 |
| Figure 12-2—Relationship among BEB managed objects | 371 |

| | |
|--|-----|
| Figure 12-3—SPB managed objects (MOs) | 425 |
| Figure 12-4—Relationships among EVB Bridge managed objects | 441 |
| Figure 12-5—Relationship among EVB station managed objects | 442 |
| Figure 12-6—Timing points for scheduled traffic | 458 |
| Figure 12-7—Timing points for PSFP | 465 |
| Figure 13-1—Diagrammatic conventions for spanning tree topologies | 472 |
| Figure 13-2—Physical topology and active topology | 473 |
| Figure 13-3—Port Roles and Port States | 473 |
| Figure 13-4—A Backup Port | 474 |
| Figure 13-5—“Ring Backbone” example | 474 |
| Figure 13-6—An MST Bridge network | 476 |
| Figure 13-7—CIST Priority Vectors, Port Roles, and MST Regions | 477 |
| Figure 13-8—MSTI Active Topology in Region 2 | 478 |
| Figure 13-9—CIST and MSTI active topologies in Region 1 of the example network | 491 |
| Figure 13-10—Agreements and Proposals | 495 |
| Figure 13-11—CIST and MSTI Active Topologies in Region 2 of Figure 13-6 | 496 |
| Figure 13-12—Enhanced Agreements | 497 |
| Figure 13-13—Spanning tree protocol state machines—overview and relationships | 508 |
| Figure 13-14—MSTP overview notation | 509 |
| Figure 13-15—Port Timers state machine | 539 |
| Figure 13-16—Port Receive state machine | 539 |
| Figure 13-17—Port Protocol Migration state machine | 540 |
| Figure 13-18—Bridge Detection state machine | 540 |
| Figure 13-19—Port Transmit state machine | 541 |
| Figure 13-20—Port Information state machine | 542 |
| Figure 13-21—Port Role Selection state machine | 543 |
| Figure 13-22—Disabled Port role transitions | 544 |
| Figure 13-23—Port Role Transitions state machine—MasterPort | 545 |
| Figure 13-24—Port Role Transitions state machine—RootPort | 546 |
| Figure 13-25—Port Role Transitions state machine—DesignatedPort | 547 |
| Figure 13-26—Port Role Transitions state machine—AlternatePort and BackupPort | 548 |
| Figure 13-27—Port State Transition state machine | 548 |
| Figure 13-28—Topology Change state machine | 550 |
| Figure 13-29—L2 Gateway Port Receive state machine | 551 |
| Figure 14-1—RST, MST, SPT, and STP Configuration BPDU format | 555 |
| Figure 14-2—STP TCN BPDU format | 555 |
| Figure 14-3—MSTI Configuration Message parameters and format | 560 |
| Figure 15-1—Internal organization of the MAC sublayer in a PBN | 563 |
| Figure 15-2—Port-based service interface to a PBN | 564 |
| Figure 15-3—Port-based service interface to a PBN | 565 |
| Figure 15-4—C-tagged service interface to a PBN | 565 |
| Figure 15-5—C-tagged service interface to a PBN | 565 |
| Figure 15-6—Customer Edge Ports (CEPs) | 566 |
| Figure 15-7—S-tagged service interface to a PBN | 566 |
| Figure 15-8—S-tagged interface to a PBN | 567 |
| Figure 15-9—RCSIs to a PBN | 567 |
| Figure 15-10—Remote Customer Access Ports (RCAPs) | 568 |
| Figure 15-11—C-tagged RCSI to a PBN | 569 |
| Figure 15-12—Port-based RCSI to a PBN | 569 |
| Figure 15-13—Provider Network Port (PNP) interface | 570 |
| Figure 16-1—PBN with interface examples | 573 |
| Figure 16-2—Examples of remote customer service access via a second PBN | 575 |
| Figure 16-3—Access service separation and “Hairpin Switching” | 576 |
| Figure 17-1—C-VLAN component internal LAN managed system | 638 |

| | |
|---|------|
| Figure 17-2—I/B-component internal LAN managed system | 643 |
| Figure 18-1—One Maintenance Domain: operator’s view | 1222 |
| Figure 18-2—One service instance: operator’s view | 1223 |
| Figure 18-3—One service instance: customer’s view | 1223 |
| Figure 18-4—MEP and MIP Symbols | 1224 |
| Figure 18-5—MAs: one service instance in a provider network | 1225 |
| Figure 18-6—MAs: Expansion of Figure 18-5 | 1226 |
| Figure 18-7—MEPs, MIPs, and MD Levels | 1227 |
| Figure 19-1—CFM Protocol shims | 1228 |
| Figure 19-2—MA Endpoint (MEP) | 1231 |
| Figure 19-3—MIP Half Function (MHF) | 1237 |
| Figure 19-4—LOM shim | 1239 |
| Figure 19-5—LOM architecture | 1239 |
| Figure 20-1—MEP state machines—overview and relationships | 1252 |
| Figure 20-2—MEP Continuity Check Initiator state machine | 1259 |
| Figure 20-3—MHF Continuity Check Receiver state machine | 1260 |
| Figure 20-4—MEP Continuity Check Receiver state machine | 1264 |
| Figure 20-5—Remote MEP state machine | 1266 |
| Figure 20-6—Remote MEP Error state machine | 1267 |
| Figure 20-7—MEP Cross Connect state machine | 1268 |
| Figure 20-8—MEP Traffic Field Mismatch state machine | 1270 |
| Figure 20-9—MEP Local Mismatch state machine | 1270 |
| Figure 20-10—MP Loopback Responder state machine | 1272 |
| Figure 20-11—MEP Loopback Initiator transmit state machine | 1275 |
| Figure 20-12—MEP Loopback Initiator receive state machine | 1276 |
| Figure 20-13—MEP Fault Notification Generator state machine | 1278 |
| Figure 20-14—MEP Mismatch Fault Notification Generator state machine | 1280 |
| Figure 20-15—MEP Linktrace Initiator receive state machine | 1285 |
| Figure 20-16—Linktrace Responder, MEPs, MHFs, and LOMs | 1287 |
| Figure 20-17—LTM Receiver state machine | 1292 |
| Figure 20-18—LTR Transmitter state machine | 1293 |
| Figure 22-1—MEPs and MIPs distinguished by VID (incomplete picture) | 1324 |
| Figure 22-2—Alternate view of Forwarding process | 1325 |
| Figure 22-3—Combining per-VLAN MPs into two shims | 1326 |
| Figure 22-4—More complete picture of MP placement in a Bridge Port | 1327 |
| Figure 22-5—Service instance spanning two Bridges protected by Up MPs | 1329 |
| Figure 22-6—Service instance spanning two Bridges protected by Down MPs | 1329 |
| Figure 22-7—MP placement in a non-VLAN-aware Bridge Port | 1331 |
| Figure 22-8—MP placement relative to other standards | 1332 |
| Figure 22-9—Creating MEPs and MIPs | 1335 |
| Figure 22-10—CFM in a Provider Edge Bridge C-tagged service interface | 1341 |
| Figure 22-11—CFM in a Provider Edge Bridge C-tagged RCSI | 1343 |
| Figure 22-12—Up MEPs in a Management Port | 1344 |
| Figure 22-13—CFM in the enterprise environment | 1345 |
| Figure 22-14—CFM on a Bridge that implements IEEE Std 802.1Q-2005 | 1346 |
| Figure 23-1—TPMR connecting two Bridge Ports | 1347 |
| Figure 23-2—TPMR chain connecting Bridge Ports | 1347 |
| Figure 23-3—MSSs and the MSPE | 1349 |
| Figure 23-4—Adding connectivity | 1351 |
| Figure 23-5—Losing connectivity | 1352 |
| Figure 23-6—TPMR recovery | 1353 |
| Figure 23-7—Notification from one end of the link to the other | 1354 |
| Figure 23-8—Immediate MAC status notification at the end of a link | 1354 |
| Figure 23-9—MSPE state machine overview | 1355 |

| | |
|--|------|
| Figure 23-10—Status Transition state machine (STM) | 1359 |
| Figure 23-11—Status Notification state machine (SNM) | 1360 |
| Figure 23-12—MSPDU structure | 1362 |
| Figure 25-1—Internal organization of the MAC sublayer in a PBBN | 1366 |
| Figure 25-2—PBB terminology | 1367 |
| Figure 25-3—Customer service interface types | 1368 |
| Figure 25-4—Port-based service interface | 1369 |
| Figure 25-5—Port-based interface equipment | 1370 |
| Figure 25-6—Encapsulated service frames at ISS | 1371 |
| Figure 25-7—S-tagged service interface | 1371 |
| Figure 25-8—S-tagged service interface equipment | 1372 |
| Figure 25-9—I-tagged service interface | 1373 |
| Figure 25-10—I-tagged service interface equipment | 1373 |
| Figure 25-11—S-tagged and Port-based service interface access classifications | 1376 |
| Figure 25-12—I-tagged service interface access protection classifications | 1377 |
| Figure 25-13—Internal organization of the MAC sublayer in a PBB-TE Region | 1379 |
| Figure 25-14—PBB-TE Region | 1381 |
| Figure 25-15—Transparent service interface | 1383 |
| Figure 25-16—Transparent service interface equipment | 1383 |
| Figure 26-1—PBBN example | 1385 |
| Figure 26-2—CFM shim model | 1392 |
| Figure 26-3—CFM example applied to a Port-based and S-tagged service interface | 1393 |
| Figure 26-4—CFM example applied to an I-tagged Service Interface | 1394 |
| Figure 26-5—CFM example applied to a hierarchal E-NNI, CBP-PIP Demarc | 1395 |
| Figure 26-6—CFM example applied to a peer E-NNI, CBP-PIP | 1396 |
| Figure 26-7—Independent ESPs using the same ESP-DAs and ESP-VIDs | 1400 |
| Figure 26-8—PBB-TE MEP placement in a CBP | 1401 |
| Figure 26-9—Independent Infrastructure Segments distinguished by SMP-SA | 1404 |
| Figure 26-10—Infrastructure Segment MEP placement in a PNP | 1405 |
| Figure 26-11—Protection switching architecture | 1406 |
| Figure 26-12—PBB-TE point-to-point protection switching | 1408 |
| Figure 26-13—Mapping data traffic to the protection entity | 1409 |
| Figure 26-14—Relationships of the Protection switching state machines—overview | 1410 |
| Figure 26-15—Hold-off state machine | 1414 |
| Figure 26-16—Clear Manual Switch state machine | 1414 |
| Figure 26-17—Service Mapping state machine | 1415 |
| Figure 26-18—Segment terminology and properties | 1416 |
| Figure 26-19—Infrastructure Segment monitoring | 1417 |
| Figure 26-20—Working Segment and Protection Segment | 1417 |
| Figure 26-21—Nested IPGs | 1418 |
| Figure 26-22—IPS Control entity | 1420 |
| Figure 26-23—M:1 IPS | 1422 |
| Figure 26-24—M:1 IPS state machines | 1423 |
| Figure 26-25—M:1 Hold-off state machine | 1426 |
| Figure 26-26—Protection Segment Selection state machine | 1427 |
| Figure 27-1—Configuring VLAN support in an SPT Region (example) | 1434 |
| Figure 27-2—SPBM group MAC address—general format | 1445 |
| Figure 27-3—SPBM group MAC addresses—source rooted SPT | 1446 |
| Figure 27-4—SPBM group MAC addresses—shared tree | 1446 |
| Figure 27-5—SPBM MEP placement in a CBP | 1449 |
| Figure 27-6—SPBV campus network example | 1451 |
| Figure 27-7—SPT Bridge Network using SPBM example | 1453 |
| Figure 28-1—Agreement Digest field format | 1458 |
| Figure 28-2—MT-Capability TLV | 1468 |

| | |
|--|------|
| Figure 28-3—SPB MCID sub-TLV | 1468 |
| Figure 28-4—SPB Digest sub-TLV | 1469 |
| Figure 28-5—SPB Base VLAN-Identifiers sub-TLV | 1470 |
| Figure 28-6—SPB Instance sub-TLV | 1471 |
| Figure 28-7—SPB Instance Opaque ECT-ALGORITHM sub-TLV | 1473 |
| Figure 28-8—ECMP ECT-ALGORITHM sub-TLV | 1474 |
| Figure 28-9—SPB Link Metric sub-TLV | 1474 |
| Figure 28-10—SPB Adjacency Opaque ECT-ALGORITHM sub-TLV | 1475 |
| Figure 28-11—SPBV MAC Address sub-TLV | 1476 |
| Figure 28-12—SPBM Service Identifier and Unicast Address sub-TLV | 1477 |
| Figure 29-1—Forward path test (FPT) | 1481 |
| Figure 29-2—Return path test (RPT) | 1482 |
| Figure 29-3—Combination of FPT and RPT | 1483 |
| Figure 29-4—Detailed functions of RR | 1484 |
| Figure 29-5—RFM Receiver on an non-MP | 1487 |
| Figure 29-6—Return Path DR | 1488 |
| Figure 29-7—RR Filter state machine | 1493 |
| Figure 29-8—RR Encapsulation state machine | 1494 |
| Figure 29-9—RR Transmit state machine | 1494 |
| Figure 29-10—RFM Receiver state machine | 1496 |
| Figure 29-11—Decapsulator Responder state machine | 1498 |
| Figure 30-1—Congestion detection in QCN CP | 1505 |
| Figure 30-2—Sampling (reflection) probability in QCN CP as a function of $ Fb $ | 1505 |
| Figure 30-3—QCN RP operation | 1506 |
| Figure 30-4—Byte Counter and Timer interaction with Rate Limiter | 1508 |
| Figure 30-5—CP-RP peering in VLAN Bridged Network | 1510 |
| Figure 30-6—CP-RP peering in PBBN | 1511 |
| Figure 31-1—CPs and congestion-aware queues in a Bridge | 1512 |
| Figure 31-2—Congestion-aware queue functions in an end station | 1514 |
| Figure 31-3—Per-CNPV station function | 1516 |
| Figure 32-1—CND defense state machine | 1529 |
| Figure 32-2—RP rate control state machine | 1541 |
| Figure 32-3—CP-RP peering in any hierarchical Bridged Network | 1542 |
| Figure 34-1—Queuing model for a Talker station | 1553 |
| Figure 35-1—Operation of MSRP | 1556 |
| Figure 35-2—Format of the components of the reservation FirstValue fields | 1566 |
| Figure 35-3—Format of the components of the Domain FirstValue | 1571 |
| Figure 36-1—PFC peering | 1583 |
| Figure 36-2—PFC Receiver state diagram for priority n | 1585 |
| Figure 36-3—PFC-aware system queue functions | 1587 |
| Figure 36-4—PFC-aware system queue functions with Link Aggregation | 1588 |
| Figure 38-1—DCBX Asymmetric state machine | 1593 |
| Figure 38-2—Symmetric state machine | 1594 |
| Figure 39-1—Operation of MIRP in an I-component | 1596 |
| Figure 39-2—Operation of MIRP in a B-component | 1596 |
| Figure 39-3—Alternate model for MIRP in a B-component | 1601 |
| Figure 40-1—EVB architecture overview | 1603 |
| Figure 40-2—EVB architecture without S-channels | 1605 |
| Figure 40-3—EVB architecture with S-channel | 1605 |
| Figure 40-4—EVB components and internal LANs with S-channels | 1606 |
| Figure 40-5—EVB architecture without S-channels, with EVB Bridge S-VLAN component | 1608 |
| Figure 40-6—EVB architecture without S-channels, with EVB station S-VLAN component | 1608 |
| Figure 41-1—VSI manager ID TLV | 1610 |
| Figure 41-2—VDP association TLV | 1611 |

| | |
|---|------|
| Figure 41-3—VID Filter Info format | 1615 |
| Figure 41-4—MAC/VID filter format | 1615 |
| Figure 41-5—GroupID/VID filter format | 1616 |
| Figure 41-6—GroupID/MAC/VID filter format | 1616 |
| Figure 41-7—Organizationally defined TLV | 1618 |
| Figure 41-8—Bridge VDP state machine | 1619 |
| Figure 41-9—Station VDP state machine | 1620 |
| Figure 42-1—CDCP state machine—Station role | 1627 |
| Figure 42-2—CDCP state machine—Bridge role | 1628 |
| Figure 43-1—Example ECP exchange | 1632 |
| Figure 43-2—ECPDU structure | 1634 |
| Figure 43-3—ECP transmit state machine | 1635 |
| Figure 43-4—ECP receive state machine | 1636 |
| Figure 44-1—Flow FilteringTCI format | 1643 |
| Figure 44-2—SPBM VID MEP and ECMP path MEP placement in a CBP | 1647 |
| Figure 45-1—An SPT Region controlled by a single PCE | 1650 |
| Figure 45-2—An SPT Region controlled by multiple PCEs | 1651 |
| Figure 45-3—The use of the SPB Instance sub-TLV for MRT | 1659 |
| Figure 45-4—Shared Risk Link Group (SRLG) TLV | 1663 |
| Figure 45-5—Topology sub-TLV | 1664 |
| Figure 45-6—A strict tree and its descriptor Topology sub-TLV | 1665 |
| Figure 45-7—Topology sub-TLV of a loose tree | 1666 |
| Figure 45-8—Hop sub-TLV | 1667 |
| Figure 45-9—Administrative Group sub-TLV | 1670 |
| Figure 45-10—Bandwidth Constraint sub-TLV | 1671 |
| Figure 45-11—Bandwidth Assignment sub-TLV | 1672 |
| Figure 45-12—Timestamp sub-TLV | 1673 |
| Figure 45-13—A GADAG and its descriptor Topology sub-TLV | 1679 |
| Figure 45-14—MRT-Blue and MRT-Red for MRT Root 55 | 1679 |
| Figure 45-15—A GADAG for a topology with multiple blocks | 1680 |
| Figure C-1—CSN backbone | 1763 |
| Figure C-2—Bridge’s CSN model for bandwidth reservation | 1764 |
| Figure C-3—Talker MSRPDU flow | 1765 |
| Figure C-4—Listener MSRPDU flow | 1765 |
| Figure C-5—IEEE DMN Device Attribute IE | 1767 |
| Figure C-6—DMN Confirmation Transaction | 1769 |
| Figure C-7—Bandwidth reservation—bridge model for IEEE 802.11 BSS (STA downstream Port) | 1772 |
| Figure C-8—Bandwidth reservation—bridge model for IEEE 802.11 BSS (STA upstream Port) | 1772 |
| Figure C-9—Bandwidth reservation—bridge model for IEEE 802.11 BSS (direct link setup) | 1773 |
| Figure C-10—MSRP/IEEE 802.11 query flows | 1773 |
| Figure C-11—MSRP/802.11 Talker STA to Listener STA reservation flows | 1774 |
| Figure C-12—MSRP/802.11 “Bridged” Listener to Talker STA reservation flows | 1775 |
| Figure C-13—MSRP/802.11 Listener STA to “Bridged” Talker reservation flows | 1775 |
| Figure D-1—Port VLAN ID TLV format | 1781 |
| Figure D-2—Port And Protocol VLAN ID TLV format | 1781 |
| Figure D-3—VLAN Name TLV format | 1782 |
| Figure D-4—Protocol Identity TLV format | 1783 |
| Figure D-5—VID Usage Digest TLV format | 1784 |
| Figure D-6—Management VID TLV format | 1784 |
| Figure D-7—Congestion Notification TLV format | 1785 |
| Figure D-8—ETS Configuration TLV format | 1786 |
| Figure D-9—ETS Recommendation TLV format | 1788 |
| Figure D-10—Priority-based Flow Control Configuration TLV format | 1789 |
| Figure D-11—Application Priority TLV format | 1790 |

| | |
|---|------|
| Figure D-12—EVB TLV format | 1792 |
| Figure D-13—CDCP TLV structure | 1795 |
| Figure D-14—Application VLAN TLV format | 1797 |
| Figure F-1—Connecting independent VLANs—1 | 1899 |
| Figure F-2—Connecting independent VLANs—2 | 1900 |
| Figure F-3—Duplicate MAC addresses | 1900 |
| Figure F-4—Asymmetric VID use: “multi-netted server” | 1901 |
| Figure F-5—Asymmetric VLAN use: “Rooted-Multipoint” | 1903 |
| Figure F-6—Rooted-Multipoint with tagged interfaces | 1904 |
| Figure F-7—SPBV VLAN Shared Learning and VID Translation | 1905 |
| Figure G-1— Example of IEEE 802.3 MAC frame format..... | 1907 |
| Figure G-2—Methods for Bridge access to IEEE 802.11 and PMPN media: example | 1910 |
| Figure H-1—Static filtering inconsistency | 1913 |
| Figure H-2—Interoperability with MAC Bridges: example 1 | 1914 |
| Figure H-3—Interoperability with MAC Bridges: example 2 | 1915 |
| Figure H-4—Interoperability between Port-based and Port-and-Protocol-based classification | 1916 |
| Figure J-1—Up MPs in a CFM Port | 1930 |
| Figure K-1—TPMR as UNI demarcation device | 1933 |
| Figure K-2—TPMRs with aggregated links | 1934 |
| Figure K-3—Multiple TPMRs | 1934 |
| Figure K-4—Recovery at the end of a chain | 1935 |
| Figure K-5—Near simultaneous recoveries | 1936 |
| Figure K-6—Near simultaneous failure and recovery | 1936 |
| Figure K-7—Loss with quick recovery | 1937 |
| Figure L-1—Credit-based shaper operation—no conflicting traffic | 1940 |
| Figure L-2—Credit-based shaper operation—conflicting traffic | 1941 |
| Figure L-3—Credit-based shaper operation—burst traffic | 1942 |
| Figure L-4—Interference and latency | 1946 |
| Figure L-5—Burst behavior and credit | 1946 |
| Figure L-6—Fan-in scenario | 1950 |
| Figure L-7—Permanent delay scenario | 1951 |
| Figure L-8—Building up buffer occupancy—1 | 1952 |
| Figure L-9—Building up buffer occupancy—2 | 1952 |
| Figure L-10—Building up buffer occupancy—3 | 1952 |
| Figure L-11—Building up buffer occupancy—4 | 1953 |
| Figure M-1—PFC PDU format | 1955 |
| Figure N-1—PFC delays | 1956 |
| Figure N-2—Delay model | 1957 |
| Figure N-3—Worst-case delay | 1958 |
| Figure O-1—Converting a CRC to an FCS | 1963 |
| Figure O-2—Detection Lossless Circuit | 1963 |
| Figure O-3—Field change adjustment | 1965 |
| Figure O-4—Field insertion adjustment | 1966 |
| Figure P-1—Frame duplication scenario | 1969 |
| Figure P-2—Frame misordering scenario | 1970 |
| Figure Q-1—Establishing a guard band | 1972 |
| Figure Q-2—Using gate operations | 1973 |
| Figure T-1—Example PSFP configuration for QCF | 1983 |
| Figure T-2—Traffic scheduling example for CQF | 1984 |
| Figure T-3—Example PSFP configuration with two values of T | 1985 |
| Figure T-4—Traffic scheduling example with two values of T | 1985 |
| Figure T-5—Interleaving example—factor of 2 | 1986 |

Tables

| | |
|--|-----|
| Table 6-1—Bridge transit delay | 135 |
| Table 6-2—Priority Code Point encoding | 143 |
| Table 6-3—Priority Code Point decoding | 143 |
| Table 6-4—Priority regeneration | 144 |
| Table 6-5—Default SRP domain boundary port priority regeneration override values | 145 |
| Table 6-6—Service Access Priority | 156 |
| Table 6-7—Encapsulated Addresses EtherType | 163 |
| Table 8-1—C-VLAN and MAC Bridge component Reserved addresses | 191 |
| Table 8-2—S-VLAN component Reserved addresses | 192 |
| Table 8-3—TPMR component Reserved addresses | 192 |
| Table 8-4—Stream gate control operations | 197 |
| Table 8-5—Recommended priority to traffic class mappings | 198 |
| Table 8-6—Transmission selection algorithm identifiers | 200 |
| Table 8-7—Gate operations | 204 |
| Table 8-8—Scheduled Traffic and PSFP procedures/variables | 213 |
| Table 8-9—Ageing time parameter value | 216 |
| Table 8-10—Combining Static and Dynamic Filtering Entries for an individual MAC address | 226 |
| Table 8-11—Combining Static Filtering Entry and MAC Address Registration Entry for “All Group Addresses” and “All Unregistered Group Addresses” | 227 |
| Table 8-12—Forwarding or Filtering for specific group MAC addresses | 228 |
| Table 8-13—Forwarding or Filtering with Dynamic Reservation Entries | 229 |
| Table 8-14—Determination of whether a Port is in a VID’s member set | 229 |
| Table 8-15—Standard LLC address assignment | 234 |
| Table 8-16—ISIS-SPB reserved addresses | 236 |
| Table 8-17—ISIS-SPB Recommended Address Usage | 236 |
| Table 8-18—CCM group destination MAC addresses | 243 |
| Table 8-19—LTM group destination MAC addresses | 243 |
| Table 9-1—IEEE 802.1Q™ EtherType allocations | 246 |
| Table 9-2—Reserved VID values | 246 |
| Table 9-3—Reserved I-SID values | 248 |
| Table 10-1—MRP application addresses | 256 |
| Table 10-2—MRP EtherType values | 257 |
| Table 10-3—Applicant state table | 270 |
| Table 10-4—Registrar state table | 271 |
| Table 10-5—LeaveAll state table | 272 |
| Table 10-6—PeriodicTransmission state table | 272 |
| Table 10-7—MRP timer parameter values | 273 |
| Table 12-1—Component table entry managed object | 304 |
| Table 12-2—Port table entry | 306 |
| Table 12-3—ISS Port Number table entry | 307 |
| Table 12-4—Bandwidth Availability Parameter Table row elements | 411 |
| Table 12-5—Transmission Selection Algorithm Table row elements | 412 |
| Table 12-6—Priority Regeneration Override Table row elements | 412 |
| Table 12-7—CN component managed object row elements | 413 |
| Table 12-8—CN component priority managed object row elements | 414 |
| Table 12-9—CN Port priority managed object row elements | 415 |
| Table 12-10—Congestion Point managed object row elements | 415 |
| Table 12-11—Reaction Point port priority managed object row elements | 416 |
| Table 12-12—Reaction Point group managed object row elements | 416 |
| Table 12-13—SRP Bridge Base Table row elements | 417 |
| Table 12-14—SRP Bridge Port Table row elements | 418 |

| | |
|--|-----|
| Table 12-15—SRP Latency Parameter Table row elements | 418 |
| Table 12-16—SRP Stream Table row elements | 418 |
| Table 12-17—SRP Reservations Table row elements | 419 |
| Table 12-18—Priority-based Flow Control objects | 420 |
| Table 12-19—EVB system base table | 444 |
| Table 12-20—EVB system parameter defaults | 445 |
| Table 12-21—SBP table entry | 446 |
| Table 12-22—VSI table entry | 446 |
| Table 12-23—VSI MAC/VLAN table entry | 447 |
| Table 12-24—UAP table entry | 448 |
| Table 12-25—UAP table entry parameters | 449 |
| Table 12-26—S-channel interface table entry | 449 |
| Table 12-27—URP table entry | 450 |
| Table 12-28—ECP table entry | 451 |
| Table 12-29—The Gate Parameter Table | 456 |
| Table 12-30—Frame Preemption Parameter table | 459 |
| Table 12-31—The Stream Parameter Table | 461 |
| Table 12-32—Stream Filter Instance Table | 461 |
| Table 12-33—The Stream Gate Instance Table | 463 |
| Table 12-34—The Flow Meter Instance Table | 466 |
| Table 13-1—Configuration Digest Signature Key | 482 |
| Table 13-2—Sample Configuration Digest Signature Keys | 483 |
| Table 13-3—Bridge and Port Priority values | 501 |
| Table 13-4—Port Path Cost values | 502 |
| Table 13-5—Timer and related parameter values | 510 |
| Table 17-1—Structure of the MIB modules | 579 |
| Table 17-2—IEEE8021-TC-MIB structure | 581 |
| Table 17-3—IEEE8021-BRIDGE-MIB structure and relationship to IETF RFC 4188 and this standard | 582 |
| Table 17-4—IEEE 802.1D objects not in the IEEE8021-BRIDGE-MIB | 586 |
| Table 17-5—IEEE8021-SPANNING-TREE MIB structure and relationship to IETF RFC 4318 and this standard | 586 |
| Table 17-6—Clause 12 objects not in the IEEE8021-SPANNING-TREE MIB | 588 |
| Table 17-7—IEEE8021-QBRIDGE MIB structure and relationship to IETF RFC 4363 and this standard | 589 |
| Table 17-8—Clause 12 management not in IEEE8021-Q-BRIDGE-MIB | 594 |
| Table 17-9—IEEE8021-PB-MIB structure and relationship to this standard | 594 |
| Table 17-10—IEEE8021-MSTP-MIB structure and relationship to this standard | 596 |
| Table 17-11—IEEE8021-CFM-MIB correspondence between variables, managed objects, and MIB objects | 599 |
| Table 17-12—IEEE8021-CFM-V2-MIB correspondence between variables, managed objects, and MIB objects | 603 |
| Table 17-13—IEEE8021-PBB-MIB structure and relationship to this standard | 605 |
| Table 17-14—IEEE8021-DDCFM-MIB structure and relationship to this standard | 608 |
| Table 17-15—IEEE8021-PBBTE-MIB Structure and relationship to this standard | 610 |
| Table 17-16—Example of ieee8021PbbTeTeSiEspTable | 611 |
| Table 17-17—IEEE8021-TPMR-MIB Structure and relationship to this standard | 613 |
| Table 17-18—FQTSS MIB structure and object cross reference | 614 |
| Table 17-19—Variables, managed object tables, and MIB objects | 615 |
| Table 17-20—SRP MIB structure and object cross reference | 617 |
| Table 17-21—IEEE8021-MVRPX-MIB structure and relationship to this standard | 619 |
| Table 17-22—IEEE8021-MIRP-MIB structure and relationship to this standard | 619 |
| Table 17-23—Variables, managed object tables, and MIB objects | 620 |
| Table 17-24—IEEE8021-TEIPS MIB structure and relationship to this standard | 620 |

| | |
|--|------|
| Table 17-25—IEEE8021-SPB-MIB structure and relationship to this standard | 622 |
| Table 17-26—EVB MIB structure and object cross reference | 626 |
| Table 17-27—IEEE8021-ECMP-MIB structure and relationship to this standard | 630 |
| Table 17-28—IEEE8021-ST-MIB structure and relationship to this standard | 631 |
| Table 17-29—IEEE8021-Preemption-MIB Structure and relationship to this standard | 632 |
| Table 17-30—IEEE8021-PSFP-MIB Structure and relationship to this standard | 633 |
| Table 17-31—PBB-TE required MIB compliances | 644 |
| Table 17-32—Sensitive managed objects: tables and notifications | 652 |
| Table 17-33—Sensitive managed objects: variables in dot1agCfmMdTable | 652 |
| Table 17-34—Sensitive managed objects (of DDCFM): tables and notifications | 654 |
| Table 17-35—Sensitive managed objects (of DDCFM) for read | 654 |
| Table 17-36—Sensitive managed objects (of EVB): tables and notifications | 661 |
| Table 17-37—Sensitive managed objects (of EVB) for read | 661 |
| Table 17-38—Provider Bridge service interface parameters | 677 |
| Table 17-39—PBB service interface parameters | 681 |
| Table 19-1—Actions taken by MP OpCode Demultiplexers | 1233 |
| Table 19-2—SAP use for LTMs and LTRs | 1240 |
| Table 20-1—Fault Alarm defects and priorities | 1245 |
| Table 20-2—Deriving enableRmepDefect and Port Status TLV in a Bridge | 1255 |
| Table 21-1—CFM PDU Encapsulation EtherType | 1299 |
| Table 21-2—Common CFM Header format | 1301 |
| Table 21-3—OpCode Field range assignments | 1301 |
| Table 21-4—TLV format | 1302 |
| Table 21-5—Type Field values | 1302 |
| Table 21-6—Organization-Specific TLV format | 1303 |
| Table 21-7—Sender ID TLV format | 1304 |
| Table 21-8—Port Status TLV format | 1306 |
| Table 21-9—Port Status TLV values | 1306 |
| Table 21-10—Interface Status TLV format | 1306 |
| Table 21-11—Interface Status TLV values | 1306 |
| Table 21-12—Data TLV format | 1307 |
| Table 21-13—End TLV format | 1307 |
| Table 21-14—CCM format | 1308 |
| Table 21-15—CCM Interval field encoding | 1309 |
| Table 21-16—CCM Maintenance Association Identifier field format: Maintenance Domain present | 1310 |
| Table 21-17—CCM Maintenance Association Identifier field format: Maintenance Domain not present | 1310 |
| Table 21-18—Maintenance Domain Name Format | 1311 |
| Table 21-19—Short MA Name Format | 1312 |
| Table 21-20—LBM and LBR formats | 1313 |
| Table 21-21—PBB-TE MIP TLV format | 1314 |
| Table 21-22—LTM format | 1315 |
| Table 21-23—LTM Flags field | 1315 |
| Table 21-24—LTM Egress Identifier TLV format | 1317 |
| Table 21-25—LTR format | 1317 |
| Table 21-26—LTR Flags field | 1317 |
| Table 21-27—Relay Action field values | 1318 |
| Table 21-28—LTR Egress Identifier TLV format | 1319 |
| Table 21-29—Reply Ingress TLV format | 1319 |
| Table 21-30—Ingress Action field values | 1320 |
| Table 21-31—Reply Egress TLV format | 1321 |
| Table 21-32—Egress Action field values | 1321 |
| Table 22-1—MEP creation | 1335 |
| Table 22-2—MIP creation | 1336 |

| | |
|---|------|
| Table 22-3—Bandwidth required for CCMs for 1 MA | 1339 |
| Table 22-4—Bandwidth required for CCMs for 1000 MAs | 1340 |
| Table 23-1—Time sequence diagram symbols | 1350 |
| Table 23-2—MSP performance parameters | 1356 |
| Table 23-3—MSP EtherType assignment | 1362 |
| Table 23-4—MSP Packet Types | 1363 |
| Table 24-1—Transmission and reception delays | 1365 |
| Table 26-1—Backbone Service Instance Group address OUI | 1388 |
| Table 26-2—Protection Requests Hierarchy | 1411 |
| Table 27-1—Allocation of VIDs to FIDs and FIDs to MSTIDs in an SPT Region (example) | 1434 |
| Table 28-1—Bridge Priority Masking | 1463 |
| Table 29-1—RFM format | 1499 |
| Table 29-2—SFM format | 1500 |
| Table 32-1—LLDP instance selection managed object overrides | 1522 |
| Table 32-2—CND defense mode selection managed object overrides | 1522 |
| Table 32-3—Determining cnpdIsAdminDefMode and cnpdDefenseMode | 1528 |
| Table 32-4—Correspondence of QCN and CCF message fields | 1530 |
| Table 32-5—NewCpSampleBase() return value as a function of cpFb | 1533 |
| Table 33-1—CN-TAG Encapsulation | 1545 |
| Table 33-2—CNM Encapsulation | 1545 |
| Table 33-3—Congestion Notification Message PDU | 1546 |
| Table 34-1—Recommended priority to traffic class mappings for SR classes A and B | 1552 |
| Table 34-2—Recommended priority to traffic class mappings for SR class B only | 1552 |
| Table 35-1—AttributeType Values | 1563 |
| Table 35-2—AttributeLength Values | 1563 |
| Table 35-3—FourPackedEvent Values | 1564 |
| Table 35-4—MSRP FirstValue NumberOfValues example | 1565 |
| Table 35-5—TSpec components examples | 1568 |
| Table 35-6—Reservation Failure Codes | 1570 |
| Table 35-7—SR class ID | 1572 |
| Table 35-8—Summary of Talker primitives | 1573 |
| Table 35-9—Summary of Listener primitives | 1574 |
| Table 35-10—Talker attribute propagation per port | 1578 |
| Table 35-11—Incoming Listener attribute propagation per port | 1579 |
| Table 35-12—Updating Dynamic Reservation Entries | 1580 |
| Table 35-13—Updating operIdleSlope(N) | 1580 |
| Table 35-14—Listener Declaration Type Summation | 1580 |
| Table 41-1—VDP TLV types | 1611 |
| Table 41-2—Flag values in VDP requests | 1612 |
| Table 41-3—Error types in VDP responses | 1612 |
| Table 41-4—Flag values in VDP responses | 1613 |
| Table 41-5—VSIID format values | 1613 |
| Table 41-6—Filter Info format values | 1614 |
| Table 43-1—ECP subtypes | 1634 |
| Table 44-1—ECMP ECT-ALGORITHM values | 1642 |
| Table 44-2—F-TAG EtherType | 1643 |
| Table 45-1—ECT-ALGORITHM values for explicit trees | 1654 |
| Table 45-2—Bridge Priority Masking for the LT and LTS ECT Algorithms | 1655 |
| Table 45-3—Hop sub-TLV flags | 1668 |
| Table C-1—SRP to MoCA PQoS Transaction mapping | 1770 |
| Table C-2—SRP TSpec to MoCA TSPEC mapping | 1771 |
| Table C-3—SRP StreamID to MoCA PQoS Flow transaction mapping | 1771 |
| Table C-4—SRP to MLME QoS Services mapping | 1777 |
| Table C-5—EDCA-AC for AV Streams | 1778 |

| | |
|--|------|
| Table C-6—HCCA for AV Streams | 1779 |
| Table D-1—IEEE 802.1 Organizationally Specific TLVs | 1780 |
| Table D-2—Port and protocol capability/status | 1782 |
| Table D-3—Priority assignment table | 1786 |
| Table D-4—Traffic class bandwidth assignment table | 1787 |
| Table D-5—TSA Assignment Table | 1787 |
| Table D-6—PFC Enable bit vector | 1790 |
| Table D-7—Application Priority Table Entry format | 1791 |
| Table D-8—Sel field values | 1791 |
| Table D-9—RRSAT flag values and meanings | 1793 |
| Table D-10—EVB Mode values | 1794 |
| Table D-11—Application VLAN Table Entry format | 1797 |
| Table D-12—Sel field values | 1798 |
| Table D-13—IEEE 802.1 extension MIB object group conformance requirements | 1803 |
| Table D-14—IEEE 802.1/LLDP extension MIB object cross reference | 1804 |
| Table E-1—State machine symbols | 1897 |
| Table I-1—Traffic type to traffic class mapping | 1918 |
| Table I-2—Traffic type acronyms | 1920 |
| Table I-3—Defining traffic types | 1921 |
| Table I-4—Defining traffic types—Credit-based shaper support of SR class B only | 1922 |
| Table I-5—Defining traffic types—Credit-based shaper support of SR classes A and B | 1922 |
| Table I-6—Priority Code Point encoding | 1924 |
| Table I-7—Priority Code Point decoding | 1924 |
| Table J-1—Provider MD Level allocation | 1926 |
| Table J-2—IEEE / ITU-T terminology differences | 1926 |
| Table N-1—IEEE 802.3 Interface Delays | 1959 |