

ISO/IEC/IEEE 8802-1Q:2020-08 (E)

Telecommunications and exchange between information technology systems - Requirements for local and metropolitan area networks - Part 1Q: Bridges and bridged networks

Contents

1.	Overview.....	61
1.1	Scope.....	61
1.2	Purpose.....	61
1.3	Introduction.....	62
2.	Normative references.....	69
3.	Definitions.....	73
4.	Abbreviations.....	95
5.	Conformance.....	101
5.1	Requirements terminology.....	101
5.2	Conformant components and equipment.....	101
5.3	Protocol Implementation Conformance Statement (PICS).....	102
5.4	VLAN Bridge component requirements.....	102
5.4.1	VLAN Bridge component options.....	103
5.4.2	Multiple VLAN Registration Protocol (MVRP) requirements.....	108
5.4.3	VLAN Bridge requirements for congestion notification.....	108
5.4.4	Multiple Stream Registration Protocol (MSRP) requirements.....	109
5.4.5	Shortest Path Bridging (SPB) operation (optional).....	109
5.4.6	Path Control and Reservation (PCR) (optional).....	110
5.5	C-VLAN component conformance.....	111
5.5.1	C-VLAN component options.....	111
5.6	S-VLAN component conformance.....	111
5.6.1	S-VLAN component options.....	112
5.6.2	S-VLAN component requirements for Provider Backbone Bridge Traffic Engineering (PBB-TE).....	112
5.6.3	S-VLAN component requirements for PBB-TE IPS.....	112
5.6.4	S-VLAN component requirements for ECMP with flow filtering.....	113
5.7	I-component conformance.....	113
5.7.1	I-component options.....	113
5.8	B-component conformance.....	113
5.8.1	B-component options.....	114
5.8.2	B-component requirements for PBB-TE.....	114
5.8.3	B-component requirements for PBB-TE IPS.....	114
5.8.4	B-component requirements for ECMP with flow filtering.....	115
5.9	C-VLAN Bridge conformance.....	115
5.9.1	C-VLAN Bridge options.....	115
5.10	Provider Bridge conformance.....	115
5.10.1	S-VLAN Bridge conformance.....	115
5.10.2	Provider Edge Bridge conformance.....	116
5.11	System requirements for Priority-based Flow Control (PFC).....	116
5.12	Backbone Edge Bridge (BEB) conformance.....	116
5.12.1	BEB requirements for PBB-TE.....	117
5.13	MAC Bridge component requirements.....	117
5.13.1	MAC Bridge component options.....	117
5.14	MAC Bridge conformance.....	118
5.14.1	MAC Bridge options.....	118
5.15	TPMR component conformance.....	118

5.15.1	TPMR component options	119
5.16	TPMR conformance.....	119
5.16.1	TPMR options	119
5.17	T-component conformance	119
5.17.1	T-component options	120
5.18	End station requirements for MMRP, MVRP, and MSRP	120
5.18.1	MMRP requirements and options	120
5.18.2	MVRP requirements and options	121
5.18.3	MSRP requirements and options	121
5.19	VLAN-aware end station requirements for CFM	122
5.20	End station requirements—FQTSS	122
5.21	End station requirements for congestion notification	123
5.22	MAC-specific bridging methods	123
5.23	EVB Bridge requirements.....	123
5.24	EVB station requirements.....	124
5.24.1	Edge relay (ER) requirements	125
5.25	End station requirements—enhancements for scheduled traffic	126
5.26	End station requirements—enhancements for frame preemption.....	126
5.27	End-station requirements—PSFP	127
5.28	End station requirements—Cyclic queuing and forwarding.....	127
6.	Support of the MAC Service	128
6.1	Basic architectural concepts and terms.....	129
6.2	Provision of the MAC Service.....	129
6.2.1	Point-to-point, multipoint-to-multipoint, and rooted-multipoint connectivity ...	130
6.3	Support of the MAC Service	130
6.4	Preservation of the MAC Service	131
6.5	Quality of service (QoS) maintenance.....	131
6.5.1	Service availability	131
6.5.2	Frame loss	132
6.5.3	Frame misordering	132
6.5.4	Frame duplication	133
6.5.5	Transit delay	134
6.5.6	Frame lifetime	135
6.5.7	Undetected frame error rate	135
6.5.8	Maximum Service Data Unit Size	135
6.5.9	Priority	135
6.5.10	Throughput	136
6.6	Internal Sublayer Service (ISS)	137
6.7	Support of the ISS by specific MAC procedures.....	137
6.7.1	Support of the ISS by IEEE Std 802.3 (Ethernet)	137
6.7.2	Frame preemption	137
6.8	Enhanced Internal Sublayer Service (EISS)	138
6.8.1	Service primitives	138
6.8.2	Status parameters	139
6.8.3	Point-to-point parameters	139
6.8.4	Control primitives and parameters	139
6.9	Support of the EISS	140
6.9.1	Data indications	141
6.9.2	Data requests	142
6.9.3	Priority Code Point encoding	142
6.9.4	Regenerating priority	144
6.10	Support of the ISS/EISS by PIPs	145

6.10.1	Data indications	147
6.10.2	Data requests	148
6.10.3	Priority Code Point encoding	148
6.11	Support of the EISS by CBPs	149
6.11.1	Data indications	150
6.11.2	Data requests	151
6.11.3	Priority Code Point decoding	152
6.11.4	Regenerating priority	152
6.12	Protocol VLAN classification.....	152
6.12.1	Protocol Templates	154
6.12.2	Protocol Group Identifiers	154
6.12.3	Protocol Group Database	154
6.13	Support of the ISS for attachment to a PBN.....	155
6.13.1	Data requests	156
6.13.2	Data indications	157
6.14	Support of the ISS within a system.....	157
6.15	Support of the ISS by additional technologies.....	157
6.16	Filtering services in Bridged Networks	158
6.16.1	Purpose(s) of filtering service provision	158
6.16.2	Goals of filtering service provision	158
6.16.3	Users of filtering services	159
6.16.4	Basis of service	159
6.16.5	Categories of service	159
6.16.6	Service configuration	159
6.16.7	Service definition for Extended Filtering Services	160
6.17	EISS Multiplex Entity.....	161
6.18	Backbone Service Instance Multiplex Entity.....	162
6.18.1	Demultiplexing direction	163
6.18.2	Multiplexing direction	164
6.18.3	Priority Code Point encoding	165
6.18.4	Status parameters	165
6.19	TESI Multiplex Entity	165
6.20	Support of the ISS with signaled priority	166
6.20.1	Data indications	167
6.20.2	Data requests	167
6.21	Infrastructure Segment Multiplex Entity.....	167
6.22	PDU and protocol discrimination and media	169
7.	Principles of Virtual Bridged Network operation.....	170
7.1	Network overview.....	170
7.2	Use of VLANs	171
7.3	Active topology.....	171
7.4	VLAN topology	172
7.5	Locating end stations	173
7.6	Ingress, forwarding, and egress rules.....	174
8.	Principles of Bridge operation	175
8.1	Bridge operation	175
8.1.1	Relay	175
8.1.2	Filtering and relaying information	176
8.1.3	Duplicate frame prevention	176
8.1.4	Traffic segregation	176
8.1.5	Traffic reduction	177

8.1.6	Traffic expediting	177
8.1.7	Conversion of frame formats	177
8.2	Bridge architecture.....	178
8.3	Model of operation.....	180
8.4	Active topologies, learning, and forwarding	184
8.5	Bridge Port Transmit and Receive.....	185
8.5.1	Bridge Port connectivity	185
8.5.2	TPMR Port connectivity	186
8.5.3	Support of Higher Layer Entities	187
8.6	The Forwarding Process	187
8.6.1	Active topology enforcement	188
8.6.2	Ingress filtering	190
8.6.3	Frame filtering	190
8.6.4	Egress filtering	193
8.6.5	Flow classification and metering	193
8.6.6	Queuing frames	197
8.6.7	Queue management	199
8.6.8	Transmission selection	199
8.6.9	Scheduled traffic state machines	205
8.6.10	Stream gate control state machines	213
8.7	The Learning Process.....	215
8.7.1	Default filtering utility criteria	215
8.7.2	Enhanced filtering utility criteria	216
8.7.3	Ageing of Dynamic Filtering Entries	216
8.8	The Filtering Database (FDB)	217
8.8.1	Static Filtering Entries	220
8.8.2	Static VLAN Registration Entries	221
8.8.3	Dynamic Filtering Entries	221
8.8.4	MAC Address Registration Entries	222
8.8.5	Dynamic VLAN Registration Entries	223
8.8.6	Default Group filtering behavior	223
8.8.7	Dynamic Reservation Entries	224
8.8.8	Allocation of VIDs to FIDs	225
8.8.9	Querying the FDB	225
8.8.10	Determination of the member set for a VID	229
8.8.11	Permanent Database	230
8.8.12	Connection_Identifier	230
8.9	MST, SPB, and ESP configuration information	230
8.9.1	MST Configuration Table	231
8.9.2	MST configuration identification	231
8.9.3	FID to MSTI Allocation Table	232
8.9.4	SPT Configuration Identification	232
8.10	Spanning Tree Protocol Entity.....	233
8.11	MRP entities	233
8.12	Bridge Management Entity.....	233
8.13	Addressing	233
8.13.1	End stations	233
8.13.2	Bridge Ports	234
8.13.3	Use of LLC by Spanning Tree Protocol Entities	234
8.13.4	Reserved MAC addresses	234
8.13.5	Group MAC addresses for spanning tree entity	235
8.13.6	Group MAC addresses for MRP Applications	237
8.13.7	Bridge Management Entities	237
8.13.8	Unique identification of a Bridge	237

8.13.9	Points of attachment and connectivity for Higher Layer Entities	238
8.13.10	VLAN attachment and connectivity for Higher Layer Entities	241
8.13.11	CFM entities	242
9.	Tagged frame format	244
9.1	Purpose of tagging	244
9.2	Representation and encoding of tag fields	244
9.3	Tag format.....	245
9.4	TPID formats	245
9.5	Tag Protocol identification	245
9.6	VLAN Tag Control Information (TCI).....	246
9.7	Backbone Service Instance Tag Control Information (I-TAG TCI).....	247
10.	Multiple Registration Protocol (MRP) and Multiple MAC Registration Protocol (MMRP)	249
10.1	MRP overview	249
10.2	MRP architecture	252
10.3	MRP Attribute Propagation (MAP).....	253
10.3.1	MAP Context	254
10.4	Requirements to be met by MRP.....	255
10.5	Requirements for interoperability between MRP Participants	256
10.6	Protocol operation.....	257
10.7	Protocol specification	261
10.7.1	Notational conventions and abbreviations	262
10.7.2	Registrar Administrative Controls	264
10.7.3	Applicant Administrative Controls	264
10.7.4	Protocol timers	264
10.7.5	Protocol event definitions	265
10.7.6	Protocol Action definitions	268
10.7.7	Applicant state machine	270
10.7.8	Registrar state machine	271
10.7.9	LeaveAll state machine	271
10.7.10	PeriodicTransmission state machine	272
10.7.11	Timer values	272
10.7.12	Operational reporting and statistics	273
10.7.13	Interoperability considerations	273
10.8	Structure and encoding of Multiple Registration Protocol Data Units (MRPDUs)	274
10.8.1	Structure	274
10.8.2	Encoding of MRPDU parameters	276
10.8.3	Packing and parsing MRPDUs	279
10.9	Multiple MAC Registration Protocol (MMRP)—Purpose.....	281
10.10	Model of operation.....	282
10.10.1	Propagation of Group Membership information	283
10.10.2	Propagation of Group service requirement information	284
10.10.3	Source pruning	284
10.10.4	Use of Group service requirement registration by end stations	284
10.11	Default Group filtering behavior and MMRP propagation	284
10.12	Definition of the MMRP application.....	286
10.12.1	Definition of MRP elements	286
10.12.2	Provision and support of Extended Filtering Services	288
10.12.3	Use of “new” declaration capability	290
10.12.4	Attribute value support requirements	290
10.12.5	Registrar Administrative Controls	290

11.	VLAN topology management.....	291
11.1	Static and dynamic VLAN configuration	291
11.2	Multiple VLAN Registration Protocol (MVRP)	292
11.2.1	MVRP overview	292
11.2.2	VLAN registration service definition	294
11.2.3	Definition of the MVRP application	295
11.2.4	VID translation table	298
11.2.5	Use of “new” declaration capability	298
11.2.6	New-Only Participant and Registrar Administrative Controls	298
11.2.7	Attribute value support requirements	298
12.	Bridge management	299
12.1	Management functions.....	299
12.1.1	Configuration Management	299
12.1.2	Fault Management	300
12.1.3	Performance Management	300
12.1.4	Security Management	300
12.1.5	Accounting Management	300
12.2	VLAN Bridge objects	300
12.3	Data types	301
12.4	Bridge Management Entity	302
12.4.1	Bridge Configuration	302
12.4.2	Port configuration	305
12.5	MAC entities.....	307
12.5.1	ISS Port Number table managed object (optional)	307
12.6	Forwarding process.....	307
12.6.1	The Port Counters	307
12.6.2	Priority handling	308
12.6.3	Traffic Class Table	316
12.7	Filtering Database (FDB).....	317
12.7.1	The Filtering Database object	317
12.7.2	A Static Filtering Entry object	318
12.7.3	A Dynamic Filtering Entry object	318
12.7.4	A MAC Address Registration Entry object	318
12.7.5	A VLAN Registration Entry object	319
12.7.6	Permanent Database object	319
12.7.7	General FDB operations	320
12.8	Bridge Protocol Entity	321
12.8.1	The Protocol Entity	322
12.8.2	Bridge Port	325
12.9	MRP Entities.....	329
12.9.1	The MRP Timer object	329
12.9.2	The MRP Attribute Type object	330
12.9.3	Periodic state machine objects	331
12.10	Bridge VLAN managed objects.....	331
12.10.1	Bridge VLAN Configuration managed object	332
12.10.2	VLAN Configuration managed object	337
12.10.3	The VID to FID allocation managed object	338
12.11	MMRP entities.....	341
12.11.1	MMRP Configuration managed object	341
12.12	MST configuration entities	342
12.12.1	The MSTI List	342
12.12.2	The FID to MSTID Allocation Table	344

12.12.3	The MST Configuration Table	345
12.13	Provider Bridge management	346
12.13.1	Provider Bridge Port Type managed object	348
12.13.2	Customer Edge Port Configuration managed object	349
12.13.3	Remote Customer Access Port Configuration managed object	352
12.14	CFM entities	354
12.14.1	Maintenance Domain list managed object	355
12.14.2	CFM Stack managed object	356
12.14.3	Default MD Level managed object	357
12.14.4	Configuration Error List managed object	358
12.14.5	Maintenance Domain managed object	358
12.14.6	Maintenance Association managed object	361
12.14.7	Maintenance association Endpoint managed object	364
12.15	Backbone Core Bridge (BCB) management.....	371
12.16	Backbone Edge Bridge (BEB) management	371
12.16.1	BEB configuration managed object	372
12.16.2	BEB/PB/VLAN Bridge Port configuration managed object	376
12.16.3	VIP configuration managed object	377
12.16.4	PIP configuration managed object	378
12.16.5	CBP Configuration managed object	384
12.17	DDCFM entities.....	387
12.17.1	DDCFM Stack managed object	387
12.17.2	Reflection Responder managed object	388
12.17.3	RFM Receiver managed object	391
12.17.4	Decapsulator Responder managed object	392
12.17.5	SFM Originator managed object	395
12.18	PBB-TE Protection Switching managed objects	398
12.18.1	TE protection group list managed object	398
12.18.2	TE protection group managed object	399
12.19	TPMR managed objects.....	401
12.19.1	TPMR management entity	402
12.19.2	MAC and PHY entities	404
12.19.3	Forwarding Process	404
12.19.4	MAC Status Propagation Entity (MSPE)	409
12.20	Management entities for FQTSS	411
12.20.1	The Bandwidth Availability Parameter Table	411
12.20.2	The Transmission Selection Algorithm Table	412
12.20.3	The Priority Regeneration Override Table	412
12.21	Congestion Notification managed objects	412
12.21.1	CN component managed object	413
12.21.2	CN component priority managed object	413
12.21.3	CN Port priority managed object	414
12.21.4	Congestion Point managed object	415
12.21.5	Reaction Point port priority managed object	416
12.21.6	Reaction Point group managed object	416
12.22	Stream Reservation Protocol (SRP) entities	417
12.22.1	SRP Bridge Base Table	417
12.22.2	SRP Bridge Port Table	417
12.22.3	SRP Latency Parameter Table	418
12.22.4	SRP Stream Table	418
12.22.5	SRP Reservations Table	419
12.23	Priority-based Flow Control objects.....	419
12.24	1:1 PBB-TE IPS managed objects.....	420
12.24.1	IPG list managed object	420

12.24.2	IPG managed object	422
12.25	Shortest Path Bridging managed objects	424
12.25.1	The SPB System managed object	425
12.25.2	The SPB MTID Static managed object	428
12.25.3	The SPB Topology Instance Dynamic managed object	429
12.25.4	The SPB ECT Static Entry managed object	430
12.25.5	The SPB ECT Dynamic Entry managed object	431
12.25.6	The SPB Adjacency Static Entry managed object	432
12.25.7	The SPB Adjacency Dynamic Entry managed object	433
12.25.8	The SPBM BSI Static Entry managed object	434
12.25.9	The SPB Topology Node Table managed object	435
12.25.10	The SPB Topology ECT Table managed object	436
12.25.11	The SPB Topology Edge Table managed object	436
12.25.12	The SPBM Topology Service Table managed object	437
12.25.13	The SPBV Topology Service Table managed object	438
12.25.14	The ECMP ECT Static Entry managed object	439
12.26	Edge Virtual Bridging (EVB) management.....	440
12.26.1	EVB system base table	444
12.26.2	SBP table entry	445
12.26.3	VSI table entry	446
12.26.4	S-channel configuration and management	448
12.26.5	ER management	450
12.27	Edge Control Protocol (ECP) management.....	451
12.27.1	ECP table entry	451
12.28	Path Control and Reservation (PCR) management.....	451
12.28.1	The PCR ECT Static Entry managed object	452
12.28.2	The PCR Topology ECT Table managed object	455
12.29	Managed objects for scheduled traffic.....	455
12.29.1	The Gate Parameter Table	455
12.29.2	Timing points for scheduled traffic	458
12.30	Managed objects for frame preemption	459
12.30.1	Frame Preemption Parameter table	459
12.31	Managed objects for per-stream filtering and policing.....	460
12.31.1	The Stream Parameter Table	460
12.31.2	The Stream Filter Instance Table	461
12.31.3	The Stream Gate Instance Table	463
12.31.4	The Flow Meter Instance Table	466
13.	Spanning tree protocols	467
13.1	Protocol design requirements.....	468
13.2	Protocol support requirements	469
13.2.1	MSTP support requirements	469
13.2.2	SPB support requirements	469
13.3	Protocol design goals	470
13.4	RSTP overview	470
13.4.1	Computation of the active topology	471
13.4.2	Example topologies	472
13.5	MSTP overview	475
13.5.1	Example topologies	476
13.5.2	Relationship of MSTP to RSTP	479
13.5.3	Modeling an MST or SPT Region as a single Bridge	479
13.6	SPB overview	480
13.7	Compatibility and interoperability.....	481

13.7.1	Designated Port selection	481
13.7.2	Force Protocol Version	481
13.8	MST Configuration Identifier (MCID).....	482
13.9	Spanning tree priority vectors.....	483
13.10	CIST Priority Vector calculations.....	485
13.11	MST Priority Vector calculations.....	487
13.12	Port Role assignments.....	489
13.13	Stable connectivity.....	490
13.14	Communicating spanning tree information	491
13.15	Changing spanning tree information.....	492
13.16	Changing Port States with RSTP or MSTP	493
13.16.1	Subtree connectivity and priority vectors	494
13.16.2	Root Port transition to Forwarding	494
13.16.3	Designated Port transition to Forwarding	494
13.16.4	Master Port transition to Forwarding	496
13.17	Changing Port States with SPB	498
13.17.1	Agreement Digest	500
13.18	Managing spanning tree topologies	501
13.19	Updating learned station location information	502
13.20	Managing reconfiguration.....	504
13.21	Partial and disputed connectivity.....	505
13.22	In-service upgrades	505
13.23	Fragile Bridges.....	507
13.24	Spanning tree protocol state machines.....	507
13.25	State machine timers	509
13.25.1	edgeDelayWhile	510
13.25.2	fdWhile	510
13.25.3	helloWhen	510
13.25.4	mdelayWhile	510
13.25.5	rbWhile	510
13.25.6	rcvdInfoWhile	510
13.25.7	rrWhile	511
13.25.8	tcDetected	511
13.25.9	tcWhile	511
13.25.10	pseudoInfoHelloWhen	511
13.26	Per Bridge variables.....	511
13.26.1	agreementDigest	512
13.26.2	BridgeIdentifier	512
13.26.3	BridgePriority	512
13.26.4	BridgeTimes	512
13.26.5	ForceProtocolVersion	513
13.26.6	MigrateTime	513
13.26.7	MstConfigId	513
13.26.8	AuxMstConfigId	513
13.26.9	rootPortId	513
13.26.10	rootPriority	513
13.26.11	rootTimes	513
13.26.12	TxHoldCount	513
13.27	Per port variables	513
13.27.1	AdminEdge	516
13.27.2	ageingTime	516
13.27.3	agree	516
13.27.4	agreed	516
13.27.5	agreedAbove	516

13.27.6	agreedDigest	516
13.27.7	agreedDigestValid	516
13.27.8	agreeDigest	516
13.27.9	agreeDigestValid	516
13.27.10	agreedMisorder	517
13.27.11	agreedN	517
13.27.12	agreedND	517
13.27.13	agreedPriority	517
13.27.14	agreedTopology	517
13.27.15	agreementOutstanding	517
13.27.16	agreeN	517
13.27.17	agreeND	517
13.27.18	AutoEdge	517
13.27.19	AutoIsolate	518
13.27.20	designatedPriority	518
13.27.21	designatedTimes	518
13.27.22	disputed	518
13.27.23	enableBPDUrx	518
13.27.24	enableBPDUtx	518
13.27.25	ExternalPortPathCost	518
13.27.26	isL2gp	518
13.27.27	isolate	519
13.27.28	fdbFlush	519
13.27.29	forward	519
13.27.30	forwarding	519
13.27.31	infoInternal	519
13.27.32	infols	519
13.27.33	InternalPortPathCost	519
13.27.34	learn	520
13.27.35	learning	520
13.27.36	master	520
13.27.37	mastered	520
13.27.38	mcheck	520
13.27.39	msgPriority	520
13.27.40	msgTimes	520
13.27.41	neighbourPriority	521
13.27.42	newInfo	521
13.27.43	newInfoMsti	521
13.27.44	operEdge	521
13.27.45	portEnabled	521
13.27.46	portId	521
13.27.47	portPriority	521
13.27.48	portTimes	522
13.27.49	proposed	522
13.27.50	proposing	522
13.27.51	pseudoRootId	522
13.27.52	rcvdBPDU	522
13.27.53	rcvdInfo	522
13.27.54	rcvdInternal	522
13.27.55	rcvdMsg	522
13.27.56	rcvdRSTP	522
13.27.57	rcvdSTP	522
13.27.58	rcvdTc	522
13.27.59	rcvdTcAck	522

13.27.60	rcvdTcn	523
13.27.61	reRoot	523
13.27.62	reselect	523
13.27.63	restrictedDomainRole	523
13.27.64	restrictedRole	523
13.27.65	restrictedTcn	523
13.27.66	role	523
13.27.67	selected	523
13.27.68	selectedRole	523
13.27.69	sendRSTP	524
13.27.70	sync	524
13.27.71	synced	524
13.27.72	tcAck	524
13.27.73	tcProp	524
13.27.74	tick	524
13.27.75	txCount	524
13.27.76	updtInfo	524
13.28	State machine conditions and parameters	524
13.28.1	allSptAgree	525
13.28.2	allSynced	525
13.28.3	allTransmitReady	525
13.28.4	BestAgreementPriority	525
13.28.5	cist	525
13.28.6	cistRootPort	525
13.28.7	cistDesignatedPort	526
13.28.8	EdgeDelay	526
13.28.9	forwardDelay	526
13.28.10	FwdDelay	526
13.28.11	HelloTime	526
13.28.12	MaxAge	526
13.28.13	msti	526
13.28.14	mstiDesignatedOrTCpropagatingRootPort	526
13.28.15	mstiMasterPort	526
13.28.16	operPointToPoint	526
13.28.17	rcvdAnyMsg	526
13.28.18	rcvdCistMsg	526
13.28.19	rcvdMstiMsg	527
13.28.20	reRooted	527
13.28.21	rstpVersion	527
13.28.22	spt	527
13.28.23	stpVersion	527
13.28.24	updtCistInfo	527
13.28.25	updtMstiInfo	527
13.29	State machine procedures	527
13.29.1	betterorsameInfo(newInfoIs)	528
13.29.2	clearAllRcvdMsgs()	528
13.29.3	clearReselectTree()	528
13.29.4	disableForwarding()	529
13.29.5	disableLearning()	529
13.29.6	enableForwarding()	529
13.29.7	enableLearning()	529
13.29.8	fromSameRegion()	529
13.29.9	newTcDetected()	529
13.29.10	newTcWhile()	529

13.29.11	pseudoRcvMsgs()	530
13.29.12	revInfo()	530
13.29.13	rcvMsgs()	531
13.29.14	rcvAgreements()	531
13.29.15	recordAgreement()	531
13.29.16	recordDispute()	532
13.29.17	recordMastered()	532
13.29.18	recordPriority()	532
13.29.19	recordProposal()	532
13.29.20	recordTimes()	532
13.29.21	setReRootTree()	533
13.29.22	setSelectedTree()	533
13.29.23	setSyncTree()	533
13.29.24	setTcFlags()	533
13.29.25	setTcPropTree()	533
13.29.26	syncMaster()	533
13.29.27	txConfig()	533
13.29.28	txRstp()	534
13.29.29	txTcn()	534
13.29.30	updtAgreement()	534
13.29.31	updtBPDUVersion()	535
13.29.32	updtDigest()	535
13.29.33	updtRcvdInfoWhile()	536
13.29.34	updtRolesTree()	537
13.29.35	uptRolesDisabledTree()	538
13.30	The Port Timers state machine	538
13.31	Port Receive state machine	539
13.32	Port Protocol Migration state machine	540
13.33	Bridge Detection state machine	540
13.34	Port Transmit state machine	541
13.35	Port Information state machine	542
13.36	Port Role Selection state machine	543
13.37	Port Role Transitions state machine	543
13.38	Port State Transition state machine	548
13.38.1	Port State transitions for the CIST and MSTIs	549
13.38.2	Port State transitions for SPTs	549
13.39	Topology Change state machine	550
13.40	Layer 2 Gateway Port Receive state machine	551
13.41	CEP spanning tree operation	551
13.41.1	PEP operPointToPointMAC and operEdge	551
13.41.2	updtRolesTree()	552
13.41.3	setReRootTree(), setSyncTree(), setTcPropTree()	552
13.41.4	allSynced, reRooted	552
13.41.5	Configuration parameters	552
13.42	Virtual Instance Port (VIP) spanning tree operation	553
14.	Encoding of Bridge Protocol Data Units (BPDUs)	554
14.1	BPDUs Structure	554
14.1.1	Transmission and representation of octets	554
14.1.2	Common BPDUs fields	554
14.2	Encoding of parameter types	556
14.2.1	Encoding of Protocol Identifiers	556
14.2.2	Encoding of Protocol Version Identifiers	556

14.2.3	Encoding of BPDU types	556
14.2.4	Encoding of flags	556
14.2.5	Encoding of Bridge Identifiers	556
14.2.6	Encoding of External Root Path Cost and Internal Root Path Cost	557
14.2.7	Encoding of Port Identifiers	557
14.2.8	Encoding of Timer Values	557
14.2.9	Encoding of Port Role values	557
14.2.10	Encoding of Length Values	558
14.2.11	Encoding of Hop Counts	558
14.3	Transmission of BPDUs	558
14.4	Encoding and decoding of STP Configuration, RST, MST, and SPT BPDUs.....	558
14.4.1	MSTI Configuration Messages	560
14.5	Validation of received BPDUs	561
14.6	Validation and interoperability	562
15.	Support of the MAC Service by PBNs	563
15.1	Service transparency	563
15.2	Customer service interfaces	564
15.3	Port-based service interface	564
15.4	C-tagged service interface	565
15.5	S-tagged service interface.....	566
15.6	Remote customer service interfaces (RCSIs)	567
15.7	Service instance segregation.....	570
15.8	Service instance selection and identification	570
15.9	Service priority selection	571
15.10	Service access protection	571
16.	Principles of Provider Bridged Network (PBN) operation.....	572
16.1	PBN overview.....	572
16.2	Provider Bridged Network (PBN)	573
16.3	Service instance connectivity.....	576
16.4	Service provider learning of customer end station addresses.....	577
16.5	Detection of connectivity loops through attached networks.....	577
16.6	Network management	578
17.	Management Information Base (MIB)	579
17.1	Internet Standard Management Framework	579
17.2	Structure of the MIB	579
17.2.1	Structure of the IEEE8021-TC-MIB	580
17.2.2	Structure of the IEEE8021-BRIDGE-MIB	582
17.2.3	Structure of the IEEE8021-SPANNING-TREE MIB	586
17.2.4	Structure of the IEEE8021-Q-BRIDGE-MIB	589
17.2.5	Structure of the IEEE8021-PB-MIB	594
17.2.6	Structure of the IEEE8021-MSTP-MIB	596
17.2.7	Structure of the IEEE8021-CFM-MIB	599
17.2.8	Structure of the IEEE8021-PBB-MIB	605
17.2.9	Structure of the IEEE8021-DDCFM-MIBs	607
17.2.10	Structure of the IEEE8021-PBBTE-MIB	610
17.2.11	Structure of the TPMR MIB	612
17.2.12	Structure of the IEEE8021-FQTSS-MIB	614
17.2.13	Structure of the Congestion Notification MIB	615
17.2.14	Structure of the IEEE8021-SRP-MIB	617

17.2.15	Structure of the MVRP extension MIB	619
17.2.16	Structure of the MIRP MIB	619
17.2.17	Structure of the PFC MIB	620
17.2.18	Structure of the IEEE80221-TEIPS MIB	620
17.2.19	Structure of the IEEE8021-SPB-MIB	622
17.2.20	Structure of the IEEE8021-EVB-MIB	626
17.2.21	Structure of the IEEE8021-ECMP-MIB	630
17.2.22	Structure of the IEEE8021-ST-MIB	631
17.2.23	Structure of the IEEE8021-Preemption-MIB	632
17.2.24	Structure of the IEEE8021-PSFP-MIB	633
17.3	Relationship to other MIBs.....	636
17.3.1	Relationship of the IEEE8021-TC-MIB to other MIB modules	636
17.3.2	Relationship of the IEEE8021-BRIDGE-MIB to other MIB modules	636
17.3.3	Relationship of the IEEE8021-RSTP MIB to other MIB modules	639
17.3.4	Relationship of the IEEE8021-Q-BRIDGE-MIB to other MIB modules	639
17.3.5	Relationship of the IEEE8021-PB-BRIDGE MIB to other MIB modules	641
17.3.6	Relationship of the IEEE8021-MSTP-MIB to other MIB modules	641
17.3.7	Relationship of the IEEE8021-CFM-MIB to other MIB modules	641
17.3.8	Relationship of the IEEE8021-PBB-MIB to other MIB modules	642
17.3.9	Relationship of the IEEE8021-DDCFM to other MIB modules	643
17.3.10	Relationship of the IEEE8021-PBBTE-MIB to other MIB modules	643
17.3.11	Relationship of the TPMR MIB to other MIB modules	644
17.3.12	Relationship of the IEEE8021-FQTSS-MIB to other MIB modules	644
17.3.13	Relationship of the IEEE802-CN-MIB to other MIB modules	644
17.3.14	Relationship of the IEEE8021-SRP-MIB to other MIB modules	645
17.3.15	Relationship of the IEEE8021-MVRPX-MIB to other MIB modules	645
17.3.16	Relationship of the IEEE8021-MIRP-MIB to other MIB modules	645
17.3.17	Relationship of the PFC MIB to other MIB modules	645
17.3.18	Relationship of the IEEE8021-TEIPS-MIB to other MIB modules	646
17.3.19	Relationship of the of the IEEE8021-SPB-MIB to other MIB modules	646
17.3.20	Relationship of the IEEE8021-EVB-MIB to other MIB modules	646
17.3.21	Relationship of the of the IEEE8021-ECMP-MIB to other MIB modules	646
17.3.22	Relationship of the PCR MIB to other MIB modules	646
17.3.23	Relationship of the IEEE8021-ST-MIB to other MIBs	646
17.3.24	Relationship of the IEEE8021-Preemption-MIB to other MIBs	647
17.3.25	Relationship of IEEE8021-PSFP-MIB to other MIBs	647
17.4	Security considerations	647
17.4.1	Security considerations of the IEEE8021-TC-MIB	647
17.4.2	Security considerations of the IEEE8021-BRIDGE-MIB	647
17.4.3	Security considerations of the IEEE8021-SPANNING-TREE MIB	648
17.4.4	Security considerations of the IEEE8021-Q-BRIDGE-MIB	649
17.4.5	Security considerations of the IEEE8021-PB-MIB	650
17.4.6	Security considerations of the IEEE8021-MSTP-MIB	650
17.4.7	Security considerations of the IEEE8021-CFM-MIB	651
17.4.8	Security considerations of the IEEE8021-PBB-MIB	653
17.4.9	Security considerations of the IEEE8021-DDCFM-MIB	653
17.4.10	Security considerations of the IEEE8021-PBBTE-MIB	654
17.4.11	Security considerations of the TPMR MIB	655
17.4.12	Security considerations of the IEEE8021-FQTSS-MIB	655
17.4.13	Security considerations of the Congestion Notification MIB	656
17.4.14	Security considerations of the IEEE8021-SRP-MIB	657
17.4.15	Security considerations of the IEEE8021-MVRPX-MIB	658
17.4.16	Security considerations of the IEEE8021-MIRP-MIB	658
17.4.17	Security considerations for the PFC MIB	659

17.4.18	Security considerations of the IEEE8021-TEIPS-MIB	659
17.4.19	Security considerations of the IEEE8021-SPB-MIB	659
17.4.20	Security considerations of the IEEE8021-EVB-MIB	660
17.4.21	Security considerations of the IEEE8021-ECMP-MIB	661
17.4.22	Security considerations of the PCR MIB	662
17.4.23	Security considerations of the IEEE8021-ST-MIB	662
17.4.24	Security considerations of the IEEE8021-Preemption-MIB	663
17.4.25	Security considerations of the IEEE8021-PSFP-MIB	663
17.5	Dynamic component and Port creation.....	665
17.5.1	Overview of the dynamically created Bridge entities	665
17.5.2	Component creation	666
17.5.3	Port creation	667
17.6	MIB operations for service interface configuration.....	677
17.6.1	Provisioning PBN service interfaces	677
17.6.2	Provisioning Backbone Bridged Network service interfaces	680
17.7	MIB modules,	686
17.7.1	Definitions for the IEEE8021-TC-MIB module	686
17.7.2	Definitions for the IEEE8021-BRIDGE-MIB module	697
17.7.3	Definitions for the IEEE8021-SPANNING-TREE-MIB module	737
17.7.4	Definitions for the IEEE8021-Q-BRIDGE-MIB module	755
17.7.5	Definitions for the IEEE8021-PB-MIB module	801
17.7.6	Definitions for the IEEE8021-MSTP-MIB module	819
17.7.7	Definitions for the CFM MIB modules	848
17.7.8	Definitions for the IEEE8021-PBB-MIB module	931
17.7.9	Definitions for the IEEE8021-DDCFM-MIB module	954
17.7.10	Definitions for the IEEE8021-PBBTE-MIB module	972
17.7.11	Definitions for the IEEE8021-TPMR-MIB module	989
17.7.12	Definitions for the IEEE8021-FQTSS-MIB module	1003
17.7.13	Definitions for the IEEE8021-CN-MIB module	1014
17.7.14	Definitions for the IEEE8021-SRP-MIB module	1050
17.7.15	Definitions for the IEEE8021-MVRPX-MIB module	1066
17.7.16	Definitions for the IEEE8021-MIRP-MIB module	1071
17.7.17	Definitions for the IEEE8021-PFC-MIB module	1077
17.7.18	Definitions for the IEEE8021-TEIPS-V2-MIB module	1081
17.7.19	Definitions for the IEEE8021-SPB-MIB module	1096
17.7.20	Definitions for the IEEE8021-EVB-MIB module	1140
17.7.21	Definitions for the IEEE8021-ECMP-MIB module	1169
17.7.22	Definitions for the IEEE8021-ST-MIB module	1177
17.7.23	Definitions for the IEEE8021-Preemption-MIB module	1190
17.7.24	Definitions for the IEEE8021-PSFP-MIB module	1196
18.	Principles of Connectivity Fault Management operation	1220
18.1	Maintenance Domains and DoSAPs.....	1221
18.2	Service instances and MAs	1223
18.3	Maintenance Domain Levels	1224
19.	CFM entity operation.....	1228
19.1	Maintenance Points (MPs).....	1228
19.2	MA Endpoints (MEPs)	1229
19.2.1	MEP identification	1229
19.2.2	MEP functions	1230
19.2.3	MEP architecture	1230
19.2.4	MP Type Demultiplexer	1232

19.2.5	MP Multiplexer	1232
19.2.6	MP Level Demultiplexer	1232
19.2.7	MP OpCode Demultiplexer	1232
19.2.8	MEP Continuity Check Receiver	1233
19.2.9	MEP Continuity Check Initiator	1233
19.2.10	MP Loopback Responder	1234
19.2.11	MEP Loopback Initiator	1234
19.2.12	MEP Linktrace Initiator	1234
19.2.13	MEP LTI SAP	1234
19.2.14	MEP Linktrace SAP	1234
19.2.15	MEP CCM Database	1234
19.2.16	MEP Fault Notification Generator	1234
19.2.17	MEP Decapsulator Responder (DR)	1235
19.2.18	MEP RFM Receiver	1235
19.3	MIP Half Function	1235
19.3.1	MHF identification	1235
19.3.2	MHF functions	1235
19.3.3	MHF architecture	1236
19.3.4	MHF Level Demultiplexer	1236
19.3.5	MHF Type Demultiplexer	1236
19.3.6	MHF OpCode Demultiplexer	1236
19.3.7	MHF Multiplexer	1236
19.3.8	MHF Loopback Responder	1236
19.3.9	MHF Continuity Check Receiver	1237
19.3.10	MIP CCM Database	1237
19.3.11	MHF Linktrace SAP	1238
19.3.12	MHF DR	1238
19.3.13	MHF RFM Receiver	1238
19.4	MP addressing.....	1238
19.5	Linktrace Output Multiplexer (LOM).....	1239
19.6	Linktrace Responder	1239
20.	CFM protocols	1241
20.1	Continuity Check protocol	1242
20.1.1	MAC status reporting in the CCM	1244
20.1.2	Defects and Fault Alarms	1244
20.1.3	CCM reception	1245
20.2	Loopback protocol	1245
20.2.1	LBM transmission	1246
20.2.2	LBM reception and LBR transmission	1246
20.2.3	LBR reception	1247
20.3	Linktrace protocol	1247
20.3.1	LTM origination	1248
20.3.2	LTM reception, forwarding, and replying	1249
20.3.3	LTR reception	1250
20.4	CFM state machines	1251
20.5	CFM state machine timers	1251
20.5.1	LTFwhile	1253
20.5.2	CCIwhile	1253
20.5.3	errorCCMwhile	1253
20.5.4	xconCCMwhile	1253
20.5.5	LBIwhile	1253
20.5.6	FNGwhile	1253

20.5.7	mmCCMwhile	1253
20.5.8	mmLocwhile	1253
20.5.9	mmFNGwhile	1253
20.5.10	rMEPwhile	1253
20.6	CFM procedures	1254
20.6.1	CCMtime()	1254
20.7	Maintenance Domain variable	1254
20.7.1	mdLevel	1254
20.8	MA variables	1254
20.8.1	CCMinterval	1254
20.9	MEP variables	1254
20.9.1	MEPactive	1255
20.9.2	enableRmepDefect	1255
20.9.3	MAdefectIndication	1256
20.9.4	allRMEPsDead	1256
20.9.5	lowestAlarmPri	1256
20.9.6	presentRDI	1256
20.9.7	MEPprimaryVID	1256
20.9.8	presentTraffic	1256
20.9.9	presentmmLoc	1256
20.9.10	ISpresentTraffic	1257
20.9.11	ISpresentmmLoc	1257
20.9.12	EpMEP	1257
20.10	MEP Continuity Check Initiator variables	1257
20.10.1	CCIenabled	1257
20.10.2	CCIsentCCMs	1257
20.10.3	MACstatusChanged	1257
20.10.4	Npaths	1257
20.10.5	flowHash[]	1258
20.10.6	pathN	1258
20.10.7	CCMent	1258
20.11	MEP Continuity Check Initiator procedures	1258
20.11.1	xmitCCM()	1258
20.12	MEP Continuity Check Initiator state machine	1259
20.13	MHF Continuity Check Receiver variables	1260
20.13.1	MHFrecvdCCM	1260
20.13.2	MHFCCMPDU	1260
20.14	MHF Continuity Check Receiver procedures	1260
20.14.1	MHFprocessCCM()	1260
20.15	MHF Continuity Check Receiver state machine	1260
20.16	MEP Continuity Check Receiver variables	1261
20.16.1	CCMreceivedEqual	1261
20.16.2	CCMequalPDU	1261
20.16.3	CCMreceivedLow	1261
20.16.4	CCMlowPDU	1261
20.16.5	recvdMacAddress	1261
20.16.6	recvdRDI	1261
20.16.7	recvdInterval	1262
20.16.8	recvdPortState	1262
20.16.9	recvdInterfaceStatus	1262
20.16.10	recvdSenderId	1262
20.16.11	recvdFrame	1262
20.16.12	CCMsequenceErrors	1262
20.16.13	recvdTrafficBit	1262

20.17	MEP Continuity Check Receiver procedures	1262
20.17.1	MEPprocessEqualCCM()	1263
20.17.2	MEPprocessLowCCM()	1263
20.18	MEP Continuity Check Receiver state machine	1264
20.19	Remote MEP variables	1264
20.19.1	rMEPCCMdefect	1264
20.19.2	rMEPlastRDI and rMEPlastRDI[i]	1264
20.19.3	rMEPlastPortState	1265
20.19.4	rMEPlastInterfaceStatus	1265
20.19.5	rMEPlastSenderId	1265
20.19.6	rCCMreceived	1265
20.19.7	rMEPmacAddress	1265
20.19.8	rMEPportStatusDefect	1265
20.19.9	rMEPinterfaceStatusDefect	1265
20.19.10	lastPathN	1265
20.20	Remote MEP state machine	1266
20.21	Remote MEP Error variables	1267
20.21.1	errorCCMreceived	1267
20.21.2	errorCCMlastFailure	1267
20.21.3	errorCCMdefect	1267
20.22	Remote MEP Error state machine	1267
20.23	MEP Cross Connect variables	1268
20.23.1	xconCCMreceived	1268
20.23.2	xconCCMlastFailure	1268
20.23.3	xconCCMdefect	1268
20.24	MEP Cross Connect state machine	1268
20.25	MEP Mismatch variables	1269
20.25.1	mmCCMreceived	1269
20.25.2	mmCCMdefect	1269
20.25.3	mmCCMTime	1269
20.25.4	disableLocdefect	1269
20.25.5	mmLocdefect	1269
20.26	MEP Mismatch state machines	1270
20.27	MP Loopback Responder variables	1271
20.27.1	LBMreceived	1271
20.27.2	LBMPPDU	1271
20.28	MP Loopback Responder procedures	1271
20.28.1	ProcessLBM()	1271
20.28.2	xmitLBR()	1272
20.29	MP Loopback Responder state machine	1272
20.30	MEP Loopback Initiator variables	1273
20.30.1	LBMsToSend	1273
20.30.2	nextLBMtransID	1273
20.30.3	expectedLBRtransID	1273
20.30.4	LBIactive	1273
20.30.5	xmitReady	1273
20.30.6	LBRreceived	1273
20.30.7	LBRPDU	1273
20.31	MEP Loopback Initiator transmit procedures	1274
20.31.1	xmitLBM()	1274
20.32	MEP Loopback Initiator transmit state machine	1275
20.33	MEP Loopback Initiator receive procedures	1275
20.33.1	ProcessLBR()	1275
20.34	MEP Loopback Initiator receive state machine	1276

20.35	MEP Fault Notification Generator variables	1276
20.35.1	fngPriority	1276
20.35.2	fngDefect	1277
20.35.3	fngAlarmTime	1277
20.35.4	fngResetTime	1277
20.35.5	someRMEPCCMdefect	1277
20.35.6	someMACstatusDefect	1277
20.35.7	someRDId defect	1277
20.35.8	highestDefectPri	1277
20.35.9	highestDefect	1277
20.36	MEP Fault Notification Generator procedures	1278
20.36.1	xmitFaultAlarm()	1278
20.37	MEP Fault Notification Generator state machine	1278
20.38	MEP Mismatch Fault Notification Generator variables	1279
20.38.1	mfngAllowed	1279
20.38.2	mmdefectIndication	1279
20.38.3	mfngAlarmTime	1279
20.38.4	mfngResetTime	1279
20.39	MEP Mismatch Fault Notification Generator procedures	1279
20.39.1	xmitFaultAlarm()	1279
20.40	MEP Mismatch Fault Notification Generator state machine	1280
20.41	MEP Linktrace Initiator variables	1280
20.41.1	nextLTMtransID	1280
20.41.2	ltmReplyList	1281
20.42	MEP Linktrace Initiator procedures	1283
20.42.1	xmitLTM()	1283
20.43	MEP Linktrace Initiator receive variables	1284
20.43.1	LTRreceived	1284
20.43.2	LTRPDU	1284
20.44	MEP Linktrace Initiator receive procedures	1284
20.44.1	ProcessLTR()	1284
20.45	MEP Linktrace Initiator receive state machine	1285
20.46	Linktrace Responder variables	1285
20.46.1	nPendingLTRs	1285
20.46.2	LTMreceived	1285
20.46.3	LTMPDU	1285
20.47	LTM Receiver procedures	1286
20.47.1	ProcessLTM()	1286
20.47.2	clearPendingLTRs()	1290
20.47.3	ForwardLTM()	1290
20.47.4	enqueLTR()	1291
20.48	LTM Receiver state machine	1292
20.49	LTR Transmitter procedure	1293
20.49.1	xmitOldestLTR()	1293
20.50	LTR Transmitter state machine	1293
20.51	CFM PDU validation and versioning	1294
20.51.1	Goals of CFM PDU versioning	1294
20.51.2	PDU transmission	1294
20.51.3	PDU validation	1294
20.51.4	Validation pass	1295
20.51.5	Execution pass	1296
20.51.6	Future extensions	1296
20.52	PDU identification	1297
20.53	Use of transaction IDs and sequence numbers	1297

21.	Encoding of CFM PDUs	1299
21.1	Structure, representation, and encoding	1299
21.2	CFM encapsulation	1299
21.3	CFM request and indication parameters	1300
21.3.1	destination_address parameter	1300
21.3.2	source_address parameter	1300
21.4	Common CFM Header	1300
21.4.1	MD Level	1300
21.4.2	Version	1300
21.4.3	OpCode	1301
21.4.4	Flags	1301
21.4.5	First TLV Offset	1302
21.5	TLV format	1302
21.5.1	General format for CFM TLVs	1302
21.5.2	Organization-Specific TLV	1303
21.5.3	Sender ID TLV	1304
21.5.4	Port Status TLV	1305
21.5.5	Interface Status TLV	1306
21.5.6	Data TLV	1307
21.5.7	End TLV	1307
21.6	CCM format	1307
21.6.1	Flags	1308
21.6.2	First TLV Offset	1309
21.6.3	Sequence Number	1309
21.6.4	Maintenance association Endpoint Identifier	1309
21.6.5	Maintenance Association Identifier	1309
21.6.6	Defined by ITU-T Y.1731 (02/2008)	1312
21.6.7	Optional CCM TLVs	1312
21.7	LBM and LBR formats	1312
21.7.1	Flags	1312
21.7.2	First TLV Offset	1313
21.7.3	Loopback Transaction Identifier	1313
21.7.4	Additional LBM/LBR TLVs	1313
21.7.5	PBB-TE MIP TLV	1314
21.8	LTM format	1315
21.8.1	Flags	1315
21.8.2	First TLV Offset	1315
21.8.3	LTM Transaction Identifier	1315
21.8.4	LTM TTL	1316
21.8.5	Original MAC Address	1316
21.8.6	Target MAC Address	1316
21.8.7	Additional LTM TLVs	1316
21.8.8	LTM Egress Identifier TLV	1316
21.9	LTR format	1317
21.9.1	Flags	1317
21.9.2	First TLV Offset	1318
21.9.3	LTR Transaction Identifier	1318
21.9.4	Reply TTL	1318
21.9.5	Relay Action	1318
21.9.6	Additional LTR TLVs	1318
21.9.7	LTR Egress Identifier TLV	1319
21.9.8	Reply Ingress TLV	1319
21.9.9	Reply Egress TLV	1321

22.	CFM in systems	1323
22.1	CFM shims in Bridges	1323
22.1.1	Preliminary positioning of MPs	1323
22.1.2	CFM and the Forwarding Process	1324
22.1.3	Up/Down separation of MPs	1326
22.1.4	Service instances over multiple Bridges	1328
22.1.5	Multiple VID service instances	1330
22.1.6	Untagged CFM PDUs	1330
22.1.7	MPs and non-VLAN-aware Bridges	1330
22.1.8	MPs and other standards	1331
22.1.9	CFM and IEEE 802.3 OAM	1333
22.2	Maintenance Entity creation	1333
22.2.1	Creating Maintenance Domains and MAs	1334
22.2.2	Creating MEPs	1334
22.2.3	Creating MIPs	1336
22.2.4	CFM configuration errors	1337
22.3	MPs, Ports, and MD Level assignment.....	1338
22.4	Stations and CFM	1338
22.5	Scalability of CFM.....	1339
22.6	CFM in Provider Bridges.....	1340
22.6.1	MPs and C-VLAN components	1340
22.6.2	Maintenance C-VLAN on a Port-based service interface	1341
22.6.3	Maintenance C-VLAN on a C-tagged service interface	1342
22.6.4	MPs and Port-mapping S-VLAN components	1342
22.7	Management Port MEPs and CFM in the enterprise environment.....	1344
22.8	Implementing CFM on Bridges that implement earlier revisions of IEEE Std 802.1Q	1346
23.	MAC status propagation	1347
23.1	Model of operation.....	1348
23.1.1	MAC Status Shim (MSS)	1349
23.1.2	Relationship of CFM to the MSS	1350
23.2	MAC Status Protocol (MSP) overview	1350
23.3	MSP state machines	1355
23.4	State machine timers	1356
23.4.1	linkNotifyWhen	1356
23.4.2	linkNotifyWhile	1356
23.4.3	macNotifyWhile	1356
23.4.4	macRecoverWhile	1356
23.5	MSP performance parameters.....	1356
23.5.1	LinkNotify	1357
23.5.2	LinkNotifyWait	1357
23.5.3	LinkNotifyRetry	1357
23.5.4	MACNotify	1357
23.5.5	MACNotifyTime	1357
23.5.6	MACRecoverTime	1357
23.6	State machine variables	1357
23.6.1	BEGIN	1357
23.6.2	addConfirmed	1357
23.6.3	disableMAC	1357
23.6.4	disabledMAC	1357
23.6.5	disableMSS	1358
23.6.6	lossConfirmed	1358
23.6.7	macOperational	1358

23.6.8	mssOperational	1358
23.6.9	prop	1358
23.6.10	rxAck	1358
23.6.11	rxAdd	1358
23.6.12	rxAddConfirm	1358
23.6.13	rxLoss	1358
23.6.14	rxLossConfirm	1358
23.6.15	txAck	1358
23.6.16	txAdd	1358
23.6.17	txAddConfirm	1359
23.6.18	txLoss	1359
23.6.19	txLossConfirm	1359
23.7	State machine procedures	1359
23.8	Status Transition state machine (STM)	1359
23.9	Status Notification state machine (SNM)	1360
23.10	Receive Process	1360
23.11	Transmit Process	1360
23.12	Management of MSP	1360
23.13	MSPDU transmission, addressing, and protocol identification	1361
23.13.1	Destination MAC Address	1361
23.13.2	Source MAC Address	1361
23.13.3	Priority	1362
23.13.4	EtherType use and encoding	1362
23.14	Representation and encoding of octets	1362
23.15	MSPDU structure	1362
23.15.1	Protocol Version	1362
23.15.2	Packet Type	1363
23.16	Validation of received MSPDUs	1363
23.17	Other MSP participants	1363
24.	Bridge performance	1364
24.1	Guaranteed Port Filtering Rate	1364
24.2	Guaranteed Bridge Relaying Rate	1364
24.3	RSTP performance requirements	1364
25.	Support of the MAC Service by PBBNs	1366
25.1	Service transparency	1368
25.2	Customer service interface	1368
25.3	Port-based service interface	1369
25.4	S-tagged service interface	1370
25.5	I-tagged service interface	1372
25.6	Service instance segregation	1374
25.7	Service instance selection and identification	1374
25.8	Service priority and drop eligibility selection	1375
25.9	Service access protection	1375
25.9.1	Class II redundant LANs access protection	1377
25.9.2	Class III simple redundant LANs and nodes access protection	1378
25.10	Support of the MAC Service by a PBB-TE Region	1379
25.10.1	Provisioning TESIS	1380
25.10.2	ESP forwarding behavior	1381
25.11	Transparent service interface	1382

26.	Principles of Provider Backbone Bridged Network (PBBN) operation	1384
26.1	PBBN overview	1384
26.2	PBBN example	1385
26.3	B-VLAN connectivity.....	1387
26.4	Backbone addressing	1388
26.4.1	Learning individual backbone addresses at a PIP	1389
26.4.2	Translating backbone destination addresses at a CBP	1389
26.4.3	Backbone addressing considerations for CFM MPs	1390
26.5	Detection of connectivity loops through attached networks.....	1390
26.6	Scaling of PBBs	1390
26.6.1	Hierarchal PBBNs	1391
26.6.2	Peer PBBNs	1391
26.7	Network management	1391
26.8	CFM in PBBs.....	1392
26.8.1	CFM over Port-based and S-tagged service interfaces	1397
26.8.2	CFM over I-tagged Service Interfaces	1398
26.8.3	CFM over hierarchal E-NNI	1398
26.8.4	CFM over peer E-NNI	1398
26.9	CFM in a PBB-TE Region.....	1399
26.9.1	Addressing PBB-TE MEPs	1399
26.9.2	TESI identification	1400
26.9.3	PBB-TE MEP placement in a Bridge Port	1400
26.9.4	PBB-TE MIP placement in a Bridge Port	1400
26.9.5	TESI Maintenance Domains	1400
26.9.6	PBB-TE enhancements of the CFM protocols	1401
26.9.7	Addressing Infrastructure Segment MEPs	1403
26.9.8	Infrastructure Segment identification	1403
26.9.9	Infrastructure Segment MEP placement in a Bridge Port	1404
26.9.10	Infrastructure Segment Maintenance Domains	1404
26.9.11	IPS extensions to Continuity Check operation	1404
26.10	Protection switching for point-to-point TESIs.....	1406
26.10.1	Introduction	1406
26.10.2	1:1 point-to-point TESI protection switching	1407
26.10.3	Protection Switching state machines	1410
26.11	IPS in PBB-TE Region	1415
26.11.1	Infrastructure Segment monitoring	1416
26.11.2	1:1 IPS	1417
26.11.3	IPS Control entity	1420
26.11.4	1:1 IPS state machines	1421
26.11.5	M:1 IPS	1421
26.12	Mismatch defect.....	1427
26.13	Signaling VLAN registrations among I-components	1428
27.	Shortest Path Bridging (SPB)	1429
27.1	Protocol design requirements.....	1431
27.2	Protocol support.....	1432
27.3	Protocol design goals	1433
27.4	ISIS-SPB VLAN configuration	1433
27.4.1	SPT Region and ISIS-SPB adjacency determination	1434
27.5	ISIS-SPB information	1436
27.6	Calculating CIST connectivity.....	1437
27.7	Connectivity between regions in the same domain	1438
27.8	Calculating SPT connectivity	1438

27.8.1	ISIS-SPB overload	1439
27.9	Loop prevention.....	1439
27.10	SPVID and SPSourceID allocation.....	1439
27.11	Allocation of VIDs to FIDs	1441
27.12	SPBV SPVID translation	1442
27.13	VLAN topology management.....	1442
27.14	Individual addresses and SPBM	1443
27.14.1	Loop mitigation	1444
27.14.2	Loop prevention	1444
27.15	SPBM group addressing	1445
27.16	Backbone service instance topology management	1447
27.17	Equal cost shortest paths, ECTs, and load spreading	1447
27.18	Connectivity Fault Management for SPBM	1448
27.18.1	SPBM MA types	1448
27.18.2	SPBM MEP placement in a Bridge Port	1448
27.18.3	SPBM MIP placement in a Bridge Port	1449
27.18.4	SPBM modifications of the CFM protocols	1449
27.19	Using SPBV and SPBM modes	1451
27.19.1	Shortest Path Bridging—VID	1451
27.19.2	Shortest Path Bridging—MAC	1452
27.20	Security considerations	1454
28.	ISIS-SPB Link State Protocol.....	1455
28.1	ISIS-SPB control plane MAC.....	1455
28.2	Formation and maintenance of ISIS-SPB adjacencies	1456
28.3	Loop prevention.....	1457
28.4	The Agreement Digest.....	1457
28.4.1	Agreement Digest Format Identifier	1458
28.4.2	Agreement Digest Format Capabilities	1458
28.4.3	Agreement Digest Convention Identifier	1458
28.4.4	Agreement Digest Convention Capabilities	1459
28.4.5	Agreement Digest Edge Count	1459
28.4.6	The Computed Topology Digest	1459
28.5	Symmetric shortest path tie breaking.....	1460
28.6	Symmetric ECT framework.....	1461
28.7	Symmetric ECT	1462
28.8	Symmetric ECT Algorithm details	1463
28.9	ECT Migration.....	1464
28.9.1	Use of a new ECT Algorithm in SPBV	1465
28.9.2	Use of a new ECT Algorithm in SPBM	1465
28.10	MAC address registration	1466
28.11	Circuit IDs and Port Identifiers.....	1467
28.12	ISIS-SPB TLVs.....	1467
28.12.1	MT-Capability TLV	1468
28.12.2	SPB MCID sub-TLV	1468
28.12.3	SPB Digest sub-TLV	1469
28.12.4	SPB Base VLAN-Identifiers sub-TLV	1469
28.12.5	SPB Instance sub-TLV	1471
28.12.6	SPB Instance Opaque ECT Algorithm sub-TLV	1473
28.12.7	SPB Link Metric sub-TLV	1474
28.12.8	SPB Adjacency Opaque ECT Algorithm sub-TLV	1475
28.12.9	SPBV MAC address sub-TLV	1476
28.12.10	SPBM Service Identifier and Unicast Address (ISID-ADDR) sub-TLV	1477

29.	DDCFM operations and protocols.....	1480
29.1	Principles of DDCFM operation.....	1480
29.1.1	Data-driven and data-dependent faults (DDFs)	1480
29.1.2	Basic principle to diagnose and isolate DDFs	1480
29.2	DDCFM Entity operation	1483
29.2.1	DDCFM implementation	1483
29.2.2	FPT RR	1484
29.2.3	RR-related parameters	1485
29.2.4	Reflection Target and RFM Receiver	1486
29.2.5	RPT-related parameters	1486
29.2.6	Decapsulator Responder (DR)	1487
29.2.7	SFM Originator	1488
29.3	DDCFM protocols	1488
29.3.1	RR variables	1488
29.3.2	RR Filter procedures	1490
29.3.3	RR Encapsulation procedures	1491
29.3.4	RR Transmit procedure	1492
29.3.5	RR-related state machines	1493
29.3.6	RFM Receiver variables	1495
29.3.7	RFM Receiver procedure	1495
29.3.8	DR variables	1496
29.3.9	DR procedures	1497
29.3.10	Decapsulator Responder state machine	1498
29.4	Encoding of DDCFM PDUs.....	1498
29.4.1	RFM and SFM Header	1498
29.4.2	RFM format	1499
29.4.3	SFM format	1500
30.	Principles of congestion notification	1502
30.1	Congestion notification design requirements	1502
30.2	Quantized Congestion Notification protocol (QCN)	1504
30.2.1	The CP algorithm	1505
30.2.2	Basic RP algorithm	1506
30.2.3	RP algorithm with timer	1507
30.3	Congestion Controlled Flow (CCF)	1508
30.4	Congestion Notification Priority Value (CNPV)	1509
30.5	Congestion Notification tag (CN-TAG)	1509
30.6	Congestion Notification Domain (CND)	1509
30.7	Multicast data	1510
30.8	Congestion notification and additional tags	1510
31.	Congestion notification entity operation	1512
31.1	Congestion-aware Bridge Forwarding Process	1512
31.1.1	Congestion Point (CP)	1513
31.1.2	CP ingress multiplexer	1513
31.2	Congestion-aware end station functions	1513
31.2.1	Output flow segregation	1514
31.2.2	Per-CNPV station function	1515
31.2.3	Flow Select Database	1517
31.2.4	Flow multiplexer	1517
31.2.5	CNM demultiplexer	1517
31.2.6	Input flow segregation	1517

31.2.7	End station input queue	1518
31.2.8	Reception selection	1518
32.	Congestion notification protocol	1519
32.1	CND operations	1519
32.1.1	CND defense	1519
32.1.2	Automatic CND recognition	1521
32.1.3	Variables controlling CND defense	1521
32.2	CN component variables	1522
32.2.1	cngMasterEnable	1523
32.2.2	cngCnmTransmitPriority	1523
32.2.3	cngDiscardedFrames	1523
32.2.4	cngErroredPortList	1523
32.3	Congestion notification per-CNPV variables	1523
32.3.1	cncpDefModeChoice	1523
32.3.2	cncpAlternatePriority	1524
32.3.3	cncpAutoAltPri	1524
32.3.4	cncpAdminDefenseMode	1524
32.3.5	cncpCreation	1524
32.3.6	cncpLdpInstanceChoice	1524
32.3.7	cncpLdpInstanceSelector	1524
32.4	CND defense per-Port per-CNPV variables	1525
32.4.1	cnpdDefModeChoice	1525
32.4.2	cnpdAdminDefenseMode	1525
32.4.3	cnpdAutoDefenseMode	1526
32.4.4	cnpdLdpInstanceChoice	1526
32.4.5	cnpdLdpInstanceSelector	1526
32.4.6	cnpdAlternatePriority	1526
32.4.7	cnpdXmitCnpvCapable	1526
32.4.8	cnpdXmitReady	1526
32.4.9	cncpDoesEdge	1527
32.4.10	cnpdAcceptsCnTag	1527
32.4.11	cnpdRcvdCnpv	1527
32.4.12	cnpdRcvdReady	1527
32.4.13	cnpdIsAdminDefMode	1527
32.4.14	cnpdDefenseMode	1528
32.5	CND defense procedures	1528
32.5.1	DisableCnpvRemapping()	1528
32.5.2	TurnOnCnDefenses()	1528
32.5.3	TurnOffCnDefenses()	1528
32.6	CND defense state machine	1528
32.7	Congestion notification protocol	1529
32.8	CP variables	1530
32.8.1	cpMacAddress	1531
32.8.2	cpId	1531
32.8.3	cpQSp	1531
32.8.4	cpQLen	1531
32.8.5	cpQLenOld	1531
32.8.6	cpW	1531
32.8.7	cpQOffset	1531
32.8.8	cpQDelta	1531
32.8.9	cpFb	1531
32.8.10	cpEnqued	1532

32.8.11	cpSampleBase	1532
32.8.12	cpDiscardedFrames	1532
32.8.13	cpTransmittedFrames	1532
32.8.14	cpTransmittedCnms	1532
32.8.15	cpMinHeaderOctets	1532
32.9	CP procedures	1532
32.9.1	Random	1532
32.9.2	NewCpSampleBase()	1532
32.9.3	EM_UNITDATA.request (parameters)	1533
32.9.4	GenerateCnmPdu()	1533
32.10	RP per-Port per-CNPV variables	1534
32.10.1	rpppMaxRps	1534
32.10.2	rpppCreatedRps	1534
32.10.3	rpppRpCentiseconds	1535
32.11	RP group variables	1535
32.11.1	rpgEnable	1535
32.11.2	rpgTimeReset	1535
32.11.3	rpgByteReset	1535
32.11.4	rpgThreshold	1536
32.11.5	rpgMaxRate	1536
32.11.6	rpgAiRate	1536
32.11.7	rpgHaiRate	1536
32.11.8	rpgGd	1536
32.11.9	rpgMinDecFac	1536
32.11.10	rpgMinRate	1536
32.12	RP timer	1536
32.12.1	RpWhile	1537
32.13	RP variables	1537
32.13.1	rpEnabled	1537
32.13.2	rpByteCount	1537
32.13.3	rpByteStage	1537
32.13.4	rpTimeStage	1537
32.13.5	rpTargetRate	1537
32.13.6	rpCurrentRate	1538
32.13.7	rpFreeze	1538
32.13.8	rpLimiterRate	1538
32.13.9	rpFb	1538
32.14	RP procedures	1538
32.14.1	ResetCnm	1538
32.14.2	TestRpTerminate	1539
32.14.3	TransmitDataFrame	1539
32.14.4	ReceiveCnm	1539
32.14.5	ProcessCnm	1540
32.14.6	AdjustRates	1540
32.15	RP rate control state machine	1540
32.16	Congestion notification and encapsulation interworking function	1542
33.	Encoding of congestion notification PDUs	1544
33.1	Structure, representation, and encoding	1544
33.2	CN-TAG format	1544
33.2.1	Flow Identifier	1545
33.3	Congestion Notification Message (CNM)	1545
33.4	Congestion Notification Message PDU format	1545

33.4.1	Version	1545
33.4.2	ReservedV	1546
33.4.3	Quantized Feedback	1546
33.4.4	Congestion Point Identifier	1546
33.4.5	cnmQOffset	1546
33.4.6	cnmQDelta	1547
33.4.7	Encapsulated priority	1547
33.4.8	Encapsulated destination MAC address	1547
33.4.9	Encapsulated MSDU length	1547
33.4.10	Encapsulated MSDU	1547
33.4.11	CNM Validation	1547
34.	Forwarding and Queuing Enhancements for time-sensitive streams (FQTSS).....	1548
34.1	Overview.....	1548
34.2	Detection of SRP domains	1548
34.3	The bandwidth availability parameters.....	1549
34.3.1	Relationships among bandwidth availability parameters	1549
34.3.2	Bandwidth availability parameter management	1550
34.4	Deriving actual bandwidth requirements from the size of the MSDU	1550
34.5	Mapping priorities to traffic classes for time-sensitive streams	1551
34.6	End station behavior	1553
34.6.1	Talker behavior	1553
34.6.2	Listener behavior	1554
35.	Stream Reservation Protocol (SRP).....	1555
35.1	Multiple Stream Registration Protocol (MSRP).....	1556
35.1.1	MSRP and Shared Media	1557
35.1.2	Behavior of end stations	1557
35.1.3	Behavior of Bridges	1559
35.1.4	SRP domains and status parameters	1559
35.2	Definition of the MSRP application.....	1559
35.2.1	Definition of internal state variables	1560
35.2.2	Definition of MRP elements	1562
35.2.3	Provision and support of Stream registration service	1572
35.2.4	MSRP Attribute Propagation	1576
35.2.5	Operational reporting and statistics	1581
35.2.6	Encoding	1581
35.2.7	Attribute value support requirements	1582
36.	Priority-based Flow Control (PFC)	1583
36.1	PFC operation	1583
36.1.1	Overview	1583
36.1.2	PFC primitives	1584
36.1.3	Detailed specification of PFC operation	1585
36.2	PFC-aware system queue functions	1586
36.2.1	PFC Initiator	1587
36.2.2	PFC Receiver	1587
37.	Enhanced Transmission Selection (ETS)	1589
37.1	Overview.....	1589
37.1.1	Relationship to other transmission selection algorithms	1589
37.2	ETS configuration parameters	1589

37.3	ETS algorithm.....	1589
37.4	Legacy configuration.....	1590
38.	Data Center Bridging eXchange protocol (DCBX).....	1591
38.1	Overview.....	1591
38.2	Goals.....	1591
38.3	Types of DCBX attributes.....	1591
38.3.1	Informational attributes.....	1591
38.4	DCBX and LLDP.....	1592
38.4.1	Asymmetric attribute passing.....	1592
38.4.2	Symmetric attribute passing.....	1593
39.	Multiple I-SID Registration Protocol (MIRP).....	1595
39.1	MIRP overview.....	1595
39.1.1	Behavior of I-components.....	1597
39.1.2	Behavior of B-components.....	1597
39.2	Definition of the MIRP application.....	1597
39.2.1	Definition of MRP elements.....	1597
39.2.2	Alternate MIRP model for B-components.....	1600
39.2.3	Use of “new” declaration capability.....	1602
39.2.4	Attribute value support requirements.....	1602
39.2.5	MRP Message filtering.....	1602
40.	Edge Virtual Bridging (EVB).....	1603
40.1	EVB architecture without S-channels.....	1604
40.2	EVB architecture with S-channels.....	1605
40.3	Asymmetric EVB architecture without S-channels.....	1607
40.4	EVB status parameters.....	1609
40.4.1	EVBMode = Not supported.....	1609
40.4.2	EVBMode = EVB Bridge.....	1609
40.4.3	EVBMode = EVB station.....	1609
41.	VSI Discovery and Configuration Protocol (VDP).....	1610
41.1	VSI manager ID TLV definition.....	1610
41.1.1	TLV type.....	1610
41.1.2	TLV information string length.....	1610
41.1.3	VSI Manager ID.....	1611
41.2	VDP association TLV definitions.....	1611
41.2.1	TLV type.....	1611
41.2.2	TLV information string length.....	1612
41.2.3	Status.....	1612
41.2.4	VSI Type ID (VTID).....	1613
41.2.5	VSI Type Version.....	1613
41.2.6	VSIID format.....	1613
41.2.7	VSIID.....	1613
41.2.8	Filter Info format.....	1614
41.2.9	Filter Info field.....	1614
41.2.10	VDP TLV type and Status semantics.....	1617
41.3	Organizationally defined TLV definitions.....	1618
41.3.1	TLV type.....	1618
41.3.2	TLV information string length.....	1618
41.3.3	Organizationally unique identifier (OUI) or Company ID (CID).....	1618

41.3.4	Organizational information	1618
41.4	Validation rules for VDP TLVs	1618
41.5	VDP state machines	1619
41.5.1	State machine conventions	1619
41.5.2	Bridge VDP state machine	1619
41.5.3	Station VDP state machine	1620
41.5.4	VDP state machine timers	1621
41.5.5	VDP state machine variables and parameters	1621
41.5.6	Command-Response TLV field references in state machines	1624
41.5.7	VDP state machine procedures	1624
42.	S-Channel Discovery and Configuration Protocol (CDCP)	1626
42.1	CDCP discovery and configuration	1626
42.2	CDCP state machine overview	1626
42.3	CDCP configuration state machine	1627
42.4	CDCP configuration variables	1629
42.4.1	AdminChnCap	1629
42.4.2	AdminRole	1629
42.4.3	AdminSVIDWants	1629
42.4.4	LastLocalSVIDPool	1629
42.4.5	LastRemoteSVIDList	1629
42.4.6	LastSVIDWants	1629
42.4.7	LocalSVIDPool	1629
42.4.8	OperChnCap	1629
42.4.9	OperRole	1630
42.4.10	OperSVIDList	1630
42.4.11	RemoteChnCap	1630
42.4.12	RemoteRole	1630
42.4.13	RemoteSVIDList	1630
42.4.14	schState	1630
42.5	CDCP configuration procedures	1630
42.5.1	SetSVIDRequest (OperRole, AdminSVIDWants, OperSVIDList)	1630
42.5.2	RxSVIDConfig (OperSVIDList, LastRemoteSVIDList)	1631
42.5.3	TxSVIDConfig (OperChnCap, RemoteChnCap, LastLocalSVIDPool, RemoteSVIDList, OperSVIDList)	1631
43.	Edge Control Protocol (ECP)	1632
43.1	ECP operation	1632
43.2	Edge Control Sublayer Service (ECSS)	1633
43.3	ECP state machines	1633
43.3.1	State machine conventions	1633
43.3.2	Overview	1633
43.3.3	Edge Control Protocol Data Unit (ECPDU)	1634
43.3.4	ECP transmit state machine	1635
43.3.5	ECP receive state machine	1636
43.3.6	ECP state machine timers	1636
43.3.7	ECP state machine variables and parameters	1637
43.3.8	ECP state machine procedures	1638
44.	Equal Cost Multiple Paths (ECMP)	1639
44.1	SPBM ECMP	1639
44.1.1	ECMP Operation	1639

44.1.2	ECMP ECT Algorithm	1640
44.1.3	Loop prevention for ECMP	1642
44.2	Support for Flow Filtering	1642
44.2.1	Flow filtering tag (F-TAG)	1643
44.2.2	F-TAG processing	1644
44.2.3	Forwarding process extension for flow filtering	1645
44.2.4	TTL Loop mitigation	1646
44.2.5	CFM for ECMP with flow filtering	1646
44.2.6	Operation with selective support for flow filtering	1648
45.	Path Control and Reservation (PCR)	1649
45.1	Explicit trees	1649
45.1.1	Tree structures	1653
45.1.2	Explicit ECT Algorithms	1654
45.1.3	ISIS-PCR VLAN configuration	1656
45.1.4	Use of VIDs for strict explicit trees	1660
45.1.5	MAC addresses and ISIS-PCR	1661
45.1.6	Filtering Database entries for explicit trees	1661
45.1.7	ISIS-PCR support	1662
45.1.8	Attributes for path computation	1662
45.1.9	Topology sub-TLV	1664
45.1.10	Hop sub-TLV	1667
45.1.11	Administrative Group sub-TLV	1670
45.1.12	Bandwidth Constraint sub-TLV	1670
45.2	Reservation	1671
45.2.1	Bandwidth Assignment sub-TLV	1671
45.2.2	Timestamp sub-TLV	1673
45.2.3	Precedence ordering	1673
45.3	Redundancy	1673
45.3.1	Loop-free alternates for unicast data flows	1674
45.3.2	Static redundant trees	1674
45.3.3	Maximally Redundant Trees (MRTs)	1675
45.3.4	MRTs with centralized GADAG computation	1678
Annex A (normative)	PICS proforma—Bridge implementations	1682
Annex B (normative)	PICS proforma—End station implementations	1748
Annex C (normative)	Designated MSRP Node (DMN) Implementations	1763
Annex D (normative)	IEEE 802.1 Organizationally Specific TLVs	1780
Annex E (normative)	Notational conventions used in state diagrams	1896
Annex F (informative)	Shared and Independent VLAN Learning (SVL and IVL)	1898
Annex G (informative)	MAC method-dependent aspects of VLAN support.....	1907
Annex H (informative)	Interoperability considerations.....	1911
Annex I (informative)	Priority and drop precedence.....	1917
Annex J (informative)	CFM protocol design and use.....	1925

Annex K (informative) TPMR use cases	1933
Annex L (informative) Operation of the credit-based shaper algorithm	1938
Annex M (normative) Support for PFC in link layers without MAC Control	1955
Annex N (informative) Buffer requirements for PFC	1956
Annex O (informative) Preserving the integrity of FCS fields in MAC Bridges	1961
Annex P (informative) Frame duplication and misordering	1968
Annex Q (informative) Traffic scheduling	1971
Annex R (informative) Preemption and IEEE 802.1AE MAC Security	1975
Annex S (informative) Preemption and scheduled traffic	1977
Annex T (informative) Cyclic queuing and forwarding	1980
Annex U (informative) Bibliography	1988

Figures

Figure 6-1—Internal organization of the MAC sublayer	128
Figure 6-2—Provider Instance Ports (PIPs)	146
Figure 6-3—B-Component CBP	149
Figure 6-4—Example of operation of Port-and-Protocol-based classification	153
Figure 6-5—Service access priority selection	155
Figure 6-6—Two back-to-back EISS Multiplex Entities	161
Figure 6-7—Two back-to-back Backbone Service Instance Multiplex Entities	162
Figure 6-8—Backbone Service Instance Multiplex Entities with example CFM shims	163
Figure 6-9—Two back-to-back Up and Down TESI Multiplex Entities	165
Figure 6-10—Supporting the ISS with signaled priority	167
Figure 6-11—Two back-to-back Up and Down Infrastructure Segment Multiplex Entities	168
Figure 7-1—VLAN Bridging overview	170
Figure 8-1—A Bridged Network	176
Figure 8-2—VLAN Bridge architecture	178
Figure 8-3—MAC Bridge architecture	179
Figure 8-4—Relaying MAC frames	181
Figure 8-5—Observation of network traffic	181
Figure 8-6—Operation of Spanning Tree Protocol Entity	182
Figure 8-7—Operation of MRP	182
Figure 8-8—Management Port transmission and reception	183
Figure 8-9—Infrastructure Segment MEP placement in a PNP	183
Figure 8-10—Bridge Port Transmit and Receive	186
Figure 8-11—TPMR Port Transmit and Receive	186
Figure 8-12—Forwarding process functions	188
Figure 8-13—Per-stream filtering and policing	194
Figure 8-14—Transmission selection with gates	203
Figure 8-15—Scheduled traffic state machines—overview and relationships	206
Figure 8-16—Cycle Timer state machine	206
Figure 8-17—List Execute state machine	208
Figure 8-18—List Config state machine	209
Figure 8-19—Logical points of attachment of the Higher Layer and Relay Entities	238
Figure 8-20—Effect of control information on the forwarding path	238
Figure 8-21—Per-Port points of attachment	239
Figure 8-22—Single point of attachment—relay permitted	239
Figure 8-23—Single point of attachment—relay not permitted	240
Figure 8-24—Effect of Port State	240
Figure 8-25—Controlled and Uncontrolled Port connectivity	241
Figure 8-26—Ingress/egress control information in the forwarding path	241
Figure 9-1—VLAN TCI format	246
Figure 9-2—I-TAG TCI format	247
Figure 10-1—Example—Attribute value propagation from one station	250
Figure 10-2—Example—Attribute value propagation from two stations	251
Figure 10-3—Example—Registrations as pointers to the sources of declarations	251
Figure 10-4—MRP architecture	253
Figure 10-5—Format of the major components of an MRPDU	276
Figure 10-6—Operation of MMRP for a single VLAN Context	282
Figure 10-7—Example Directed Graph	283
Figure 10-8—Example of MMRP propagation in a VLAN Context	285
Figure 11-1—Operation of MVRP	293
Figure 12-1—Relationships among CFM managed objects	354
Figure 12-2—Relationship among BEB managed objects	371

Figure 12-3—SPB managed objects (MOs)	425
Figure 12-4—Relationships among EVB Bridge managed objects	441
Figure 12-5—Relationship among EVB station managed objects	442
Figure 12-6—Timing points for scheduled traffic	458
Figure 12-7—Timing points for PSFP	465
Figure 13-1—Diagrammatic conventions for spanning tree topologies	472
Figure 13-2—Physical topology and active topology	473
Figure 13-3—Port Roles and Port States	473
Figure 13-4—A Backup Port	474
Figure 13-5—“Ring Backbone” example	474
Figure 13-6—An MST Bridge network	476
Figure 13-7—CIST Priority Vectors, Port Roles, and MST Regions	477
Figure 13-8—MSTI Active Topology in Region 2	478
Figure 13-9—CIST and MSTI active topologies in Region 1 of the example network	491
Figure 13-10—Agreements and Proposals	495
Figure 13-11—CIST and MSTI Active Topologies in Region 2 of Figure 13-6	496
Figure 13-12—Enhanced Agreements	497
Figure 13-13—Spanning tree protocol state machines—overview and relationships	508
Figure 13-14—MSTP overview notation	509
Figure 13-15—Port Timers state machine	539
Figure 13-16—Port Receive state machine	539
Figure 13-17—Port Protocol Migration state machine	540
Figure 13-18—Bridge Detection state machine	540
Figure 13-19—Port Transmit state machine	541
Figure 13-20—Port Information state machine	542
Figure 13-21—Port Role Selection state machine	543
Figure 13-22—Disabled Port role transitions	544
Figure 13-23—Port Role Transitions state machine—MasterPort	545
Figure 13-24—Port Role Transitions state machine—RootPort	546
Figure 13-25—Port Role Transitions state machine—DesignatedPort	547
Figure 13-26—Port Role Transitions state machine—AlternatePort and BackupPort	548
Figure 13-27—Port State Transition state machine	548
Figure 13-28—Topology Change state machine	550
Figure 13-29—L2 Gateway Port Receive state machine	551
Figure 14-1—RST, MST, SPT, and STP Configuration BPDU format	555
Figure 14-2—STP TCN BPDU format	555
Figure 14-3—MSTI Configuration Message parameters and format	560
Figure 15-1—Internal organization of the MAC sublayer in a PBN	563
Figure 15-2—Port-based service interface to a PBN	564
Figure 15-3—Port-based service interface to a PBN	565
Figure 15-4—C-tagged service interface to a PBN	565
Figure 15-5—C-tagged service interface to a PBN	565
Figure 15-6—Customer Edge Ports (CEPs)	566
Figure 15-7—S-tagged service interface to a PBN	566
Figure 15-8—S-tagged interface to a PBN	567
Figure 15-9—RCSIs to a PBN	567
Figure 15-10—Remote Customer Access Ports (RCAPs)	568
Figure 15-11—C-tagged RCSI to a PBN	569
Figure 15-12—Port-based RCSI to a PBN	569
Figure 15-13—Provider Network Port (PNP) interface	570
Figure 16-1—PBN with interface examples	573
Figure 16-2—Examples of remote customer service access via a second PBN	575
Figure 16-3—Access service separation and “Hairpin Switching”	576
Figure 17-1—C-VLAN component internal LAN managed system	638

Figure 17-2—I/B-component internal LAN managed system	643
Figure 18-1—One Maintenance Domain: operator’s view	1222
Figure 18-2—One service instance: operator’s view	1223
Figure 18-3—One service instance: customer’s view	1223
Figure 18-4—MEP and MIP Symbols	1224
Figure 18-5—MAs: one service instance in a provider network	1225
Figure 18-6—MAs: Expansion of Figure 18-5	1226
Figure 18-7—MEPs, MIPs, and MD Levels	1227
Figure 19-1—CFM Protocol shims	1228
Figure 19-2—MA Endpoint (MEP)	1231
Figure 19-3—MIP Half Function (MHF)	1237
Figure 19-4—LOM shim	1239
Figure 19-5—LOM architecture	1239
Figure 20-1—MEP state machines—overview and relationships	1252
Figure 20-2—MEP Continuity Check Initiator state machine	1259
Figure 20-3—MHF Continuity Check Receiver state machine	1260
Figure 20-4—MEP Continuity Check Receiver state machine	1264
Figure 20-5—Remote MEP state machine	1266
Figure 20-6—Remote MEP Error state machine	1267
Figure 20-7—MEP Cross Connect state machine	1268
Figure 20-8—MEP Traffic Field Mismatch state machine	1270
Figure 20-9—MEP Local Mismatch state machine	1270
Figure 20-10—MP Loopback Responder state machine	1272
Figure 20-11—MEP Loopback Initiator transmit state machine	1275
Figure 20-12—MEP Loopback Initiator receive state machine	1276
Figure 20-13—MEP Fault Notification Generator state machine	1278
Figure 20-14—MEP Mismatch Fault Notification Generator state machine	1280
Figure 20-15—MEP Linktrace Initiator receive state machine	1285
Figure 20-16—Linktrace Responder, MEPs, MHFs, and LOMs	1287
Figure 20-17—LTM Receiver state machine	1292
Figure 20-18—LTR Transmitter state machine	1293
Figure 22-1—MEPs and MIPs distinguished by VID (incomplete picture)	1324
Figure 22-2—Alternate view of Forwarding process	1325
Figure 22-3—Combining per-VLAN MPs into two shims	1326
Figure 22-4—More complete picture of MP placement in a Bridge Port	1327
Figure 22-5—Service instance spanning two Bridges protected by Up MPs	1329
Figure 22-6—Service instance spanning two Bridges protected by Down MPs	1329
Figure 22-7—MP placement in a non-VLAN-aware Bridge Port	1331
Figure 22-8—MP placement relative to other standards	1332
Figure 22-9—Creating MEPs and MIPs	1335
Figure 22-10—CFM in a Provider Edge Bridge C-tagged service interface	1341
Figure 22-11—CFM in a Provider Edge Bridge C-tagged RCSI	1343
Figure 22-12—Up MEPs in a Management Port	1344
Figure 22-13—CFM in the enterprise environment	1345
Figure 22-14—CFM on a Bridge that implements IEEE Std 802.1Q-2005	1346
Figure 23-1—TPMR connecting two Bridge Ports	1347
Figure 23-2—TPMR chain connecting Bridge Ports	1347
Figure 23-3—MSSs and the MSPE	1349
Figure 23-4—Adding connectivity	1351
Figure 23-5—Losing connectivity	1352
Figure 23-6—TPMR recovery	1353
Figure 23-7—Notification from one end of the link to the other	1354
Figure 23-8—Immediate MAC status notification at the end of a link	1354
Figure 23-9—MSPE state machine overview	1355

Figure 23-10—Status Transition state machine (STM)	1359
Figure 23-11—Status Notification state machine (SNM)	1360
Figure 23-12—MSPDU structure	1362
Figure 25-1—Internal organization of the MAC sublayer in a PBBN	1366
Figure 25-2—PBB terminology	1367
Figure 25-3—Customer service interface types	1368
Figure 25-4—Port-based service interface	1369
Figure 25-5—Port-based interface equipment	1370
Figure 25-6—Encapsulated service frames at ISS	1371
Figure 25-7—S-tagged service interface	1371
Figure 25-8—S-tagged service interface equipment	1372
Figure 25-9—I-tagged service interface	1373
Figure 25-10—I-tagged service interface equipment	1373
Figure 25-11—S-tagged and Port-based service interface access classifications	1376
Figure 25-12—I-tagged service interface access protection classifications	1377
Figure 25-13—Internal organization of the MAC sublayer in a PBB-TE Region	1379
Figure 25-14—PBB-TE Region	1381
Figure 25-15—Transparent service interface	1383
Figure 25-16—Transparent service interface equipment	1383
Figure 26-1—PBBN example	1385
Figure 26-2—CFM shim model	1392
Figure 26-3—CFM example applied to a Port-based and S-tagged service interface	1393
Figure 26-4—CFM example applied to an I-tagged Service Interface	1394
Figure 26-5—CFM example applied to a hierarchal E-NNI, CBP-PIP Demarc	1395
Figure 26-6—CFM example applied to a peer E-NNI, CBP-PIP	1396
Figure 26-7—Independent ESPs using the same ESP-DAs and ESP-VIDs	1400
Figure 26-8—PBB-TE MEP placement in a CBP	1401
Figure 26-9—Independent Infrastructure Segments distinguished by SMP-SA	1404
Figure 26-10—Infrastructure Segment MEP placement in a PNP	1405
Figure 26-11—Protection switching architecture	1406
Figure 26-12—PBB-TE point-to-point protection switching	1408
Figure 26-13—Mapping data traffic to the protection entity	1409
Figure 26-14—Relationships of the Protection switching state machines—overview	1410
Figure 26-15—Hold-off state machine	1414
Figure 26-16—Clear Manual Switch state machine	1414
Figure 26-17—Service Mapping state machine	1415
Figure 26-18—Segment terminology and properties	1416
Figure 26-19—Infrastructure Segment monitoring	1417
Figure 26-20—Working Segment and Protection Segment	1417
Figure 26-21—Nested IPGs	1418
Figure 26-22—IPS Control entity	1420
Figure 26-23—M:1 IPS	1422
Figure 26-24—M:1 IPS state machines	1423
Figure 26-25—M:1 Hold-off state machine	1426
Figure 26-26—Protection Segment Selection state machine	1427
Figure 27-1—Configuring VLAN support in an SPT Region (example)	1434
Figure 27-2—SPBM group MAC address—general format	1445
Figure 27-3—SPBM group MAC addresses—source rooted SPT	1446
Figure 27-4—SPBM group MAC addresses—shared tree	1446
Figure 27-5—SPBM MEP placement in a CBP	1449
Figure 27-6—SPBV campus network example	1451
Figure 27-7—SPT Bridge Network using SPBM example	1453
Figure 28-1—Agreement Digest field format	1458
Figure 28-2—MT-Capability TLV	1468

Figure 28-3—SPB MCID sub-TLV	1468
Figure 28-4—SPB Digest sub-TLV	1469
Figure 28-5—SPB Base VLAN-Identifiers sub-TLV	1470
Figure 28-6—SPB Instance sub-TLV	1471
Figure 28-7—SPB Instance Opaque ECT-ALGORITHM sub-TLV	1473
Figure 28-8—ECMP ECT-ALGORITHM sub-TLV	1474
Figure 28-9—SPB Link Metric sub-TLV	1474
Figure 28-10—SPB Adjacency Opaque ECT-ALGORITHM sub-TLV	1475
Figure 28-11—SPBV MAC Address sub-TLV	1476
Figure 28-12—SPBM Service Identifier and Unicast Address sub-TLV	1477
Figure 29-1—Forward path test (FPT)	1481
Figure 29-2—Return path test (RPT)	1482
Figure 29-3—Combination of FPT and RPT	1483
Figure 29-4—Detailed functions of RR	1484
Figure 29-5—RFM Receiver on an non-MP	1487
Figure 29-6—Return Path DR	1488
Figure 29-7—RR Filter state machine	1493
Figure 29-8—RR Encapsulation state machine	1494
Figure 29-9—RR Transmit state machine	1494
Figure 29-10—RFM Receiver state machine	1496
Figure 29-11—Decapsulator Responder state machine	1498
Figure 30-1—Congestion detection in QCN CP	1505
Figure 30-2—Sampling (reflection) probability in QCN CP as a function of $ Fb $	1505
Figure 30-3—QCN RP operation	1506
Figure 30-4—Byte Counter and Timer interaction with Rate Limiter	1508
Figure 30-5—CP-RP peering in VLAN Bridged Network	1510
Figure 30-6—CP-RP peering in PBBN	1511
Figure 31-1—CPs and congestion-aware queues in a Bridge	1512
Figure 31-2—Congestion-aware queue functions in an end station	1514
Figure 31-3—Per-CNPV station function	1516
Figure 32-1—CND defense state machine	1529
Figure 32-2—RP rate control state machine	1541
Figure 32-3—CP-RP peering in any hierarchical Bridged Network	1542
Figure 34-1—Queuing model for a Talker station	1553
Figure 35-1—Operation of MSRP	1556
Figure 35-2—Format of the components of the reservation FirstValue fields	1566
Figure 35-3—Format of the components of the Domain FirstValue	1571
Figure 36-1—PFC peering	1583
Figure 36-2—PFC Receiver state diagram for priority n	1585
Figure 36-3—PFC-aware system queue functions	1587
Figure 36-4—PFC-aware system queue functions with Link Aggregation	1588
Figure 38-1—DCBX Asymmetric state machine	1593
Figure 38-2—Symmetric state machine	1594
Figure 39-1—Operation of MIRP in an I-component	1596
Figure 39-2—Operation of MIRP in a B-component	1596
Figure 39-3—Alternate model for MIRP in a B-component	1601
Figure 40-1—EVB architecture overview	1603
Figure 40-2—EVB architecture without S-channels	1605
Figure 40-3—EVB architecture with S-channel	1605
Figure 40-4—EVB components and internal LANs with S-channels	1606
Figure 40-5—EVB architecture without S-channels, with EVB Bridge S-VLAN component	1608
Figure 40-6—EVB architecture without S-channels, with EVB station S-VLAN component	1608
Figure 41-1—VSI manager ID TLV	1610
Figure 41-2—VDP association TLV	1611

Figure 41-3—VID Filter Info format	1615
Figure 41-4—MAC/VID filter format	1615
Figure 41-5—GroupID/VID filter format	1616
Figure 41-6—GroupID/MAC/VID filter format	1616
Figure 41-7—Organizationally defined TLV	1618
Figure 41-8—Bridge VDP state machine	1619
Figure 41-9—Station VDP state machine	1620
Figure 42-1—CDCP state machine—Station role	1627
Figure 42-2—CDCP state machine—Bridge role	1628
Figure 43-1—Example ECP exchange	1632
Figure 43-2—ECPDU structure	1634
Figure 43-3—ECP transmit state machine	1635
Figure 43-4—ECP receive state machine	1636
Figure 44-1—Flow FilteringTCI format	1643
Figure 44-2—SPBM VID MEP and ECMP path MEP placement in a CBP	1647
Figure 45-1—An SPT Region controlled by a single PCE	1650
Figure 45-2—An SPT Region controlled by multiple PCEs	1651
Figure 45-3—The use of the SPB Instance sub-TLV for MRT	1659
Figure 45-4—Shared Risk Link Group (SRLG) TLV	1663
Figure 45-5—Topology sub-TLV	1664
Figure 45-6—A strict tree and its descriptor Topology sub-TLV	1665
Figure 45-7—Topology sub-TLV of a loose tree	1666
Figure 45-8—Hop sub-TLV	1667
Figure 45-9—Administrative Group sub-TLV	1670
Figure 45-10—Bandwidth Constraint sub-TLV	1671
Figure 45-11—Bandwidth Assignment sub-TLV	1672
Figure 45-12—Timestamp sub-TLV	1673
Figure 45-13—A GADAG and its descriptor Topology sub-TLV	1679
Figure 45-14—MRT-Blue and MRT-Red for MRT Root 55	1679
Figure 45-15—A GADAG for a topology with multiple blocks	1680
Figure C-1—CSN backbone	1763
Figure C-2—Bridge’s CSN model for bandwidth reservation	1764
Figure C-3—Talker MSRPDU flow	1765
Figure C-4—Listener MSRPDU flow	1765
Figure C-5—IEEE DMN Device Attribute IE	1767
Figure C-6—DMN Confirmation Transaction	1769
Figure C-7—Bandwidth reservation—bridge model for IEEE 802.11 BSS (STA downstream Port)	1772
Figure C-8—Bandwidth reservation—bridge model for IEEE 802.11 BSS (STA upstream Port)	1772
Figure C-9—Bandwidth reservation—bridge model for IEEE 802.11 BSS (direct link setup)	1773
Figure C-10—MSRP/IEEE 802.11 query flows	1773
Figure C-11—MSRP/802.11 Talker STA to Listener STA reservation flows	1774
Figure C-12—MSRP/802.11 “Bridged” Listener to Talker STA reservation flows	1775
Figure C-13—MSRP/802.11 Listener STA to “Bridged” Talker reservation flows	1775
Figure D-1—Port VLAN ID TLV format	1781
Figure D-2—Port And Protocol VLAN ID TLV format	1781
Figure D-3—VLAN Name TLV format	1782
Figure D-4—Protocol Identity TLV format	1783
Figure D-5—VID Usage Digest TLV format	1784
Figure D-6—Management VID TLV format	1784
Figure D-7—Congestion Notification TLV format	1785
Figure D-8—ETS Configuration TLV format	1786
Figure D-9—ETS Recommendation TLV format	1788
Figure D-10—Priority-based Flow Control Configuration TLV format	1789
Figure D-11—Application Priority TLV format	1790

Figure D-12—EVB TLV format	1792
Figure D-13—CDCP TLV structure	1795
Figure D-14—Application VLAN TLV format	1797
Figure F-1—Connecting independent VLANs—1	1899
Figure F-2—Connecting independent VLANs—2	1900
Figure F-3—Duplicate MAC addresses	1900
Figure F-4—Asymmetric VID use: “multi-netted server”	1901
Figure F-5—Asymmetric VLAN use: “Rooted-Multipoint”	1903
Figure F-6—Rooted-Multipoint with tagged interfaces	1904
Figure F-7—SPBV VLAN Shared Learning and VID Translation	1905
Figure G-1— Example of IEEE 802.3 MAC frame format.....	1907
Figure G-2—Methods for Bridge access to IEEE 802.11 and PMPN media: example	1910
Figure H-1—Static filtering inconsistency	1913
Figure H-2—Interoperability with MAC Bridges: example 1	1914
Figure H-3—Interoperability with MAC Bridges: example 2	1915
Figure H-4—Interoperability between Port-based and Port-and-Protocol-based classification	1916
Figure J-1—Up MPs in a CFM Port	1930
Figure K-1—TPMR as UNI demarcation device	1933
Figure K-2—TPMRs with aggregated links	1934
Figure K-3—Multiple TPMRs	1934
Figure K-4—Recovery at the end of a chain	1935
Figure K-5—Near simultaneous recoveries	1936
Figure K-6—Near simultaneous failure and recovery	1936
Figure K-7—Loss with quick recovery	1937
Figure L-1—Credit-based shaper operation—no conflicting traffic	1940
Figure L-2—Credit-based shaper operation—conflicting traffic	1941
Figure L-3—Credit-based shaper operation—burst traffic	1942
Figure L-4—Interference and latency	1946
Figure L-5—Burst behavior and credit	1946
Figure L-6—Fan-in scenario	1950
Figure L-7—Permanent delay scenario	1951
Figure L-8—Building up buffer occupancy—1	1952
Figure L-9—Building up buffer occupancy—2	1952
Figure L-10—Building up buffer occupancy—3	1952
Figure L-11—Building up buffer occupancy—4	1953
Figure M-1—PFC PDU format	1955
Figure N-1—PFC delays	1956
Figure N-2—Delay model	1957
Figure N-3—Worst-case delay	1958
Figure O-1—Converting a CRC to an FCS	1963
Figure O-2—Detection Lossless Circuit	1963
Figure O-3—Field change adjustment	1965
Figure O-4—Field insertion adjustment	1966
Figure P-1—Frame duplication scenario	1969
Figure P-2—Frame misordering scenario	1970
Figure Q-1—Establishing a guard band	1972
Figure Q-2—Using gate operations	1973
Figure T-1—Example PSFP configuration for QCF	1983
Figure T-2—Traffic scheduling example for CQF	1984
Figure T-3—Example PSFP configuration with two values of T	1985
Figure T-4—Traffic scheduling example with two values of T	1985
Figure T-5—Interleaving example—factor of 2	1986

Tables

Table 6-1—Bridge transit delay	135
Table 6-2—Priority Code Point encoding	143
Table 6-3—Priority Code Point decoding	143
Table 6-4—Priority regeneration	144
Table 6-5—Default SRP domain boundary port priority regeneration override values	145
Table 6-6—Service Access Priority	156
Table 6-7—Encapsulated Addresses EtherType	163
Table 8-1—C-VLAN and MAC Bridge component Reserved addresses	191
Table 8-2—S-VLAN component Reserved addresses	192
Table 8-3—TPMR component Reserved addresses	192
Table 8-4—Stream gate control operations	197
Table 8-5—Recommended priority to traffic class mappings	198
Table 8-6—Transmission selection algorithm identifiers	200
Table 8-7—Gate operations	204
Table 8-8—Scheduled Traffic and PSFP procedures/variables	213
Table 8-9—Ageing time parameter value	216
Table 8-10—Combining Static and Dynamic Filtering Entries for an individual MAC address	226
Table 8-11—Combining Static Filtering Entry and MAC Address Registration Entry for “All Group Addresses” and “All Unregistered Group Addresses”	227
Table 8-12—Forwarding or Filtering for specific group MAC addresses	228
Table 8-13—Forwarding or Filtering with Dynamic Reservation Entries	229
Table 8-14—Determination of whether a Port is in a VID’s member set	229
Table 8-15—Standard LLC address assignment	234
Table 8-16—ISIS-SPB reserved addresses	236
Table 8-17—ISIS-SPB Recommended Address Usage	236
Table 8-18—CCM group destination MAC addresses	243
Table 8-19—LTM group destination MAC addresses	243
Table 9-1—IEEE 802.1Q™ EtherType allocations	246
Table 9-2—Reserved VID values	246
Table 9-3—Reserved I-SID values	248
Table 10-1—MRP application addresses	256
Table 10-2—MRP EtherType values	257
Table 10-3—Applicant state table	270
Table 10-4—Registrar state table	271
Table 10-5—LeaveAll state table	272
Table 10-6—PeriodicTransmission state table	272
Table 10-7—MRP timer parameter values	273
Table 12-1—Component table entry managed object	304
Table 12-2—Port table entry	306
Table 12-3—ISS Port Number table entry	307
Table 12-4—Bandwidth Availability Parameter Table row elements	411
Table 12-5—Transmission Selection Algorithm Table row elements	412
Table 12-6—Priority Regeneration Override Table row elements	412
Table 12-7—CN component managed object row elements	413
Table 12-8—CN component priority managed object row elements	414
Table 12-9—CN Port priority managed object row elements	415
Table 12-10—Congestion Point managed object row elements	415
Table 12-11—Reaction Point port priority managed object row elements	416
Table 12-12—Reaction Point group managed object row elements	416
Table 12-13—SRP Bridge Base Table row elements	417
Table 12-14—SRP Bridge Port Table row elements	418

Table 12-15—SRP Latency Parameter Table row elements	418
Table 12-16—SRP Stream Table row elements	418
Table 12-17—SRP Reservations Table row elements	419
Table 12-18—Priority-based Flow Control objects	420
Table 12-19—EVB system base table	444
Table 12-20—EVB system parameter defaults	445
Table 12-21—SBP table entry	446
Table 12-22—VSI table entry	446
Table 12-23—VSI MAC/VLAN table entry	447
Table 12-24—UAP table entry	448
Table 12-25—UAP table entry parameters	449
Table 12-26—S-channel interface table entry	449
Table 12-27—URP table entry	450
Table 12-28—ECP table entry	451
Table 12-29—The Gate Parameter Table	456
Table 12-30—Frame Preemption Parameter table	459
Table 12-31—The Stream Parameter Table	461
Table 12-32—Stream Filter Instance Table	461
Table 12-33—The Stream Gate Instance Table	463
Table 12-34—The Flow Meter Instance Table	466
Table 13-1—Configuration Digest Signature Key	482
Table 13-2—Sample Configuration Digest Signature Keys	483
Table 13-3—Bridge and Port Priority values	501
Table 13-4—Port Path Cost values	502
Table 13-5—Timer and related parameter values	510
Table 17-1—Structure of the MIB modules	579
Table 17-2—IEEE8021-TC-MIB structure	581
Table 17-3—IEEE8021-BRIDGE-MIB structure and relationship to IETF RFC 4188 and this standard	582
Table 17-4—IEEE 802.1D objects not in the IEEE8021-BRIDGE-MIB	586
Table 17-5—IEEE8021-SPANNING-TREE MIB structure and relationship to IETF RFC 4318 and this standard	586
Table 17-6—Clause 12 objects not in the IEEE8021-SPANNING-TREE MIB	588
Table 17-7—IEEE8021-QBRIDGE MIB structure and relationship to IETF RFC 4363 and this standard	589
Table 17-8—Clause 12 management not in IEEE8021-Q-BRIDGE-MIB	594
Table 17-9—IEEE8021-PB-MIB structure and relationship to this standard	594
Table 17-10—IEEE8021-MSTP-MIB structure and relationship to this standard	596
Table 17-11—IEEE8021-CFM-MIB correspondence between variables, managed objects, and MIB objects	599
Table 17-12—IEEE8021-CFM-V2-MIB correspondence between variables, managed objects, and MIB objects	603
Table 17-13—IEEE8021-PBB-MIB structure and relationship to this standard	605
Table 17-14—IEEE8021-DDCFM-MIB structure and relationship to this standard	608
Table 17-15—IEEE8021-PBBTE-MIB Structure and relationship to this standard	610
Table 17-16—Example of ieee8021PbbTeTeSiEspTable	611
Table 17-17—IEEE8021-TPMR-MIB Structure and relationship to this standard	613
Table 17-18—FQTSS MIB structure and object cross reference	614
Table 17-19—Variables, managed object tables, and MIB objects	615
Table 17-20—SRP MIB structure and object cross reference	617
Table 17-21—IEEE8021-MVRPX-MIB structure and relationship to this standard	619
Table 17-22—IEEE8021-MIRP-MIB structure and relationship to this standard	619
Table 17-23—Variables, managed object tables, and MIB objects	620
Table 17-24—IEEE8021-TEIPS MIB structure and relationship to this standard	620

Table 17-25—IEEE8021-SPB-MIB structure and relationship to this standard	622
Table 17-26—EVB MIB structure and object cross reference	626
Table 17-27—IEEE8021-ECMP-MIB structure and relationship to this standard	630
Table 17-28—IEEE8021-ST-MIB structure and relationship to this standard	631
Table 17-29—IEEE8021-Preemption-MIB Structure and relationship to this standard	632
Table 17-30—IEEE8021-PSFP-MIB Structure and relationship to this standard	633
Table 17-31—PBB-TE required MIB compliances	644
Table 17-32—Sensitive managed objects: tables and notifications	652
Table 17-33—Sensitive managed objects: variables in dot1agCfmMdTable	652
Table 17-34—Sensitive managed objects (of DDCFM): tables and notifications	654
Table 17-35—Sensitive managed objects (of DDCFM) for read	654
Table 17-36—Sensitive managed objects (of EVB): tables and notifications	661
Table 17-37—Sensitive managed objects (of EVB) for read	661
Table 17-38—Provider Bridge service interface parameters	677
Table 17-39—PBB service interface parameters	681
Table 19-1—Actions taken by MP OpCode Demultiplexers	1233
Table 19-2—SAP use for LTMs and LTRs	1240
Table 20-1—Fault Alarm defects and priorities	1245
Table 20-2—Deriving enableRmepDefect and Port Status TLV in a Bridge	1255
Table 21-1—CFM PDU Encapsulation EtherType	1299
Table 21-2—Common CFM Header format	1301
Table 21-3—OpCode Field range assignments	1301
Table 21-4—TLV format	1302
Table 21-5—Type Field values	1302
Table 21-6—Organization-Specific TLV format	1303
Table 21-7—Sender ID TLV format	1304
Table 21-8—Port Status TLV format	1306
Table 21-9—Port Status TLV values	1306
Table 21-10—Interface Status TLV format	1306
Table 21-11—Interface Status TLV values	1306
Table 21-12—Data TLV format	1307
Table 21-13—End TLV format	1307
Table 21-14—CCM format	1308
Table 21-15—CCM Interval field encoding	1309
Table 21-16—CCM Maintenance Association Identifier field format: Maintenance Domain present	1310
Table 21-17—CCM Maintenance Association Identifier field format: Maintenance Domain not present	1310
Table 21-18—Maintenance Domain Name Format	1311
Table 21-19—Short MA Name Format	1312
Table 21-20—LBM and LBR formats	1313
Table 21-21—PBB-TE MIP TLV format	1314
Table 21-22—LTM format	1315
Table 21-23—LTM Flags field	1315
Table 21-24—LTM Egress Identifier TLV format	1317
Table 21-25—LTR format	1317
Table 21-26—LTR Flags field	1317
Table 21-27—Relay Action field values	1318
Table 21-28—LTR Egress Identifier TLV format	1319
Table 21-29—Reply Ingress TLV format	1319
Table 21-30—Ingress Action field values	1320
Table 21-31—Reply Egress TLV format	1321
Table 21-32—Egress Action field values	1321
Table 22-1—MEP creation	1335
Table 22-2—MIP creation	1336

Table 22-3—Bandwidth required for CCMs for 1 MA	1339
Table 22-4—Bandwidth required for CCMs for 1000 MAs	1340
Table 23-1—Time sequence diagram symbols	1350
Table 23-2—MSP performance parameters	1356
Table 23-3—MSP EtherType assignment	1362
Table 23-4—MSP Packet Types	1363
Table 24-1—Transmission and reception delays	1365
Table 26-1—Backbone Service Instance Group address OUI	1388
Table 26-2—Protection Requests Hierarchy	1411
Table 27-1—Allocation of VIDs to FIDs and FIDs to MSTIDs in an SPT Region (example)	1434
Table 28-1—Bridge Priority Masking	1463
Table 29-1—RFM format	1499
Table 29-2—SFM format	1500
Table 32-1—LLDP instance selection managed object overrides	1522
Table 32-2—CND defense mode selection managed object overrides	1522
Table 32-3—Determining cnpdIsAdminDefMode and cnpdDefenseMode	1528
Table 32-4—Correspondence of QCN and CCF message fields	1530
Table 32-5—NewCpSampleBase() return value as a function of cpFb	1533
Table 33-1—CN-TAG Encapsulation	1545
Table 33-2—CNM Encapsulation	1545
Table 33-3—Congestion Notification Message PDU	1546
Table 34-1—Recommended priority to traffic class mappings for SR classes A and B	1552
Table 34-2—Recommended priority to traffic class mappings for SR class B only	1552
Table 35-1—AttributeType Values	1563
Table 35-2—AttributeLength Values	1563
Table 35-3—FourPackedEvent Values	1564
Table 35-4—MSRP FirstValue NumberOfValues example	1565
Table 35-5—TSpec components examples	1568
Table 35-6—Reservation Failure Codes	1570
Table 35-7—SR class ID	1572
Table 35-8—Summary of Talker primitives	1573
Table 35-9—Summary of Listener primitives	1574
Table 35-10—Talker attribute propagation per port	1578
Table 35-11—Incoming Listener attribute propagation per port	1579
Table 35-12—Updating Dynamic Reservation Entries	1580
Table 35-13—Updating operIdleSlope(N)	1580
Table 35-14—Listener Declaration Type Summation	1580
Table 41-1—VDP TLV types	1611
Table 41-2—Flag values in VDP requests	1612
Table 41-3—Error types in VDP responses	1612
Table 41-4—Flag values in VDP responses	1613
Table 41-5—VSIID format values	1613
Table 41-6—Filter Info format values	1614
Table 43-1—ECP subtypes	1634
Table 44-1—ECMP ECT-ALGORITHM values	1642
Table 44-2—F-TAG EtherType	1643
Table 45-1—ECT-ALGORITHM values for explicit trees	1654
Table 45-2—Bridge Priority Masking for the LT and LTS ECT Algorithms	1655
Table 45-3—Hop sub-TLV flags	1668
Table C-1—SRP to MoCA PQoS Transaction mapping	1770
Table C-2—SRP TSpec to MoCA TSPEC mapping	1771
Table C-3—SRP StreamID to MoCA PQoS Flow transaction mapping	1771
Table C-4—SRP to MLME QoS Services mapping	1777
Table C-5—EDCA-AC for AV Streams	1778

Table C-6—HCCA for AV Streams	1779
Table D-1—IEEE 802.1 Organizationally Specific TLVs	1780
Table D-2—Port and protocol capability/status	1782
Table D-3—Priority assignment table	1786
Table D-4—Traffic class bandwidth assignment table	1787
Table D-5—TSA Assignment Table	1787
Table D-6—PFC Enable bit vector	1790
Table D-7—Application Priority Table Entry format	1791
Table D-8—Sel field values	1791
Table D-9—RRSAT flag values and meanings	1793
Table D-10—EVB Mode values	1794
Table D-11—Application VLAN Table Entry format	1797
Table D-12—Sel field values	1798
Table D-13—IEEE 802.1 extension MIB object group conformance requirements	1803
Table D-14—IEEE 802.1/LLDP extension MIB object cross reference	1804
Table E-1—State machine symbols	1897
Table I-1—Traffic type to traffic class mapping	1918
Table I-2—Traffic type acronyms	1920
Table I-3—Defining traffic types	1921
Table I-4—Defining traffic types—Credit-based shaper support of SR class B only	1922
Table I-5—Defining traffic types—Credit-based shaper support of SR classes A and B	1922
Table I-6—Priority Code Point encoding	1924
Table I-7—Priority Code Point decoding	1924
Table J-1—Provider MD Level allocation	1926
Table J-2—IEEE / ITU-T terminology differences	1926
Table N-1—IEEE 802.3 Interface Delays	1959