

ISO 12647-6:2020 (E)

Graphic technology — Process control for the production of half-tone colour separations, proofs and production prints — Part 6: Flexographic printing

Contents

| | |
|---------|---|
| | Foreword |
| | Introduction |
| 1 | Scope |
| 2 | Normative references |
| 3 | Terms and definitions |
| 4 | Requirements |
| 4.1 | General |
| 4.2 | Material input requirements |
| 4.2.1 | General |
| 4.2.2 | Distortion correction |
| 4.2.3 | Proof requirements |
| 4.2.4 | Digital data files |
| 4.2.5 | Film/printing forme requirements |
| 4.2.5.1 | Colour separations |
| 4.2.5.2 | Printing forme digital (laser ablative mask or thermal imaging layer) |
| 4.2.5.3 | Film |
| 4.2.5.4 | Printing forme verification for delivery |
| 4.2.5.5 | Image size tolerance (film or printing forme) |
| 4.3 | Printing aims |
| 4.3.1 | General |
| 4.3.2 | Halftoning parameters |
| 4.3.2.1 | General |
| 4.3.2.2 | Screen frequency |
| 4.3.2.3 | Screen angle |
| 4.3.2.4 | Dot shape and its relationship to tone value |
| 4.3.2.5 | Tone value sum of the printing forme |
| 4.3.2.6 | Tone value reproduction limits |
| 4.3.3 | Print substrates |
| 4.3.4 | Ink set colours |
| 4.3.5 | Reproducibility of ink colour set |
| 4.3.6 | Ink set gloss |
| 4.3.7 | Tolerance for image positioning |
| 4.3.8 | Tone value increase (TVI) |
| 4.3.9 | Reproducibility of printing |
| 5 | Communication |
| Annex A | (normative) Communication of spot colour data |
| Annex B | (informative) Information exchange |
| Annex C | (informative) Determination of quality parameters of half-tone dots on a colour separation film |
| C.1 | Microline target |
| C.2 | Scanning microdensitometer |