

ISO/IEC 11574:2000-03 (E)

Information technology — Telecommunications and information exchange between systems — Private Integrated Services Network — Circuit-mode 64 kbit/s bearer services — Service description, functional capabilities and information flows

Contents	Page
Foreword	vi
Introduction	vii
Section 1: General	1
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 Symbols and abbreviations	2
5 Provision of services by a PISN	3
5.1 Bearer services	3
5.2 Teleservices	3
5.3 Control and signalling	4
5.4 Interworking considerations	4
5.5 Service model	4
Section 2: Service Description (stage 1 description)	5
6 Circuit-mode 64 kbit/s unrestricted 8 kHz structured bearer service category	5
6.1 Definition	5
6.2 Description	5
6.3 Procedures	6
6.4 Network capability for charging	6
6.5 Interworking considerations	6
6.5.1 Interworking with a public ISDN and certain other digital networks	6
6.5.2 Interworking with networks supporting only a restricted digital information transfer capability	6
6.5.3 Interworking with analogue networks	6
6.6 Static Description: Service Attributes	6
7 Circuit-mode 64 kbit/s 8 kHz structured bearer service category usable for speech information transfer	7
7.1 Definition	7
7.2 Description	7
7.3 Procedures	7
7.4 Network capability for charging	7
7.5 Interworking considerations	7
7.5.1 Interworking with a public ISDN and certain other digital networks	7
7.5.2 Interworking with analogue networks	7
7.5.3 Encoding law conversion	7
7.6 Static Description: Service Attributes	8
8 Circuit-mode 64 kbit/s 8 kHz structured bearer service category usable for 3,1 kHz audio information transfer	8
8.1 Definition	8
8.2 Description	8
8.3 Procedures	9
8.4 Network capability for charging	9
8.5 Interworking considerations	9
8.5.1 Interworking with a public ISDN and certain other digital networks	9
8.5.2 Interworking with analogue networks	9
8.5.3 Encoding law conversion	9

8.6	Static Description: Service Attributes	9
9	Common procedures for services within a PISN	10
9.1	Provision of services	10
9.2	Normal procedures	10
9.2.1	Call establishment at the calling PISN user	10
9.2.2	Call establishment at the called PISN user	11
9.2.3	Terminating the service (call release)	11
9.3	Exceptional procedures / unsuccessful outcome	12
10	Interworking	13
10.1	General Interworking considerations	13
10.1.1	Incoming calls	13
10.1.2	Outgoing calls	13
10.1.3	PISN transit calls	13
10.2	Interworking with public-ISDN	13
10.2.1	Receipt of service request from a public ISDN	13
10.2.2	Sending a service request to a public ISDN	14
10.2.3	Receipt of a service response from public ISDN	14
10.2.4	Sending service response to public ISDN	14
11	Dynamic Description	14
Section 3: Functional capabilities and information flows (stage 2 description)		18
12	Functional model	18
12.1	Functional model description	18
12.2	Description of the functional entities	18
12.2.1	Call Control Agent functional entity	18
12.2.2	Call Control functional entity	19
13	Definition of information flows	20
13.1	Conventions used within the description of information flows	20
13.1.1	Convention for the description of mandatory or optional information	20
13.1.2	Convention for the naming of information flows	21
13.2	SETUP	22
13.3	REPORT	25
13.4	CHANNEL_ACKNOWLEDGE	26
13.5	CHANNEL_CONNECT	26
13.6	DISCONNECT	26
13.7	RELEASE	27
13.8	INFORMATION	27
13.9	SETUP_REJECT	27
13.10	PROCEEDING	28
14	Information flow sequences	28
14.1	Functional entity actions	28
14.1.1	Originating CCA functional entity	28
14.1.2	Originating CC functional entity	29
14.1.3	Transit CC functional entity	30
14.1.4	Destination CC functional entity	31
14.1.5	Destination CCA functional entity	32
14.1.6	Incoming gateway CC functional entity	33
14.1.7	Outgoing gateway CC functional entity	34

14.2	Normal call establishment	36
14.3	Normal call establishment with digit-by-digit sending and automatic answer	37
14.4	Unsuccessful calls with the provision of tones and announcements	38
14.5	Unsuccessful calls without the provision of tones and announcements	39
14.6	Incoming interworking with a non-ISDN	40
14.7	Outgoing interworking with a non-ISDN	41
14.8	Outgoing interworking with digit-by-digit sending	42
14.9	Basic call clearing	43
14.10	Incoming interworking with a public ISDN	44
14.11	Outgoing interworking with a public ISDN	45
15	SDL diagrams for functional entities	46
15.1	Originating CCA functional entity SDL diagrams	46
15.1.1	Originating CCA states used in SDL diagrams	46
15.1.2	Originating CCA SDL diagrams	47
15.2	Originating CC functional entity SDL diagrams	51
15.2.1	Originating CC states used in SDL diagrams	51
15.2.2	Originating CC SDL diagrams	52
15.3	Transit CC functional entity SDL diagrams	59
15.3.1	Transit CC states used in SDL diagrams	59
15.3.2	Transit CC SDL diagrams	60
15.4	Destination CC functional entity SDL diagrams	65
15.4.1	Destination CC states used in SDL diagrams	65
15.4.2	Destination CC SDL diagrams	66
15.5	Destination CCA functional entity SDL diagrams	73
15.5.1	Destination CCA states used in SDL diagrams	73
15.5.2	Destination CCA SDL diagrams	73
16	Allocation of functional entities to physical entities	77
Annex A	(normative) Service attributes	78
Annex B	(normative) Teleservices	79
Annex C	(informative) Bibliography	81
Annex D	(informative) Errors in ISO/IEC 11574 1st edition	82