

ISO/IEC 18046-3:2020 (E)

Information technology — Radio frequency identification device performance test methods — Part 3: Test methods for tag performance

Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	Symbols and abbreviated terms
4.1	Symbols
4.2	Abbreviated terms
5	Conditions applicable to the test methods
5.1	Number of tags to be tested
5.2	Test environment
5.3	RF environment
5.4	Pre-conditioning
5.5	Default tolerance
5.6	Total measurement uncertainty
5.7	Test result reporting
5.8	Test mounting material
5.9	Test communication parameters
5.10	Test equipment limitations
5.11	Human exposure to EMF
6	Setup of test equipment for tag test
6.1	Test apparatus and test circuits for ISO/IEC 18000-2 tags
6.2	Test apparatus and test circuits for ISO/IEC 18000-3 tags
6.3	Test apparatus and test circuits for ISO/IEC 18000-61, ISO/IEC 18000-62, ISO/IEC 18000-63 and ISO/IEC 18000-64 tags
6.3.1	Propagative UHF tags measurement
6.3.1.1	General
6.3.1.2	Setup of the devices
6.3.1.3	DUT placement
6.3.1.4	Antenna polarization and requirements
6.3.1.5	Test setup for interference rejection measurements of propagative UHF tags
6.3.2	Inductive UHF tags measurement
6.4	Test apparatus and test circuits for ISO/IEC 18000-7 tags
7	Functional tests for inductive tags as defined in ISO/IEC 18000-2 and ISO/IEC 18000-3, ISO/IEC 18000-61, ISO/IEC 18000-62, ISO/IEC 18000-63 and ISO/IEC 18000-64
7.1	Identification magnetic field threshold (HTHR Identification)
7.1.1	Purpose
7.1.2	Test procedure
7.1.2.1	General
7.1.2.2	ISO/IEC 18000-2 tags
7.1.2.3	ISO/IEC 18000-3 tags
7.1.2.4	ISO/IEC 18000-61, ISO/IEC 18000-62, ISO/IEC 18000-63 and ISO/IEC 18000-64 tags
7.2	Reading magnetic field threshold (HTHR Read)
7.2.1	Purpose
7.2.2	Test procedure

- 7.2.2.1 General
 - 7.2.2.2 ISO/IEC 18000-2 tags
 - 7.2.2.3 ISO/IEC 18000-3 tags
 - 7.2.3 Test report
 - 7.3 Writing magnetic field threshold (HTHR Write)
 - 7.3.1 Purpose
 - 7.3.2 Test procedure
 - 7.3.2.1 General
 - 7.3.2.2 ISO/IEC 18000-2 tags
 - 7.3.2.3 ISO/IEC 18000-3 tags
 - 7.4 Maximum operating magnetic field (HMax)
 - 7.4.1 Purpose
 - 7.4.2 Test procedure
 - 7.5 Survival magnetic field (HSurvival)
 - 7.5.1 Purpose
 - 7.5.2 Test procedure
 - 7.6 Load modulation (LM)
 - 7.6.1 Purpose
 - 7.6.2 Test procedure
 - 7.6.2.1 General
 - 7.6.2.2 ISO/IEC 18000-2 tags
 - 7.6.2.3 ISO/IEC 18000-3 tags
 - 7.7 Optional resonant frequency and Q factor measurement for inductive tag
 - 7.7.1 Purpose
 - 7.7.2 Test procedure
- 8 Functional tests for propagative tags as defined in ISO/IEC 18000-61, ISO/IEC 18000-62, ISO/IEC 18000-63 and ISO/IEC 18000-64
- 8.1 Minimum power operation threshold (PMin) for identification, read and write
 - 8.1.1 Purpose
 - 8.1.2 Test procedure
 - 8.1.3 Test report
 - 8.2 Sensitivity degradation (SDegradation)
 - 8.2.1 Purpose
 - 8.2.2 Test procedure
 - 8.2.3 Test report
 - 8.3 Maximum operating power of tag (PMax)
 - 8.3.1 Purpose
 - 8.3.2 Test procedure
 - 8.3.3 Test report
 - 8.4 Survival electromagnetic power of tag (PSurvial)
 - 8.4.1 Purpose
 - 8.4.2 Test procedure
 - 8.4.3 Test report
 - 8.5 Interference rejection (IRejection)
 - 8.5.1 Purpose
 - 8.5.2 Test procedure
 - 8.5.2.1 General
 - 8.5.2.2 Continuous wave (CW) interference rejection
 - 8.5.2.3 Modulated interference rejection
 - 8.5.3 Test report
 - 8.6 Maximum fade rate (PMin,Fade)
 - 8.6.1 Purpose
 - 8.6.2 Test procedure
 - 8.6.3 Test report
- 9 Functional tests for 433,920 MHz propagative tags as defined in ISO/IEC 18000-7
- 9.1 Identification electromagnetic field threshold (ETHR Identification) and frequency tolerance
 - 9.1.1 Purpose
 - 9.1.2 Test procedure
 - 9.1.3 Test report
 - 9.2 Reading electromagnetic field threshold (ETHR Read) and frequency tolerance
 - 9.2.1 Purpose

- 9.2.2 Test procedure
- 9.2.3 Test report
- 9.3 Writing electromagnetic field threshold (ETHR Write)
- 9.3.1 Purpose
- 9.3.2 Test procedure
- 9.3.3 Test report
- 9.4 Sensitivity Directivity (SDirectivity)
- 9.4.1 Purpose
- 9.4.2 Test procedure
- 9.4.3 Test report
- 9.5 Interference rejection (IRejection)
- 9.5.1 Purpose
- 9.5.2 Test procedure
- 9.5.2.1 General
- 9.5.2.2 Unmodulated interference rejection:
- 9.5.2.3 Modulated interference rejection
- 9.5.3 Test report
- 9.6 Maximum operating electromagnetic field (EMax)
- 9.6.1 Purpose
- 9.6.2 Test procedure
- 9.6.3 Test report
- 9.7 Survival electromagnetic field (ESurvival)
- 9.7.1 Purpose
- 9.7.2 Test procedure
- 9.7.3 Test report

Annex A (informative) Resonant frequency and Q factor measurement for inductive tag

- A.1 Purpose
- A.2 Test for ISO/IEC 18000-2 tags
- A.2.1 Test procedure
- A.2.2 Test report
- A.3 Test for ISO/IEC 18000-3 tags
- A.3.1 Test apparatus for ISO/IEC 18000-3
- A.3.2 Test procedure
- A.3.3 Test report

Annex B (normative) Test apparatus modification for ISO/IEC 18000-3 tags for field strengths >5 A/m

- B.1 Purpose
- B.2 Details

Annex C (normative) Test apparatus modification for ISO/IEC 18000-61, ISO/IEC 18000-62, ISO/IEC 18000-63 and ISO/IEC 18000-64 tags

- C.1 Purpose
- C.2 Antenna for UHF inductive tags
- C.3 Pad detail and matching network
- C.4 Enclosure and mounting
- C.5 Measurement range

Annex D (informative) Inventory command for all parts of ISO/IEC 18000

- D.1 ISO/IEC 18000-2
- D.2 ISO/IEC 18000-3

Annex E (normative) Backscatter power measurement