

ISO/IEC TR 23008-13:2020 (E)

Information technology — High efficiency coding and media delivery in heterogeneous environments — Part 13: MMT implementation guidance

Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	General overview of MPEG media transport
4.1	System overview
4.2	Tools specified in ISO/IEC 23008-1
5	MMT function deployments
5.1	General
5.2	Object reconstruction
5.2.1	General
5.2.2	Recovery in MPU mode
5.2.3	Recovery in GFD mode
5.3	Default assets
5.4	Low-delay live streaming
5.5	Parallel processing in MMT sending and receiving entities
5.5.1	Processing in MMT sending entity
5.5.2	Processing in MMT receiving entity
5.6	MPU streaming for live services
5.6.1	MPU packetization
5.6.1.1	MPU fragment building block
5.6.1.2	MMT broadcast sending procedure for low latency
5.6.1.2.1	General
5.6.1.2.2	The MPU sending procedure
5.6.1.2.3	Signalling message sending procedure
5.6.2	Sending of MPU and signalling message
5.6.3	MPU generation for SHVC-encoded video in real-time streaming
5.6.3.1	General
5.6.3.2	MPU generating method for timed media with multi-layered video
5.6.3.3	Resolution-switching scenario
5.7	Fast MMT session acquisition
5.8	Referencing and processing non-timed data
5.8.1	General
5.8.2	Resource grouping and referencing
5.8.3	Receiver handling
5.9	Media adaptation for quality control in MMTP
5.9.1	General
5.9.2	Parameters for media adaptation
5.9.3	Adaptation operation of MMT entity
5.10	Hybrid delivery in MMT
5.10.1	General
5.10.2	Classification of hybrid delivery
5.10.3	Technical elements for hybrid delivery
5.11	Example of detailed implementation of MMT
5.11.1	Use case: Combination of MMT and MPEG-2 TS for synchronized presentation
5.11.1.1	MMT asset information

- 5.11.1.2 Information on temporal relationships among media components
 - 5.11.2 Use case: Combination of MMT and HTTP streaming for synchronized decoding
 - 5.11.2.1 Asset information
 - 5.11.2.2 Information on spatial relationships among media components
 - 5.11.3 Use case: Content request in advance for synchronized play-out
 - 5.11.3.1 Application scenarios
 - 5.11.3.2 Content request procedure for synchronized play-out (see Figure 21)
 - 5.12 HRBM signalling for hybrid delivery
 - 5.12.1 Hybrid delivery from the single MMT sending entity
 - 5.12.2 Hybrid delivery from the multiple MMT sending entities
 - 5.13 Error resilience in MMT protocol
 - 5.14 Delay constrained ARQ
 - 5.14.1 General
 - 5.14.2 Delivery-time constrained ARQ
 - 5.14.3 Arrival-deadline constrained ARQ
 - 5.14.3.1 Basic operation of the arrival-deadline constrained ARQ
 - 5.14.3.2 Example of calculating arrival-deadline
 - 5.15 Delivery of encrypted MPUs
 - 5.16 HRBM message updating
 - 5.16.1 General
 - 5.16.2 HRBM message sending schedule
 - 5.16.3 Use case
 - 5.16.4 HRBM buffer operation in unicast environment
 - 5.17 MMTP packet with padded data
 - 5.18 Constraints on signalling splicing points
 - 5.18.1 General
 - 5.18.2 Constraints on Case 1 – Asset change at the start of MPU
 - 5.18.3 Constraints on Case 2 – Asset change at a point in MPU
 - 5.18.4 Signal the splicing point for target assets in Case 1 and Case 2
- 6 Use cases for MMT deployment**
- 6.1 General
 - 6.2 Delivery of DASH presentations using MMT
 - 6.2.1 General
 - 6.2.2 Delivery of the MPD
 - 6.2.3 Delivery of the data segments
 - 6.2.3.1 Delivery using the MPU mode
 - 6.2.3.2 Delivery using the GFD mode
 - 6.3 Client operation for DASH service delivered through MMT protocol
 - 6.3.1 Delivery of MPD with MMTP
 - 6.3.2 Delivery and consumption of DASH segments with MMTP
 - 6.3.2.1 Reconstruction of DASH segments
 - 6.3.2.1.1 Use of GFD mode
 - 6.3.2.1.2 Use of MPU mode
 - 6.3.2.2 Consumption of DASH segments
 - 6.3.2.2.1 Client with HTTP cache
 - 6.3.2.2.2 Client without HTTP cache
 - 6.4 Hybrid of MMT and DASH over heterogeneous network
 - 6.5 MMT caching for effective bandwidth utilization
 - 6.5.1 Overview of MMT caching middlebox architecture
 - 6.5.2 Content-based caching of MMT media
 - 6.5.2.1 Content-based caching
 - 6.5.2.2 Caching unit
 - 6.5.2.3 MPU ID (chunk ID) generation
 - 6.5.2.3.1 General
 - 6.5.2.3.2 MPU with timed media
 - 6.5.2.3.3 MPU with non-timed media
 - 6.5.3 MPU sync protocol between server and caching middlebox
 - 6.5.3.1 General
 - 6.5.3.2 Protocol overview
 - 6.5.3.3 Request messages
 - 6.5.3.3.1 General
 - 6.5.3.3.2 X-CIRequest
 - 6.5.3.3.3 X-HTMLRequest

- 6.5.3.3.4 X-MPUIRange
- 6.5.3.3.5 X-MPURequest
- 6.5.3.3.6 X-MPUHeaderRequest
- 6.5.3.4 Response messages (see Table 2)
- 6.5.3.4.1 General
- 6.5.3.4.2 X-MPUIRange
- 6.5.3.4.3 X-MPUHeader
- 6.5.3.4.4 X-MPUContent
- 6.5.4 MMT cache manifest
- 6.6 Usage of ADC signalling message
- 6.6.1 General
- 6.6.2 Operation in MMT sending entity
- 6.6.3 Operation in MANE router
- 6.6.4 Example operation in MMT-receiving entities
- 6.6.5 QoE multiplexing gain and bottleneck coordination
- 6.7 MMT deployment in Japanese broadcasting systems
- 6.7.1 General
- 6.7.2 Broadcasting systems using MMT
- 6.7.2.1 System structure
- 6.7.2.2 Service configuration in a broadcasting channel
- 6.7.2.3 Service configuration in broadcasting channels and broadband networks
- 6.7.3 Media transport protocol
- 6.7.3.1 General
- 6.7.3.2 Header extension of MMTP packets
- 6.7.3.3 Encapsulation of multimedia data
- 6.7.3.3.1 General
- 6.7.3.3.2 Encapsulation of video data
- 6.7.3.3.2.1 MFU format for HEVC stream
- 6.7.3.3.2.2 Encapsulation of HEVC bitstream subsets
- 6.7.3.3.2.3 Clean random access of HEVC bitstream (for SAP Type 3)
- 6.7.3.3.2.4 Fast random access of HEVC bitstream (for SAP Types 2 and 3)
- 6.7.3.3.3 Encapsulation of audio data: MFU format for MPEG-4 AAC and MPEG-4 ALS
- 6.7.4 Signalling information
- 6.7.4.1 General
- 6.7.4.2 MMT signalling information messages
- 6.7.4.2.1 List of MMT-signalling information messages
- 6.7.4.2.2 Detailed specifications of messages
- 6.7.4.2.2.1 PA message
- 6.7.4.2.2.2 M2section message
- 6.7.4.3 MMT signalling information tables
- 6.7.4.3.1 List of MMT-signalling information tables
- 6.7.4.3.2 Detailed specifications of tables
- 6.7.4.3.2.1 MMT package table
- 6.7.4.3.2.2 package list table
- 6.7.4.4 MMT signalling information descriptors
- 6.7.4.4.1 List of MMT-signalling information descriptors
- 6.7.4.4.2 Detailed specifications of descriptors
- 6.7.4.4.2.1 MPU Timestamp descriptor
- 6.7.4.4.2.2 Dependency descriptor
- 6.7.4.5 Packet identification
- 6.7.4.6 Signalling information in ARIB systems
- 6.7.5 Start-up procedure of broadcasting service
- 6.7.6 Actual packet structure
- 6.7.6.1 Structure of MMTP packet
- 6.7.6.2 Structure of MP table
- 6.7.6.3 MMT/TLV packet structure
- 6.7.6.4 Captured packet
- 6.8 MMT deployment in ATSC 3.0 systems
- 6.9 Implementation of MMT based on D-TMB in China
- 6.9.1 Background
- 6.9.2 MMT over legacy DTMB infrastructure
- 6.9.3 Use cases
- 6.9.3.1 Synchronized and personalized presentation of multi-view
- 6.9.3.2 Seamless switching between multiple networks

- 6.10 Conversion of MMTP stream to MPEG-2 TS
 - 6.10.1 Overview of conversion operation
 - 6.10.2 Restrictions to MMTP packets
 - 6.10.3 Calculation of PTS, DTS
 - 6.10.4 Restriction related to MPEG-2 T-STD
 - 6.10.5 Packet field conversion rule
 - 6.10.6 PSI Conversion rule
 - 6.10.6.1 Comparison of content model
 - 6.10.6.2 Handling of program specific information
 - 6.11 MMT service provisioning at conventional broadcast environment
 - 6.12 Usage of multimedia configuration for interface switching management
 - 6.13 MMT signalling for multiple timed text assets
 - 6.13.1 Multiple timed text assets within an MMT presentation
 - 6.13.2 Selective spatial assignment for multiple timed text assets
 - 6.13.3 Example of multiple timed text assets signalling in MMT
 - 6.13.4 Carriage of TTML based timed text in MMT
 - 6.13.4.1 General
 - 6.13.4.2 MPU encapsulation of TTML based timed text
 - 6.13.4.3 Metadata signalling for TTML timed text contained MMT Assets
 - 6.14 Viewport-dependent baseline media profile with packed streaming for VR
- 7 Application layer forward error correction (AL-FEC)
 - 7.1 FEC decoding method for ssvg_mode2
 - 7.1.1 General
 - 7.1.2 Source symbol block format for ssvg_mode2
 - 7.1.3 Regionalization of source symbol Block for FEC decoding
 - 7.1.4 How to choose a proper unit of data for FEC decoding
 - 7.2 Usage of two stage FEC coding structure
 - 7.2.1 General
 - 7.2.2 Use case: Hybrid content delivery
 - 7.2.3 Use case: Streaming multicasting (or broadcasting) to two different end-user groups which is under two different channel conditions each other
 - 7.3 Usage of layer-aware FEC coding structure
 - 7.3.1 General
 - 7.3.2 Use case 1: Layered multicast streaming
 - 7.3.3 Use case 2: Hybrid delivery
 - 7.3.4 Use case 3: Fast zapping with long time interleaving (LA-FEC UI)
 - 7.3.5 Use case 4: Prioritized transmission
 - 7.4 MPU mapping to source packet block
 - 7.4.1 General
 - 7.4.2 Aligned MPU mapping method to source packet block
 - 7.5 FEC for hybrid service
 - 7.6 Usage of rate-adaptive AL-FEC
 - 7.6.1 General
 - 7.6.2 AL-FEC rate control
 - 7.6.2.1 General
 - 7.6.2.2 QoS-related feedback messages
 - 7.6.2.3 AL-FEC configuration information
 - 7.6.2.4 Procedure of rate control
 - 7.7 FEC scheme for interleaved source symbol block
 - 7.7.1 General
 - 7.7.2 Re-order buffer for interleaved source symbol block
- 8 MMT developments in mobile environments
 - 8.1 True realtime video streaming over a lossy channel
 - 8.1.1 General
 - 8.1.2 Main features
 - 8.1.3 Ring buffer in the client
 - 8.1.4 FEC/deFEC performance and delay
 - 8.1.5 Characteristics of UDP based multi-path and multi-session transmitting for true real-time video streaming
 - 8.1.5.1 Multi-path (multi-interface MPUDP)
 - 8.1.5.2 Single path (multi-session UDP)
 - 8.1.5.3 Analysis

8.2	Dynamic asset change
8.3	Media adaptation for quality control
8.3.1	Use cases of QoS management for adaptive video service
8.3.1.1	Use case 1: Adaptation in MMT aware network entity (MANE)
8.3.1.1.1	System architecture
8.3.1.1.2	Scenario description
8.3.1.1.3	Sequence diagram (see Figure 99)
8.3.1.1.4	Usage of MMT parameter (see Table 27)
8.3.1.2	Use case 2: Adaptation in server
8.3.1.2.1	System architecture (see Figure 100)
8.3.1.2.2	Scenario description
8.3.1.2.3	Sequence diagram (see Figure 101)
8.3.1.2.4	Usage of MMT parameter (see Table 28)
8.3.2	Advanced adaptation operation of MMT entity: selective transmission
8.3.2.1	General
8.3.2.2	The baseline logic of advanced adaptation logic: 1-depth
8.3.2.3	Advanced MMT adaptation operation of MANE
8.3.2.4	QoE improvement with advanced MMT adaptation over TCP
8.4	Transition time decision using MTR and MTN
8.5	Usage of DRI and DSI message
8.5.1	Overview
8.5.2	Operation in MMT sending entity or MANE
8.5.3	Operation in MMT receiving entity
8.6	Usage of dynamic media resource identification information update
8.6.1	General
8.6.2	Classification of dynamic media resource allocation
8.6.3	Operation in MMT sending entity
8.6.4	Operation in MMT receiving entity
8.6.5	Example operation in MANE proxy
8.7	MMT service list
8.8	Usage of DNS message for MMT URL resolution
8.8.1	General
8.8.2	Example on DNS resolution procedure
8.9	Usage of guide information for dynamic media resource allocation
8.9.1	General
8.9.2	Classification of guide information
8.9.3	Classification of dynamic media resource allocation
8.9.4	Operation in MANEs
8.9.5	Operation in MMT sending entity
8.9.6	Example of dynamic media resource allocation using guide information
8.10	Usage of DARI for supporting DNS in MMT
8.10.1	General
8.10.2	Classification of DARI proxy
8.10.3	Operation in MANE DNS or DNS
8.10.4	Operation in DARI proxy
8.10.5	Relation between the media resource identification in MMT and DNS message