

ISO/IEC TR 23008-13:2020 (E)

Information technology — High efficiency coding and media delivery in heterogeneous environments — Part 13: MMT implementation guidance

Contents

| | |
|-----------|--|
| | Foreword |
| | Introduction |
| 1 | Scope |
| 2 | Normative references |
| 3 | Terms and definitions |
| 4 | General overview of MPEG media transport |
| 4.1 | System overview |
| 4.2 | Tools specified in ISO/IEC 23008-1 |
| 5 | MMT function deployments |
| 5.1 | General |
| 5.2 | Object reconstruction |
| 5.2.1 | General |
| 5.2.2 | Recovery in MPU mode |
| 5.2.3 | Recovery in GFD mode |
| 5.3 | Default assets |
| 5.4 | Low-delay live streaming |
| 5.5 | Parallel processing in MMT sending and receiving entities |
| 5.5.1 | Processing in MMT sending entity |
| 5.5.2 | Processing in MMT receiving entity |
| 5.6 | MPU streaming for live services |
| 5.6.1 | MPU packetization |
| 5.6.1.1 | MPU fragment building block |
| 5.6.1.2 | MMT broadcast sending procedure for low latency |
| 5.6.1.2.1 | General |
| 5.6.1.2.2 | The MPU sending procedure |
| 5.6.1.2.3 | Signalling message sending procedure |
| 5.6.2 | Sending of MPU and signalling message |
| 5.6.3 | MPU generation for SHVC-encoded video in real-time streaming |
| 5.6.3.1 | General |
| 5.6.3.2 | MPU generating method for timed media with multi-layered video |
| 5.6.3.3 | Resolution-switching scenario |
| 5.7 | Fast MMT session acquisition |
| 5.8 | Referencing and processing non-timed data |
| 5.8.1 | General |
| 5.8.2 | Resource grouping and referencing |
| 5.8.3 | Receiver handling |
| 5.9 | Media adaptation for quality control in MMTP |
| 5.9.1 | General |
| 5.9.2 | Parameters for media adaptation |
| 5.9.3 | Adaptation operation of MMT entity |
| 5.10 | Hybrid delivery in MMT |
| 5.10.1 | General |
| 5.10.2 | Classification of hybrid delivery |
| 5.10.3 | Technical elements for hybrid delivery |
| 5.11 | Example of detailed implementation of MMT |
| 5.11.1 | Use case: Combination of MMT and MPEG-2 TS for synchronized presentation |
| 5.11.1.1 | MMT asset information |

- 5.11.1.2 Information on temporal relationships among media components
 - 5.11.2 Use case: Combination of MMT and HTTP streaming for synchronized decoding
 - 5.11.2.1 Asset information
 - 5.11.2.2 Information on spatial relationships among media components
 - 5.11.3 Use case: Content request in advance for synchronized play-out
 - 5.11.3.1 Application scenarios
 - 5.11.3.2 Content request procedure for synchronized play-out (see Figure 21)
 - 5.12 HRBM signalling for hybrid delivery
 - 5.12.1 Hybrid delivery from the single MMT sending entity
 - 5.12.2 Hybrid delivery from the multiple MMT sending entities
 - 5.13 Error resilience in MMT protocol
 - 5.14 Delay constrained ARQ
 - 5.14.1 General
 - 5.14.2 Delivery-time constrained ARQ
 - 5.14.3 Arrival-deadline constrained ARQ
 - 5.14.3.1 Basic operation of the arrival-deadline constrained ARQ
 - 5.14.3.2 Example of calculating arrival-deadline
 - 5.15 Delivery of encrypted MPUs
 - 5.16 HRBM message updating
 - 5.16.1 General
 - 5.16.2 HRBM message sending schedule
 - 5.16.3 Use case
 - 5.16.4 HRBM buffer operation in unicast environment
 - 5.17 MMTP packet with padded data
 - 5.18 Constraints on signalling splicing points
 - 5.18.1 General
 - 5.18.2 Constraints on Case 1 – Asset change at the start of MPU
 - 5.18.3 Constraints on Case 2 – Asset change at a point in MPU
 - 5.18.4 Signal the splicing point for target assets in Case 1 and Case 2
- 6 Use cases for MMT deployment**
- 6.1 General
 - 6.2 Delivery of DASH presentations using MMT
 - 6.2.1 General
 - 6.2.2 Delivery of the MPD
 - 6.2.3 Delivery of the data segments
 - 6.2.3.1 Delivery using the MPU mode
 - 6.2.3.2 Delivery using the GFD mode
 - 6.3 Client operation for DASH service delivered through MMT protocol
 - 6.3.1 Delivery of MPD with MMTP
 - 6.3.2 Delivery and consumption of DASH segments with MMTP
 - 6.3.2.1 Reconstruction of DASH segments
 - 6.3.2.1.1 Use of GFD mode
 - 6.3.2.1.2 Use of MPU mode
 - 6.3.2.2 Consumption of DASH segments
 - 6.3.2.2.1 Client with HTTP cache
 - 6.3.2.2.2 Client without HTTP cache
 - 6.4 Hybrid of MMT and DASH over heterogeneous network
 - 6.5 MMT caching for effective bandwidth utilization
 - 6.5.1 Overview of MMT caching middlebox architecture
 - 6.5.2 Content-based caching of MMT media
 - 6.5.2.1 Content-based caching
 - 6.5.2.2 Caching unit
 - 6.5.2.3 MPU ID (chunk ID) generation
 - 6.5.2.3.1 General
 - 6.5.2.3.2 MPU with timed media
 - 6.5.2.3.3 MPU with non-timed media
 - 6.5.3 MPU sync protocol between server and caching middlebox
 - 6.5.3.1 General
 - 6.5.3.2 Protocol overview
 - 6.5.3.3 Request messages
 - 6.5.3.3.1 General
 - 6.5.3.3.2 X-CIRequest
 - 6.5.3.3.3 X-HTMLRequest

- 6.5.3.3.4 X-MPUIRange
- 6.5.3.3.5 X-MPURequest
- 6.5.3.3.6 X-MPUHeaderRequest
- 6.5.3.4 Response messages (see Table 2)
- 6.5.3.4.1 General
- 6.5.3.4.2 X-MPUIRange
- 6.5.3.4.3 X-MPUHeader
- 6.5.3.4.4 X-MPUContent
- 6.5.4 MMT cache manifest
- 6.6 Usage of ADC signalling message
- 6.6.1 General
- 6.6.2 Operation in MMT sending entity
- 6.6.3 Operation in MANE router
- 6.6.4 Example operation in MMT-receiving entities
- 6.6.5 QoE multiplexing gain and bottleneck coordination
- 6.7 MMT deployment in Japanese broadcasting systems
- 6.7.1 General
- 6.7.2 Broadcasting systems using MMT
- 6.7.2.1 System structure
- 6.7.2.2 Service configuration in a broadcasting channel
- 6.7.2.3 Service configuration in broadcasting channels and broadband networks
- 6.7.3 Media transport protocol
- 6.7.3.1 General
- 6.7.3.2 Header extension of MMTP packets
- 6.7.3.3 Encapsulation of multimedia data
- 6.7.3.3.1 General
- 6.7.3.3.2 Encapsulation of video data
- 6.7.3.3.2.1 MFU format for HEVC stream
- 6.7.3.3.2.2 Encapsulation of HEVC bitstream subsets
- 6.7.3.3.2.3 Clean random access of HEVC bitstream (for SAP Type 3)
- 6.7.3.3.2.4 Fast random access of HEVC bitstream (for SAP Types 2 and 3)
- 6.7.3.3.3 Encapsulation of audio data: MFU format for MPEG-4 AAC and MPEG-4 ALS
- 6.7.4 Signalling information
- 6.7.4.1 General
- 6.7.4.2 MMT signalling information messages
- 6.7.4.2.1 List of MMT-signalling information messages
- 6.7.4.2.2 Detailed specifications of messages
- 6.7.4.2.2.1 PA message
- 6.7.4.2.2.2 M2section message
- 6.7.4.3 MMT signalling information tables
- 6.7.4.3.1 List of MMT-signalling information tables
- 6.7.4.3.2 Detailed specifications of tables
- 6.7.4.3.2.1 MMT package table
- 6.7.4.3.2.2 package list table
- 6.7.4.4 MMT signalling information descriptors
- 6.7.4.4.1 List of MMT-signalling information descriptors
- 6.7.4.4.2 Detailed specifications of descriptors
- 6.7.4.4.2.1 MPU Timestamp descriptor
- 6.7.4.4.2.2 Dependency descriptor
- 6.7.4.5 Packet identification
- 6.7.4.6 Signalling information in ARIB systems
- 6.7.5 Start-up procedure of broadcasting service
- 6.7.6 Actual packet structure
- 6.7.6.1 Structure of MMTP packet
- 6.7.6.2 Structure of MP table
- 6.7.6.3 MMT/TLV packet structure
- 6.7.6.4 Captured packet
- 6.8 MMT deployment in ATSC 3.0 systems
- 6.9 Implementation of MMT based on D-TMB in China
- 6.9.1 Background
- 6.9.2 MMT over legacy DTMB infrastructure
- 6.9.3 Use cases
- 6.9.3.1 Synchronized and personalized presentation of multi-view
- 6.9.3.2 Seamless switching between multiple networks

- 6.10 Conversion of MMTP stream to MPEG-2 TS
 - 6.10.1 Overview of conversion operation
 - 6.10.2 Restrictions to MMTP packets
 - 6.10.3 Calculation of PTS, DTS
 - 6.10.4 Restriction related to MPEG-2 T-STD
 - 6.10.5 Packet field conversion rule
 - 6.10.6 PSI Conversion rule
 - 6.10.6.1 Comparison of content model
 - 6.10.6.2 Handling of program specific information
 - 6.11 MMT service provisioning at conventional broadcast environment
 - 6.12 Usage of multimedia configuration for interface switching management
 - 6.13 MMT signalling for multiple timed text assets
 - 6.13.1 Multiple timed text assets within an MMT presentation
 - 6.13.2 Selective spatial assignment for multiple timed text assets
 - 6.13.3 Example of multiple timed text assets signalling in MMT
 - 6.13.4 Carriage of TTML based timed text in MMT
 - 6.13.4.1 General
 - 6.13.4.2 MPU encapsulation of TTML based timed text
 - 6.13.4.3 Metadata signalling for TTML timed text contained MMT Assets
 - 6.14 Viewport-dependent baseline media profile with packed streaming for VR
- 7 Application layer forward error correction (AL-FEC)
 - 7.1 FEC decoding method for ssvg_mode2
 - 7.1.1 General
 - 7.1.2 Source symbol block format for ssvg_mode2
 - 7.1.3 Regionalization of source symbol Block for FEC decoding
 - 7.1.4 How to choose a proper unit of data for FEC decoding
 - 7.2 Usage of two stage FEC coding structure
 - 7.2.1 General
 - 7.2.2 Use case: Hybrid content delivery
 - 7.2.3 Use case: Streaming multicasting (or broadcasting) to two different end-user groups which is under two different channel conditions each other
 - 7.3 Usage of layer-aware FEC coding structure
 - 7.3.1 General
 - 7.3.2 Use case 1: Layered multicast streaming
 - 7.3.3 Use case 2: Hybrid delivery
 - 7.3.4 Use case 3: Fast zapping with long time interleaving (LA-FEC UI)
 - 7.3.5 Use case 4: Prioritized transmission
 - 7.4 MPU mapping to source packet block
 - 7.4.1 General
 - 7.4.2 Aligned MPU mapping method to source packet block
 - 7.5 FEC for hybrid service
 - 7.6 Usage of rate-adaptive AL-FEC
 - 7.6.1 General
 - 7.6.2 AL-FEC rate control
 - 7.6.2.1 General
 - 7.6.2.2 QoS-related feedback messages
 - 7.6.2.3 AL-FEC configuration information
 - 7.6.2.4 Procedure of rate control
 - 7.7 FEC scheme for interleaved source symbol block
 - 7.7.1 General
 - 7.7.2 Re-order buffer for interleaved source symbol block
- 8 MMT developments in mobile environments
 - 8.1 True realtime video streaming over a lossy channel
 - 8.1.1 General
 - 8.1.2 Main features
 - 8.1.3 Ring buffer in the client
 - 8.1.4 FEC/deFEC performance and delay
 - 8.1.5 Characteristics of UDP based multi-path and multi-session transmitting for true real-time video streaming
 - 8.1.5.1 Multi-path (multi-interface MPUDP)
 - 8.1.5.2 Single path (multi-session UDP)
 - 8.1.5.3 Analysis

| | |
|-----------|---|
| 8.2 | Dynamic asset change |
| 8.3 | Media adaptation for quality control |
| 8.3.1 | Use cases of QoS management for adaptive video service |
| 8.3.1.1 | Use case 1: Adaptation in MMT aware network entity (MANE) |
| 8.3.1.1.1 | System architecture |
| 8.3.1.1.2 | Scenario description |
| 8.3.1.1.3 | Sequence diagram (see Figure 99) |
| 8.3.1.1.4 | Usage of MMT parameter (see Table 27) |
| 8.3.1.2 | Use case 2: Adaptation in server |
| 8.3.1.2.1 | System architecture (see Figure 100) |
| 8.3.1.2.2 | Scenario description |
| 8.3.1.2.3 | Sequence diagram (see Figure 101) |
| 8.3.1.2.4 | Usage of MMT parameter (see Table 28) |
| 8.3.2 | Advanced adaptation operation of MMT entity: selective transmission |
| 8.3.2.1 | General |
| 8.3.2.2 | The baseline logic of advanced adaptation logic: 1-depth |
| 8.3.2.3 | Advanced MMT adaptation operation of MANE |
| 8.3.2.4 | QoE improvement with advanced MMT adaptation over TCP |
| 8.4 | Transition time decision using MTR and MTN |
| 8.5 | Usage of DRI and DSI message |
| 8.5.1 | Overview |
| 8.5.2 | Operation in MMT sending entity or MANE |
| 8.5.3 | Operation in MMT receiving entity |
| 8.6 | Usage of dynamic media resource identification information update |
| 8.6.1 | General |
| 8.6.2 | Classification of dynamic media resource allocation |
| 8.6.3 | Operation in MMT sending entity |
| 8.6.4 | Operation in MMT receiving entity |
| 8.6.5 | Example operation in MANE proxy |
| 8.7 | MMT service list |
| 8.8 | Usage of DNS message for MMT URL resolution |
| 8.8.1 | General |
| 8.8.2 | Example on DNS resolution procedure |
| 8.9 | Usage of guide information for dynamic media resource allocation |
| 8.9.1 | General |
| 8.9.2 | Classification of guide information |
| 8.9.3 | Classification of dynamic media resource allocation |
| 8.9.4 | Operation in MANEs |
| 8.9.5 | Operation in MMT sending entity |
| 8.9.6 | Example of dynamic media resource allocation using guide information |
| 8.10 | Usage of DARI for supporting DNS in MMT |
| 8.10.1 | General |
| 8.10.2 | Classification of DARI proxy |
| 8.10.3 | Operation in MANE DNS or DNS |
| 8.10.4 | Operation in DARI proxy |
| 8.10.5 | Relation between the media resource identification in MMT and DNS message |