ISO/IEC 30190:2021 (E)

Information technology — Digitally recorded media for information interchange and storage — 120 mm Single Layer (25,0 Gbytes per disk) and Dual Layer (50,0 Gbytes per disk) BD Recordable disk

Contents

Foreword

Introduction

1 Scope

2 Normative references

3 Terms and definitions

4 Symbol and abbreviated terms

5 Conformance

5.1 Optical disk
5.2 Generating system
5.3 Receiving system
5.4 Compatibility statement

6 Conventions and notations

6.1 Levels of grouping
6.2 Representation of numbers
6.3 Integer calculus

7 General description of disk

8 General requirements

8.1 Environments
8.1.1 Test environment
8.1.1.1 General
8.1.1.2 Test conditions for sudden change in operating environment
8.1.2 Operating environment
8.1.3 Storage environment
8.1.3.1 General
8.1.3.2 Climate storage tests
8.1.4 Transportation
8.1.4.1 General
8.1.4.2 Packaging
8.1.4.2.1 General
8.1.4.2.2 Temperature and humidity
8.1.4.2.3 Impact loads and vibrations
8.2 Safety requirements
8.3 Flammability

9 Reference drive

9.1 General
9.2 Measurement conditions
9.3 Optical system
9.4 Optical beam
9.5 HF read channel
9.6 Radial PP read channel
9.7 Disk clamping
9.8 Rotation of disk and measurement velocity

9.9 Normalized servo transfer function
9.10 Measurement velocities and reference servos for axial tracking
9.10.1 General
9.10.2 Reference servo for axial tracking for 1x measurement velocity
9.10.3 Reference servo for axial tracking for 2x measurement velocity and 3x measurement velocity
9.11 Measurement velocities and reference servos for radial tracking
9.11.1 General
9.11.2 Reference servo for radial tracking for 1x measurement velocity
9.11.3 Reference servo for radial tracking for 2x measurement velocity and 3x measurement velocity

10 Dimensional characteristics

10.1 General
10.2 Disk reference planes and reference axis
10.3 Overall dimensions
10.4 First transition area
10.5 Protection ring
10.6 Clamping zone
10.7 Second transition area
10.8 Information area
10.8.1 General
10.8.2 Subdivision of information zone on SL disks
10.8.3 Subdivision of information zone on DL disks
10.9 Rim area

11 Mechanical characteristics

11.1 Mass
11.2 Moment of inertia
11.3 Dynamic imbalance
11.4 Axial run-out
11.4.1 General
11.4.2 Residual axial tracking error for 1x measurement velocity
11.4.3 Residual axial tracking error for 2x measurement velocity
11.4.4 Residual axial tracking error for 3x measurement velocity
11.5 Radial run-out
11.5.1 General
11.5.2 Residual radial tracking error for 1x measurement velocity on SL disks
11.5.3 Residual radial tracking error for 1x measurement velocity on DL disks
11.5.4 Residual radial tracking error for 2x measurement velocity on SL and DL disks
11.5.5 Residual radial tracking error for 3x measurement velocity on SL and DL disks
11.6 Durability of cover layer
11.6.1 Impact resistance of cover layer
11.6.2 Scratch resistance of cover layer
11.6.3 Repulsion of fingerprints by cover layer

12 Optical characteristics in information area

12.1 General
12.2 Refractive index of transmission stacks (TS)
12.3 Thickness of transmission stacks (TS)
12.3.1 Thickness of transmission stack of SL disks
12.3.2 Thickness of transmission stacks of DL disks
12.4 Reflectivity
12.4.1 Reflectivity of recording layer of SL disks
12.4.2 Reflectivity of recording layers of DL disks
12.5 Birefringence
12.6 Angular deviation

13 Data format

13.1 General
13.2 Data frame
13.3 Error detection code (EDC)
13.4 Scrambled data frame
13.5 Data block

13.6 LDC block
13.7 LDC code words
13.8 LDC cluster
13.8.1 General
13.8.2 First interleaving step
13.8.3 Second interleaving step
13.9 Addressing and control data
13.9.1 General
13.9.2 Address units
13.9.2.1 General
13.9.2.2 Byte assignment for address fields
13.9.2.3 Address unit numbers
13.9.2.4 Assignments for flag bits
13.9.2.5 Usage of status bits Sai,j
13.9.3 User control data
13.9.4 Byte/bit assignment for user control data
13.10 Access block
13.11 BIS block
13.12 BIS code words
13.13 BIS cluster
13.14 ECC cluster
13.15 Recording frames
13.16 Physical cluster
13.17 17PP modulation for recordable data
13.17.1 General
13.17.2 Bit conversion rules
13.17.3 dc-control procedure
13.17.4 Frame sync
13.18 Modulation and NRZI conversion

14 Physical data allocating and linking

14.1 General
14.2 Recording unit block (RUB)
14.2.1 General
14.2.2 Data run-in
14.2.2.1 General
14.2.2.2 Content of Guard_1 fields
14.2.2.3 Automatic power control (APC)
14.2.2.4 Content of PrA fields
14.2.3 Data run-out
14.2.3.1 General
14.2.3.2 Content of PoA fields
14.2.3.3 Content of Guard_2 fields
14.2.4 Guard_3 field
14.2.4.1 General
14.2.4.2 Automatic power control (APC)
14.2.4.3 Linking requirements
14.3 Locating data relative to wobble addresses

15 Track format

15.1 General
15.2 Track shape
15.3 Track path
15.4 Track pitch
15.4.1 Track pitch in BCA zone
15.4.2 Track pitch in embossed HFM area
15.4.3 Track pitch in recordable area(s)
15.4.4 Track pitch between embossed HFM area and recordable area
15.5 Track layout of HFM groove
15.5.1 General
15.5.2 Data format
15.5.2.1 Data frame
15.5.2.2 Scrambled data frame
15.5.2.3 Data block

15.5.2.4 LDC block
15.5.2.5 Interleaving
15.5.3 Addressing and control data
15.5.3.1 General
15.5.3.2 Address fields
15.5.3.3 User control data
15.5.3.4 BIS code words
15.5.3.5 BIS cluster
15.5.4 Recording frames
15.5.4.1 General
15.5.4.2 Modulation
15.5.4.3 Frame sync
15.6 Track layout of wobbled groove(s)
15.6.1 General
15.6.2 Modulation of wobbles
15.6.2.1 General
15.6.2.2 MSK-cos modulation
15.6.2.3 HMW modulation
15.6.3 Wobble polarity
15.7 ADIP information
15.7.1 General
15.7.2 ADIP unit types
15.7.3 ADIP word structure
15.7.4 ADIP data structure
15.7.4.1 General
15.7.4.2 ADIP information bit assignments
15.7.4.3 Relation between physical ADIP addresses on layer L0 and layer L1
15.7.5 ADIP error correction
15.8 Disk information in ADIP frame
15.8.1 General
15.8.2 Error protection for disk information aux frames
15.8.3 Disk information data structure
15.8.3.1 General
15.8.3.2 General definitions for DI unit
15.8.3.3 Definitions for DI format 1 (N–1 write strategy)
15.8.3.4 Definitions for DI format 2 (N/2 write strategy)
15.8.3.5 Definition for DI format 3 (Castle write strategy)
15.8.3.6 Write strategy requirements
15.8.3.7 Usage of DI units for write strategy

16 General description of information zone

16.1 General
16.2 Format of information zone on single-layer disk
16.3 Format of information zone on dual-layer disk

17 Layout of recordable area of information zone

18 Inner zone

18.1 General
18.2 Permanent information and control data (PIC) zone
18.2.1 General
18.2.2 Content of PIC zone
18.2.3 Emergency brake
18.3 Recordable area of inner zone 0
18.3.1 Protection zone 2
18.3.2 INFO 2/Reserved 8
18.3.3 INFO 2/Reserved 7
18.3.4 INFO 2/Reserved 6
18.3.5 INFO 2/Reserved 5
18.3.6 INFO 2/PAC 2
18.3.7 INFO 2/DMA 2
18.3.8 INFO 2/Control data 2
18.3.9 INFO 2/Buffer 2
18.3.10 OPC 0/Test zone

18.3.11 Usage of OPC areas
18.3.11.1 OPC procedure order
18.3.11.2 OPC physical cluster usage
18.3.11.3 OPC update in TDMA
18.3.12 OPC 0/OPC 0 Buffer
18.3.13 TDMA 0
18.3.14 INFO 1/Pre-write area
18.3.15 INFO 1/Drive area
18.3.15.1 General
18.3.15.2 Format of drive-specific information
18.3.16 INFO 1/DMA 1
18.3.17 INFO 1/Control data 1
18.3.18 INFO 1/PAC 1
18.4 Recordable area of inner zone 1
18.4.1 Buffer
18.4.2 OPC 1
18.4.3 Buffer
18.4.4 INFO 2/Reserved 8
18.4.5 INFO 2/Reserved 7
18.4.6 INFO 2/Reserved 6
18.4.7 INFO 2/Reserved 5
18.4.8 INFO 2/PAC 2
18.4.9 INFO 2/DMA 2
18.4.10 INFO 2/Control data 2
18.4.11 INFO 2/Buffer 2
18.4.12 TDMA 1
18.4.13 Reserved
18.4.14 INFO 1/Pre-write area
18.4.15 INFO 1/Drive area
18.4.16 INFO 1/DMA 1
18.4.17 INFO 1/Control data 1
18.4.18 INFO 1/PAC 1

19 Data zone

20 Outer zone(s)

20.1 General
20.2 Recordable area of outer zone(s)
20.2.1 INFO 3/Buffer 4
20.2.2 INFO 3/DMA 3
20.2.3 INFO 3/Control data 3
20.2.4 Angular buffer
20.2.5 INFO 4/DMA 4
20.2.6 INFO 4/Control data 4
20.2.7 INFO 4/Buffer 6
20.2.8 DCZ 0/Test zone and DCZ 1 / Test zone
20.2.9 Usage of DCZ area
20.2.9.1 DCZ procedure order
20.2.9.2 DCZ physical cluster usage
20.2.9.3 Update of TDMA
20.2.10 Protection zone 3

21 Physical access control clusters

21.1 General
21.2 Layout of PAC zones
21.3 General structure of PAC clusters
21.4 IS1 and IS2 PAC clusters

22 Disk management

22.1 General
22.2 Recording management
22.2.1 General
22.2.2 Sequential recording mode (SRM)
22.2.3 Recording user data in SRR

22.2.4 SRR status
22.2.5 Closing SRR
22.3 Temporary disk management areas (TDMA)
22.3.1 General
22.3.2 TDMA access indicators
22.4 Disk management structure (DMS)
22.4.1 General
22.4.2 Temporary disk management structure (TDMS)
22.4.3 TDMS in sequential recording mode
22.4.4 Temporary disk definition structure (TDDS)
22.4.5 Temporary defect list (TDFL)
22.4.5.1 General
22.4.5.2 TDFL data structure
22.4.5.3 Defect list header
22.4.5.4 Defect list terminator
22.4.6 Sequential recording range information (SRRI)
22.4.6.1 General
22.4.6.2 SRRI data structure
22.4.6.3 SRRI header
22.4.6.4 SRR entry
22.4.6.5 SRRI terminator
22.5 Unrecorded (blank) disk structure
22.5.1 General
22.5.2 Pre-recorded areas on unrecorded disk
22.5.3 Pre-recorded BCA
22.5.4 Pre-recorded INFO 2/Reserved 5, Reserved 8 and Pre-recorded INFO 1/Pre-write area
22.5.5 Pre-recorded INFO 1/PAC 1 and Pre-recorded INFO 2/PAC 2
22.5.6 OPC 0/Test zone and OPC 1/Test zone
22.5.7 TDMA 0
22.5.8 Initialization of disk
22.6 Recorded (closed) disk structure
22.6.1 General
22.6.2 DMA zones
22.6.3 Disk management structures (DMS)
22.6.3.1 General
22.6.3.2 Disk management structure (DMS) on SL disk
22.6.3.3 Disk management structure (DMS) on DL disk

23 Assignment of logica sector numbers (LSNs)

24 Characteristics of grooved areas

25 Method of testing for grooved area

25.1 General
25.2 Environment
25.3 Reference drive
25.3.1 General
25.3.2 Read power
25.3.3 Read channels
25.3.4 Tracking requirements
25.3.5 Scanning velocities
25.4 Definition of signals

26 Signals from HFM groove

26.1 Push-pull polarity
26.2 Push-pull signal
26.3 Wobble signal
26.4 Jitter of HFM signal

27 Signals from wobbled groove(s)

27.1 Phase depth
27.2 Push-pull signal
27.3 Wobble signal
27.3.1 General

27.3.2 Measurement of INWS
27.3.3 Measurement of wobble CNR
27.3.4 Measurement of harmonic distortion of wobble
27.4 HFM and wobbled groove transition requirements for LTH disks

28 Characteristics of recording layer

29 Method of testing for recording layer

29.1 General
29.2 Environment
29.3 Reference drive
29.3.1 General
29.3.2 Read power
29.3.3 Read channels
29.3.4 Tracking requirements
29.3.5 Scanning velocities
29.4 Write conditions
29.4.1 Write pulse waveform
29.4.2 Write powers
29.4.3 Write conditions for jitter measurement
29.5 Definition of signals

30 Signals from recorded areas

30.1 HF signals
30.2 Modulated amplitude
30.3 Reflectivity modulation product
30.4 Asymmetry
30.5 Jitter
30.6 Read stability

31 Local defects

32 Characteristics of user data

33 Method of testing for user data

33.1 General
33.2 Environment
33.3 Reference drive
33.3.1 General
33.3.2 Read power
33.3.3 Read channels
33.3.4 Error correction
33.3.5 Tracking requirements
33.3.6 Scanning velocities
33.4 Error signals

34 Minimum quality of recorded information

34.1 Symbol error rate
34.2 Maximum burst errors
34.3 User-written data

35 BCA

Annex A (normative) Thickness of transmission stacks in case of multiple layers

A.1 General
A.2 Refractive index ni of all layers in cover layer and spacer layer
A.3 Thickness variation of transmission stack
A.4 Example of thickness calculation for SL

Annex B (normative) Measurement of reflectivity

B.1 General
B.2 Calibration method
B.3 Measuring method

Annex C (normative) Measurement of scratch resistance of cover layer

- **C.1 General**
- **C.2 Taber abrasion test**

Annex D (normative) Measurement of repulsion of grime by cover layer

- **D.1 General**
- **D.2 Specifications of stamp**
- **D.3 Preparation of ink**
- **D.4 Preparation of ink pad**
- **D.5 Using ink pad and stamp**

Annex E (normative) Measurement of wobble amplitude

- **E.1 Measurement methods**
- **E.2 Calibration of filters**

Annex F (normative) Write pulse waveform for testing

- **F.1 General write pulse waveform**
- **F.2 N–1 write strategy**
- **F.3 N/2 write strategy**
- **F.4 Castle write strategy**
- **F.5 Definition of pulse widths and rise and fall times**

Annex G (normative) Optimum power control (OPC) procedure for disk

- **G.1 General**
- **G.2 Mathematical model for modulation versus power function**
- **G.3 Procedure for determination of OPC parameters for disk**
- **G.4 Procedure to determine beta value**

Annex H (normative) HF signal pre-processing for jitter measurements

- **H.1 General**
- **H.2 General implementation of equalizer**
- **H.3 Conventional equalizer circuit**
- **H.4 Limit equalizer circuit**
- **H.5 Specifications of supporting circuits**
- **H.5.1 Amplifiers and filters**
- **H.5.2 Open-loop transfer function for PLL**
- **H.5.3 Slicer**
- **H.6 Condition for measurement**
- **H.7 Jitter measurement**

Annex I (normative) Measurement procedure

- **I.1 General**
- **I.2 Initial adjustments of reference drive**
- **I.3 Jitter measurement**
- **I.4 Modulated amplitude measurements**
- **I.5 Measurements of resolution I2pp/I8pp and I3pp/I8pp**
- **I.5.1 Method for measuring I2pp and I8pp**
- **I.5.2 I3pp/I8pp, I8pp/I8H and asymmetry measurement procedure**
- **I.6 Tracking error signal measurements (VPPnorm measurement procedure)**
- **I.7 Residual error of axial tracking measurement procedure**
- **I.8 Residual error of radial tracking measurement procedure**
- **I.9 Random SER measurement**

Annex J (informative) Measurement of birefringence

- **J.1 Principle of measurement**
- **J.2 Measurements conditions**
- **J.3 Example of measurement procedure**

Annex K (informative) Measurement of thickness of cover layer and spacer layer

- **K.1 Focusing method**
- **K.2 Interferometer method**

Annex L (informative) Measurement of impact resistance of cover layer

L.1 General
L.2 Recommendation for drives
L.3 Measurements of impact resistance of cover layer

Annex M (informative) Groove deviation and wobble amplitude

M.1 Relation between normalized wobble signal and wobble amplitude
M.2 Tolerance of normalized wobble signal

Page count: 231