ISO/IEC 17982:2021 (E)

Information technology — Telecommunications and information exchange between systems — Close capacitive coupling communication physical layer (CCCC PHY)

Contents

Foreword

1 Scope

2 Normative references

3 Terms, definitions and abbreviated terms

3.1 Terms and definitions
3.2 Abbreviated terms

4 Conventions and notations

5 Conformance

6 Architecture

7 Reference plate-electrode assembly

8 PHY parameters

8.1 Voltage conditions
8.2 Bit representation
8.2.1 Bit duration
8.2.2 Bit encoding
8.3 Transmission
8.4 DC balance of a P-PDU
8.5 Reception of a P-PDU

9 P-PDU

9.1 Structure
9.2 Space
9.3 Level adjust
9.4 Pre-amble and Sync
9.5 Attribute
9.6 TDS number
9.7 Sequence number
9.7.1 Initial and range
9.7.2 Acknowledgement
9.8 Payload
9.9 CRC
9.10 Post-amble
9.11 Null P-PDU
9.12 Data P-PDU

10 PHY data unit (P-DU)

11 Segmentation and reassembly

12 TDS

13 LBT and synchronisation

13.1 LBT
13.2 Synchronisation

14 Association procedure

15 Communication

15.1 General
15.2 Full duplex communication
15.3 Broadcast communication

Annex A (normative) Tests

A.1 Reference plate-electrode test
A.2 P-PDU DC balance test
A.3 Protocol test
A.3.1 Test setup
A.3.2 Test scenario 1
A.3.3 Test scenario 2
A.3.4 Test scenario 3
A.3.5 Test scenario 4
A.3.6 Test scenario 5
A.3.7 Test scenario 6
A.3.8 Test scenario 7
A.3.9 Test scenario 8

Annex B (informative) Guidance for implementation of this document

Page count: 58