

# ISO/IEC TS 22924:2021 (E)

## Identification cards — Transport layer topologies — Configuration for HCI/HCP interchange

---

### Contents

|         |  |
|---------|--|
|         | Foreword   |
|         | Introduction   |
| 1       | Scope  |
| 2       | Normative references   |
| 3       | Terms and definitions  |
| 4       | Symbols and abbreviated terms  |
| 5       | Architecture   |
| 5.1     | System architecture view   |
| 5.1.1   | General  |
| 5.1.2   | Hosts  |
| 5.1.3   | Gates  |
| 5.1.4   | Pipes  |
| 5.1.5   | Host controller  |
| 5.1.6   | General aspects on APDU gate   |
| 5.2     | System architecture with legacy COS                                      |
| 6       | Configuration requirements   |
| 6.1     | General  |
| 6.2     | Logical components of an APDU-enabled host                               |
| 6.3     | Gates registry   |
| 6.3.1   | General  |
| 6.3.2   | Administration gate registry   |
| 6.3.2.1 | Host controller administration gate                                      |
| 6.3.2.2 | Host administration gate   |
| 6.3.3   | Link management gate   |
| 6.3.4   | Identity management gate   |
| 6.3.5   | Loop back gate   |
| 6.3.6   | APDU gate  |
| 6.3.7   | APDU application gate registry   |
| 6.4     | Example of exchanging APDU via HCI/HCP                                   |
| 6.5     | APDU transport versus HCP frames   |
| 6.5.1   | General  |
| 6.5.2   | Chaining of T=1 message blocks wrapping HCP packets                      |
| 6.5.3   | Handling of error recovery with T=1 features                             |
| 6.6     | APDU fragmentation   |
| 6.7     | Supported set of commands and events                                     |
| Annex A | (informative) Examples of architecture variants                          |
| A.1     | Architecture variants  |
| A.1.1   | Variant with full legacy secure element                                  |
| A.1.2   | Variant with ICC-managed device  |
| A.1.3   | Variant with application interface to secure element                     |
| A.1.4   | Variant in a simplified HCI architecture when only two hosts are present |
| Annex B | (informative) Background information                                     |
| B.1     | ICC communication within the OSI model                                   |
| B.2     | HCI/HCP communication within the OSI model                               |

- B.3**      **Comparison of HCI/HCP versus T=1**
- B.4**      **Area for new investigations**
- B.5**      **Differences between HCP and T=1**
- B.6**      **HCP packets**
- B.7**      **HCP message structure**

**Page count: 26**