

ISO/IEC 39794-17:2021 (E)

Information technology — Extensible biometric data interchange formats — Part 17: Gait image sequence data

Contents

| | |
|-------|---|
| | Foreword |
| | Introduction |
| 1 | Scope |
| 2 | Normative references |
| 3 | Terms and definitions |
| 4 | Abbreviated terms |
| 5 | Conformance |
| 6 | Modality specific information |
| 6.1 | Purpose |
| 6.2 | Practices |
| 6.3 | Data models for gait recognition |
| 6.3.1 | General |
| 6.3.2 | Model-based methods |
| 6.3.3 | Appearance-based methods |
| 6.4 | Data flow of gait recognition |
| 6.5 | Body tree concept for gait |
| 6.6 | Camera image sequence requirements |
| 6.7 | Gait recognition recordings |
| 6.7.1 | General |
| 6.7.2 | Gait and upper body movement image encoding |
| 6.7.3 | Gait and upper body camera image resolutions |
| 6.8 | Gait modality |
| 6.8.1 | General |
| 6.8.2 | Gait silhouette |
| 6.8.3 | Surveillance systems |
| 6.9 | Upper body movement modality |
| 6.9.1 | General |
| 6.9.2 | Face Features Motion (FFM) |
| 6.9.3 | Head movement recognition |
| 6.9.4 | Head Movements Static Body (HMS) |
| 6.9.5 | Head Movements Dynamic Body (HMD) |
| 6.9.6 | Hands movement |
| 7 | Profile-specific information |
| 7.1 | Purpose |
| 7.1.1 | General |
| 7.1.2 | Gait representations |
| 7.1.3 | Scene requirements |
| 7.2 | 2D gait image sequence profile |
| 7.2.1 | General |
| 7.2.2 | Gait image sequence representation profile requirements |
| 7.2.3 | Post-acquisition processing |
| 7.2.4 | Neural network training and testing |
| 7.3 | UBM 2D upper body movement profile |
| 8 | Encoding |

- 8.1 Tagged binary encoding
 - 8.2 XML encoding
- 9 Registered BDB format identifiers

Annex A (informative) Conditions for capturing

- A.1 Recommendations for Gait Recording Systems
 - A.1.1 Architecture
 - A.1.2 Usability and accessibility
 - A.1.3 Practical applications
 - A.1.3.1 General
 - A.1.3.2 Body vs. gait
 - A.1.3.3 Recognition methods
 - A.1.4 Submillimetre imaging
- A.2 Recommendations for full body video recording
- A.3 Gait recording — technical recommendations
 - A.3.1 General
 - A.3.2 Error factor limitation
 - A.3.3 Walkway construction
 - A.3.4 Camera arrangements
 - A.3.4.1 General camera arrangements
 - A.3.4.2 Enrolment camera arrangements
 - A.3.4.2.1 General
 - A.3.4.2.2 Single-view enrolment
 - A.3.4.2.3 Dual-view enrolment
 - A.3.4.2.4 Multi-view enrolment
 - A.3.5 Studio lighting and layout
 - A.3.6 Walk-through gait recording corridor lighting and layout

Annex B (informative) Encoding examples

- B.1 Binary encoding examples
 - B.1.1 General
 - B.1.2 Binary encoding example using mandatory data fields
 - B.1.3 Binary encoding example using JPEG image sequence elements
 - B.1.4 Binary encoding example using MPEG-4
- B.2 XML encoding examples
 - B.2.1 General
 - B.2.2 XML encoding example using mandatory data fields
 - B.2.3 XML encoding example using JPEG gait sequence elements
 - B.2.4 XML encoding example using MPEG-4

Annex C (informative) Image sequence acquisition measurements

- C.1 General
 - C.1.1 Introduction
 - C.1.2 Measurement environment
- C.2 Biometric capturing environment checking
 - C.2.1 General
 - C.2.2 Lighting checking
 - C.2.3 Background checking
- C.3 Measurements for low resolution video cameras
 - C.3.1 The IEC 1088-14 test panel
 - C.3.2 Measurement preparations and analysis
 - C.3.2.1 General
 - C.3.2.2 Preparations
 - C.3.2.3 Analysis
 - C.3.2.3.1 General
 - C.3.2.3.2 Camera image dynamic range checking
 - C.3.2.3.3 Camera greyscale checking
 - C.3.2.3.4 Colour fidelity checking
 - C.3.2.3.5 Camera resolution checking (IEC 1088-14)
 - C.3.2.3.6 Camera resolution checking (ISO 12233)
- C.4 Measurements for submillimetre cameras
 - C.4.1 General
 - C.4.2 Test targets for submillimetre imaging

- C.4.3 Reflective targets**
- C.4.4 Absorbent targets**
- C.4.5 Analysis of submillimetre images**

Page count: 55