ISO/IEC 18000-63:2021-11 (E)

Information technology - Radio frequency identification for item management - Part 63: Parameters for air interface communications at 860 MHz to 960 MHz Type C

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Normative references 1

3 Terms and definitions 2

4 Symbols, abbreviated terms and notation 5
4.1 Symbols 5
4.2 Abbreviated terms 7
4.3 Notation 8

5 Conformance 9
5.1 Claiming conformance 9
5.2 General conformance requirements 9
5.2.1 Interrogators 9
5.2.2 Tags 10
5.3 Command structure and extensibility 10
5.3.1 General 10
5.3.2 Mandatory commands 10
5.3.3 Optional commands 10
5.3.4 Proprietary commands 10
5.3.5 Custom commands 10
5.4 Reserved for Future Use (RFU) 11
5.5 Cryptographic Suite Indicators 11

6 Protocol requirements 11
6.1 Protocol overview 11
6.1.1 Physical layer 11
6.1.2 Tag-identification layer 11
6.2 Protocol parameters 12
6.2.1 Signaling -- Physical and media access control parameters 12
6.2.2 Logical -- Operating procedure parameters 15
6.3 Description of operating procedure 15
6.3.1 Physical interface 16
6.3.2 Logical interface 37

7 Battery Assisted Passive (BAP) Interrogator Talks First systems (optional) 112
7.1 Applicability 112
7.2 General overview, definitions, and requirements of BAP 113
7.3 BAP inventoried flag and state machine behaviour modifications 114
7.3.1 Modification to ready state and power-down support for BAP Tags 114
7.3.2 Signal loss tolerance via timer (mandatory) 115
7.3.3 Modified persistence of BAP PIE inventory flags (optional) 117
7.4 BAP PIE (optional) 119
7.4.1 Flex_Query command (optional) 119
7.4.2 BAP PIE detailed operation including optional Battery Saver Mode 121
7.5 Manchester mode Battery Assisted operation protocol extensions 126

7.5.1 General 126
7.5.2 Physical layer 127
7.5.3 Manchester activation 133
7.5.4 Commands summary 148

8 Sensor support (optional) 163
8.1 Applicability 163
8.2 Overview 163
8.3 Real Time Clock (RTC) 164
8.3.1 General 164
8.3.2 Setting the RTC 164
8.3.3 BroadcastSync command (optional) 165
8.3.4 Time synchronisation 165
8.4 HandleSensor command (optional) 166
8.5 Simple Sensors 167
8.5.1 Simple Sensor implementation 167
8.6 Full Function Sensors and Sensor Directory System 169
8.6.1 General 169
8.6.2 Sensor Access -- General approach 170
8.7 Snapshot Sensors 176
8.7.1 General 176
8.7.2 Initiating Snapshot Sensor measurements 179
8.7.3 Reporting Snapshot Sensor Information 180

Annex A (normative) Extensible bit vectors (EBV) 182

Annex B (normative) State-transition tables 183

Annex C (normative) Command-response tables 240

Annex D (informative) Example slot-count (Q) selection algorithm 267

Annex E (informative) Example Tag inventory and access 268

Annex F (informative) Calculation of 5-bit and 16-bit cyclic redundancy checks 269

Annex G (normative) Multiple- and dense-Interrogator channelized signaling 271

Annex H (informative) Interrogator-to-Tag link modulation 274

Annex I (normative) Error codes 276

Annex J (normative) Slot counter 278

Annex K (informative) Example data-flow exchange 279

Annex L (informative) Optional Tag features 282

Annex M (informative) Cryptographic-Suite checklist 285

Annex N (informative) Battery Assisted Tag to Interrogator synchronization 286

Annex O (normative) Simple Sensors Data Block 289

Annex P (normative) Record structures and commands for Ported Simple Sensors 300

Annex Q (informative) Battery Assisted Passive (BAP) PIE and Manchester mode tutorial guide ... 316

Annex R (informative) Manchester mode RF power control 327

Bibliography 332