ISO/IEC 17913:2000-06 (E)

Information technology_- 12,7_mm 128-track magnetic tape cartridge for information interchange_- Parallel serpentine format

Contents

Page

Section 1 - General **1**

1 Scope **1**

2 Conformance **1**

2.1 Magnetic tape cartridge **1**
2.2 Generating system **1**
2.3 Receiving system **1**

3 Normative references **1**

4 Definitions **1**

4.1 algorithm **1**
4.2 anhysteretic erase **1**
4.3 average signal amplitude **2**
4.4 azimuth **2**
4.5 back surface **2**
4.6 beginning of partition (BOP) **2**
4.7 beginning of tape (BOT) **2**
4.8 cartridge **2**
4.9 cyclic redundancy check (CRC) character **2**
4.10 end of tape (EOT) **2**
4.11 error-correcting code (ECC) **2**
4.12 error-detecting code (EDC) **2**
4.13 File Mark **2**
4.14 flux transition position **2**
4.15 flux transition spacing **2**
4.16 half-wrap **2**
4.17 logical block **2**
4.18 logical forward **2**
4.19 logical reverse **2**
4.20 magnetic tape **2**
4.21 mark tach count **2**
4.22 Master Standard Reference Tape **2**
4.23 physical recording density **2**
4.24 pre-record condition **2**
4.25 recorded element **2**
4.26 Reference Field **2**
4.27 resync character **2**
4.28 SDM set **2**
4.29 Secondary Standard Reference Tape (SSRT) **2**
4.30 servo track **3**
4.31 Standard Reference Amplitude (SRA) **3**
4.32 Standard Reference Current (I_r) **3**
4.33 Test Recording Current (I_m) **3**
4.34 track **3**
4.35 track group **3**
4.36 trailer **3**
4.37 Typical Field **3**
4.38 write equalisation **3**

5 Conventions and notations **3**

5.1 Representation of numbers **3**
5.2 Dimensions **3**
5.3 Names **3**
5.4 Acronyms **3**

6 Environment and safety **4**

6.1 Cartridge and tape testing environment **4**
6.2 Cartridge operating environment **4**
6.3 Cartridge storage environment **4**
6.4 Safety **5**

6.4.1 Safeness **5**
6.4.2 Flammability **5**

6.5 Transportation **5**

Section 2 - Requirements for the unrecorded tape **5**

7 Mechanical and electrical requirements **5**

7.1 Material **5**
7.2 Tape length **5**
7.3 Width **5**
7.4 Total thickness **5**
7.5 Base material thickness **5**
7.6 Discontinuity **5**
7.7 Longitudinal curvature **5**

7.7.1 Requirement **5**
7.7.2 Procedure **5**

7.8 Out-of-Plane distortions **5**
7.9 Cupping **6**

7.9.1 Requirement **6**
7.9.2 Procedure **6**

7.10 Coefficient of dynamic friction **6**

7.10.1 Requirements **6**
7.10.2 Procedure **6**

7.11 Coating adhesion **7**
7.12 Layer-to-layer adhesion **7**

7.12.1 Requirements **7**
7.12.2 Procedure **7**

7.13 Electrical resistance **8**

7.13.1 Requirement **8**
7.13.2 Procedure **8**

7.14 Abrasivity **9**
7.15 Friction characteristics after stress **9**

7.15.1 Requirements **9**
7.15.2 Procedure **9**

7.16 Surface roughness **9**

7.16.1 Requirement **9**
7.16.2 Procedure **9**

7.17 Inhibitor tape **10**

8 Magnetic recording characteristics **10**

8.1 Typical Field **10**
8.2 Signal amplitude **10**
8.3 Resolution **10**
8.4 Broad-band signal-to-noise ratio (BBSNR) **10**
8.4.1 Requirement **10**
8.4.2 Procedure **10**

9 Tape quality **11**

9.1 Missing pulse **11**

9.1.1 Requirement **11**
9.1.2 Procedure **11**

9.2 Coincident missing pulse **11**

9.2.1 Requirement **11**
9.2.2 Procedure **11**

9.3 Missing pulse density **12**

9.3.1 Requirement **12**
9.3.2 Procedure **12**

9.4 Tape durability **12**

Section 3 - Mechanical specifications of the tape cartridge **12**

10 General **12**

10.1 Overall dimensions **13**
10.2 Write-inhibit mechanism **13**
10.3 Label areas of the rear side **13**
10.4 Label area on the top side **14**
10.5 Case opening **14**
10.6 Locating notches **14**
10.7 Locating areas **15**
10.8 Inside configuration of the case around the case opening **15**
10.9 Other external dimensions of the case **15**
10.10 Central window **15**
10.11 Stacking ribs **16**
10.12 Recessed area **16**
10.13 Flexibility of the case **16**

10.13.1 Requirements **16**
10.13.2 Procedure **17**

10.14 Tape reel **17**

10.14.1 Locking mechanism **17**
10.14.2 Axis of rotation of the reel **17**
10.14.3 Metallic insert **17**
10.14.4 Toothed rim **17**
10.14.5 Hub of the reel **18**
10.14.6 Relative positions **18**
10.14.7 Characteristics of the toothed rim **19**

10.15 Leader block **19**
10.16 Attachment of the tape to the leader block **20**
10.17 Latching mechanism **20**
10.18 Tape wind **20**
10.19 Wind tension **20**
10.20 Circumference of the tape reel **20**
10.21 Moment of inertia **21**
10.22 Material **21**

10.23 Cartridge identification notches **21**
10.24 Finger slot **21**

Section 4 - Requirements for an interchanged tape **31**

11 Method of recording **31**

11.1 Physical recording density **31**
11.2 Bit cell length **31**
11.3 Average bit cell length **31**

11.3.1 Long-term average RLL bit cell length **31**
11.3.2 Short-term average RLL bit cell length **31**
11.4 Rate of change of the short-term average RLL bit cell length **31**
11.5 Bit shift **31**
11.6 Total character skew **31**
11.7 Missing zero-crossing zones **32**
11.8 Coincident missing zero-crossing zones **32**

12 Servo tracks **32**

12.1 Locations of the servo tracks **32**
12.2 Physical width of the servo tracks **33**
12.3 Format of the servo tracks **33**
12.4 Servo requirements **34**

12.4.1 Servo amplitude **34**
12.4.2 Servo azimuth **34**
12.4.3 Servo errors **34**
12.4.4 Servo edge spacing **35**

12.5 Procedure **35**

13 Data track format **35**

13.1 Number of data tracks **35**
13.2 Track positions **35**
13.3 Track width **37**
13.4 Data azimuth **37**
13.5 Half-wraps **37**

14 Tape format **37**

14.1 General **37**
14.2 Recording area **37**
14.3 Tach count **39**
14.4 Physical blocks **39**
14.5 Servo acquisition region **40**
14.6 Volume control region **40**
14.7 Data region **40**
14.8 Data entities **40**

15 Packet format **42**

15.1 Packet header **43**
15.2 Packet data **45**
15.3 Packet trailer **45**

16 Device blocks **45**

16.1 Data device blocks **45**
16.2 Mark device blocks **45**
16.3 File Mark **45**
16.4 Void mark **46**
16.5 Beginning of half-wrap mark **46**
16.6 End of half-wrap mark **46**
16.7 BOP mark **46**

16.8 EOD mark **46**
16.9 SDM mark **46**
16.10 FID mark **47**
16.11 DBM mark **48**

16.11.1 DBM general information packet **48**
16.11.2 DBM wrap region packet **49**
16.11.3 DBM partitions packet **49**
16.11.4 DBM servo demark packet **50**
16.11.5 DBM File Mark packet **50**

16.12 SARS mark **51**
16.13 DBM checked out mark **51**
16.14 DBM valid mark **51**

17 Device block format **51**

17.1 Device block header **51**

17.1.1 Device block control **52**
17.1.2 Device block sequence control **54**
17.1.3 Vendor identification code **54**

17.2 Device block data **54**
17.3 Device block trailer **54**

18 ECC **54**

18.1 CRC **54**
18.2 Code block **55**
18.3 ECC encoded code block **55**
18.4 Codeword correction code generation **56**
18.5 MIE pointer code generation **57**
18.6 ECC encoded interleave unit **57**
18.7 Short error correction code generation **57**

19 Recording of bytes on tape **59**

19.1 Synchronisation format **59**
19.2 Interblock gap formatting **62**
19.3 RLL byte translation **63**
19.4 Write equalisation bit translation **63**
19.5 Writing bits on tape **63**

Annexes

A - Tape abrasivity measurement procedure **64**

B - Media type label **66**

C - Measurement of bit shift **70**

D - Vendor Identification Code **72**

E - Recommendations for transportation **73**

F - Inhibitor tape **74**

G - Tape durability **75**