

ISO/IEC 21122-2:2022-03 (E)

Information technology - JPEG XS low-latency lightweight image coding system - Part 2 : Profiles and buffer models

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms, definitions, symbols and abbreviated terms	1
3.1	Terms and definitions	1
3.2	Abbreviated terms	4
3.3	Symbols	4
4	Conventions	6
4.1	Conformance language	6
4.2	Operators	6
4.2.1	Arithmetic operators	6
4.2.2	Logical operators	6
4.2.3	Relational operators	6
4.2.4	Precedence order of operators	6
4.2.5	Mathematical functions	7
5	Buffer model	7
5.1	General system block diagram	7
5.2	Influencing variables on the required buffer sizes	8
5.3	Role of the buffer model	9
6	Interpretation of Bayer data	9
Annex A (normative)	Profiles, levels and sublevels	11
Annex B (normative)	Packet-based JPEG XS decoder model	25
Annex C (normative)	Packet-based constant bit rate buffer model	31
Annex D (informative)	Encoder model, latency bounds and codestream conformance properties for the packet-based constant bit rate buffer model	37
Annex E (informative)	JPEG XS latency analysis	42
Bibliography		49