ISO/IEC 13818-1:2022-09 (E)

Information technology - Generic coding of moving pictures and associated audio information - Part 1: Systems

Contents

Page

SECTION 1 – GENERAL 1
1.1 Scope 1
1.2 Normative references 1
SECTION 2 – TECHNICAL ELEMENTS 4
2.1 Definitions 4
2.2 Symbols and abbreviations 12
2.3 Method of describing bit stream syntax 14
2.4 Transport stream bitstream requirements 15
2.5 Program stream bitstream requirements 63
2.6 Program and program element descriptors 76
2.7 Restrictions on the multiplexed stream semantics 157
2.8 Compatibility with ISO/IEC 11172 161
2.9 Registration of copyright identifiers 161
2.10 Registration of private data format 162
2.11 Carriage of ISO/IEC 14496 data 162
2.12 Carriage of metadata 174
2.13 Carriage of ISO 15938 data 182
2.14 Carriage of Rec. ITU-T H.264 | ISO/IEC 14496-10 video 183
2.15 Carriage of ISO/IEC 14496-17 text streams 199
2.16 Carriage of auxiliary video streams 200
2.17 Carriage of HEVC 201
2.18 Carriage of green access units 215
2.19 Carriage of ISO/IEC 23008-3 MPEG-H 3D audio data 217
2.20 Carriage of Quality Access Units in MPEG-2 sections 219
2.21 Carriage of sample variants 220
2.22 Carriage of Media Orchestration Access Units 221
2.23 Carriage of VVC 221
2.24 Carriage of EVC 226
Annex A CRC decoder model 230
A.1 CRC decoder model 230
Annex B Digital storage medium command and control (DSM-CC) 231
B.1 Introduction 231
B.2 General elements 232
B.3 Technical elements 234
Annex C Program-specific information 240
C.1 Explanation of program-specific information in transport streams 240
C.2 Introduction 240
C.3 Functional mechanism 240
C.4 The mapping of sections into transport stream packets 241
C.5 Repetition rates and random access 241
C.6 What is a program? 242
C.7 Allocation of program_number 242
C.8 Usage of PSI in a typical system 242
C.9 The relationships of PSI structures 243
C.10 Bandwidth utilization and signal acquisition time 245
Annex D Systems timing model and application implications of this Recommendation | International Standard 248
D.1 Introduction 248

Annex E Data transmission applications 257
E.1 General considerations 257
E.2 Suggestion 257
Annex F Graphics of syntax for this Recommendation | International Standard 258
F.1 Introduction 258
Annex G General information 262
G.1 General information 262
Annex H Private data 263
H.1 Private data 263
Annex I Systems conformance and real-time interface 264
I.1 Systems conformance and real-time interface 264
Annex J Interfacing jitter-inducing networks to MPEG-2 decoders 265
J.1 Introduction 265
J.2 Network compliance models 265
J.3 Network specification for jitter smoothing 266
J.4 Example decoder implementations 267
Annex K Splicing transport streams 268
K.1 Introduction 268
K.2 The different types of splicing point 268
K.3 Decoder behaviour on splices 269
Annex L Registration procedure (see 2.9) 271
L.1 Procedure for the request of a Registered Identifier (RID) 271
L.2 Responsibilities of the Registration Authority 271
L.3 Responsibilities of parties requesting an RID 271
L.4 Appeal procedure for denied applications 271
Annex M Registration application form (see 2.9) 273
M.1 Contact information of organization requesting a Registered Identifier (RID) 273
M.2 Statement of an intention to apply the assigned RID 273
M.3 Date of intended implementation of the RID 273
M.4 Authorized representative 273
M.5 For official use only of the Registration Authority 273
Annex N Registration Authority Diagram of administration structure (see 2.9) 274
Annex O Registration procedure (see 2.10) 275
O.1 Procedure for the request of an RID 275
O.2 Responsibilities of the Registration Authority 275
O.3 Contact information for the Registration Authority 275
O.4 Responsibilities of parties requesting an RID 275
O.5 Appeal procedure for denied applications 275
Annex P Registration application form 277
P.1 Contact information of organization requesting an RID 277
P.2 Request for a specific RID 277
P.3 Short description of RID that is in use and date system that was implemented 277
P.4 Statement of an intention to apply the assigned RID 277
P.5 Date of intended implementation of the RID 277
P.6 Authorized representative 277
P.7 For official use of the Registration Authority 277
Annex Q T-STD and P-STD buffer models for ISO/IEC 13818-7 ADTS 278
Q.1 Introduction 278
Q.2 Leak rate from transport buffer 278
Q.3 Buffer size 278
Q.4 Conclusion 279
Annex R Carriage of ISO/IEC 14496 scenes in Rec. ITU-T H.222.0 | ISO/IEC 13818-1 281
R.1 Content access procedure for ISO/IEC 14496 program components within a program stream 281
R.2 Content access procedure for ISO/IEC 14496 program components within a transport stream 282
Annex S Carriage of JPEG 2000 part 1 video over MPEG-2 transport streams 286
S.1 Introduction 286
S.2 J2K video access unit, J2K video elementary stream, J2K video sequence and J2K still picture 286
S.3 Optional J2K block mode for high resolution support 286

S.4 Optional J2K stripe mode for Ultra-Low Latency 287
S.5 Elementary stream header (elsm) and mapping to PES packets 287
S.6 J2K transport constraints 290
S.7 Interpretation of flags in adaptation and PES headers for J2K video elementary streams 291
S.8 T-STD extension for J2K video elementary streams 291
Annex T MIME type for MPEG-2 transport streams 294
T.1 Introduction 294
T.2 MIME type and subtype 294
T.3 Security considerations 295
T.4 Parameters 295
Annex U Carriage of timeline and external media information over MPEG-2 transport streams 297
U.1 Introduction 297
U.2 TEMI access unit and TEMI elementary stream 298
U.3 AF descriptors 299
Annex V Transport of HEVC tiles 308
V.1 Introduction 308
V.2 HEVC tile substream identification example 309
V.3 Subregion layout example 309
Annex W Carriage of JPEG XS part 1 video over MPEG-2 Transport Streams 311
W.1 Introduction 311
W.2 JPEG XS video access unit, JPEG XS video elementary stream, JPEG XS video sequence and JPEG XS still picture 311
W.3 Elementary stream header (jxes) and mapping to PES packets 311
W.4 JPEG XS transport constraints 312
W.5 Interpretation of flags in adaptation field and PES packet for JPEG XS video elementary streams 313
W.6 T-STD extension for JPEG XS video elementary streams 313

List of Tables

Table 2-1 – Transport stream 26
Table 2-2 – Transport packet of this Recommendation | International Standard 26
Table 2-3 – PID table 27
Table 2-4 – Scrambling control values 27
Table 2-5 – Adaptation field control values 28
Table 2-6 – Transport stream adaptation field 28
Table 2-7 – Splice parameters Table 1 Simple Profile Main Level, Main Profile Main Level, SNR Profile Main Level (both layers), Spatial Profile High-1440 Level (base layer), High Profile Main Level (middle + base layers), Multi-view Profile Main Level (base layer) Video 35
Table 2-8 – Splice parameters Table 2 Main Profile Low Level, SNR Profile Low Level (both layers), High Profile Main Level (base layer), Multi-view Profile Low Level (base layer) Video 36
Table 2-9 – Splice parameters Table 3 Main Profile High-1440 Level, Spatial Profile High-1440 Level (all layers), High Profile High-1440 Level (middle + base layers), Multi-view Profile High-1440 Level (base layer) Video 36
Table 2-10 – Splice parameters Table 4 Main Profile High Level, High Profile High-1440 Level (all layers), High Profile High Level (middle + base layers), Multi-view Profile High Level (base layer) Video 36
Table 2-11 – Splice parameters Table 5 SNR Profile Low Level (base layer) Video 36
Table 2-12 – Splice parameters Table 6 SNR Profile Main Level (base layer) Video 37
Table 2-13 – Splice parameters Table 7 Spatial Profile High-1440 Level (middle + base layers) Video 37
Table 2-14 – Splice parameters Table 8 High Profile Main Level (all layers), High Profile High-1440 Level (base layer) Video 37
Table 2-15 – Splice parameters Table 9 High Profile High Level (base layer), Multi-view Profile Main Level (both layers) Video 37
Table 2-16 – Splice parameters Table 10 High Profile High Level (all layers), Multi-view Profile High-1440 Level (both layers) Video 38
Table 2-17 – Splice parameters Table 11 4:2:2 Profile Main Level Video 38
Table 2-18 – Splice parameters Table 12 Multi-view Profile Low Level (both layers) Video 38
Table 2-19 – Splice parameters Table 13 Multi-view Profile High Level (both layers) Video 38
Table 2-20 – Splice parameters Table 14 4:2:2 Profile High Level Video 39
Table 2-21 – PES packet 39
Table 2-22 – Stream_id assignments 42
Table 2-23 – PES scrambling control values 43
Table 2-24 – Trick mode control values 48
Table 2-25 – Field_id field control values 49
Table 2-26 – Coefficient selection values 49
Table 2-27 – Stream_id_extension assignments 51
Table 2-28 – Program-specific information 52
Table 2-29 – Program-specific information pointer 54
Table 2-30 – Program association section 54
Table 2-31 – table_id assignment values 55
Table 2-32 – Conditional access section 56
Table 2-33 – Transport stream program map section 57
Table 2-34 – Stream type assignments 58
Table 2-35 – Private section 61
Table 2-36 – The transport stream description table 62
Table 2-37 – Program stream 68
Table 2-38 – Program stream pack 68
Table 2-39 – Program stream pack header 68
Table 2-40 – Program stream system header 69
Table 2-41 – Program stream map 72
Table 2-42 – Program stream directory packet 74
Table 2-43 – Intra_coded indicator 76
Table 2-44 – Coding_parameters indicator 76
Table 2-45 – Program and program element descriptors 77
Table 2-46 – Video stream descriptor 78

Table 2-47 – Frame rate code 78
Table 2-48 – Audio stream descriptor 79
Table 2-49 – Hierarchy descriptor 80
Table 2-50 – Hierarchy_type field values 81
Table 2-51 – Registration descriptor 81
Table 2-52 – Data stream alignment descriptor 82
Table 2-53 – Video stream alignment values 82
Table 2-54 – AVC video stream alignment values 83
Table 2-55 – HEVC video stream alignment values 83
Table 2-56 – Audio stream alignment values 83
Table 2-57 – VVC video stream alignment values 84
Table 2-58 – EVC video stream alignment values 84
Table 2-59 – Target background grid descriptor 85
Table 2-60 – Video window descriptor 85
Table 2-61 – Conditional access descriptor 86
Table 2-62 – ISO 639 language descriptor 86
Table 2-63 – Audio type values 87
Table 2-64 – System clock descriptor 88
Table 2-65 – Multiplex buffer utilization descriptor 88
Table 2-66 – Copyright descriptor 89
Table 2-67 – Maximum bitrate descriptor 89
Table 2-68 – Private data indicator descriptor 90
Table 2-69 – Smoothing buffer descriptor 90
Table 2-70 – STD descriptor 91
Table 2-71 – IBP descriptor 91
Table 2-72 – MPEG-4 video descriptor 92
Table 2-73 – MPEG-4 audio descriptor 92
Table 2-75 – IOD descriptor 95
Table 2-76 – SL descriptor 95
Table 2-77 – FMC descriptor 96
Table 2-78 – External_ES_ID descriptor 96
Table 2-79 – Muxcode descriptor 97
Table 2-80 – FmxBufferSize descriptor 97
Table 2-81 – MultiplexBuffer descriptor 98
Table 2-82 – FlexMuxTiming descriptor 98
Table 2-83 – Content labelling descriptor 99
Table 2-84 – Metadata_application_format 99
Table 2-85 – Content_time_base_indicator values 100
Table 2-86 – Metadata pointer descriptor 101
Table 2-87 – Metadata format values 101
Table 2-88 – MPEG_carriage_flags 102
Table 2-89 – Metadata descriptor 103
Table 2-90 – decoder_config_flags 104
Table 2-91 – Metadata STD descriptor 105
Table 2-92 – AVC video descriptor 105
Table 2-93 – AVC timing and HRD descriptor 107
Table 2-94 – MPEG-2 AAC_audio_descriptor 108
Table 2-95 – MPEG-2_AAC_additional_information field values 109
Table 2-96 – MPEG-4 text descriptor 109
Table 2-97 – MPEG-4 audio extension descriptor 109
Table 2-98 – Auxiliary video stream descriptor 110
Table 2-99 – SVC extension descriptor 111
Table 2-100 – MVC extension descriptor 112
Table 2-101 – J2K video descriptor 113

Table 2-102 – Example frame rates based on DEN_frame_rate and NUM_frame_rate values 115
Table 2-103 – MVC operation point descriptor 117
Table 2-104 – MPEG2_stereoscopic_video_format_descriptor syntax 118
Table 2-105 – Stereoscopic_program_info_descriptor syntax 118
Table 2-106 – Stereoscopic_service_type values 119
Table 2-107 – Stereoscopic_video_info_descriptor syntax 119
Table 2-108 – Upsampling factor values 120
Table 2-109 – Extension descriptor 120
Table 2-110 – Extension descriptor tag values 123
Table 2-111 – Transport_profile_descriptor syntax 124
Table 2-112 – Transport_profile values 124
Table 2-113 – HEVC video descriptor 125
Table 2-115 – HEVC timing and HRD descriptor 127
Table 2-116 – Adaptation field extension descriptor 128
Table 2-117 – HEVC operation point descriptor 129
Table 2-118 – HEVC hierarchy extension descriptor 131
Table 2-119 – Semantics of extension dimension bits 131
Table 2-120 – Green extension descriptor 132
Table 2-121 – MPEG-H 3D audio descriptor 133
Table 2-122 – MPEG-H 3D audio config descriptor 133
Table 2-123 – MPEG-H 3D audio scene descriptor 134
Table 2-124 – MPEG-H 3D audio text label descriptor 137
Table 2-125 – MPEG-H 3D audio multi-stream descriptor 139
Table 2-126 – MPEG-H 3D audio DRC and Loudness descriptor() 140
Table 2-127 – MPEG-H 3D audio command descriptor 142
Table 2-128 – Quality extension descriptor 143
Table 2-129 – Virtual segmentation descriptor 144
Table 2-130 – HEVC tile substream descriptor 145
Table 2-131 — HEVC subregion descriptor 146
Table 2-132 – JPEG XS video descriptor 148
Table 2-133 – VVC video descriptor 150
Table 2-134 – Semantics of HDR_WGC_idc 151
Table 2-135 – SDR widely used video property combinations 152
Table 2-136 – WCG widely used video property combinations 152
Table 2-137 – HDR/WCG widely used video property combinations 152
Table 2-138 – No Indication 153
Table 2-139 – VVC timing and HRD descriptor 153
Table 2-140 – EVC video descriptor 154
Table 2-141 – EVC timing and HRD descriptor 156
Table 2-139 – Carriage of individual ISO/IEC 14496 streams in Rec. ITU-T H.222.0 | ISO/IEC 13818-1 163
Table 2-142 – Section syntax for transport of ISO/IEC 14496 stream 168
Table 2-143 – ISO/IEC defined options for carriage of an ISO/IEC 14496 scene and associated streams in Rec. ITU-T H.222.0 | ISO/IEC 13818-1 171
Table 2-144 – Metadata Access Unit Wrapper 177
Table 2-145 – Metadata AU cell 178
Table 2-146 – Cell fragment indication 178
Table 2-147 – Section syntax for transport of metadata 179
Table 2-148 – Section fragment indication 179
Table 2-149 – View and dependency representation delimiter NAL unit 188
Table 2-150 – Implied hierarchy_layer_index if no hierarchy descriptors are used 209
Table 2-151 – Green access unit section syntax 215
Table 2-152 – Green access unit 216
Table 2-153 – Quality Access Unit 219
Table B.1 – DSM-CC syntax 235
Table B.2 – Command_id assigned values 235

Table B.3 – DSM-CC control 236
Table B.4 – Select mode assigned values 237
Table B.5 – DSM-CC Acknowledgement 238
Table B.6 – Time code 239
Table C.1 – Composite_descriptor 245
Table C.2 – Sub-descriptor 245
Table C.3 – Program association table bandwidth usage (bit/s) Number of programs per transport stream 246
Table C.4 – Program map table bandwidth usage (bit/s) Number of programs per transport stream 246
Table D.1 – Re-multiplexing strategy 253
Table E.1 – PES packet header example 257
Table S.1 – J2K Access unit elementary stream header 288
Table S.2 – Operating levels and maximum buffer size for JPEG 2000 broadcast profiles (from Table A.49 in Rec. ITU-T T.800 (2015) | ISO/IEC 15444-1:2016) 293
Table T.1 – 'codecs' parameter values for some specific stream_type values 295
Table U.1 – Variable field length notation example 297
Table U.1*bis* – Table U.1 in equivalent full notation 298
Table U.2 – TEMI access unit 298
Table U.3 – AF descriptor tags 299
Table U.4 – TEMI location descriptor 300
Table U.5 – TEMI URL scheme types 300
Table U.6 – TEMI service types 301
Table U.7 – TEMI base URL descriptor 301
Table U.8 – TEMI timeline descriptor 302
Table U.9 – TEMI MPEG-H_3dAudio_extStreamID descriptor 304
Table U.10 – Boundary descriptor 305
Table U.11 – sequence_number_length_code interpretation 305
Table U.12 – Labelling Descriptor 306
Table U.13 – label_length_code interpretation 306
Table U.14 – label_type values 306
Table U.15 – HEVC tile substream af_descriptor 307
Table W.1 – JPEG XS Access unit elementary stream header (jxes header) 311

List of Figures

Figure Intro. 1 – Simplified overview of the scope of this Recommendation | International Standard xiii
Figure Intro. 2 – Prototypical transport demultiplexing and decoding example xv
Figure Intro. 3 – Prototypical transport multiplexing example xv
Figure Intro. 4 – Prototypical transport stream to program stream conversion xv
Figure Intro. 5 – Prototypical decoder for program streams xvi
Figure 2-1 – Transport stream system target decoder notation 16
Figure 2-2 – Program stream system target decoder notation 63
Figure 2-3 – Target background grid descriptor display area 84
Figure 2-4 – T-STD model extensions for individual ISO/IEC 14496 elementary streams 163
Figure 2-5 – T-STD model for ISO/IEC 14496 content 169
Figure 2-6 – P-STD model for ISO/IEC 14496 Systems stream 172
Figure 2-7 – Timing model for delivery of content and metadata 175
Figure 2-8 – Delivery of metadata in PES packets 176
Figure 2-9 – Metadata signalling and referencing 181
Figure 2-10 – Metadata decoding in the STD 182
Figure 2-11 – T-STD model extensions for Rec. ITU-T H.264 | ISO/IEC 14496-10 video 186
Figure 2-12 – P-STD model extensions for Rec. ITU-T H.264 | ISO/IEC 14496-10 video 188
Figure 2-13 – T-STD model extensions for Rec. ITU-T H.264 | ISO/IEC 14496-10 Video with scalable video sub-bitstreams 189
Figure 2-14 – P-STD model extensions for Rec. ITU-T H.264 | ISO/IEC 14496-10 Video with scalable video sub-bitstreams 192
Figure 2-15 – T-STD model extensions for Rec. ITU-T H.264 | ISO/IEC 14496-10 Video with MVC video sub-bitstreams 194
Figure 2-16 – P-STD model extensions for Rec. ITU-T H.264 | ISO/IEC 14496-10 Video with MVC video sub-bitstreams 197
Figure 2-17 – T-STD model extensions for ISO/IEC 14496-17 text streams 200
Figure 2-18 – T-STD model extensions for single layer HEVC 203
Figure 2-19 – T-STD model extensions for layered transport of HEVC temporal video subsets 204
Figure 2-20 – T-STD model extensions for bitstream-partition-specific CPB operation 207
Figure 2-21 – T-STD model extensions for transport of HEVC tiles through individual ESs 211
Figure 2-22 – T-STD model extensions for transport of HEVC tiles in a common ES using AF descriptors 213
Figure 2-23 – T-STD model extension for transport of HEVC tiles in a common ES ignoring AF descriptors 214
Figure 2-24 – T-STD model extension for green access units 217
Figure 2-25 – Transport stream system target decoder for multiple audio elementary streams 218
Figure 2-26 – Quality Access Unit decoder processing model 220
Figure 2-27 – T-STD model extensions for single layer VVC 222
Figure 2-28 – T-STD model extensions for layered transport of VVC temporal video subsets 224
Figure A.1 – 32-bit CRC decoder model 230
Figure B.1 – Configuration of DSM-CC application 233
Figure B.2 – BSM-CC bitstream decoded as a stand-alone bitstream 233
Figure B.3 – DSM-CC bitstream decoded as part of the system bitstream 234
Figure C.1 – Program and network mapping relationships 243
Figure D.1 – Constant delay model 248
Figure D.2 – STC recovery using PLL 252
Figure F.1 – Transport stream syntax diagram 258
Figure F.2 – PES packet syntax diagram 259
Figure F.3 – Program association section diagram 259
Figure F.4 – Conditional access section diagram 259
Figure F.5 – TS program map section diagram 260
Figure F.6 – Private section diagram 260
Figure F.7 – Program stream diagram 261
Figure F.8 – Program stream map diagram 261
Figure J.1 – Sending system streams over a jitter-inducing network 266
Figure J.2 – Jitter-smoothing using network-layer timestamps 266

Figure J.3 – Integrated dejittering and MPEG-2 decoding 267
Figure R.1 – Example of ISO/IEC 14496 content in a program stream 282
Figure R.2 – Example of ISO/IEC 14496 content in a transport stream 283
Figure R.3 – Usage of MPEG-4 in a transport stream with BIFS scene referring to native PES 284
Figure R.4 – Usage of MPEG-4 in a transport stream with an ODUpdate_descriptor carrying an image ObjectDescriptor in the PMT 285
Figure S.1 – Structure and order of JPEG 2000 access units 290
Figure S.2 – T-STD model extensions for J2K Video 291
Figure U.1 – Stream partitioning into 2 and 5 second segments 305
Figure V.1 – Illustration of HEVC tiled encoding of panoramic content beyond UHD 308
Figure V.2 – Example of HEVC tile substream identification 309
Figure V.3 – Example of subregion layout for a 3 x 3 RoI 309
Figure W.1 – Structure and order of JPEG XS access units 312
Figure W.2 – T-STD model extensions for JPEG XS Video 313