

ISO/IEC TS 23465-3:2023-05 (E)

Card and security devices for personal identification - Programming interface for security devices - Part 3: Proxy

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Symbols and abbreviated terms	2
5	Proxy related requirements	2
5.1	Link between client application and security device	2
5.2	Proxy layers	3
5.2.1	Proxy layer model	3
5.2.2	Resolution layer of ISO/IEC 23465-API calls	3
5.2.3	Layer representing/resolving class model	4
5.2.4	Administration layer for security devices	4
5.2.5	Security related layer	4
5.2.6	Translation layer	4
5.2.7	Exception handler	5
5.2.8	Connectivity related layer	5
5.3	Conditional proxy functionality	5
5.3.1	Multitasking/Multiplexing	5
5.3.2	Crypto functionality	5
5.3.3	Discovery functionality	6
5.3.4	Registration functionality	6
6	Instantiation of class objects	6
6.1	Class model	6
6.2	Process of instantiation	7
6.3	Life cycle of an instance	8
7	Services of the proxy	8
7.1	Security device management	8
7.1.1	Identification of security device	8
7.1.2	Retrieval of security device information	9
7.1.3	Security device related functionality	9
7.2	Security related layer	10
7.2.1	General	10
7.2.2	Security conditions and fulfilment	10
7.2.3	Interpretation of ISO/IEC 7816-4 security conditions	11
7.2.4	Security attributes for complex multistep authentication	12
7.2.5	Security attribute "user verification"	12
7.2.6	Security attribute "authentication"	12
7.2.7	Security attribute "secure messaging" (SM)	12
7.2.8	Implicit fulfilment of security conditions	13
7.3	Connectivity layer	13
7.4	Multi-client/multi-security device support	13
7.4.1	Task management	13
7.4.2	Management of security devices	13
8	Life cycle model of the proxy	14
8.1	Start-up phase	14
8.2	Initialization and administration	14
Annex A (informative)	Example of client API call processing with proxy functionality	15
Bibliography		19