ISO/IEC TS 23465-3:2023-05 (E)

Card and security devices for personal identification - Programming interface for security devices - Part 3: Proxy

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Terms and definitions 1

4 Symbols and abbreviated terms 2

5 Proxy related requirements 2
5.1 Link between client application and security device 2
5.2 Proxy layers 3
5.2.1 Proxy layer model 3
5.2.2 Resolution layer of ISO/IEC 23465-API calls 3
5.2.3 Layer representing/resolving class model 4
5.2.4 Administration layer for security devices 4
5.2.5 Security related layer 4
5.2.6 Translation layer 4
5.2.7 Exception handler 5
5.2.8 Connectivity related layer 5
5.3 Conditional proxy functionality 5
5.3.1 Multitasking/Multiplexing 5
5.3.2 Crypto functionality 5
5.3.3 Discovery functionality 6
5.3.4 Registration functionality 6

6 Instantiation of class objects 6
6.1 Class model 6
6.2 Process of instantiation 7
6.3 Life cycle of an instance 8

7 Services of the proxy 8
7.1 Security device management 8
7.1.1 Identification of security device 8
7.1.2 Retrieval of security device information 9
7.1.3 Security device related functionality 9
7.2 Security related layer 10
7.2.1 General 10
7.2.2 Security conditions and fulfilment 10
7.2.3 Interpretation of ISO/IEC 7816-4 security conditions 11
7.2.4 Security attributes for complex multistep authentication 12
7.2.5 Security attribute "user verification" 12
7.2.6 Security attribute "authentication" 12
7.2.7 Security attribute "secure messaging" (SM) 12
7.2.8 Implicit fulfilment of security conditions 13
7.3 Connectivity layer 13
7.4 Multi-client/multi-security device support 13
7.4.1 Task management 13
7.4.2 Management of security devices 13

8 Life cycle model of the proxy 14
8.1 Start-up phase 14
8.2 Initialization and administration 14

Annex A (informative) Example of client API call processing with proxy functionality 15

Bibliography 19