

ISO/IEC 15444-17:2023-06 (E)

Information technology - JPEG 2000 image coding system - Part 17: Extensions for coding of discontinuous media

Contents		Page
1	Scope.....	1
2	Normative references	1
3	Terms and definitions.....	1
4	Abbreviations	2
5	5 Conventions.....	3
6	Conformance.....	3
6.1	Codestream conformance	3
6.2	Decoder.....	3
7	Breakpoint component structure.....	4
7.1	Breakpoint components and the reference grid.....	4
7.2	Division of breakpoint resolutions into cells, arcs and the CL band.....	4
7.3	Division of breakpoint resolutions into precincts and code-blocks	5
7.4	Root and non-root arc breakpoint associations.....	7
7.5	Breakpoint values and vertices	8
8	Breakpoint-dependent spatial wavelet transformation	10
8.1	Overview	10
8.2	TriBPT-dependent irreversible transforms	11
8.2.1	Introduction.....	11
8.2.2	Arcs with $tb = 0$	12
8.2.3	Arcs with $tb = 3$	13
8.2.4	Arcs with $tb = 2$	13
8.2.5	Arcs with $tb = 1$	17
8.3	TriBPT-dependent reversible transforms.....	21
8.3.1	Arcs with $tb = 0$	22
8.3.2	Arcs with $tb = 3$	22
8.3.3	Arcs with $tb = 2$	22
8.3.4	Arcs with $tb = 1$	22
8.4	QuadBPT-dependent transforms.....	23
8.4.1	Introduction.....	23
8.4.2	BD_2D_SR phase 1	24
8.4.3	BD_2D_SR phase 2	26
9	Decoding of breakpoint code-blocks.....	28
9.1	Embedded bit-plane decoding of breakpoints.....	28
9.2	Inter-band coding mode (BPT_INTER).....	29
9.3	Cell-based scanning patterns and CBAP-based block flipping.....	30
9.4	QuadBPT decoding procedures	32
9.4.1	MQ Coder contexts and initial states for QuadBPT decoding	32
9.4.2	Derivation of context labels for QuadBPT CL band significance coding passes.....	33
9.4.3	Non-root significance decoding for QuadBPT CL code-blocks	35
9.4.4	Root significance decoding for QuadBPT CL code-blocks	36
9.4.5	Root significance decoding for QuadBPT LL code-blocks	37
9.4.6	Position refinement decoding for QuadBPT code-blocks.....	37
9.5	TriBPT decoding procedures	38
9.5.1	MQ Coder contexts and initial states for TriBPT decoding.....	38
9.5.2	Derivation of context labels for TriBPT CL band significance coding passes.....	39
9.5.3	Non-root significance decoding for TriBPT CL code-blocks	42
9.5.4	Root significance decoding for TriBPT CL code-blocks	43
9.5.5	Root significance decoding for TriBPT LL code-blocks	44
9.5.6	Position refinement decoding for TriBPT code-blocks.....	45
9.6	Quality layers and packets for breakpoint components	45

10	Reconstruction of breakpoint components	47
10.1	Overview	47
10.2	Direct induction step.....	47
10.2.1	Introduction.....	47
10.2.2	Extrapolation Qualifier for TriBPT direct induction.....	48
10.3	QuadBPT spatial induction.....	49
10.3.1	Introduction.....	49
10.4	TriBPT spatial induction.....	51
10.4.1	TriBPT induction modes and corner notation	51
10.4.2	4-arc mode	51
10.4.3	3-arc mode	52
10.4.4	Extrapolation qualifier for TriBPT spatial induction	53
10.4.5	Rounding policies for TriBPT spatial induction	56
10.4.6	Image boundary handling for TriBPT.....	56
Annex A	(This annex forms an integral part of this Recommendation International Standard.) – Codestream syntax... 58	
A.1	General	58
A.2	SIZ marker segment.....	58
A.3	CAP marker segment.....	58
A.4	Hierarchical data type (HDT) marker segment.....	59
A.5	COD and COC marker segments.....	59
Annex B	(This annex does not form an integral part of this Recommendation International Standard) –	
	Hierarchical breakpoint encapsulation and raw file format	62
B.1	General	62
B.2	Raster organization of breakpoints	62
B.3	16- and 32-bit packed breakpoint values	63
B.4	A raw file format for breakpoints	64
Bibliography	67

List of Tables

	Page
Table 1 – Constraints on PPx and PPy precinct size parameters breakpoint components	6
Table 2 – MQ coder contexts for QuadBPT CL code-block decoding passes. State index values correspond to the Qe values and probability estimation transitions tabulated in Rec. ITU-T T.800 ISO/IEC 15444-1	33
Table 3 – Context labels from Table 2 that are used for QuadBPT LL code-block decoding passes.....	33
Table 4 – MQ coder contexts for TriBPT CL code-block decoding passes. State index values correspond to the Qe values and probability estimation transitions tabulated in Rec. ITU-T T.800 ISO/IEC 15444-1	38
Table 5 – Context labels from Table 4 that are used for TriBPT LL code-block decoding passes.....	38
Table A.1 – Extensions and constraints to marker segments specified in Rec. ITU-T T.800 ISO/IEC 15444-1 and new marker segments specified in this Recommendation International Standard	58
Table A.2 – Ccap ¹⁷ Syntax and Semantics	58
Table A.3 – Hierarchical data type parameter values	59
Table A.4 – Allowed values for Ihdt ⁱ	59
Table A.5 – Scod and Scoc semantics for bit 5	60
Table A.6 – SXcod bit fields specified by this Recommendation International Standard	60
Table A.7 – Allowed values for the SEcod field	61
Table A.8 – Transformation for the SPcod and SPcoc parameters when Dc ≠ 0.....	61

List of Figures

	Page
Figure 1 – Arc arrangements within a single 2-span. A 2×2 cell is shown here with solid grid-points. See Figure 2 for other geometric relationships between cells and 2-spans.....	5
Figure 2 – Cell-span geometry for each of the four possible code-block anchor points.....	5
Figure 3 – Root arc (dotted lines) and non-root arcs (solid lines).....	8
Figure 4 – Possible break locations (tick-points) at the finest resolution, with $FB = 2$, shown for the QuadBPT case. Also shows the mapping of vertices with precision Pb to tick-points	9
Figure 5 – Stages of the breakpoint dependent inverse discrete wavelet transform	10
Figure 6 – Interleaving of sub-band coefficients to a triangular grid for a given resolution r	12
Figure 7 – Update step examples for TriBPT-LR arrangement.....	12
Figure 8 – Predict step examples for a horizontal arc.....	12
Figure 9 – Example of direct induction of a breakpoint	14
Figure 10 – Example illustrating spatially induced breaks	14
Figure 11 – Example of a spatially induced breakpoint on a non-root arc for the TriBPT-LR arrangement.....	15
Figure 12 – Examples showing base-arc bsa and gradients $Gbsa$ and $Gwdg$ along with corresponding binary flags ORN and $DRCTNX_FLAG$ induced for root arcs.....	16
Figure 13 – Example showing base-arc bsa and gradients $Gbsa$ and $Gwdg$ along with corresponding binary flags ORN and $DRCTNX_FLAG$ induced for diagonal non-root arc containing a spatially induced break	16
Figure 14 – Examples of arcs prl parallel in orientation to root arcs centred at p and containing a spatially induced break. Gradient calculated across arc prl is denoted as $Gprl$	19
Figure 15 – Example of arc prl parallel to the non-root arc centred and at p and containing a spatially induced break. Corresponding gradient across arc prl is shown as $Gprl$	19
Figure 16 – Algorithm for determining the gradient Gb based on validity flags VALID_WDG and VALID_PRL and corresponding attributes.....	20
Figure 17 – Parent 4-span arrangement at resolution $rrt = r - 1$ for arc a at resolution r and centred at p	21
Figure 18 – Algorithm for determining the gradient Gb for the reversible transform, based on validity flags VALID_WDG and VALID_PRL and corresponding attributes.....	23
Figure 19 – Interleaving of sub-band coefficients to a quadrilateral grid for a given resolution r	23
Figure 20 – Phase 1 update step for (even, even) location $2n, 2m$	24
Figure 21 – Phase 1 update step for (even, odd) location $2n, 2m + 1$ and (odd, even) location $2n + 1, 2m$	25
Figure 22 – Phase 1 predict step for (odd, odd) location $2n + 1, 2m + 1$ with source locations of Ic, r *shown.....	26
Figure 23 – Phase 2 update step for (even, even) location $2n, 2m$	27
Figure 24 – Phase 2 predict step examples	28
Figure 25 – Canonical scanning pattern used for the significance coding passes of CL band code-blocks in a QuadBPT component. In this case, missing cells within a 2×2 group are not included in the scan	30
Figure 26 – Canonical scanning pattern used for the significance coding passes of CL band code-blocks in TriLR components. Arcs belonging to cells that lie beyond the code-block boundaries are included in the significance coding passes	31
Figure 27 – Canonical scanning pattern used for the significance coding passes of CL band code-blocks in TriRL components. Arcs belonging to cells that lie beyond the code-block boundaries are included in the significance coding passes	31
Figure 28 – Neighbouring cells and arcs involved in forming coding contexts for QuadBPT significance decoding in CL band code-blocks	34
Figure 29 – Neighbouring cells and arcs involved in forming coding contexts for TriLR significance decoding in CL band code-blocks	39

Figure 30 – Neighbouring cells and arcs involved in forming coding contexts for TriRL significance decoding in CL band code-blocks	40
Figure 31 – Breakpoint synthesis stages.....	47
Figure 32 – Relationship between non-root and parent arcs during direct induction in synthesis stage r , shown for the case of horizontal arcs.....	48
Figure 33 – Rounding policies used in QuadBPT spatial induction, showing different induction examples in three of the four 2-spans within a 4-span.....	50
Figure 34 – Arc and corner labels for the TriBPT-LR arrangement.....	51
Figure 35 – 4-arc mode spatial induction examples for the TriBPT-LR arrangement.....	52
Figure 36 – 3-arc mode spatial induction examples for the TriBPT-LR arrangement.....	53
Figure 37 – Example of intersection points, arcs and grid-lines required for determining the extrapolation qualifier for a spatially induced break	55
Figure 38 – Examples of rounding policy for 3-arc mode spatial induction when the inducing line intersects the root arc X at its centre. The direction of rounding is highlighted by the black arrows	56
Figure A.1 – Hierarchical data type syntax	59
Figure A.2 – Coding style default syntax	60
Figure A.3 – Coding style component syntax.....	60
Figure B.1 – Bit fields within 16- and 32-bit packed breakpoint representations. The most significant bit of the 16- or 32-bit integer, as appropriate, is shown at the top of the figure, while the least significant bit appears at the bottom.....	64