

ISO/IEC 13818-1:2023-12 (E)

Information technology - Generic coding of moving pictures and associated audio information - Part 1: Systems

Contents

Page

SECTION 1 – GENERAL.....	1
1.1 Scope.....	1
1.2 Normative references	1
SECTION 2 – TECHNICAL ELEMENTS	4
2.1 Definitions.....	4
2.2 Symbols and abbreviations	12
2.3 Method of describing bit stream syntax	14
2.4 Transport stream bitstream requirements	15
2.5 Program stream bitstream requirements.....	63
2.6 Program and program element descriptors.....	77
2.7 Restrictions on the multiplexed stream semantics	166
2.8 Compatibility with ISO/IEC 11172	170
2.9 Registration of copyright identifiers	170
2.10 Registration of private data format.....	171
2.11 Carriage of ISO/IEC 14496 data	171
2.12 Carriage of metadata	183
2.13 Carriage of ISO 15938 data.....	192
2.14 Carriage of Rec. ITU-T H.264 ISO/IEC 14496-10 video	192
2.15 Carriage of ISO/IEC 14496-17 text streams	208
2.16 Carriage of auxiliary video streams	210
2.17 Carriage of HEVC.....	210
2.18 Carriage of green access units.....	224
2.19 Carriage of ISO/IEC 23008-3 MPEG-H 3D audio data.....	226
2.20 Carriage of Quality Access Units in MPEG-2 sections.....	228
2.21 Carriage of sample variants.....	229
2.22 Carriage of Media Orchestration Access Units	230
2.23 Carriage of VVC	230
2.24 Carriage of EVC	235
2.25 Carriage of LCEVC	238
Annex A CRC decoder model.....	240
A.1 CRC decoder model.....	240
Annex B Digital storage medium command and control (DSM-CC).....	241
B.1 Introduction.....	241
B.2 General elements.....	242
B.3 Technical elements.....	244
Annex C Program-specific information.....	250
C.1 Explanation of program-specific information in transport streams.....	250
C.2 Introduction.....	250
C.3 Functional mechanism	250
C.4 The mapping of sections into transport stream packets.....	251
C.5 Repetition rates and random access	251
C.6 What is a program?	252
C.7 Allocation of program_number	252
C.8 Usage of PSI in a typical system.....	252
C.9 The relationships of PSI structures	253
C.10 Bandwidth utilization and signal acquisition time	255
Annex D Systems timing model and application implications of this Recommendation International Standard.....	258
D.1 Introduction.....	258

Annex E Data transmission applications	267
E.1 General considerations	267
E.2 Suggestion.....	267
Annex F Graphics of syntax for this Recommendation International Standard.....	268
F.1 Introduction.....	268
Annex G General information	272
G.1 General information	272
Annex H Private data.....	273
H.1 Private data.....	273
Annex I Systems conformance and real-time interface	274
I.1 Systems conformance and real-time interface.....	274
Annex J Interfacing jitter-inducing networks to MPEG-2 decoders.....	275
J.1 Introduction.....	275
J.2 Network compliance models.....	275
J.3 Network specification for jitter smoothing	276
J.4 Example decoder implementations	277
Annex K Splicing transport streams	278
K.1 Introduction.....	278
K.2 The different types of splicing point	278
K.3 Decoder behaviour on splices	279
Annex L Registration procedure (see 2.9).....	281
L.1 Procedure for the request of a Registered Identifier (RID)	281
L.2 Responsibilities of the Registration Authority	281
L.3 Responsibilities of parties requesting an RID	281
L.4 Appeal procedure for denied applications.....	281
Annex M Registration application form (see 2.9)	283
M.1 Contact information of organization requesting a Registered Identifier (RID).....	283
M.2 Statement of an intention to apply the assigned RID	283
M.3 Date of intended implementation of the RID	283
M.4 Authorized representative	283
M.5 For official use only of the Registration Authority	283
Annex N Registration Authority Diagram of administration structure (see 2.9)	284
Annex O Registration procedure (see 2.10).....	285
O.1 Procedure for the request of an RID.....	285
O.2 Responsibilities of the Registration Authority	285
O.3 Contact information for the Registration Authority	285
O.4 Responsibilities of parties requesting an RID	285
O.5 Appeal procedure for denied applications.....	285
Annex P Registration application form	287
P.1 Contact information of organization requesting an RID	287
P.2 Request for a specific RID.....	287
P.3 Short description of RID that is in use and date system that was implemented	287
P.4 Statement of an intention to apply the assigned RID	287
P.5 Date of intended implementation of the RID	287
P.6 Authorized representative	287
P.7 For official use of the Registration Authority	287
Annex Q T-STD and P-STD buffer models for ISO/IEC 13818-7 ADTS	288
Q.1 Introduction.....	288
Q.2 Leak rate from transport buffer	288
Q.3 Buffer size.....	288
Q.4 Conclusion	289
Annex R Carriage of ISO/IEC 14496 scenes in Rec. ITU-T H.222.0 ISO/IEC 13818-1	291
R.1 Content access procedure for ISO/IEC 14496 program components within a program stream.....	291
R.2 Content access procedure for ISO/IEC 14496 program components within a transport stream	292
Annex S Carriage of JPEG 2000 part 1 video over MPEG-2 transport streams.....	296
S.1 Introduction.....	296

S.2	J2K video access unit, J2K video elementary stream, J2K video sequence and J2K still picture.....	296
S.3	Optional J2K block mode for high resolution support	296
S.4	Optional J2K stripe mode for Ultra-Low Latency	297
S.5	Elementary stream header (elsm) and mapping to PES packets	297
S.6	J2K transport constraints.....	300
S.7	Interpretation of flags in adaptation and PES headers for J2K video elementary streams	301
S.8	T-STD extension for J2K video elementary streams	301
Annex T	MIME type for MPEG-2 transport streams	304
T.1	Introduction.....	304
T.2	MIME type and subtype.....	304
T.3	Security considerations	305
T.4	Parameters.....	305
Annex U	Carriage of timeline and external media information over MPEG-2 transport streams	307
U.1	Introduction.....	307
U.2	TEMI access unit and TEMI elementary stream.....	308
U.3	AF descriptors.....	309
Annex V	Transport of HEVC tiles	318
V.1	Introduction.....	318
V.2	HEVC tile substream identification example.....	319
V.3	Subregion layout example.....	319
Annex W	Carriage of JPEG XS part 1 video over MPEG-2 Transport Streams	321
W.1	Introduction.....	321
W.2	JPEG XS video access unit, JPEG XS video elementary stream, JPEG XS video sequence and JPEG XS still picture	321
W.3	Elementary stream header (jxes) and mapping to PES packets.....	321
W.4	JPEG XS transport constraints	322
W.5	Interpretation of flags in adaptation field and PES packet for JPEG XS video elementary streams.....	323
W.6	T-STD extension for JPEG XS video elementary streams.....	323
Bibliography	326

Table 2-1 – Transport stream.....	26
Table 2-2 – Transport packet of this Recommendation International Standard.....	26
Table 2-3 – PID table	27
Table 2-4 – Scrambling control values	27
Table 2-5 – Adaptation field control values	28
Table 2-6 – Transport stream adaptation field.....	28
Table 2-7 – Splice parameters Table 1 Simple Profile Main Level, Main Profile Main Level, SNR Profile Main Level (both layers), Spatial Profile High-1440 Level (base layer), High Profile Main Level (middle + base layers), Multi-view Profile Main Level (base layer) Video	35
Table 2-8 – Splice parameters Table 2 Main Profile Low Level, SNR Profile Low Level (both layers), High Profile Main Level (base layer), Multi-view Profile Low Level (base layer) Video.....	35
Table 2-9 – Splice parameters Table 3 Main Profile High-1440 Level, Spatial Profile High-1440 Level (all layers), High Profile High-1440 Level (middle + base layers), Multi-view Profile High-1440 Level (base layer) Video	36
Table 2-10 – Splice parameters Table 4 Main Profile High Level, High Profile High-1440 Level (all layers), High Profile High Level (middle + base layers), Multi-view Profile High Level (base layer) Video.....	36
Table 2-11 – Splice parameters Table 5 SNR Profile Low Level (base layer) Video	36
Table 2-12 – Splice parameters Table 6 SNR Profile Main Level (base layer) Video	36
Table 2-13 – Splice parameters Table 7 Spatial Profile High-1440 Level (middle + base layers) Video	37
Table 2-14 – Splice parameters Table 8 High Profile Main Level (all layers), High Profile High-1440 Level (base layer) Video	37
Table 2-15 – Splice parameters Table 9 High Profile High Level (base layer), Multi-view Profile Main Level (both layers) Video	37
Table 2-16 – Splice parameters Table 10 High Profile High Level (all layers), Multi-view Profile High-1440 Level (both layers) Video	38
Table 2-17 – Splice parameters Table 11 4:2:2 Profile Main Level Video	38
Table 2-18 – Splice parameters Table 12 Multi-view Profile Low Level (both layers) Video.....	38
Table 2-19 – Splice parameters Table 13 Multi-view Profile High Level (both layers) Video.....	38
Table 2-20 – Splice parameters Table 14 4:2:2 Profile High Level Video.....	39
Table 2-21 – PES packet	39
Table 2-22 – Stream_id assignments.....	42
Table 2-23 – PES scrambling control values.....	43
Table 2-24 – Trick mode control values.....	48
Table 2-25 – Field_id field control values.....	49
Table 2-26 – Coefficient selection values.....	49
Table 2-27 – Stream_id_extension assignments.....	51
Table 2-28 – Program-specific information.....	52
Table 2-29 – Program-specific information pointer	54
Table 2-30 – Program association section	54
Table 2-31 – table_id assignment values.....	55
Table 2-32 – Conditional access section.....	56
Table 2-33 – Transport stream program map section	57
Table 2-34 – Stream type assignments	58
Table 2-35 – Private section	61
Table 2-36 – The transport stream description table	62
Table 2-37 – Program stream	68
Table 2-38 – Program stream pack.....	68
Table 2-39 – Program stream pack header	69
Table 2-40 – Program stream system header.....	70
Table 2-41 – Program stream map.....	73
Table 2-42 – Program stream directory packet.....	75
Table 2-43 – Intra_coded indicator.....	76
Table 2-44 – Coding_parameters indicator	77
Table 2-45 – Program and program element descriptors.....	77
Table 2-46 – Video stream descriptor	79

Table 2-47 – Frame rate code	79
Table 2-48 – Audio stream descriptor	80
Table 2-49 – Hierarchy descriptor	80
Table 2-50 – Hierarchy_type field values	82
Table 2-51 – Registration descriptor	82
Table 2-52 – Data stream alignment descriptor	83
Table 2-53 – Video stream alignment values	83
Table 2-54 – AVC video stream alignment values	84
Table 2-55 – HEVC video stream alignment values	84
Table 2-56 – Audio stream alignment values	84
Table 2-57 – VVC video stream alignment values	85
Table 2-58 – EVC video stream alignment values	85
Table 2-59 – Target background grid descriptor	86
Table 2-60 – Video window descriptor	86
Table 2-61 – Conditional access descriptor	87
Table 2-62 – ISO 639 language descriptor	87
Table 2-63 – Audio type values	88
Table 2-64 – System clock descriptor	89
Table 2-65 – Multiplex buffer utilization descriptor	89
Table 2-66 – Copyright descriptor	90
Table 2-67 – Maximum bitrate descriptor	90
Table 2-68 – Private data indicator descriptor	91
Table 2-69 – Smoothing buffer descriptor	91
Table 2-70 – STD descriptor	92
Table 2-71 – IBP descriptor	92
Table 2-72 – MPEG-4 video descriptor	93
Table 2-73 – MPEG-4 audio descriptor	93
Table 2-75 – IOD descriptor	96
Table 2-76 – SL descriptor	96
Table 2-77 – FMC descriptor	97
Table 2-78 – External_ES_ID descriptor	97
Table 2-79 – Muxcode descriptor	98
Table 2-80 – M4MuxBufferSize descriptor	98
Table 2-81 – MultiplexBuffer descriptor	99
Table 2-82 – M4MuxTiming descriptor	99
Table 2-83 – Content labelling descriptor	100
Table 2-84 – Metadata_application_format	100
Table 2-85 – Content_time_base_indicator values	101
Table 2-86 – Metadata pointer descriptor	102
Table 2-87 – Metadata format values	102
Table 2-88 – MPEG_carriage_flags	103
Table 2-89 – Metadata descriptor	104
Table 2-90 – decoder_config_flags	105
Table 2-91 – Metadata STD descriptor	106
Table 2-92 – AVC video descriptor	106
Table 2-93 – AVC timing and HRD descriptor	108
Table 2-94 – MPEG-2 AAC_audio_descriptor	109
Table 2-95 – MPEG-2 AAC_additional_information field values	110
Table 2-96 – MPEG-4 text descriptor	110
Table 2-97 – MPEG-4 audio extension descriptor	110
Table 2-98 – Auxiliary video stream descriptor	111
Table 2-99 – SVC extension descriptor	112
Table 2-100 – MVC extension descriptor	113
Table 2-101 – J2K video descriptor	114

Table 2-102 – Example frame rates based on DEN_frame_rate and NUM_frame_rate values	116
Table 2-103 – MVC operation point descriptor.....	118
Table 2-104 – MPEG2_stereoscopic_video_format_descriptor syntax	119
Table 2-105 – Stereoscopic_program_info_descriptor syntax	119
Table 2-106 – Stereoscopic_service_type values	120
Table 2-107 – Stereoscopic_video_info_descriptor syntax	120
Table 2-108 – Upsampling factor values	121
Table 2-109 – Extension descriptor.....	121
Table 2-110 – Extension descriptor tag values	124
Table 2-111 – Transport_profile_descriptor syntax	125
Table 2-112 – Transport_profile values	125
Table 2-113 – HEVC video descriptor	126
Table 2-114 – Semantics of HDR_WGC_idc.....	128
Table 2-115 – HEVC timing and HRD descriptor.....	128
Table 2-116 – Adaptation field extension descriptor.....	129
Table 2-117 – HEVC operation point descriptor.....	130
Table 2-118 – HEVC hierarchy extension descriptor.....	132
Table 2-119 – Semantics of extension dimension bits.....	132
Table 2-120 – Green extension descriptor.....	133
Table 2-121 – MPEG-H 3D audio descriptor.....	134
Table 2-122 – MPEG-H 3D audio config descriptor.....	134
Table 2-123 – MPEG-H 3D audio scene descriptor	135
Table 2-124 – MPEG-H 3D audio text label descriptor	138
Table 2-125 – MPEG-H 3D audio multi-stream descriptor.....	140
Table 2-126 – MPEG-H 3D audio DRC and Loudness descriptor()	141
Table 2-127 – MPEG-H 3D audio command descriptor	143
Table 2-128 – Quality extension descriptor.....	144
Table 2-129 – Virtual segmentation descriptor	145
Table 2-130 – HEVC tile substream descriptor.....	146
Table 2-131 – HEVC subregion descriptor	147
Table 2-132 – JPEG XS video descriptor.....	149
Table 2-133 – VVC video descriptor.....	151
Table 2-134 – Semantics of HDR_WGC_idc.....	152
Table 2-135 – SDR widely used video property combinations	153
Table 2-136 – WCG widely used video property combinations.....	153
Table 2-137 – HDR/WCG widely used video property combinations	153
Table 2-138 – No Indication.....	154
Table 2-139 – VVC timing and HRD descriptor.....	154
Table 2-140 – EVC video descriptor	156
Table 2-141 – EVC timing and HRD descriptor	157
Table 2-142 – LCEVC video descriptor.....	158
Table 2-143 – LCEVC linkage descriptor	159
Table 2-144 – Media service kind descriptor	160
Table 2-145 – media_description_flag	160
Table 2-146 – Media type indicator.....	160
Table 2-147 – ID_length_code	161
Table 2-148 – ID_type.....	161
Table 2-149 – configuration type values	161
Table 2-150 – lang_len_indicator.....	162
Table 2-151 – Media service type values	162
Table 2-152 – Carriage of individual ISO/IEC 14496 streams in Rec. ITU-T H.222.0 ISO/IEC 13818-1	172
Table 2-153 – Section syntax for transport of ISO/IEC 14496 stream.....	177
Table 2-154 – ISO/IEC defined options for carriage of an ISO/IEC 14496 scene and associated streams in Rec. ITU-T H.222.0 ISO/IEC 13818-1	180
Table 2-155 – Metadata Access Unit Wrapper.....	187

Table 2-156 – Metadata AU cell	187
Table 2-157 – Cell fragment indication	187
Table 2-158 – Section syntax for transport of metadata	188
Table 2-159 – Section fragment indication	189
Table 2-160 – View and dependency representation delimiter NAL unit	198
Table 2-161 – Implied hierarchy_layer_index if no hierarchy descriptors are used	218
Table 2-162 – Green access unit section syntax	225
Table 2-163 – Green access unit	225
Table 2-164 – Quality Access Unit	228
Table B.1 – DSM-CC syntax	245
Table B.2 – Command_id assigned values	245
Table B.3 – DSM-CC control	246
Table B.4 – Select mode assigned values	247
Table B.5 – DSM-CC Acknowledgement	248
Table B.6 – Time code	249
Table C.1 – Composite_descriptor	255
Table C.2 – Sub-descriptor	255
Table C.3 – Program association table bandwidth usage (bit/s) Number of programs per transport stream	256
Table C.4 – Program map table bandwidth usage (bit/s) Number of programs per transport stream	256
Table D.1 – Re-multiplexing strategy	263
Table E.1 – PES packet header example	267
Table S.1 – J2K Access unit elementary stream header	298
Table S.2 – Operating levels and maximum buffer size for JPEG 2000 broadcast profiles (from Table A.49 in Rec. ITU-T T.800 (2015) ISO/IEC 15444-1:2016)	303
Table T.1 – 'codecs' parameter values for some specific stream_type values	305
Table U.1 – Variable field length notation example	307
Table U.1bis – Table U.1 in equivalent full notation	308
Table U.2 – TEMI access unit	308
Table U.3 – AF descriptor tags	309
Table U.4 – TEMI location descriptor	310
Table U.5 – TEMI URL scheme types	310
Table U.6 – TEMI service types	311
Table U.7 – TEMI base URL descriptor	311
Table U.8 – TEMI timeline descriptor	312
Table U.9 – TEMI MPEG-H_3dAudio_extStreamID descriptor	314
Table U.10 – Boundary descriptor	315
Table U.11 – sequence_number_length_code interpretation	315
Table U.12 – Labelling Descriptor	316
Table U.13 – label_length_code interpretation	316
Table U.14 – label_type values	317
Table U.15 – HEVC tile substream af_descriptor	317
Table W.1 – JPEG XS Access unit elementary stream header (jxes header)	321

Figure Intro. 1 – Simplified overview of the scope of this Recommendation International Standard	xiv
Figure Intro. 2 – Prototypical transport demultiplexing and decoding example.....	xvi
Figure Intro. 3 – Prototypical transport multiplexing example.....	xvi
Figure Intro. 4 – Prototypical transport stream to program stream conversion	xvi
Figure Intro. 5 – Prototypical decoder for program streams.....	xvii
Figure 2-1 – Transport stream system target decoder notation.....	16
Figure 2-2 – Program stream system target decoder notation	63
Figure 2-3 – Target background grid descriptor display area.....	85
Figure 2-4 – Media Service Kind Descriptor semantics at program level.....	165
Figure 2-5 – Media Program Kind Descriptor semantics at elementary stream level	165
Figure 2-6 – T-STD model extensions for individual ISO/IEC 14496 elementary streams	172
Figure 2-7 – T-STD model for ISO/IEC 14496 content.....	178
Figure 2-8 – P-STD model for ISO/IEC 14496 Systems stream	181
Figure 2-9 – Timing model for delivery of content and metadata	184
Figure 2-10 – Delivery of metadata in PES packets	185
Figure 2-11 – Metadata signalling and referencing	191
Figure 2-12 – Metadata decoding in the STD.....	191
Figure 2-13 – T-STD model extensions for Rec. ITU-T H.264 ISO/IEC 14496-10 video.....	195
Figure 2-14 – P-STD model extensions for Rec. ITU-T H.264 ISO/IEC 14496-10 video.....	197
Figure 2-15 – T-STD model extensions for Rec. ITU-T H.264 ISO/IEC 14496-10 Video with scalable video sub-bitstreams.....	198
Figure 2-16 – P-STD model extensions for Rec. ITU-T H.264 ISO/IEC 14496-10 Video with scalable video sub-bitstreams.....	201
Figure 2-17 – T-STD model extensions for Rec. ITU-T H.264 ISO/IEC 14496-10 Video with MVC video sub-bitstreams.....	203
Figure 2-18 – P-STD model extensions for Rec. ITU-T H.264 ISO/IEC 14496-10 Video with MVC video sub-bitstreams.....	207
Figure 2-19 – T-STD model extensions for ISO/IEC 14496-17 text streams.....	209
Figure 2-20 – T-STD model extensions for single layer HEVC.....	212
Figure 2-21 – T-STD model extensions for layered transport of HEVC temporal video subsets.....	214
Figure 2-22 – T-STD model extensions for bitstream-partition-specific CPB operation	216
Figure 2-23 – T-STD model extensions for transport of HEVC tiles through individual ESs	220
Figure 2-24 – T-STD model extensions for transport of HEVC tiles in a common ES using AF descriptors.....	222
Figure 2-25 – T-STD model extension for transport of HEVC tiles in a common ES ignoring AF descriptors	224
Figure 2-26 – T-STD model extension for green access units.....	226
Figure 2-27 – Transport stream system target decoder for multiple audio elementary streams	228
Figure 2-28 – Quality Access Unit decoder processing model.....	229
Figure 2-29 – T-STD model extensions for single layer VVC	231
Figure 2-30 – T-STD model extensions for layered transport of VVC temporal video subsets	233
Figure 2-31 – T-STD model extensions for single layer EVC	236
Figure A.1 – 32-bit CRC decoder model.....	240
Figure B.1 – Configuration of DSM-CC application.....	243
Figure B.2 – BSM-CC bitstream decoded as a stand-alone bitstream	243
Figure B.3 – DSM-CC bitstream decoded as part of the system bitstream	244
Figure C.1 – Program and network mapping relationships	253
Figure D.1 – Constant delay model	258
Figure D.2 – STC recovery using PLL.....	262
Figure F.1 – Transport stream syntax diagram	268
Figure F.2 – PES packet syntax diagram.....	269
Figure F.3 – Program association section diagram.....	269
Figure F.4 – Conditional access section diagram	269
Figure F.5 – TS program map section diagram	270
Figure F.6 – Private section diagram.....	270
Figure F.7 – Program stream diagram	271

Figure F.8 – Program stream map diagram	271
Figure J.1 – Sending system streams over a jitter-inducing network	276
Figure J.2 – Jitter-smoothing using network-layer timestamps	276
Figure J.3 – Integrated dejittering and MPEG-2 decoding	277
Figure R.1 – Example of ISO/IEC 14496 content in a program stream	292
Figure R.2 – Example of ISO/IEC 14496 content in a transport stream.....	293
Figure R.3 – Usage of MPEG-4 in a transport stream with BIFS scene referring to native PES	294
Figure R.4 – Usage of MPEG-4 in a transport stream with an ODUpdate_descriptor carrying an image ObjectDescriptor in the PMT	295
Figure S.1 – Structure and order of JPEG 2000 access units.....	300
Figure S.2 – T-STD model extensions for J2K Video.....	301
Figure U.1 – Stream partitioning into 2 and 5 second segments	315
Figure V.1 – Illustration of HEVC tiled encoding of panoramic content beyond UHD.....	318
Figure V.2 – Example of HEVC tile substream identification	319
Figure V.3 – Example of subregion layout for a 3 x 3 RoI	319
Figure W.1 – Structure and order of JPEG XS access units	322
Figure W.2 – T-STD model extensions for JPEG XS Video.....	324