ISO/IEC 4396-3:2023-12 (E)

Telecommunications and information exchange between systems - Recursive inter-network architecture - Part 3: Common distributed application protocol

Contents

Page

Foreword ..... **v**

Introduction ..... **vi**

1 Scope **1**

2 Normative references **1**

3 Terms and definitions **1**

4 Description of CDAP **3**
4.1 CDAP –RINA application protocol 3
4.2 Application entities (AEs) within applications 3
4.3 Objects 4
4.4 Method calls on objects 4
4.5 Object model 4
4.6 Application connection 5
4.7 Application connection state vector (ACSV) 5
4.8 Requestor and responder roles 5
4.9 Validation of values/operations by CDAP 5
4.10 CDAP application programming interface (API) 6
4.11 Standardization and policies 6

5 Specification **6**
5.1 CDAP profile — Policies and standardization 6
5.2 Application connection establishment 7
5.3 Application connection state vector (ACSV) 7
5.4 Objects and the object model 9
5.4.1 Object properties 9
5.4.2 Object model definition 9
5.4.3 Object model version 10
5.4.4 Object class 10
5.4.5 Object name 10
5.4.6 Object ID — Shorthand name alias 11
5.5 Messages and replies 11
5.6 Message encoding 11
5.7 Methods on objects 12
5.8 CDAP message 12
5.8.1 General 12
5.8.2 Opcode 15
5.8.3 InvokeID 15
5.8.4 ObjName, ObjID 16
5.8.5 ObjNameParent, ObjIDParent 16
5.8.6 ObjClass 17
5.8.7 ObjValue 17
5.8.8 Result and ResultReason 18
5.8.9 Scope and filter 18
5.8.10 Flags 19
5.9 Object identification in messages 19
5.10 CDAP message/method Ttpes 20
5.10.1 Object creation: CREATE(_R), DELETE(_R) 20
5.10.2 Object Read: READ(_R), CANCELREAD(_R) 20
5.10.3 Object Write: WRITE(_R) 21
5.10.4 Object Stop/Start: START(_R), STOP(_R) 22

6 Policies **22**
6.1 General 22
6.2 POL-CDAP-CSYNTAX — Concrete syntax 22
6.2.1 General 22
6.2.2 Default 23
6.3 POL-CDAP-AUTH — Authentication 23
6.3.1 General 23
6.3.2 Default 23
6.4 POL-CDAP-ORDERING — Order of execution of method calls 23
6.4.1 General 23
6.4.2 Default 24
6.5 POL-CDAP-OBJECTMODEL — Overall object model definition 24
6.5.1 General 24
6.5.2 POL-CDAP-OBJ-VERSION — Object model version 24
6.5.3 POL-CDAP-OBJ-VISIBILITY — RIB objects visible to this AC 25
6.5.4 POL-CDAP-OBJ-NAMING — Object naming convention 25
6.5.5 POL-CDAP-OBJ-ObjRef — Use of ObjName/ObjID to edentify objects 26
6.5.6 POL-CDAP-OBJ-OBJCREATE — Object creation 26
6.5.7 POL-CDAP-OBJ-Types — Scalar types 28
6.5.8 POL-CDAP-OBJ-CLASSES — Defined classes 29
6.5.9 POL-CDAP-OBJ-METHODS — Object methods 29
6.5.10 POL-CDAP-OBJ-ObjID — ObjID values 29
6.5.11 POL-CDAP-OBJ-INITIAL — Pre-defined objects 30
6.6 POL-CDAP-ERROR — Error handling and return values 30
6.6.1 General 30
6.6.2 Default 30
6.7 POL-CDAP-InvokeID — Convention for assigning InvokeID values 32
6.7.1 General 32
6.7.2 Default 32
6.8 POL-CDAP-READINCOMPLETE — Use of incomplete READ_R 33
6.8.1 General 33
6.8.2 Default 33
6.9 POL-CDAP-SCOPEFILTER — Scope and filter policy 33
6.9.1 General 33
6.9.2 Default 34
6.10 POL-CDAP-ACSVContents — ACSV contents 34
6.10.1 General 34
6.10.2 Default 34
7 CDAP context notes **34**
7.1 General 34
7.2 RIB Daemon model 34
7.3 Distributed applications 35
Annex A (informative) **Google Protocol Buffers™ (GPB) concrete syntax** **39**
Annex B (informative) **JSON concrete syntax** **42**
Bibliography **44**