ISO/IEC 23090-18:2024-01 (E)

Information technology - Coded representation of immersive media - Part 18: Carriage of geometry-based point cloud compression data

Contents

Page

Foreword ..... **v**

Introduction ..... **vi**

1 Scope **1**

2 Normative references **1**

3 Terms and definitions **1**

4 Abbreviated terms **3**

5 Overview **3**
5.1 Overall architecture for carriage of geometry-based point cloud compression data 3
5.2 Referenceable code points 5
5.2.1 Brands 5
5.2.2 Sample entry type 5
5.2.3 Box types 5
5.2.4 Track reference types 6
5.2.5 Entity grouping types 6
5.2.6 Sample grouping types 7
5.2.7 Uniform resource names 7

6 Volumetric media **7**
6.1 Volumetric visual media 7
6.1.1 General 7
6.1.2 Volumetric visual media header 7
6.1.3 Volumetric visual sample entry 8
6.1.4 Volumetric visual sample group entry 8
6.1.5 Volumetric visual samples 8

7 Timed G-PCC data storage in ISOBMFF **8**
7.1 General 8
7.2 Common boxes and data structures 9
7.2.1 G-PCC decoder configuration record 9
7.2.2 G-PCC decoder configuration box 10
7.2.3 G-PCC component information box 10
7.2.4 Tile inventory information sample group 12
7.3 Single track encapsulation 12
7.3.1 General 12
7.3.2 Sample entry 13
7.3.3 Sample format 13
7.4 Multiple track encapsulation 15
7.4.1 General 15
7.4.2 Sample entry 15
7.4.3 Sample format 16
7.4.4 Track references 17
7.5 Encapsulation of tiled G-PCC bitstream 17
7.5.1 General 17
7.5.2 G-PCC tile base track 18
7.5.3 G-PCC tile tracks 19
7.5.4 Relationship between samples in G-PCC tile base track and tile track 20
7.5.5 Track references 21
7.6 Indication of alternatives 21

8 Non-timed G-PCC data storage in ISOBMFF **21**
8.1 General 21
8.2 Image item 22
8.2.1 G-PCC item 22
8.2.2 G-PCC tile item 23
8.3 Image properties 23
8.3.1 G-PCC configuration item property 23
8.3.2 G-PCC component information item property 24
8.3.3 G-PCC spatial region item property 24
8.3.4 sub-sample item property 25
8.3.5 G-PCC tile information item property 25
8.4 Entity grouping 26
8.4.1 Viewport association 26

9 Signalling of metadata in ISOBMFF **26**
9.1 G-PCC Spatial region information 26
9.1.1 Information structure 26
9.1.2 Signalling of static spatial region information 29
9.1.3 Signalling of dynamic spatial region information 29
9.2 G-PCC viewport information 32
9.2.1 General 32
9.2.2 Information structure 32
9.2.3 Signalling of static viewport information 35
9.2.4 Signalling of dynamic viewport information 36

10 Encapsulation and signalling in DASH **37**
10.1 Single-track mode 37
10.1.1 General 37
10.2 Multi-track mode 37
10.2.1 General 37
10.2.2 DASH MPD descriptors 38
10.2.3 GPCC Preselection 41
10.2.4 Supporting multiple versions of GPCC data 41
10.3 Partial delivery and access 41
10.3.1 Signalling of static spatial regions 41
10.3.2 Signalling of dynamic spatial regions 43
10.3.3 Tiled G-PCC data encapsulation and signalling 43
10.4 Signalling recommended viewports 45
10.4.1 Signalling of static recommended viewports 45
10.4.2 Signalling of dynamic recommended viewports 47

11 Encapsulation and signalling in MMT **47**
11.1 Encapsulation of G-PCC bitstream for MMT streaming 47
11.2 MMT signalling descriptors 47
11.2.1 Asset reference descriptor 47
11.2.2 G-PCC Asset descriptor 48
11.3 MMT application-specific signalling messages 49
11.3.1 General 49
11.3.2 GPCC Asset Group Metadata Message 50
11.3.3 GPCC Asset Selection Message 52
11.3.4 GPCC View Change Feedback Message 53

Annex A (normative) **File format toolsets and brands** **56**

Annex B (normative) **GPCC DASH Schema** **57**

Annex C (normative) **MIME types and sub-parameters** **59**

Annex D (informative) **Sample entry type and sample format** **60**

Annex E (informative) **Alternative Indication Examples** **61**

Annex F (informative) **Partial access support with G-PCC tile tracks** **63**

Annex G (informative) **Partial access support with non-timed G-PCC data** **65**

Annex H (informative) **DASH MPD examples** **67**

Bibliography **75**