

ISO/IEC 17310:2000-09 (E)

Information technology - Telecommunications and information exchange between systems; Private integrated Services Network - Mapping functions for the employment of 64-kbit/s circuit mode connections with 16-kbit/s sub-multiplexing

| Contents | | Page |
|--------------------|--|-------------|
| Foreword | | iv |
| Introduction | | v |
| 1 | Scope | 1 |
| 2 | Conformance | 1 |
| 3 | Normative references | 1 |
| 4 | Definitions | 2 |
| 4.1 | External definitions | 2 |
| 4.2 | Special definitions | 2 |
| 4.2.1 | Channel | 2 |
| 4.2.2 | End PINX | 2 |
| 4.2.3 | Inter-PINX Connection | 2 |
| 4.2.4 | Inter-PINX Link | 2 |
| 4.2.5 | Transit PINX | 2 |
| 5 | Abbreviations | 2 |
| 6 | Introduction | 2 |
| 7 | Capabilities at the Q reference point | 3 |
| 8 | Mapping functions | 3 |
| 8.1 | Physical adaptation | 3 |
| 8.1.1 | 64 kbit/s Unrestricted Digital Leased Line (D64U) | 3 |
| 8.2 | Mapping Matrix | 4 |
| 8.2.1 | Channel allocation | 4 |
| 8.2.2 | Bearer Conditioning for the DQ-channel | 4 |
| 8.2.3 | Bearer Conditioning for the UQ-channels | 4 |
| Annexes A | Implementation Conformance Statement (ICS) Proforma | 5 |
| B | Bibliography | 8 |
| C | QSIG Protocol Codepoints | 9 |
| D | Example figure for Bearer Conditioning of UQ-channels | 10 |