ISO/IEC 17310:2000-09 (E)

Information technology - Telecommunications and information exchange between systems; Private integrated Services Network - Mapping functions for the employment of 64-kbit/s circuit mode connections with 16-kbit/s sub-multiplexing

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Conformance 1

3 Normative references 1

4 Definitions 2
4.1 External definitions 2
4.2 Special definitions 2
4.2.1 Channel 2
4.2.2 End PINX 2
4.2.3 Inter-PINX Connection 2
4.2.4 Inter-PINX Link 2
4.2.5 Transit PINX 2

5 Abbreviations 2

6 Introduction 2

7 Capabilities at the Q reference point 3

8 Mapping functions 3
8.1 Physical adaptation 3
8.1.1 64 kbit/s Unrestricted Digital Leased Line (D64U) 3
8.2 Mapping Matrix 4
8.2.1 Channel allocation 4
8.2.2 Bearer Conditioning for the DQ-channel 4
8.2.3 Bearer Conditioning for the UQ-channels 4

Annexes A Implementation Conformance Statement (ICS) Proforma 5

B Bibliography 8

C QSIG Protocol Codepoints 9

D Example figure for Bearer Conditioning of UQ-channels 10