ISO/IEC 21122-2:2024-08 (E)

Information technology - JPEG XS low-latency lightweight image coding system - Part 2 : Profiles and buffer models

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Terms and definitions 1

4 Abbreviated terms 4

5 Symbols 4

6 Conventions 7
6.1 Conformance language 7
6.2 Operators 7
6.2.1 Arithmetic operators 7
6.2.2 Logical operators 7
6.2.3 Relational operators 7
6.2.4 Other operators 7
6.2.5 Precedence order of operators 8
6.2.6 Mathematical functions 8

7 Buffer model 8
7.1 General system block diagram 8
7.2 Influencing variables on the required buffer sizes 9
7.3 Role of the buffer model 10

8 Interpretation of Bayer data 10

9 Conformance 11

Annex A (normative) Profiles, levels, sublevels and frame buffer bandwidth levels 12

Annex B (normative) Packet-based JPEG XS decoder model 35

Annex C (normative) Packet-based constant bit rate buffer model 41

Annex D (informative) Encoder model, latency bounds and codestream conformance properties for the packet-based constant bit rate buffer model 47

Annex E (informative) JPEG XS latency analysis 52

Bibliography 61