

ISO/IEC/IEEE 8802-1Q:2024-08 (E)

Telecommunications and exchange between information technology systems - Requirements for local and metropolitan area networks - Part 1Q: Bridges and bridged networks

Contents

Page

- 1. Overview..... 74
 - 1.1 Scope..... 74
 - 1.2 Purpose..... 74
 - 1.3 Introduction..... 75
- 2. Normative references..... 83
- 3. Definitions 87
- 4. Abbreviations..... 109
- 5. Conformance..... 115
 - 5.1 Requirements terminology..... 115
 - 5.2 Conformant components and equipment..... 115
 - 5.3 Protocol Implementation Conformance Statement (PICS)..... 116
 - 5.4 VLAN Bridge component requirements..... 116
 - 5.4.1 VLAN Bridge component options 117
 - 5.4.2 Multiple VLAN Registration Protocol (MVRP) requirements 123
 - 5.4.3 VLAN Bridge requirements for congestion notification 123
 - 5.4.4 Multiple Stream Registration Protocol (MSRP) requirements 124
 - 5.4.5 Shortest Path Bridging (SPB) operation (optional) 124
 - 5.4.6 Path Control and Reservation (PCR) (optional) 125
 - 5.5 C-VLAN component conformance..... 126
 - 5.5.1 C-VLAN component options 126
 - 5.5.2 TE-MSTID (optional) 126
 - 5.6 S-VLAN component conformance 127
 - 5.6.1 S-VLAN component options 127
 - 5.6.2 S-VLAN component requirements for Provider Backbone Bridge Traffic Engineering (PBB-TE) 127
 - 5.6.3 S-VLAN component requirements for PBB-TE IPS 128
 - 5.6.4 S-VLAN component requirements for ECMP with flow filtering 128
 - 5.7 I-component conformance 128
 - 5.7.1 I-component options 128
 - 5.8 B-component conformance..... 129
 - 5.8.1 B-component options 129
 - 5.8.2 B-component requirements for PBB-TE 129
 - 5.8.3 B-component requirements for PBB-TE IPS 130
 - 5.8.4 B-component requirements for ECMP with flow filtering 130
 - 5.9 C-VLAN Bridge conformance..... 130
 - 5.9.1 C-VLAN Bridge options 130
 - 5.10 Provider Bridge conformance..... 130
 - 5.10.1 S-VLAN Bridge conformance 131
 - 5.10.2 Provider Edge Bridge conformance 131
 - 5.11 System requirements for Priority-based Flow Control (PFC) 131
 - 5.12 Backbone Edge Bridge (BEB) conformance 131
 - 5.12.1 BEB requirements for PBB-TE 132
 - 5.13 MAC Bridge component requirements..... 132
 - 5.13.1 MAC Bridge component options 132
 - 5.14 MAC Bridge conformance..... 133
 - 5.14.1 MAC Bridge options 133

5.15	TPMR component conformance.....	134
5.15.1	TPMR component options	134
5.16	TPMR conformance.....	134
5.16.1	TPMR options	135
5.17	T-component conformance.....	135
5.17.1	T-component options	135
5.18	End station requirements for MMRP, MVRP, and MSRP.....	135
5.18.1	MMRP requirements and options	135
5.18.2	MVRP requirements and options	136
5.18.3	MSRP requirements and options	136
5.19	VLAN-aware end station requirements for CFM.....	137
5.20	End station requirements—FQTSS	137
5.21	End station requirements for congestion notification	138
5.22	MAC-specific bridging methods	138
5.23	EVB Bridge requirements.....	139
5.24	EVB station requirements.....	139
5.24.1	Edge relay (ER) requirements	140
5.25	End station requirements—enhancements for scheduled traffic	141
5.26	End station requirements—enhancements for frame preemption.....	142
5.27	End station requirements—PSFP.....	142
5.28	End station requirements—Cyclic queuing and forwarding.....	142
5.29	TSN CNC station requirements	142
5.30	VDP-NVO3 requirements.....	143
5.30.1	VDP-NVO3 nNVE requirements	143
5.30.2	VDP-NVO3 tNVE requirements	143
5.31	End station requirements—ATS.....	143
6.	Support of the MAC Service	144
6.1	Basic architectural concepts and terms.....	145
6.2	Provision of the MAC Service.....	145
6.2.1	Point-to-point, multipoint-to-multipoint, and rooted-multipoint connectivity ...	146
6.3	Support of the MAC Service	146
6.4	Preservation of the MAC Service	147
6.5	Quality of service (QoS) maintenance.....	147
6.5.1	Service availability	147
6.5.2	Frame loss	148
6.5.3	Frame misordering	148
6.5.4	Frame duplication	149
6.5.5	Transit delay	150
6.5.6	Frame lifetime	150
6.5.7	Undetected frame error rate	151
6.5.8	Maximum Service Data Unit Size	151
6.5.9	Priority	151
6.5.10	Throughput	152
6.6	Internal Sublayer Service (ISS)	153
6.7	Support of the ISS by specific MAC procedures.....	153
6.7.1	Support of the ISS by IEEE Std 802.3 (Ethernet)	153
6.7.2	Frame preemption	153
6.8	Enhanced Internal Sublayer Service (EISS).....	154
6.8.1	Service primitives	154
6.8.2	Status parameters	155
6.8.3	Point-to-point parameters	155
6.8.4	Control primitives and parameters	155

6.9	Support of the EISS	156
6.9.1	Data indications	157
6.9.2	Data requests	158
6.9.3	Priority Code Point encoding	158
6.9.4	Regenerating priority	160
6.10	Support of the ISS/EISS by PIPs	161
6.10.1	Data indications	163
6.10.2	Data requests	164
6.10.3	Priority Code Point encoding	164
6.11	Support of the EISS by CBPs	165
6.11.1	Data indications	166
6.11.2	Data requests	167
6.11.3	Priority Code Point decoding	168
6.11.4	Regenerating priority	168
6.12	Protocol VLAN classification.....	168
6.12.1	Protocol Templates	170
6.12.2	Protocol Group Identifiers	170
6.12.3	Protocol Group Database	170
6.13	Support of the ISS for attachment to a PBN.....	171
6.13.1	Data requests	172
6.13.2	Data indications	172
6.14	Support of the ISS within a system.....	173
6.15	Support of the ISS by additional technologies.....	173
6.16	Filtering services in Bridged Networks	173
6.16.1	Purpose(s) of filtering service provision	174
6.16.2	Goals of filtering service provision	174
6.16.3	Users of filtering services	174
6.16.4	Basis of service	174
6.16.5	Categories of service	175
6.16.6	Service configuration	175
6.16.7	Service definition for Extended Filtering Services	175
6.17	EISS Multiplex Entity.....	177
6.18	Backbone Service Instance Multiplex Entity.....	178
6.18.1	Demultiplexing direction	179
6.18.2	Multiplexing direction	180
6.18.3	Priority Code Point encoding	180
6.18.4	Status parameters	180
6.19	TESI Multiplex Entity	181
6.20	Support of the ISS with signaled priority	182
6.20.1	Data indications	182
6.20.2	Data requests	183
6.21	Infrastructure Segment Multiplex Entity	183
6.22	PDU and protocol discrimination and media.....	184
7.	Principles of Virtual Bridged Network operation.....	185
7.1	Network overview.....	185
7.2	Use of VLANs	186
7.3	Active topology.....	186
7.4	VLAN topology	187
7.5	Locating end stations	188
7.6	Ingress, forwarding, and egress rules.....	189

8.	Principles of Bridge operation	190
8.1	Bridge operation	190
8.1.1	Relay	190
8.1.2	Filtering and relaying information	191
8.1.3	Duplicate frame prevention	191
8.1.4	Traffic segregation	191
8.1.5	Traffic reduction	192
8.1.6	Traffic expediting	192
8.1.7	Conversion of frame formats	192
8.2	Bridge architecture.....	193
8.3	Model of operation.....	195
8.4	Active topologies, learning, and forwarding	199
8.5	Bridge Port Transmit and Receive.....	200
8.5.1	Bridge Port connectivity	200
8.5.2	TPMR Port connectivity	201
8.5.3	Support of Higher Layer Entities	202
8.6	The Forwarding Process	202
8.6.1	Active topology enforcement	203
8.6.2	Ingress filtering	205
8.6.3	Frame filtering	205
8.6.4	Egress filtering	208
8.6.5	Flow classification and metering	208
8.6.6	Queuing frames	217
8.6.7	Queue management	218
8.6.8	Transmission selection	219
8.6.9	Scheduled traffic state machines	225
8.6.10	Stream gate control state machines	232
8.6.11	ATS Scheduler state machines	234
8.7	The Learning Process.....	238
8.7.1	Default filtering utility criteria	238
8.7.2	Enhanced filtering utility criteria	238
8.7.3	Ageing of Dynamic Filtering Entries	239
8.8	The Filtering Database (FDB)	239
8.8.1	Static Filtering Entries	242
8.8.2	Static VLAN Registration Entries	243
8.8.3	Dynamic Filtering Entries	244
8.8.4	MAC Address Registration Entries	245
8.8.5	Dynamic VLAN Registration Entries	245
8.8.6	Default Group filtering behavior	246
8.8.7	Dynamic Reservation Entries	247
8.8.8	Allocation of VIDs to FIDs	247
8.8.9	Querying the FDB	248
8.8.10	Determination of the member set for a VID	252
8.8.11	Permanent Database	252
8.8.12	Connection_Identifier	252
8.9	MST, SPB, and ESP configuration information	253
8.9.1	MST Configuration Table	254
8.9.2	MST configuration identification	254
8.9.3	FID to MSTI Allocation Table	254
8.9.4	SPT Configuration Identification	254
8.10	Spanning Tree Protocol Entity.....	255
8.11	MRP entities	255
8.12	Bridge Management Entity	256

8.13	Addressing	256
8.13.1	End stations	256
8.13.2	Bridge Ports	256
8.13.3	Use of LLC by Spanning Tree Protocol Entities	257
8.13.4	Reserved MAC addresses	257
8.13.5	Group MAC addresses for spanning tree entity	257
8.13.6	Group MAC addresses for MRP Applications	259
8.13.7	Bridge Management Entities	260
8.13.8	Unique identification of a Bridge	260
8.13.9	Points of attachment and connectivity for Higher Layer Entities	260
8.13.10	VLAN attachment and connectivity for Higher Layer Entities	264
8.13.11	CFM entities	265
9.	Tagged frame format	267
9.1	Purpose of tagging	267
9.2	Representation and encoding of tag fields	267
9.3	Tag format.....	268
9.4	TPID formats	268
9.5	Tag Protocol identification	268
9.6	VLAN Tag Control Information (TCI).....	269
9.7	Backbone Service Instance Tag Control Information (I-TAG TCI).....	270
10.	Multiple Registration Protocol (MRP) and Multiple MAC Registration Protocol (MMRP)	272
10.1	MRP overview	272
10.2	MRP architecture	275
10.3	MRP Attribute Propagation (MAP).....	276
10.3.1	MAP Context	277
10.4	Requirements to be met by MRP.....	278
10.5	Requirements for interoperability between MRP Participants	278
10.6	Protocol operation.....	280
10.7	Protocol specification	284
10.7.1	Notational conventions and abbreviations	285
10.7.2	Registrar Administrative Controls	286
10.7.3	Applicant Administrative Controls	287
10.7.4	Protocol timers	287
10.7.5	Protocol event definitions	288
10.7.6	Protocol Action definitions	290
10.7.7	Applicant state machine	292
10.7.8	Registrar state machine	292
10.7.9	LeaveAll state machine	292
10.7.10	PeriodicTransmission state machine	295
10.7.11	Timer values	295
10.7.12	Operational reporting and statistics	296
10.7.13	Interoperability considerations	296
10.7.14	External control	297
10.8	Structure and encoding of Multiple Registration Protocol Data Units (MRPDUs)	297
10.8.1	Structure	297
10.8.2	Encoding of MRPDUs parameters	299
10.8.3	Packing and parsing MRPDUs	302
10.9	Multiple MAC Registration Protocol (MMRP)—Purpose.....	304

10.10	MMRP Model of operation.....	305
10.10.1	Propagation of Group Membership information	306
10.10.2	Propagation of Group service requirement information	307
10.10.3	Source pruning	307
10.10.4	Use of Group service requirement registration by end stations	307
10.11	Default Group filtering behavior and MMRP propagation	307
10.12	Definition of the MMRP application	309
10.12.1	Definition of MRP elements	309
10.12.2	Provision and support of Extended Filtering Services	311
10.12.3	Use of “new” declaration capability	313
10.12.4	Attribute value support requirements	313
10.12.5	Registrar Administrative Controls	313
11.	VLAN topology management.....	314
11.1	Static and dynamic VLAN configuration	314
11.2	Multiple VLAN Registration Protocol (MVRP)	315
11.2.1	MVRP overview	315
11.2.2	VLAN registration service definition	317
11.2.3	Definition of the MVRP application	318
11.2.4	VID translation table	321
11.2.5	Use of “new” declaration capability	321
11.2.6	New-Only Participant and Registrar Administrative Controls	321
11.2.7	Attribute value support requirements	321
12.	Bridge management	322
12.1	Management functions.....	322
12.1.1	Configuration Management	322
12.1.2	Fault Management	323
12.1.3	Performance Management	323
12.1.4	Security Management	323
12.1.5	Accounting Management	323
12.2	VLAN Bridge objects	323
12.3	Data types	324
12.4	Bridge Management Entity	325
12.4.1	Bridge Configuration	325
12.4.2	Port configuration	328
12.5	MAC entities.....	330
12.5.1	ISS Port Number table managed object (optional)	330
12.6	Forwarding process.....	331
12.6.1	The Port Counters	331
12.6.2	Priority handling	332
12.6.3	Traffic Class Table	339
12.7	Filtering Database (FDB).....	340
12.7.1	The Filtering Database object	340
12.7.2	A Static Filtering Entry object	341
12.7.3	A Dynamic Filtering Entry object	341
12.7.4	A MAC Address Registration Entry object	342
12.7.5	A VLAN Registration Entry object	342
12.7.6	Permanent Database object	342
12.7.7	General FDB operations	343
12.8	Bridge Protocol Entity	345
12.8.1	The Protocol Entity	345
12.8.2	Bridge Port	348

12.9	MRP Entities.....	352
12.9.1	The MRP Timer object	352
12.9.2	The MRP Attribute Type object	353
12.9.3	Periodic state machine objects	354
12.10	Bridge VLAN managed objects.....	354
12.10.1	Bridge VLAN Configuration managed object	355
12.10.2	VLAN Configuration managed object	360
12.10.3	The VID to FID allocation managed object	361
12.11	MMRP entities.....	363
12.11.1	MMRP Configuration managed object	363
12.12	MST configuration entities	365
12.12.1	The MSTI List	365
12.12.2	The FID to MSTID Allocation Table	366
12.12.3	The MST Configuration Table	367
12.13	Provider Bridge management	369
12.13.1	Provider Bridge Port Type managed object	370
12.13.2	Customer Edge Port Configuration managed object	371
12.13.3	Remote Customer Access managed object	374
12.14	CFM entities	376
12.14.1	Maintenance Domain list managed object	376
12.14.2	CFM Stack managed object	378
12.14.3	Default MD Level managed object	379
12.14.4	Configuration Error List managed object	380
12.14.5	Maintenance Domain managed object	381
12.14.6	Maintenance Association managed object	383
12.14.7	Maintenance association Endpoint managed object	386
12.15	Backbone Core Bridge (BCB) management.....	393
12.16	Backbone Edge Bridge (BEB) management	393
12.16.1	BEB configuration managed object	395
12.16.2	BEB/PB/VLAN Bridge Port configuration managed object	399
12.16.3	VIP configuration managed object	399
12.16.4	PIP configuration managed object	400
12.16.5	CBP Configuration managed object	407
12.17	DDCFM entities.....	410
12.17.1	DDCFM Stack managed object	410
12.17.2	Reflection Responder managed object	410
12.17.3	RFM Receiver managed object	414
12.17.4	Decapsulator Responder managed object	415
12.17.5	SFM Originator managed object	417
12.18	PBB-TE Protection Switching managed objects	420
12.18.1	TE protection group list managed object	420
12.18.2	TE protection group managed object	421
12.19	TPMR managed objects.....	423
12.19.1	TPMR management entity	424
12.19.2	MAC and PHY entities	426
12.19.3	Forwarding Process	426
12.19.4	MAC Status Propagation Entity (MSPE)	431
12.20	Management entities for FQTSS	433
12.20.1	The Bandwidth Availability Parameter Table	433
12.20.2	The Transmission Selection Algorithm Table	434
12.20.3	The Priority Regeneration Override Table	434
12.20.4	SR Class to Priority Mapping Table	434

12.21	Congestion Notification managed objects	435
12.21.1	CN component managed object	435
12.21.2	CN component priority managed object	435
12.21.3	CN Port priority managed object	437
12.21.4	Congestion Point managed object	438
12.21.5	Reaction Point port priority managed object	438
12.21.6	Reaction Point group managed object	439
12.22	Stream Reservation Protocol (SRP) entities	439
12.22.1	SRP Bridge Base Table	440
12.22.2	SRP Bridge Port Table	440
12.22.3	SRP Latency Parameter Table	441
12.22.4	SRP Stream Table	441
12.22.5	SRP Reservations Table	441
12.22.6	SRP Stream Preload Table	442
12.22.7	SRP Reservations Preload Table	442
12.23	Priority-based Flow Control objects	444
12.24	1:1 PBB-TE IPS managed objects	444
12.24.1	IPG list managed object	444
12.24.2	IPG managed object	446
12.25	Shortest Path Bridging managed objects	448
12.25.1	The SPB System managed object	449
12.25.2	The SPB MTID Static managed object	451
12.25.3	The SPB Topology Instance Dynamic managed object	453
12.25.4	The SPB ECT Static Entry managed object	453
12.25.5	The SPB ECT Dynamic Entry managed object	455
12.25.6	The SPB Adjacency Static Entry managed object	456
12.25.7	The SPB Adjacency Dynamic Entry managed object	457
12.25.8	The SPBM BSI Static Entry managed object	457
12.25.9	The SPB Topology Node Table managed object	459
12.25.10	The SPB Topology ECT Table managed object	460
12.25.11	The SPB Topology Edge Table managed object	460
12.25.12	The SPBM Topology Service Table managed object	461
12.25.13	The SPBV Topology Service Table managed object	462
12.25.14	The ECMP ECT Static Entry managed object	463
12.26	Edge Virtual Bridging (EVB) management.....	464
12.26.1	EVB system base table	467
12.26.2	SBP table entry	469
12.26.3	VSI table entry	470
12.26.4	S-channel configuration and management	471
12.26.5	ER management	473
12.27	Edge Control Protocol (ECP) management.....	474
12.27.1	ECP table entry	474
12.28	Path Control and Reservation (PCR) management.....	475
12.28.1	The PCR ECT Static Entry managed object	476
12.28.2	The PCR Topology ECT Table managed object	478
12.29	Managed objects for scheduled traffic.....	479
12.29.1	The Gate Parameter Table	479
12.29.2	Timing points for scheduled traffic	481
12.30	Managed objects for frame preemption.....	482
12.30.1	Frame Preemption Parameter table	482

12.31	Managed objects for per-stream classification and metering	484
12.31.1	The Stream Parameter Table	484
12.31.2	The Stream Filter Instance Table	485
12.31.3	The Stream Gate Instance Table	487
12.31.4	The Flow Meter Instance Table	490
12.31.5	The Scheduler Instance Table	490
12.31.6	The Scheduler Group Instance Table	491
12.31.7	The Scheduler Port Parameter Table	492
12.31.8	The Scheduler Timing Characteristics Table	492
12.32	Stream reservation remote management.....	494
12.32.1	Bridge Delay	494
12.32.2	Propagation Delay	496
12.32.3	Static Trees	496
12.32.4	MRP External Control	497
13.	Spanning tree protocols	501
13.1	Protocol design requirements.....	502
13.2	Protocol support requirements	503
13.2.1	MSTP support requirements	503
13.2.2	SPB support requirements	503
13.3	Protocol design goals	504
13.4	RSTP overview	504
13.4.1	Computation of the active topology	505
13.4.2	Example topologies	506
13.5	MSTP overview	509
13.5.1	Example topologies	510
13.5.2	Relationship of MSTP to RSTP	513
13.5.3	Modeling an MST or SPT Region as a single Bridge	513
13.6	SPB overview	514
13.7	Compatibility and interoperability.....	515
13.7.1	Designated Port selection	515
13.7.2	Force Protocol Version	515
13.8	MST Configuration Identifier (MCID).....	516
13.9	Spanning tree priority vectors.....	517
13.10	CIST Priority Vector calculations.....	519
13.11	MST Priority Vector calculations	521
13.12	Port Role assignments.....	523
13.13	Stable connectivity.....	524
13.14	Communicating spanning tree information	525
13.15	Changing spanning tree information.....	526
13.16	Changing Port States with RSTP or MSTP	527
13.16.1	Subtree connectivity and priority vectors	528
13.16.2	Root Port transition to Forwarding	528
13.16.3	Designated Port transition to Forwarding	528
13.16.4	Master Port transition to Forwarding	530
13.17	Changing Port States with SPB	532
13.17.1	Agreement Digest	534
13.18	Managing spanning tree topologies	535
13.19	Updating learned station location information	536
13.20	Managing reconfiguration.....	538
13.21	Partial and disputed connectivity.....	539
13.22	In-service upgrades	539
13.23	Fragile Bridges.....	541

13.24	Spanning tree protocol state machines.....	541
13.25	State machine timers	543
13.25.1	edgeDelayWhile	544
13.25.2	fdWhile	544
13.25.3	helloWhen	544
13.25.4	mdelayWhile	544
13.25.5	rbWhile	544
13.25.6	rcvdInfoWhile	544
13.25.7	rrWhile	545
13.25.8	tcDetected	545
13.25.9	tcWhile	545
13.25.10	pseudoInfoHelloWhen	545
13.26	Per Bridge variables.....	545
13.26.1	agreementDigest	546
13.26.2	BridgeIdentifier	546
13.26.3	BridgePriority	546
13.26.4	BridgeTimes	546
13.26.5	ForceProtocolVersion	547
13.26.6	MigrateTime	547
13.26.7	MstConfigId	547
13.26.8	AuxMstConfigId	547
13.26.9	rootPortId	547
13.26.10	rootPriority	547
13.26.11	rootTimes	547
13.26.12	TxHoldCount	547

13.27	Per port variables	547
13.27.1	AdminEdge	550
13.27.2	ageingTime	550
13.27.3	agree	550
13.27.4	agreed	550
13.27.5	agreedAbove	550
13.27.6	agreedDigest	550
13.27.7	agreedDigestValid	550
13.27.8	agreeDigest	550
13.27.9	agreeDigestValid	550
13.27.10	agreedMisorder	551
13.27.11	agreedN	551
13.27.12	agreedND	551
13.27.13	agreedPriority	551
13.27.14	agreedTopology	551
13.27.15	agreementOutstanding	551
13.27.16	agreeN	551
13.27.17	agreeND	551
13.27.18	AutoEdge	551
13.27.19	AutoIsolate	552
13.27.20	designatedPriority	552
13.27.21	designatedTimes	552
13.27.22	disputed	552
13.27.23	enableBPDUrx	552
13.27.24	enableBPDUtx	552
13.27.25	ExternalPortPathCost	552
13.27.26	isL2gp	552
13.27.27	isolate	553
13.27.28	fdbFlush	553
13.27.29	forward	553
13.27.30	forwarding	553
13.27.31	infoInternal	553
13.27.32	infols	553
13.27.33	InternalPortPathCost	553
13.27.34	learn	554
13.27.35	learning	554
13.27.36	master	554
13.27.37	mastered	554
13.27.38	mcheck	554
13.27.39	msgPriority	554
13.27.40	msgTimes	554
13.27.41	neighbourPriority	555
13.27.42	newInfo	555
13.27.43	newInfoMsti	555
13.27.44	operEdge	555
13.27.45	portEnabled	555
13.27.46	portId	555
13.27.47	portPriority	555
13.27.48	portTimes	556
13.27.49	proposed	556
13.27.50	proposing	556
13.27.51	pseudoRootId	556
13.27.52	revdBPDU	556
13.27.53	revdInfo	556

13.27.54	rcvdInternal	556
13.27.55	rcvdMsg	556
13.27.56	rcvdRSTP	556
13.27.57	rcvdSTP	556
13.27.58	rcvdTc	556
13.27.59	rcvdTcAck	556
13.27.60	rcvdTcn	557
13.27.61	reRoot	557
13.27.62	reselect	557
13.27.63	restrictedDomainRole	557
13.27.64	restrictedRole	557
13.27.65	restrictedTcn	557
13.27.66	role	557
13.27.67	selected	557
13.27.68	selectedRole	557
13.27.69	sendRSTP	558
13.27.70	sync	558
13.27.71	synced	558
13.27.72	tcAck	558
13.27.73	tcProp	558
13.27.74	tick	558
13.27.75	txCount	558
13.27.76	updtInfo	558
13.28	State machine conditions and parameters	558
13.28.1	allSptAgree	559
13.28.2	allSynced	559
13.28.3	allTransmitReady	559
13.28.4	BestAgreementPriority	559
13.28.5	cist	559
13.28.6	cistRootPort	559
13.28.7	cistDesignatedPort	560
13.28.8	EdgeDelay	560
13.28.9	forwardDelay	560
13.28.10	FwdDelay	560
13.28.11	HelloTime	560
13.28.12	MaxAge	560
13.28.13	msti	560
13.28.14	mstiDesignatedOrTCpropagatingRootPort	560
13.28.15	mstiMasterPort	560
13.28.16	operPointToPoint	560
13.28.17	rcvdAnyMsg	560
13.28.18	rcvdCistMsg	560
13.28.19	rcvdMstiMsg	561
13.28.20	reRooted	561
13.28.21	rstpVersion	561
13.28.22	spt	561
13.28.23	stpVersion	561
13.28.24	updtCistInfo	561
13.28.25	updtMstiInfo	561

13.29	State machine procedures	561
13.29.1	betterorsameInfo(newInfoIs)	562
13.29.2	clearAllRcvdMsgs()	562
13.29.3	clearReselectTree()	562
13.29.4	disableForwarding()	563
13.29.5	disableLearning()	563
13.29.6	enableForwarding()	563
13.29.7	enableLearning()	563
13.29.8	fromSameRegion()	563
13.29.9	newTcDetected()	563
13.29.10	newTcWhile()	563
13.29.11	pseudoRcvMsgs()	564
13.29.12	rcvInfo()	564
13.29.13	rcvMsgs()	565
13.29.14	rcvAgreements()	565
13.29.15	recordAgreement()	565
13.29.16	recordDispute()	566
13.29.17	recordMastered()	566
13.29.18	recordPriority()	566
13.29.19	recordProposal()	566
13.29.20	recordTimes()	566
13.29.21	setReRootTree()	567
13.29.22	setSelectedTree()	567
13.29.23	setSyncTree()	567
13.29.24	setTcFlags()	567
13.29.25	setTcPropTree()	567
13.29.26	syncMaster()	567
13.29.27	txConfig()	567
13.29.28	txRstp()	568
13.29.29	txTcn()	568
13.29.30	updtAgreement()	568
13.29.31	updtBPDUVersion()	569
13.29.32	updtDigest()	569
13.29.33	updtRcvdInfoWhile()	570
13.29.34	updtRolesTree()	571
13.29.35	uptRolesDisabledTree()	572
13.30	The Port Timers state machine	572
13.31	Port Receive state machine	573
13.32	Port Protocol Migration state machine	574
13.33	Bridge Detection state machine	574
13.34	Port Transmit state machine	575
13.35	Port Information state machine	576
13.36	Port Role Selection state machine	577
13.37	Port Role Transitions state machine	577
13.38	Port State Transition state machine	582
	13.38.1 Port State transitions for the CIST and MSTIs	583
	13.38.2 Port State transitions for SPTs	583
13.39	Topology Change state machine	584
13.40	Layer 2 Gateway Port Receive state machine	585

13.41	CEP spanning tree operation.....	585
13.41.1	PEP operPointToPointMAC and operEdge	585
13.41.2	updtRolesTree()	586
13.41.3	setReRootTree(), setSyncTree(), setTcPropTree()	586
13.41.4	allSynced, reRooted	586
13.41.5	Configuration parameters	586
13.42	Virtual Instance Port (VIP) spanning tree operation	587
14.	Encoding of Bridge Protocol Data Units (BPDUs)	588
14.1	BPDU Structure	588
14.1.1	Transmission and representation of octets	588
14.1.2	Common BPDU fields	588
14.2	Encoding of parameter types	590
14.2.1	Encoding of Protocol Identifiers	590
14.2.2	Encoding of Protocol Version Identifiers	590
14.2.3	Encoding of BPDU types	590
14.2.4	Encoding of flags	590
14.2.5	Encoding of Bridge Identifiers	590
14.2.6	Encoding of External Root Path Cost and Internal Root Path Cost	591
14.2.7	Encoding of Port Identifiers	591
14.2.8	Encoding of Timer Values	591
14.2.9	Encoding of Port Role values	591
14.2.10	Encoding of Length Values	592
14.2.11	Encoding of Hop Counts	592
14.3	Transmission of BPDUs	592
14.4	Encoding and decoding of STP Configuration, RST, MST, and SPT BPDUs.....	592
14.4.1	MSTI Configuration Messages	594
14.5	Validation of received BPDUs	595
14.6	Validation and interoperability	596
15.	Support of the MAC Service by PBNs	597
15.1	Service transparency	597
15.2	Customer service interfaces	598
15.3	Port-based service interface	598
15.4	C-tagged service interface	599
15.5	S-tagged service interface.....	600
15.6	Remote customer service interfaces (RCSIs)	601
15.7	Service instance segregation.....	604
15.8	Service instance selection and identification	604
15.9	Service priority selection	605
15.10	Service access protection	605
16.	Principles of Provider Bridged Network (PBN) operation	606
16.1	PBN overview.....	606
16.2	Provider Bridged Network (PBN)	607
16.3	Service instance connectivity.....	610
16.4	Service provider learning of customer end station addresses.....	611
16.5	Detection of connectivity loops through attached networks.....	611
16.6	Network management	612
17.	Management Information Base (MIB)	613
17.1	Internet Standard Management Framework	613

17.2	Structure of the MIB	613
17.2.1	Structure of the IEEE8021-TC-MIB	615
17.2.2	Structure of the IEEE8021-BRIDGE-MIB	616
17.2.3	Structure of the IEEE8021-SPANNING-TREE MIB	620
17.2.4	Structure of the IEEE8021-Q-BRIDGE-MIB	623
17.2.5	Structure of the IEEE8021-PB-MIB	628
17.2.6	Structure of the IEEE8021-MSTP-MIB	630
17.2.7	Structure of the IEEE8021-CFM-MIB	633
17.2.8	Structure of the IEEE8021-PBB-MIB	639
17.2.9	Structure of the IEEE8021-DDCFM-MIBs	642
17.2.10	Structure of the IEEE8021-PBBTE-MIB	644
17.2.11	Structure of the TPMR MIB	647
17.2.12	Structure of the IEEE8021-FQTSS-MIB	649
17.2.13	Structure of the IEEE8021-CN-MIB	650
17.2.14	Structure of the IEEE8021-SRP-MIB	652
17.2.15	Structure of the IEEE8021-MVRPX-MIB	654
17.2.16	Structure of the IEEE8021-MIRP-MIB	654
17.2.17	Structure of the IEEE8021-PFC-MIB	655
17.2.18	Structure of the IEEE8021-TEIPS-MIB	655
17.2.19	Structure of the IEEE8021-SPB-MIB	657
17.2.20	Structure of the IEEE8021-EVB-MIB	662
17.2.21	Structure of the IEEE8021-ECMP-MIB	666
17.2.22	Structure of the IEEE8021-ST-MIB	667
17.2.23	Structure of the IEEE8021-Preemption-MIB	668
17.2.24	Structure of the IEEE8021-PSFP-MIB	668
17.2.25	Structure of the IEEE8021-TSN-REMOTE-MANAGEMENT-MIB	671
17.3	MIB module relationships	673
17.3.1	Relationship of the IEEE8021-TC-MIB to other MIB modules	673
17.3.2	Relationship of the IEEE8021-BRIDGE-MIB to other MIB modules	673
17.3.3	Relationship of the IEEE8021-RSTP MIB to other MIB modules	676
17.3.4	Relationship of the IEEE8021-Q-BRIDGE-MIB to other MIB modules	676
17.3.5	Relationship of the IEEE8021-PB-BRIDGE MIB to other MIB modules	678
17.3.6	Relationship of the IEEE8021-MSTP-MIB to other MIB modules	678
17.3.7	Relationship of the IEEE8021-CFM-MIB to other MIB modules	678
17.3.8	Relationship of the IEEE8021-PBB-MIB to other MIB modules	679
17.3.9	Relationship of the IEEE8021-DDCFM to other MIB modules	680
17.3.10	Relationship of the IEEE8021-PBBTE-MIB to other MIB modules	680
17.3.11	Relationship of the IEEE8021-TPMR MIB to other MIB modules	681
17.3.12	Relationship of the IEEE8021-FQTSS-MIB to other MIB modules	681
17.3.13	Relationship of the IEEE8021-CN-MIB to other MIB modules	681
17.3.14	Relationship of the IEEE8021-SRP-MIB to other MIB modules	682
17.3.15	Relationship of the IEEE8021-MVRPX-MIB to other MIB modules	682
17.3.16	Relationship of the IEEE8021-MIRP-MIB to other MIB modules	682
17.3.17	Relationship of the IEEE8021-PFC-MIB to other MIB modules	682
17.3.18	Relationship of the IEEE8021-TEIPS-MIB to other MIB modules	683
17.3.19	Relationship of the IEEE8021-SPB-MIB to other MIB modules	683
17.3.20	Relationship of the IEEE8021-EVB-MIB to other MIB modules	683
17.3.21	Relationship of the IEEE8021-ECMP-MIB to other MIB modules	683
17.3.22	Relationship of the IEEE8021-ST-MIB to other MIB modules	683
17.3.23	Relationship of the IEEE8021-Preemption-MIB to other MIB modules	684
17.3.24	Relationship of IEEE8021-PSFP-MIB to other MIB modules	684
17.3.25	Relationship of IEEE8021-TSN-REMOTE-MANAGEMENT-MIB to other MIB modules	684

17.4	Security considerations	684
17.4.1	Security considerations of the IEEE8021-TC-MIB	684
17.4.2	Security considerations of the IEEE8021-BRIDGE-MIB	685
17.4.3	Security considerations of the IEEE8021-SPANNING-TREE MIB	686
17.4.4	Security considerations of the IEEE8021-Q-BRIDGE-MIB	686
17.4.5	Security considerations of the IEEE8021-PB-MIB	687
17.4.6	Security considerations of the IEEE8021-MSTP-MIB	687
17.4.7	Security considerations of the IEEE8021-CFM-MIB	688
17.4.8	Security considerations of the IEEE8021-PBB-MIB	690
17.4.9	Security considerations of the IEEE8021-DDCFM-MIB	691
17.4.10	Security considerations of the IEEE8021-PBBTE-MIB	691
17.4.11	Security considerations of the IEEE8021-TPMR-MIB	692
17.4.12	Security considerations of the IEEE8021-FQTSS-MIB	692
17.4.13	Security considerations of the IEEE8021-CN-MIB	693
17.4.14	Security considerations of the IEEE8021-SRP-MIB	695
17.4.15	Security considerations of the IEEE8021-MVRPX-MIB	695
17.4.16	Security considerations of the IEEE8021-MIRP-MIB	696
17.4.17	Security considerations of the IEEE8021-PFC-MIB	696
17.4.18	Security considerations of the IEEE8021-TEIPS-MIB	696
17.4.19	Security considerations of the IEEE8021-SPB-MIB	697
17.4.20	Security considerations of the IEEE8021-EVB-MIB	697
17.4.21	Security considerations of the IEEE8021-ECMP-MIB	699
17.4.22	Security considerations of the IEEE8021-ST-MIB	699
17.4.23	Security considerations of the IEEE8021-Preemption-MIB	700
17.4.24	Security considerations of the IEEE8021-PSFP-MIB	700
17.4.25	Security considerations of the IEEE8021-TSN-REMOTE-MANAGEMENT-MIB 702	
17.5	Dynamic component and Port creation.....	703
17.5.1	Overview of the dynamically created Bridge entities	703
17.5.2	Component creation	704
17.5.3	Port creation	705
17.6	MIB operations for service interface configuration.....	715
17.6.1	Provisioning PBN service interfaces	715
17.6.2	Provisioning Backbone Bridged Network service interfaces	718

17.7	MIB modules	724
17.7.1	Definitions for the IEEE8021-TC-MIB module	724
17.7.2	Definitions for the IEEE8021-BRIDGE-MIB module	733
17.7.3	Definitions for the IEEE8021-SPANNING-TREE-MIB module	766
17.7.4	Definitions for the IEEE8021-Q-BRIDGE-MIB module	781
17.7.5	Definitions for the IEEE8021-PB-MIB module	819
17.7.6	Definitions for the IEEE8021-MSTP-MIB module	834
17.7.7	Definitions for the CFM MIB modules	858
17.7.8	Definitions for the IEEE8021-PBB-MIB module	926
17.7.9	Definitions for the IEEE8021-DDCFM-MIB module	945
17.7.10	Definitions for the IEEE8021-PBBTE-MIB module	960
17.7.11	Definitions for the IEEE8021-TPMR-MIB module	974
17.7.12	Definitions for the IEEE8021-FQTSS-MIB module	986
17.7.13	Definitions for the IEEE8021-CN-MIB module	998
17.7.14	Definitions for the IEEE8021-SRP-MIB module	1028
17.7.15	Definitions for the IEEE8021-MVRPX-MIB module	1046
17.7.16	Definitions for the IEEE8021-MIRP-MIB module	1050
17.7.17	Definitions for the IEEE8021-PFC-MIB module	1055
17.7.18	Definitions for the IEEE8021-TEIPS-V2-MIB module	1058
17.7.19	Definitions for the IEEE8021-SPB-MIB module	1070
17.7.20	Definitions for the IEEE8021-EVB-MIB module	1106
17.7.21	Definitions for the IEEE8021-ECMP-MIB module	1130
17.7.22	Definitions for the IEEE8021-ST-MIB module	1137
17.7.23	Definitions for the IEEE8021-Preemption-MIB module	1148
17.7.24	Definitions for the IEEE8021-PSFP-MIB module	1153
17.7.25	Definitions for the IEEE8021-TSN-REMOTE-MANAGEMENT-MIB module	1173
18.	Principles of Connectivity Fault Management operation	1182
18.1	Maintenance Domains and DoSAPs.....	1183
18.2	Service instances and MAs	1185
18.3	Maintenance Domain Levels	1186
19.	CFM entity operation.....	1190
19.1	Maintenance Points (MPs).....	1190

19.2	MA Endpoints (MEPs)	1190
19.2.1	MEP identification	1190
19.2.2	MEP functions	1192
19.2.3	MEP architecture	1192
19.2.4	MP Type Demultiplexer	1194
19.2.5	MP Multiplexer	1194
19.2.6	MP Level Demultiplexer	1194
19.2.7	MP OpCode Demultiplexer	1194
19.2.8	MEP Continuity Check Receiver	1194
19.2.9	MEP Continuity Check Initiator	1195
19.2.10	MP Loopback Responder	1195
19.2.11	MEP Loopback Initiator	1196
19.2.12	MEP Linktrace Initiator	1196
19.2.13	MEP LTI SAP	1196
19.2.14	MEP Linktrace SAP	1196
19.2.15	MEP CCM Database	1196
19.2.16	MEP Fault Notification Generator	1196
19.2.17	MEP Decapsulator Responder (DR)	1196
19.2.18	MEP RFM Receiver	1197
19.3	MIP Half Function	1197
19.3.1	MHF identification	1197
19.3.2	MHF functions	1197
19.3.3	MHF architecture	1198
19.3.4	MHF Level Demultiplexer	1198
19.3.5	MHF Type Demultiplexer	1199
19.3.6	MHF OpCode Demultiplexer	1199
19.3.7	MHF Multiplexer	1199
19.3.8	MHF Loopback Responder	1199
19.3.9	MHF Continuity Check Receiver	1199
19.3.10	MIP CCM Database	1199
19.3.11	MHF Linktrace SAP	1199
19.3.12	MHF DR	1199
19.3.13	MHF RFM Receiver	1199
19.4	MP addressing.....	1200
19.5	Linktrace Output Multiplexer (LOM).....	1200
19.6	Linktrace Responder	1201
20.	CFM protocols	1203
20.1	Continuity Check protocol.....	1204
20.1.1	MAC status reporting in the CCM	1206
20.1.2	Defects and Fault Alarms	1206
20.1.3	CCM reception	1206
20.2	Loopback protocol	1207
20.2.1	LBM transmission	1207
20.2.2	LBM reception and LBR transmission	1208
20.2.3	LBR reception	1209
20.3	Linktrace protocol.....	1209
20.3.1	LTM origination	1210
20.3.2	LTM reception, forwarding, and replying	1211
20.3.3	LTR reception	1212
20.4	CFM state machines.....	1213

20.5	CFM state machine timers	1213
20.5.1	LTFwhile	1213
20.5.2	CCIwhile	1213
20.5.3	errorCCMwhile	1214
20.5.4	xconCCMwhile	1215
20.5.5	LBIwhile	1215
20.5.6	FNGwhile	1215
20.5.7	mmCCMwhile	1215
20.5.8	mmLocwhile	1215
20.5.9	mmFNGwhile	1215
20.5.10	rMEPwhile	1215
20.6	CFM procedures	1215
20.6.1	CCMtime()	1215
20.7	Maintenance Domain variable	1216
20.7.1	mdLevel	1216
20.8	MA variables.....	1216
20.8.1	CCMinterval	1216
20.9	MEP variables.....	1216
20.9.1	MEPactive	1217
20.9.2	enableRmepDefect	1217
20.9.3	MAdefectIndication	1217
20.9.4	allRMEPsDead	1218
20.9.5	lowestAlarmPri	1218
20.9.6	presentRDI	1218
20.9.7	MEPprimaryVID	1218
20.9.8	presentTraffic	1218
20.9.9	presentmmLoc	1218
20.9.10	ISpresentTraffic	1218
20.9.11	ISpresentmmLoc	1218
20.9.12	EpMEP	1219
20.10	MEP Continuity Check Initiator variables.....	1219
20.10.1	CCIenabled	1219
20.10.2	CCIsentCCMs	1219
20.10.3	MACstatusChanged	1219
20.10.4	Npaths	1219
20.10.5	flowHash[]	1219
20.10.6	pathN	1219
20.10.7	CCMent	1220
20.11	MEP Continuity Check Initiator procedures	1220
20.11.1	xmitCCM()	1220
20.12	MEP Continuity Check Initiator state machine	1221
20.13	MHF Continuity Check Receiver variables.....	1221
20.13.1	MHFrecvdCCM	1221
20.13.2	MHFCCMPDU	1221
20.14	MHF Continuity Check Receiver procedures.....	1222
20.14.1	MHFprocessCCM()	1222
20.15	MHF Continuity Check Receiver state machine	1222

20.16	MEP Continuity Check Receiver variables	1222
20.16.1	CCMreceivedEqual	1223
20.16.2	CCMequalPDU	1223
20.16.3	CCMreceivedLow	1223
20.16.4	CCMlowPDU	1223
20.16.5	recvdMacAddress	1223
20.16.6	recvdRDI	1223
20.16.7	recvdInterval	1223
20.16.8	recvdPortState	1223
20.16.9	recvdInterfaceStatus	1223
20.16.10	recvdSenderId	1224
20.16.11	recvdFrame	1224
20.16.12	CCMsequenceErrors	1224
20.16.13	rcvdTrafficBit	1224
20.17	MEP Continuity Check Receiver procedures	1224
20.17.1	MEPprocessEqualCCM()	1224
20.17.2	MEPprocessLowCCM()	1225
20.18	MEP Continuity Check Receiver state machine.....	1225
20.19	Remote MEP variables	1225
20.19.1	rMEPCCMdefect	1226
20.19.2	rMEPlastRDI and rMEPlastRDI[i]	1226
20.19.3	rMEPlastPortState	1226
20.19.4	rMEPlastInterfaceStatus	1226
20.19.5	rMEPlastSenderId	1227
20.19.6	rCCMreceived	1227
20.19.7	rMEPmacAddress	1227
20.19.8	rMEPportStatusDefect	1227
20.19.9	rMEPinterfaceStatusDefect	1227
20.19.10	lastPathN	1227
20.20	Remote MEP state machine.....	1227
20.21	Remote MEP Error variables.....	1227
20.21.1	errorCCMreceived	1228
20.21.2	errorCCMlastFailure	1228
20.21.3	errorCCMdefect	1229
20.22	Remote MEP Error state machine	1229
20.23	MEP Cross Connect variables	1229
20.23.1	xconCCMreceived	1229
20.23.2	xconCCMlastFailure	1229
20.23.3	xconCCMdefect	1230
20.24	MEP Cross Connect state machine.....	1230
20.25	MEP Mismatch variables.....	1230
20.25.1	mmCCMreceived	1230
20.25.2	mmCCMdefect	1231
20.25.3	mmCCMTime	1231
20.25.4	disableLocdefect	1231
20.25.5	mmLocdefect	1231
20.26	MEP Mismatch state machines.....	1231
20.27	MP Loopback Responder variables	1231
20.27.1	LBMreceived	1231
20.27.2	LBMpDU	1232
20.28	MP Loopback Responder procedures	1233
20.28.1	ProcessLBM()	1233
20.28.2	xmitLBR()	1233
20.29	MP Loopback Responder state machine.....	1234

20.30	MEP Loopback Initiator variables	1234
20.30.1	LBMstosend	1235
20.30.2	nextLBMtransID	1235
20.30.3	expectedLBRtransID	1235
20.30.4	LBIactive	1235
20.30.5	xmitReady	1235
20.30.6	LBRreceived	1235
20.30.7	LBRPDU	1235
20.31	MEP Loopback Initiator transmit procedures.....	1235
20.31.1	xmitLBM()	1236
20.32	MEP Loopback Initiator transmit state machine	1236
20.33	MEP Loopback Initiator receive procedures	1236
20.33.1	ProcessLBR()	1237
20.34	MEP Loopback Initiator receive state machine.....	1238
20.35	MEP Fault Notification Generator variables	1238
20.35.1	fngPriority	1238
20.35.2	fngDefect	1238
20.35.3	fngAlarmTime	1238
20.35.4	fngResetTime	1239
20.35.5	someRMEPCCMdefect	1239
20.35.6	someMACstatusDefect	1239
20.35.7	someRDId defect	1239
20.35.8	highestDefectPri	1239
20.35.9	highestDefect	1239
20.36	MEP Fault Notification Generator procedures	1239
20.36.1	xmitFaultAlarm()	1240
20.37	MEP Fault Notification Generator state machine.....	1240
20.38	MEP Mismatch Fault Notification Generator variables	1240
20.38.1	mfngAllowed	1241
20.38.2	mmdefectIndication	1241
20.38.3	mfngAlarmTime	1241
20.38.4	mfngResetTime	1241
20.39	MEP Mismatch Fault Notification Generator procedures	1241
20.39.1	xmitFaultAlarm()	1241
20.40	MEP Mismatch Fault Notification Generator state machine.....	1241
20.41	MEP Linktrace Initiator variables.....	1241
20.41.1	nextLTMtransID	1242
20.41.2	ltmReplyList	1242
20.42	MEP Linktrace Initiator procedures	1244
20.42.1	xmitLTM()	1244
20.43	MEP Linktrace Initiator receive variables	1245
20.43.1	LTRreceived	1245
20.43.2	LTRPDU	1245
20.44	MEP Linktrace Initiator receive procedures.....	1245
20.44.1	ProcessLTR()	1246
20.45	MEP Linktrace Initiator receive state machine.....	1246
20.46	Linktrace Responder variables.....	1246
20.46.1	nPendingLTRs	1246
20.46.2	LTMreceived	1247
20.46.3	LTMpdu	1247

20.47	LTM Receiver procedures	1247
20.47.1	ProcessLTM()	1247
20.47.2	clearPendingLTRs()	1251
20.47.3	ForwardLTM()	1251
20.47.4	enqueLTR()	1252
20.48	LTM Receiver state machine	1254
20.49	LTR Transmitter procedure	1254
20.49.1	xmitOldestLTR()	1254
20.50	LTR Transmitter state machine	1254
20.51	CFM PDU validation and versioning	1254
20.51.1	Goals of CFM PDU versioning	1255
20.51.2	PDU transmission	1255
20.51.3	PDU validation	1256
20.51.4	Validation pass	1256
20.51.5	Execution pass	1257
20.51.6	Future extensions	1258
20.52	PDU identification	1258
20.53	Use of transaction IDs and sequence numbers	1258
21.	Encoding of CFM PDUs	1260
21.1	Structure, representation, and encoding	1260
21.2	CFM encapsulation	1260
21.3	CFM request and indication parameters	1261
21.3.1	destination_address parameter	1261
21.3.2	source_address parameter	1261
21.4	Common CFM Header	1261
21.4.1	MD Level	1261
21.4.2	Version	1261
21.4.3	OpCode	1262
21.4.4	Flags	1262
21.4.5	First TLV Offset	1263
21.5	TLV format	1263
21.5.1	General format for CFM TLVs	1263
21.5.2	Organization-Specific TLV	1263
21.5.3	Sender ID TLV	1265
21.5.4	Port Status TLV	1266
21.5.5	Interface Status TLV	1267
21.5.6	Data TLV	1268
21.5.7	End TLV	1268
21.6	CCM format	1268
21.6.1	Flags	1269
21.6.2	First TLV Offset	1270
21.6.3	Sequence Number	1270
21.6.4	Maintenance association Endpoint Identifier	1270
21.6.5	Maintenance Association Identifier	1270
21.6.6	Defined by ITU-T G.8013/Y.1731	1273
21.6.7	Optional CCM TLVs	1273
21.7	LBM and LBR formats	1273
21.7.1	Flags	1274
21.7.2	First TLV Offset	1274
21.7.3	Loopback Transaction Identifier	1274
21.7.4	Additional LBM/LBR TLVs	1274
21.7.5	PBB-TE MIP TLV	1274

21.8	LTM format	1275
21.8.1	Flags	1276
21.8.2	First TLV Offset	1276
21.8.3	LTM Transaction Identifier	1276
21.8.4	LTM TTL	1276
21.8.5	Original MAC Address	1276
21.8.6	Target MAC Address	1276
21.8.7	Additional LTM TLVs	1277
21.8.8	LTM Egress Identifier TLV	1277
21.9	LTR format	1277
21.9.1	Flags	1277
21.9.2	First TLV Offset	1278
21.9.3	LTR Transaction Identifier	1278
21.9.4	Reply TTL	1278
21.9.5	Relay Action	1279
21.9.6	Additional LTR TLVs	1279
21.9.7	LTR Egress Identifier TLV	1279
21.9.8	Reply Ingress TLV	1280
21.9.9	Reply Egress TLV	1281
22.	CFM in systems	1283
22.1	CFM shims in Bridges	1283
22.1.1	Preliminary positioning of MPs	1283
22.1.2	CFM and the Forwarding Process	1284
22.1.3	Up/Down separation of MPs	1286
22.1.4	Service instances over multiple Bridges	1288
22.1.5	Multiple VID service instances	1290
22.1.6	Untagged CFM PDUs	1290
22.1.7	MPs and non-VLAN-aware Bridges	1290
22.1.8	MPs and other standards	1291
22.1.9	CFM and IEEE 802.3 OAM	1293
22.2	Maintenance Entity creation	1293
22.2.1	Creating Maintenance Domains and MAs	1294
22.2.2	Creating MEPs	1294
22.2.3	Creating MIPs	1296
22.2.4	CFM configuration errors	1297
22.3	MPs, Ports, and MD Level assignment.....	1298
22.4	Stations and CFM	1298
22.5	Scalability of CFM.....	1299
22.6	CFM in Provider Bridges.....	1300
22.6.1	MPs and C-VLAN components	1300
22.6.2	Maintenance C-VLAN on a Port-based service interface	1300
22.6.3	Maintenance C-VLAN on a C-tagged service interface	1302
22.6.4	MPs and Port-mapping S-VLAN components	1302
22.7	Management Port MEPs and CFM in the enterprise environment.....	1304
22.8	Implementing CFM on Bridges that implement earlier revisions of IEEE Std 802.1Q	1306
23.	MAC status propagation	1307
23.1	Model of operation.....	1309
23.1.1	MAC Status Shim (MSS)	1310
23.1.2	Relationship of CFM to the MSS	1310
23.2	MAC Status Protocol (MSP) overview	1310
23.3	MSP state machines	1315

23.4	State machine timers	1316
23.4.1	linkNotifyWhen	1316
23.4.2	linkNotifyWhile	1316
23.4.3	macNotifyWhile	1316
23.4.4	macRecoverWhile	1316
23.5	MSP performance parameters.....	1316
23.5.1	LinkNotify	1317
23.5.2	LinkNotifyWait	1317
23.5.3	LinkNotifyRetry	1317
23.5.4	MACNotify	1317
23.5.5	MACNotifyTime	1317
23.5.6	MACRecoverTime	1317
23.6	State machine variables	1317
23.6.1	BEGIN	1317
23.6.2	addConfirmed	1317
23.6.3	disableMAC	1317
23.6.4	disabledMAC	1317
23.6.5	disableMSS	1317
23.6.6	lossConfirmed	1317
23.6.7	macOperational	1318
23.6.8	mssOperational	1318
23.6.9	prop	1318
23.6.10	rxAck	1318
23.6.11	rxAdd	1318
23.6.12	rxAddConfirm	1318
23.6.13	rxLoss	1318
23.6.14	rxLossConfirm	1318
23.6.15	txAck	1318
23.6.16	txAdd	1318
23.6.17	txAddConfirm	1318
23.6.18	txLoss	1318
23.6.19	txLossConfirm	1318
23.7	State machine procedures	1319
23.8	Status Transition state machine (STM)	1319
23.9	Status Notification state machine (SNM)	1319
23.10	Receive Process	1319
23.11	Transmit Process.....	1319
23.12	Management of MSP	1320
23.13	MSPDU transmission, addressing, and protocol identification.....	1321
23.13.1	Destination MAC Address	1321
23.13.2	Source MAC Address	1321
23.13.3	Priority	1321
23.13.4	EtherType use and encoding	1321
23.14	Representation and encoding of octets	1322
23.15	MSPDU structure.....	1322
23.15.1	Protocol Version	1322
23.15.2	Packet Type	1322
23.16	Validation of received MSPDUs	1323
23.17	Other MSP participants.....	1323
24.	Bridge performance	1324
24.1	Guaranteed Port Filtering Rate	1324
24.2	Guaranteed Bridge Relaying Rate	1324

24.3	RSTP performance requirements.....	1324
25.	Support of the MAC Service by PBBNs	1326
25.1	Service transparency	1328
25.2	Customer service interface.....	1328
25.3	Port-based service interface	1329
25.4	S-tagged service interface	1330
25.5	I-tagged service interface	1332
25.6	Service instance segregation	1334
25.7	Service instance selection and identification	1334
25.8	Service priority and drop eligibility selection.....	1334
25.9	Service access protection	1335
25.9.1	Class II redundant LANs access protection	1337
25.9.2	Class III simple redundant LANs and nodes access protection	1337
25.10	Support of the MAC Service by a PBB-TE Region	1338
25.10.1	Provisioning TESIS	1339
25.10.2	ESP forwarding behavior	1341
25.11	Transparent service interface	1342
26.	Principles of Provider Backbone Bridged Network (PBBN) operation	1344
26.1	PBBN overview	1344
26.2	PBBN example	1345
26.3	B-VLAN connectivity.....	1347
26.4	Backbone addressing	1347
26.4.1	Learning individual backbone addresses at a PIP	1348
26.4.2	Translating backbone destination addresses at a CBP	1349
26.4.3	Backbone addressing considerations for CFM MPs	1349
26.5	Detection of connectivity loops through attached networks.....	1350
26.6	Scaling of PBBs.....	1350
26.6.1	Hierarchical PBBNs	1350
26.6.2	Peer PBBNs	1351
26.7	Network management	1351
26.8	CFM in PBBs.....	1351
26.8.1	CFM over Port-based and S-tagged service interfaces	1356
26.8.2	CFM over I-tagged Service Interfaces	1357
26.8.3	CFM over hierarchical E-NNI	1357
26.8.4	CFM over peer E-NNI	1358
26.9	CFM in a PBB-TE Region.....	1358
26.9.1	Addressing PBB-TE MEPs	1359
26.9.2	TESI identification	1359
26.9.3	PBB-TE MEP placement in a Bridge Port	1359
26.9.4	PBB-TE MIP placement in a Bridge Port	1360
26.9.5	TESI Maintenance Domains	1360
26.9.6	PBB-TE enhancements of the CFM protocols	1360
26.9.7	Addressing Infrastructure Segment MEPs	1362
26.9.8	Infrastructure Segment identification	1363
26.9.9	Infrastructure Segment MEP placement in a Bridge Port	1363
26.9.10	Infrastructure Segment Maintenance Domains	1365
26.9.11	IPS extensions to Continuity Check operation	1365
26.10	Protection switching for point-to-point TESIS.....	1365
26.10.1	Introduction	1365
26.10.2	1:1 point-to-point TESI protection switching	1366
26.10.3	Protection Switching state machines	1369

26.11	IPS in PBB-TE Region	1375
26.11.1	Infrastructure Segment monitoring	1376
26.11.2	1:1 IPS	1376
26.11.3	IPS Control entity	1379
26.11.4	1:1 IPS state machines	1380
26.11.5	M:1 IPS	1381
26.12	Mismatch defect.....	1386
26.13	Signaling VLAN registrations among I-components	1387
27.	Shortest Path Bridging (SPB)	1388
27.1	Protocol design requirements.....	1390
27.2	Protocol support.....	1391
27.3	Protocol design goals	1392
27.4	ISIS-SPB VLAN configuration	1392
27.4.1	SPT Region and ISIS-SPB adjacency determination	1393
27.5	ISIS-SPB information	1395
27.6	Calculating CIST connectivity.....	1396
27.7	Connectivity between regions in the same domain	1397
27.8	Calculating SPT connectivity	1397
27.8.1	ISIS-SPB overload	1398
27.9	Loop prevention.....	1398
27.10	SPVID and SPSourceID allocation.....	1398
27.11	Allocation of VIDs to FIDs	1400
27.12	SPBV SPVID translation	1401
27.13	VLAN topology management.....	1401
27.14	Individual addresses and SPBM	1402
27.14.1	Loop mitigation	1403
27.14.2	Loop prevention	1403
27.15	SPBM group addressing	1403
27.16	Backbone service instance topology management	1405
27.17	Equal cost shortest paths, ECTs, and load spreading	1406
27.18	Connectivity Fault Management for SPBM	1406
27.18.1	SPBM MA types	1406
27.18.2	SPBM MEP placement in a Bridge Port	1407
27.18.3	SPBM MIP placement in a Bridge Port	1408
27.18.4	SPBM modifications of the CFM protocols	1408
27.19	Using SPBV and SPBM modes	1409
27.19.1	Shortest Path Bridging—VID	1409
27.19.2	Shortest Path Bridging—MAC	1410
27.20	Security considerations	1412
28.	ISIS-SPB Link State Protocol.....	1413
28.1	ISIS-SPB control plane MAC.....	1413
28.2	Formation and maintenance of ISIS-SPB adjacencies	1414
28.3	Loop prevention.....	1415
28.4	The Agreement Digest.....	1415
28.4.1	Agreement Digest Format Identifier	1415
28.4.2	Agreement Digest Format Capabilities	1416
28.4.3	Agreement Digest Convention Identifier	1416
28.4.4	Agreement Digest Convention Capabilities	1416
28.4.5	Agreement Digest Edge Count	1417
28.4.6	The Computed Topology Digest	1417
28.5	Symmetric shortest path tie breaking.....	1418

28.6	Symmetric ECT framework.....	1419
28.7	Symmetric ECT	1420
28.8	Symmetric ECT Algorithm details	1421
28.9	ECT Migration.....	1422
28.9.1	Use of a new ECT Algorithm in SPBV	1422
28.9.2	Use of a new ECT Algorithm in SPBM	1423
28.10	MAC address registration	1424
28.11	Circuit IDs and Port Identifiers.....	1424
28.12	ISIS-SPB TLVs.....	1424
28.12.1	MT-Capability TLV	1425
28.12.2	SPB MCID sub-TLV	1425
28.12.3	SPB Digest sub-TLV	1426
28.12.4	SPB Base VLAN-Identifiers sub-TLV	1427
28.12.5	SPB Instance sub-TLV	1428
28.12.6	SPB Instance Opaque ECT Algorithm sub-TLV	1429
28.12.7	SPB Link Metric sub-TLV	1431
28.12.8	SPB Adjacency Opaque ECT Algorithm sub-TLV	1431
28.12.9	SPBV MAC address sub-TLV	1432
28.12.10	SPBM Service Identifier and Unicast Address (ISID-ADDR) sub-TLV	1433
29.	DDCFM operations and protocols.....	1436
29.1	Principles of DDCFM operation.....	1436
29.1.1	Data-driven and data-dependent faults (DDFs)	1436
29.1.2	Basic principle to diagnose and isolate DDFs	1436
29.2	DDCFM Entity operation	1439
29.2.1	DDCFM implementation	1439
29.2.2	FPT RR	1440
29.2.3	RR-related parameters	1441
29.2.4	Reflection Target and RFM Receiver	1442
29.2.5	RPT-related parameters	1442
29.2.6	Decapsulator Responder (DR)	1443
29.2.7	SFM Originator	1444
29.3	DDCFM protocols	1444
29.3.1	RR variables	1444
29.3.2	RR Filter procedures	1446
29.3.3	RR Encapsulation procedures	1447
29.3.4	RR Transmit procedure	1448
29.3.5	RR-related state machines	1449
29.3.6	RFM Receiver variables	1450
29.3.7	RFM Receiver procedure	1451
29.3.8	DR variables	1452
29.3.9	DR procedures	1452
29.3.10	Decapsulator Responder state machine	1454
29.4	Encoding of DDCFM PDUs.....	1454
29.4.1	RFM and SFM Header	1454
29.4.2	RFM format	1454
29.4.3	SFM format	1455
30.	Principles of congestion notification	1457
30.1	Congestion notification design requirements	1457

30.2	Quantized Congestion Notification protocol (QCN)	1459
30.2.1	The CP algorithm	1460
30.2.2	Basic RP algorithm	1461
30.2.3	RP algorithm with timer	1462
30.3	Congestion Controlled Flow (CCF).....	1463
30.4	Congestion Notification Priority Value (CNPV).....	1464
30.5	Congestion Notification tag (CN-TAG)	1464
30.6	Congestion Notification Domain (CND).....	1464
30.7	Multicast data.....	1465
30.8	Congestion notification and additional tags.....	1465
31.	Congestion notification entity operation.....	1467
31.1	Congestion-aware Bridge Forwarding Process.....	1467
31.1.1	Congestion Point (CP)	1468
31.1.2	CP ingress multiplexer	1468
31.2	Congestion-aware end station functions	1468
31.2.1	Output flow segregation	1470
31.2.2	Per-CNPV station function	1470
31.2.3	Flow Select Database	1472
31.2.4	Flow multiplexer	1472
31.2.5	CNM demultiplexer	1472
31.2.6	Input flow segregation	1473
31.2.7	End station input queue	1473
31.2.8	Reception selection	1473
32.	Congestion notification protocol	1474
32.1	CND operations	1474
32.1.1	CND defense	1474
32.1.2	Automatic CND recognition	1476
32.1.3	Variables controlling CND defense	1476
32.2	CN component variables.....	1477
32.2.1	cngMasterEnable	1478
32.2.2	cngCnmTransmitPriority	1478
32.2.3	cngDiscardedFrames	1478
32.2.4	cngErroredPortList	1478
32.3	Congestion notification per-CNPV variables	1478
32.3.1	cncpDefModeChoice	1478
32.3.2	cncpAlternatePriority	1479
32.3.3	cncpAutoAltPri	1479
32.3.4	cncpAdminDefenseMode	1479
32.3.5	cncpCreation	1479
32.3.6	cncpLdpInstanceChoice	1479
32.3.7	cncpLdpInstanceSelector	1479

32.4	CND defense per-Port per-CNPV variables	1480
32.4.1	cnpdDefModeChoice	1480
32.4.2	cnpdAdminDefenseMode	1480
32.4.3	cnpdAutoDefenseMode	1481
32.4.4	cnpdLldpInstanceChoice	1481
32.4.5	cnpdLldpInstanceSelector	1481
32.4.6	cnpdAlternatePriority	1481
32.4.7	cnpdXmitCnpvCapable	1481
32.4.8	cnpdXmitReady	1481
32.4.9	cncpDoesEdge	1482
32.4.10	cnpdAcceptsCnTag	1482
32.4.11	cnpdRcvdCnpv	1482
32.4.12	cnpdRcvdReady	1482
32.4.13	cnpdIsAdminDefMode	1482
32.4.14	cnpdDefenseMode	1482
32.5	CND defense procedures	1483
32.5.1	DisableCnpvRemapping()	1483
32.5.2	TurnOnCnDefenses()	1483
32.5.3	TurnOffCnDefenses()	1483
32.6	CND defense state machine	1483
32.7	Congestion notification protocol	1484
32.8	CP variables	1485
32.8.1	cpMacAddress	1486
32.8.2	cpId	1486
32.8.3	cpQSp	1486
32.8.4	cpQLen	1486
32.8.5	cpQLenOld	1486
32.8.6	cpW	1486
32.8.7	cpQOffset	1486
32.8.8	cpQDelta	1486
32.8.9	cpFb	1486
32.8.10	cpEnqueued	1487
32.8.11	cpSampleBase	1487
32.8.12	cpDiscardedFrames	1487
32.8.13	cpTransmittedFrames	1487
32.8.14	cpTransmittedCnms	1487
32.8.15	cpMinHeaderOctets	1487
32.9	CP procedures	1487
32.9.1	Random	1487
32.9.2	NewCpSampleBase()	1487
32.9.3	EM_UNITDATA.request (parameters)	1488
32.9.4	GenerateCnmPdu()	1488
32.10	RP per-Port per-CNPV variables	1489
32.10.1	rpppMaxRps	1489
32.10.2	rpppCreatedRps	1489
32.10.3	rpppRpCentiseconds	1490

32.11	RP group variables	1490
32.11.1	rpgEnable	1490
32.11.2	rpgTimeReset	1490
32.11.3	rpgByteReset	1490
32.11.4	rpgThreshold	1491
32.11.5	rpgMaxRate	1491
32.11.6	rpgAiRate	1491
32.11.7	rpgHaiRate	1491
32.11.8	rpgGd	1491
32.11.9	rpgMinDecFac	1491
32.11.10	rpgMinRate	1491
32.12	RP timer	1491
32.12.1	RpWhile	1491
32.13	RP variables	1492
32.13.1	rpEnabled	1492
32.13.2	rpByteCount	1492
32.13.3	rpByteStage	1492
32.13.4	rpTimeStage	1492
32.13.5	rpTargetRate	1492
32.13.6	rpCurrentRate	1492
32.13.7	rpFreeze	1492
32.13.8	rpLimiterRate	1493
32.13.9	rpFb	1493
32.14	RP procedures	1493
32.14.1	ResetCnm	1493
32.14.2	TestRpTerminate	1493
32.14.3	TransmitDataFrame	1493
32.14.4	ReceiveCnm	1494
32.14.5	ProcessCnm	1494
32.14.6	AdjustRates	1494
32.15	RP rate control state machine	1495
32.16	Congestion notification and encapsulation interworking function	1497
33.	Encoding of congestion notification PDUs	1499
33.1	Structure, representation, and encoding	1499
33.2	CN-TAG format	1499
33.2.1	Flow Identifier	1500
33.3	Congestion Notification Message (CNM)	1500
33.4	Congestion Notification Message PDU format	1500
33.4.1	Version	1500
33.4.2	ReservedV	1500
33.4.3	Quantized Feedback	1501
33.4.4	Congestion Point Identifier	1501
33.4.5	cnmQOffset	1501
33.4.6	cnmQDelta	1501
33.4.7	Encapsulated priority	1502
33.4.8	Encapsulated destination MAC address	1502
33.4.9	Encapsulated MSDU length	1502
33.4.10	Encapsulated MSDU	1502
33.4.11	CNM Validation	1502
34.	Forwarding and Queuing Enhancements for time-sensitive streams (FQTSS)	1503
34.1	Overview	1503

34.2	Detection of SRP domains	1503
34.3	The bandwidth availability parameters	1504
34.3.1	deltaBandwidth when lockClassBandwidth is false	1504
34.3.2	deltaBandwidth when lockClassBandwidth is true	1505
34.3.3	Bandwidth availability parameter management	1505
34.4	Deriving actual bandwidth requirements from the size of the MSDU	1506
34.5	Default SR class configuration	1507
34.6	Transmission selection.....	1508
34.6.1	Credit-based shaper	1509
34.6.2	Strict priority	1510
34.6.3	Scheduled traffic	1511
35.	Stream Reservation Protocol (SRP).....	1512
35.1	Multiple Stream Registration Protocol (MSRP).....	1513
35.1.1	MSRP and Shared Media	1514
35.1.2	Behavior of end stations	1515
35.1.3	Behavior of Bridges	1517
35.1.4	SRP domains and status parameters	1517
35.2	Definition of the MSRP application	1518
35.2.1	Definition of internal state variables	1518
35.2.2	Definition of MRP elements	1520
35.2.3	Provision and support of Stream registration service	1544
35.2.4	MSRP Attribute Propagation	1549
35.2.5	Operational reporting and statistics	1558
35.2.6	Encoding	1558
35.2.7	Attribute value support requirements	1559
36.	Priority-based Flow Control (PFC).....	1560
36.1	PFC operation	1560
36.1.1	Overview	1560
36.1.2	PFC primitives	1561
36.1.3	Detailed specification of PFC operation	1562
36.2	PFC-aware system queue functions.....	1563
36.2.1	PFC Initiator	1563
36.2.2	PFC Receiver	1563
37.	Enhanced Transmission Selection (ETS)	1566
37.1	Overview.....	1566
37.1.1	Relationship to other transmission selection algorithms	1566
37.2	ETS configuration parameters	1566
37.3	ETS algorithm.....	1566
37.4	Legacy configuration	1567
38.	Data Center Bridging eXchange protocol (DCBX).....	1568
38.1	Overview.....	1568
38.2	Goals	1568
38.3	Types of DCBX attributes	1568
38.3.1	Informational attributes	1568
38.4	DCBX and LLDP.....	1568
38.4.1	Asymmetric attribute passing	1569
38.4.2	Symmetric attribute passing	1570

39.	Multiple I-SID Registration Protocol (MIRP)	1572
39.1	MIRP overview	1572
39.1.1	Behavior of I-components	1574
39.1.2	Behavior of B-components	1574
39.2	Definition of the MIRP application	1574
39.2.1	Definition of MRP elements	1574
39.2.2	Alternate MIRP model for B-components	1577
39.2.3	Use of “new” declaration capability	1579
39.2.4	Attribute value support requirements	1579
39.2.5	MRP Message filtering	1579
40.	Edge Virtual Bridging (EVB)	1580
40.1	EVB architecture without S-channels	1581
40.2	EVB architecture with S-channels	1582
40.3	Asymmetric EVB architecture without S-channels	1584
40.4	EVB status parameters	1586
40.4.1	EVBMode = Not supported	1586
40.4.2	EVBMode = EVB Bridge	1586
40.4.3	EVBMode = EVB station	1586
40.4.4	EVBMode = NVO3 Mode	1587
40.5	EVB Status Parameter for NVO3 Mode Support	1587
40.5.1	NVERole = nNVE	1587
40.5.2	NVERole = tNVE	1587
41.	VSI Discovery and Configuration Protocol (VDP)	1588
41.1	VSI manager ID TLV definition	1588
41.1.1	TLV type	1589
41.1.2	TLV information string length	1589
41.1.3	VSI Manager ID	1589
41.2	VDP association TLV definitions	1589
41.2.1	TLV type	1590
41.2.2	TLV information string length	1590
41.2.3	Status	1590
41.2.4	VSI Type ID (VTID)	1591
41.2.5	VSI Type Version	1591
41.2.6	VSIID format	1591
41.2.7	VSIID	1592
41.2.8	Filter Info format	1592
41.2.9	Filter Info field	1593
41.2.10	VDP TLV type and status semantics	1597
41.3	Organizationally defined TLV definitions	1598
41.3.1	TLV type	1598
41.3.2	TLV information string length	1598
41.3.3	Organizationally unique identifier (OUI) or Company ID (CID)	1598
41.3.4	Organizationally defined information	1599
41.4	Validation rules for VDP TLVs	1599

41.5	VDP state machines	1599
41.5.1	State machine conventions	1599
41.5.2	Bridge VDP state machine	1600
41.5.3	Station VDP state machine	1601
41.5.4	VDP state machine timers	1602
41.5.5	VDP state machine variables and parameters	1602
41.5.6	Command-Response TLV field references in state machines	1604
41.5.7	VDP state machine procedures	1605
42.	S-Channel Discovery and Configuration Protocol (CDCP)	1607
42.1	CDCP discovery and configuration	1607
42.2	CDCP state machine overview	1607
42.3	CDCP configuration state machine.....	1608
42.4	CDCP configuration variables	1609
42.4.1	AdminChnCap	1609
42.4.2	AdminRole	1610
42.4.3	AdminSVIDWants	1610
42.4.4	LastLocalSVIDPool	1610
42.4.5	LastRemoteSVIDList	1610
42.4.6	LastSVIDWants	1610
42.4.7	LocalSVIDPool	1610
42.4.8	OperChnCap	1610
42.4.9	OperRole	1610
42.4.10	OperSVIDList	1611
42.4.11	RemoteChnCap	1611
42.4.12	RemoteRole	1611
42.4.13	RemoteSVIDList	1611
42.4.14	schState	1611
42.5	CDCP configuration procedures.....	1611
42.5.1	SetSVIDRequest (OperRole, AdminSVIDWants, OperSVIDList)	1611
42.5.2	RxSVIDConfig (OperSVIDList, LastRemoteSVIDList)	1612
42.5.3	TxSVIDConfig (OperChnCap, RemoteChnCap, LastLocalSVIDPool, RemoteSVIDList, OperSVIDList)	1612
43.	Edge Control Protocol (ECP)	1613
43.1	ECP operation	1613
43.2	Edge Control Sublayer Service (ECSS).....	1614
43.3	ECP state machines.....	1614
43.3.1	State machine conventions	1614
43.3.2	Overview	1614
43.3.3	Edge Control Protocol Data Unit (ECPDU)	1615
43.3.4	ECP transmit state machine	1616
43.3.5	ECP receive state machine	1617
43.3.6	ECP state machine timers	1617
43.3.7	ECP state machine variables and parameters	1618
43.3.8	ECP state machine procedures	1619
44.	Equal Cost Multiple Paths (ECMP).....	1620
44.1	SPBM ECMP	1620
44.1.1	ECMP Operation	1620
44.1.2	ECMP ECT Algorithm	1621
44.1.3	Loop prevention for ECMP	1623

44.2	Support for Flow Filtering	1623
44.2.1	Flow filtering tag (F-TAG)	1624
44.2.2	F-TAG processing	1625
44.2.3	Forwarding process extension for flow filtering	1626
44.2.4	TTL Loop mitigation	1627
44.2.5	CFM for ECMP with flow filtering	1627
44.2.6	Operation with selective support for flow filtering	1629
45.	Path Control and Reservation (PCR)	1630
45.1	Explicit trees	1630
45.1.1	Tree structures	1634
45.1.2	Explicit ECT Algorithms	1635
45.1.3	ISIS-PCR VLAN configuration	1637
45.1.4	Use of VIDs for strict explicit trees	1641
45.1.5	MAC addresses and ISIS-PCR	1642
45.1.6	Filtering Database entries for explicit trees	1642
45.1.7	ISIS-PCR support	1643
45.1.8	Attributes for path computation	1643
45.1.9	Topology sub-TLV	1645
45.1.10	Hop sub-TLV	1648
45.1.11	Administrative Group sub-TLV	1652
45.1.12	Bandwidth Constraint sub-TLV	1652
45.2	Reservation	1653
45.2.1	Bandwidth Assignment sub-TLV	1653
45.2.2	Timestamp sub-TLV	1654
45.2.3	Precedence ordering	1655
45.3	Redundancy	1655
45.3.1	Loop-free alternates for unicast data flows	1655
45.3.2	Static redundant trees	1656
45.3.3	Maximally Redundant Trees (MRTs)	1657
45.3.4	MRTs with centralized GADAG computation	1659
46.	Time-Sensitive Networking (TSN) configuration	1664
46.1	Overview of TSN configuration	1664
46.1.1	User/Network Interface (UNI)	1664
46.1.2	Modeling of user/network configuration information	1664
46.1.3	TSN configuration models	1664
46.1.4	Stream transformation	1669
46.2	User/network configuration information	1671
46.2.1	Data types	1671
46.2.2	Protocol integration	1672
46.2.3	Talker	1673
46.2.4	Listener	1685
46.2.5	Status	1686
46.3	YANG for TSN user/network configuration	1692
47.	Asynchronous Traffic Shaping (ATS) in end stations	1693
47.1	Talker transmission behavior	1693
47.1.1	ATS traffic class model in Talkers	1693
47.1.2	Simplified ProcessFrame(frame) procedure	1693
47.1.3	System clock functions and processing delays	1693
47.2	Scheduler parameter consistency	1694

48.	YANG Data Models	1695
48.1	YANG Framework	1696
48.1.1	Interface Management (IETF RFC 8343) Model	1697
48.2	IEEE 802.1Q YANG models.....	1698
48.2.1	VLAN Bridge components model	1698
48.2.2	Two-Port MAC Relay (TPMR) model	1701
48.2.3	Customer VLAN Bridge model	1702
48.2.4	Provider Bridge model	1703
48.2.5	CFM Model	1706
48.2.6	Stream filters and stream gates model	1710
48.2.7	Asynchronous Traffic Shaping (ATS) model	1711
48.3	Structure of the YANG models	1712
48.3.1	VLAN Bridge components model	1713
48.3.2	Two-Port MAC Relay model	1713
48.3.3	Customer VLAN Bridge model	1713
48.3.4	Provider Bridge model	1713
48.3.5	CFM model	1714
48.3.6	Stream filters and stream gates model	1714
48.3.7	Asynchronous Traffic Shaping (ATS) model	1714
48.4	Security considerations	1716
48.4.1	Security considerations of the VLAN Bridge components model	1716
48.4.2	Security considerations of the Two-Port MAC Relay model	1717
48.4.3	Security considerations of the Customer VLAN Bridge model	1717
48.4.4	Security considerations of the Provider Bridge model	1717
48.4.5	Security considerations of the CFM model	1718
48.4.6	Security considerations of the Stream filters and stream gates model	1718
48.4.7	Security considerations of the Asynchronous Traffic Shaping model	1718
48.5	YANG schema tree definitions.....	1719
48.5.1	Schema for the ieee802-types YANG module	1719
48.5.2	Schema for the ieee802-dot1q-types YANG module	1719
48.5.3	Schema for the ieee802-dot1q-tsn-types YANG module	1719
48.5.4	Schema for the ieee802-dot1q-bridge YANG module	1719
48.5.5	Schema for the ieee802-dot1q-tpmr YANG module	1723
48.5.6	Schema for the ieee802-dot1q-pb YANG module	1723
48.5.7	Schema for the ieee802-dot1q-cfm-types YANG module	1723
48.5.8	Schema for the ieee802-dot1q-cfm YANG module	1724
48.5.9	Schema for the ieee802-dot1q-cfm-bridge YANG module	1726
48.5.10	Schema for the ieee802-dot1q-cfm-alarm YANG module	1727
48.5.11	Schema for the ieee802-dot1q-stream-filters-gates YANG module	1727
48.5.12	Schema for the ieee802-dot1q-ats YANG module	1728
48.6	YANG modules	1729
48.6.1	The ieee802-types YANG module	1729
48.6.2	The ieee802-dot1q-types YANG module	1734
48.6.3	The ieee802-dot1q-tsn-types YANG module	1748
48.6.4	The ieee802-dot1q-bridge YANG module	1767
48.6.5	The ieee802-dot1q-tpmr YANG module	1792
48.6.6	The ieee802-dot1q-pb YANG module	1797
48.6.7	The ieee802-dot1q-cfm-types YANG module	1800
48.6.8	The ieee802-dot1q-cfm YANG module	1811
48.6.9	The ieee802-dot1q-cfm-bridge YANG module	1830
48.6.10	The ieee802-dot1q-cfm-alarm YANG module	1838
48.6.11	The ieee802-dot1q-stream-filters-gates YANG module	1840
48.6.12	The ieee802-dot1q-ats YANG module	1846

Annex A (normative) PICS proforma—Bridge implementations	1851
A.1 Introduction.....	1851
A.2 Abbreviations and special symbols.....	1851
A.2.1 Status symbols	1851
A.2.2 General abbreviations	1851
A.3 Instructions for completing the PICS proforma.....	1852
A.3.1 General structure of the PICS proforma	1852
A.3.2 Additional information	1852
A.3.3 Exception information	1852
A.3.4 Conditional status	1853
A.4 PICS proforma for IEEE Std 802.1Q—Bridge implementations	1854
A.4.1 Implementation identification	1854
A.4.2 Protocol summary, IEEE Std 802.1Q	1854
A.5 Major capabilities	1855
A.6 Media access control methods	1860
A.7 Relay and filtering of frames	1861
A.8 Basic Filtering Services	1862
A.9 Addressing	1863
A.10 Rapid Spanning Tree Protocol (RSTP).....	1865
A.12 Implementation parameters.....	1867
A.11 BPDU encoding	1867
A.13 Performance	1868
A.14 Bridge management	1869
A.15 Remote management.....	1879
A.16 Expedited traffic classes	1880
A.17 Extended Filtering Services	1880
A.18 Multiple Spanning Tree Protocol (MSTP).....	1881
A.19 VLAN support	1883
A.20 Multiple MAC Registration Protocol (MMRP).....	1886
A.21 Multiple VLAN Registration Protocol (MVRP)	1887
A.22 Multiple Registration Protocol (MRP)	1888
A.23 Connectivity Fault Management (CFM).....	1889
A.24 Management Information Base (MIB)	1894
A.25 Protection Switching (PS).....	1897
A.26 Data-driven and data-dependent connectivity fault management (DDCFM).....	1897
A.27 Two-Port MAC Relay (TPMR)	1897
A.28 MAC Status Protocol (MSP)	1898
A.29 Forwarding and Queuing Enhancements for time-sensitive streams (FQTSS).....	1899
A.30 Congestion notification.....	1899
A.31 Stream Reservation Protocol (SRP).....	1900
A.32 Multiple I-SID Registration Protocol (MIRP)	1904
A.34 Enhanced Transmission Selection (ETS)	1905
A.33 Priority-based Flow Control (PFC).....	1905
A.35 Data Center Bridging eXchange protocol (DCBX).....	1906
A.36 Infrastructure Protection Switching (IPS).....	1906
A.38 EVB Bridge.....	1907
A.37 Shortest Path Bridging (SPB)	1907
A.39 EVB station.....	1908
A.40 Edge relay (ER)	1909
A.42 VDP, CDCP, and ECP	1911
A.41 VEB and VEPA ER components.....	1911
A.43 Path Control and Reservation	1912
A.44 Scheduled traffic	1913

ISO/IEC/IEEE 8802-1Q:2024(en)

A.45	Frame preemption	1913
A.46	Per-Stream Filtering and Policing.....	1914
A.47	YANG	1915
A.48	Stream reservation remote management (SRRM).....	1916
A.49	TSN Centralized Network Configuration (CNC) station	1917
A.50	VDP for NVO3 nNVE Devices	1918
A.51	VDP for NVO3 tNVE Devices	1919
A.52	Asynchronous Traffic Shaping	1920
Annex B (normative) PICS proforma—End station implementations		1921
B.1	Introduction.....	1921
B.2	Abbreviations and special symbols.....	1921
B.2.1	Status symbols	1921
B.2.2	General abbreviations	1921
B.3	Instructions for completing the PICS proforma.....	1922
B.3.1	General structure of the PICS proforma	1922
B.3.2	Additional information	1922
B.3.3	Exception information	1922
B.3.4	Conditional status	1923
B.4	PICS proforma for IEEE Std 802.1Q—End station implementations	1924
B.4.1	Implementation identification	1924
B.4.2	Protocol summary, IEEE Std 802.1Q	1924
B.5	Major capabilities	1925
B.6	Multiple MAC Registration Protocol (MMRP).....	1926
B.8	Multiple Registration Protocol (MRP)	1927
B.7	Multiple VLAN Registration Protocol (MVRP)	1927
B.9	Forwarding and Queuing Enhancements for time-sensitive streams (FQTSS).....	1928
B.10	Stream Reservation Protocol (SRP).....	1929
B.11	Congestion notification.....	1932
B.13	Enhanced Transmission Selection (ETS)	1934
B.14	Data Center Bridging eXchange protocol (DCBX).....	1934
B.12	Priority-based Flow Control (PFC).....	1934
B.16	Frame Preemption.....	1935
B.17	Per-Stream Filtering and Policing.....	1935
B.15	Scheduled traffic	1935
B.18	Asynchronous Traffic Shaping	1936
Annex C (normative) Designated MSRP Node (DMN) Implementations		1937
C.1	DMNs on CSNs	1937
C.1.1	CSN characteristics	1937
C.1.2	DMN handling on CSN	1938
C.1.3	MSRPDU handling on a CSN	1939
C.1.4	CSN bandwidth fluctuations	1940
C.2	DMN on MoCA	1940
C.2.1	DMN Selection on MoCA Network	1940
C.2.2	MoCA network bandwidth management	1944
C.3	DMNs on IEEE 802.11 media	1945
C.3.1	MSRP handling	1946
C.3.2	BSS DMN selection	1949
C.3.3	BSS network bandwidth management	1950

ISO/IEC/IEEE 8802-1Q:2024(en)

Annex D (normative) IEEE 802.1 Organizationally Specific TLVs	1953
D.1 Requirements of the IEEE 802.1 Organizationally Specific TLV sets.....	1953
D.2 Organizationally Specific TLV definitions.....	1954
D.2.1 Port VLAN ID TLV	1954
D.2.2 Port And Protocol VLAN ID TLV	1954
D.2.3 VLAN Name TLV	1955
D.2.4 Protocol Identity TLV	1956
D.2.5 VID Usage Digest TLV	1957
D.2.6 Management VID TLV	1957
D.2.7 Congestion Notification TLV	1958
D.2.8 ETS Configuration TLV	1959
D.2.9 ETS Recommendation TLV	1961
D.2.10 Priority-based Flow Control Configuration TLV	1962
D.2.11 Application Priority TLV	1963
D.2.12 EVB TLV	1964
D.2.13 CDCP TLV	1969
D.2.14 Application VLAN TLV	1971
D.3 IEEE 802.1 Organizationally Specific TLV management.....	1972
D.3.1 IEEE 802.1 Organizationally Specific TLV selection management	1972
D.3.2 IEEE 802.1 managed objects—TLV variables	1973
D.4 PICS proforma for IEEE 802.1 Organizationally Specific TLV extensions	1974
D.4.1 Implementation identification	1974
D.4.2 Protocol summary, IEEE Std 802.1Q	1974
D.4.3 Major capabilities and options	1975
D.5 IEEE 802.1/LLDP extension MIB.....	1977
D.5.1 Internet Standard Management Framework	1977
D.5.2 Structure of the IEEE 802.1/LLDP extension MIB	1977
D.5.3 Relationship to other MIBs	1984
D.5.4 Security considerations for IEEE 802.1 LLDP extension MIB module	1985
D.5.5 IEEE 802.1 LLDP extension MIB module—version 2	1987
D.5.6 EVB extensions to the IEEE 802.1 LLDP extension MIB module	2047
Annex E (normative) Notational conventions used in state diagrams.....	2054
Annex F (informative) Shared and Independent VLAN Learning (SVL and IVL)	2056
F.1 Requirements for Shared and Independent Learning	2056
F.1.1 Connecting independent VLANs	2057
F.1.2 Duplicate MAC addresses	2058
F.1.3 Asymmetric VLANs and Rooted-Multipoint connectivity	2059
F.1.4 Shared learning and Shortest Path Bridging VID (SPBV) mode	2062
F.1.5 Generic constraints on SVL and IVL use	2064
Annex G (informative) MAC method-dependent aspects of VLAN support.....	2065
G.1 Example tagged IEEE 802.3 EtherType-encoded frame format	2065
G.2 Padding and frame size considerations	2065
G.2.1 Treatment of PAD fields in IEEE 802.3 frames	2065
G.2.2 Maximum PDU size	2066
G.2.3 Minimum PDU size	2066
G.3 Tag insertion and removal for LLC media	2067

ISO/IEC/IEEE 8802-1Q:2024(en)

G.4	IEEE 802.11 and PMPN media	2068
G.4.1	IEEE 802.11 Portal convergence	2068
G.4.2	Point-to-Multipoint Network convergence: multiple connections	2068
G.4.3	Point-to-Multipoint Network convergence: single connection	2068
Annex H	(informative) Interoperability considerations.....	2069
H.1	Requirements for interoperability	2069
H.1.1	Static filtering requirements	2069
H.1.2	Configuration requirements for VLAN-tagging	2069
H.2	Homogeneous VLAN-aware networks.....	2070
H.2.1	Consistency of static VLAN filtering	2070
H.2.2	Consistent view of the “untagged VLAN(s)” on a given LAN	2071
H.3	Heterogeneous networks: Intermixing MAC Bridges (M) and VLAN Bridges (V)	2072
H.3.1	Example: Adding a VLAN Bridge to provide filtering to a MAC Bridged Network 2072	
H.3.2	Example: Adding a MAC Bridge to a (previously) Homogeneous VLAN Bridged Network	2073
H.4	Intermixing Port-based classification and Port-and-Protocol-based classification or future enhancements in VLAN Bridges	2073
H.4.1	Example: Intermixing Protocol-based ingress rules	2074
H.4.2	Differing views of untagged traffic on a given LAN	2074
Annex I	(informative) Priority and drop precedence.....	2075
I.1	Traffic types.....	2075
I.2	Managing latency and throughput	2076
I.3	Traffic type to traffic class mapping.....	2076
I.4	Traffic types and priority values.....	2078
I.5	Supporting the credit-based shaper algorithm	2079
I.6	Supporting drop precedence	2080
I.7	Priority Code Point allocation.....	2080
I.8	Interoperability.....	2081
Annex J	(informative) CFM protocol design and use.....	2083
J.1	Origin of CFM	2083
J.2	Deployment of CFM	2083
J.3	MD Level allocation alternative	2084
J.4	Relationship of IEEE Std 802.1Q CFM to other standards	2084
J.5	Interpreting Linktrace results.....	2085
J.6	MP addressing: Individual and Shared MP addresses	2086
J.6.1	Individual MP address model	2087
J.6.2	Shared MP address model and the CFM Port	2087
Annex K	(informative) TPMR use cases.....	2090
K.1	Use case 1—TPMR as User to Network Interface (UNI) demarcation device	2090
K.2	Use case 2—TPMRs with aggregated links	2091
K.3	Use case 3—Multiple TPMRs	2091
K.4	Special cases	2092
Annex L	(informative) Operation of the credit-based shaper algorithm	2095
L.1	Overview of credit-based shaper operation	2095
L.2	“Class measurement intervals” in Bridges.....	2100

ISO/IEC/IEEE 8802-1Q:2024(en)

L.3	Determining worst-case latency contribution and buffering requirements	2101
L.3.1	Interference delay	2102
L.3.2	Maximum interference delay and maximum buffer requirement	2110
L.4	Operation of credit-based shaper in Coordinated Shared Network (CSN).....	2111
Annex M	(normative) Support for PFC in link layers without MAC Control	2112
M.1	Overview.....	2112
M.2	PFC PDU format.....	2112
Annex N	(informative) Buffer requirements for PFC	2113
N.1	Overview.....	2113
N.2	Delay model.....	2113
N.3	Interface Delay.....	2116
N.4	Cable Delay.....	2116
N.5	Higher Layer Delay	2116
N.6	Computation example	2117
Annex O	(informative) Preserving the integrity of FCS fields in MAC Bridges	2118
O.1	Background.....	2118
O.2	Basic mathematical ideas behind CRC and FCS	2119
O.3	Detection Lossless Circuit approach.....	2120
O.4	Algorithmic modification of an FCS	2121
O.4.1	Data changed, length unchanged	2121
O.4.2	Length changed, original data unchanged	2122
O.4.3	Preservation of detectability	2123
O.5	Conclusions.....	2124
Annex P	(informative) Frame duplication and misordering.....	2125
P.1	Background.....	2125
P.2	Frame duplication	2125
P.3	Frame misordering.....	2126
P.4	Other considerations	2127
Annex Q	(informative) Traffic scheduling.....	2128
Q.1	Motivation.....	2128
Q.2	Using gate operations to create protected windows.....	2129
Q.3	Availability of PTP	2130
Q.4	Scheduled traffic and end stations	2130
Q.5	CycleTimeExtension variables	2130
Annex R	(informative) Preemption and IEEE 802.1AE MAC Security	2131
Annex S	(informative) Preemption and scheduled traffic	2133
S.1	Scheduling used in isolation	2133
S.2	Preemption used in isolation.....	2133
S.3	Scheduling and preemption used in combination, no HOLD/RELEASE	2134
S.4	Scheduling and preemption used in combination with HOLD/RELEASE	2134
S.5	Bandwidth allocation and express traffic.....	2134

Annex T (informative) Cyclic queuing and forwarding	2136
T.1 Overview of CQF.....	2136
T.2 An approach to CQF implementation.....	2137
T.3 Use of Per-Stream Filtering and Policing for CQF.....	2138
T.3.1 Stream filter configuration	2138
T.3.2 Stream gate configuration	2138
T.4 Use of traffic scheduling for CQF	2139
T.5 Timing considerations.....	2140
T.5.1 Choice of T	2140
T.5.2 Cycle interleaving	2141
T.5.3 Cycle alignment between adjacent Ports	2143
Annex U (informative) TSN configuration examples	2144
U.1 Examples for time-aware talker	2144
U.1.1 Using enhancements for scheduled traffic	2145
U.1.2 Using strict priority	2146
U.1.3 Using per-stream scheduling	2147
U.2 Example of workflow for fully centralized models	2148
Annex V (informative) Asynchronous Traffic Shaping delay analysis framework	2152
V.1 General assumptions	2152
V.2 End-to-end delay modeling approach	2152
V.3 Buffering delays.....	2153
V.4 Media-dependent delays	2155
V.5 Bridge—Internal arrival time recognition delays	2155
V.6 Bridge—Internal processing delays.....	2155
V.7 Bridge—Internal clock offset variations.....	2156
V.8 Inter-device clock rate deviations	2156
V.9 Combined delay bounds.....	2157
Annex W (informative) Bibliography.....	2158

Figures

Figure 6-1	Internal organization of the MAC sublayer	144
Figure 6-2	Provider Instance Ports (PIPs)	162
Figure 6-3	B-Component CBP	165
Figure 6-4	Example of operation of Port-and-Protocol-based classification	168
Figure 6-5	Service access priority selection	171
Figure 6-6	Two back-to-back EISS Multiplex Entities	177
Figure 6-7	Two back-to-back Backbone Service Instance Multiplex Entities	178
Figure 6-8	Backbone Service Instance Multiplex Entities with example CFM shims	178
Figure 6-9	Two back-to-back Up and Down TESI Multiplex Entities	181
Figure 6-10	Supporting the ISS with signaled priority	182
Figure 6-11	Two back-to-back Up and Down Infrastructure Segment Multiplex Entities	183
Figure 7-1	VLAN Bridging overview	185
Figure 8-1	A Bridged Network	191
Figure 8-2	VLAN Bridge architecture	193
Figure 8-3	MAC Bridge architecture	194
Figure 8-4	Relaying MAC frames	196
Figure 8-5	Observation of network traffic	196
Figure 8-6	Operation of Spanning Tree Protocol Entity	197
Figure 8-7	Operation of MRP	197
Figure 8-8	Management Port transmission and reception	198
Figure 8-9	Infrastructure Segment MEP placement in a PNP	198
Figure 8-10	Bridge Port Transmit and Receive	201
Figure 8-11	TPMR Port Transmit and Receive	201
Figure 8-12	Forwarding process functions	203
Figure 8-13	Flow classification and metering	208
Figure 8-14	Per-stream classification for PSFP	210
Figure 8-15	Per-stream classification and metering for ATS	212
Figure 8-16	Transmission selection with gates	222
Figure 8-17	Frame timing at gate-close events	224
Figure 8-18	Scheduled traffic state machines—overview and relationships	226
Figure 8-19	Cycle Timer state machine	226
Figure 8-20	List Execute state machine	227
Figure 8-21	List Config state machine	228
Figure 8-22	Logical points of attachment of the Higher Layer and Relay Entities	261
Figure 8-23	Effect of control information on the forwarding path	261
Figure 8-24	Per-Port points of attachment	262
Figure 8-25	Single point of attachment—relay permitted	262
Figure 8-26	Single point of attachment—relay not permitted	262
Figure 8-27	Effect of Port State	263
Figure 8-28	Controlled and Uncontrolled Port connectivity	264
Figure 8-29	Ingress/egress control information in the forwarding path	264
Figure 9-1	VLAN TCI format	269
Figure 9-2	I-TAG TCI format	270
Figure 10-1	Example—Attribute value propagation from one station	273
Figure 10-2	Example—Attribute value propagation from two stations	273
Figure 10-3	Example—Registrations as pointers to the sources of declarations	274
Figure 10-4	MRP architecture	276
Figure 10-5	Format of the major components of an MRPDU	299
Figure 10-6	Operation of MMRP for a single VLAN Context	305
Figure 10-7	Example Directed Graph	306
Figure 10-8	Example of MMRP propagation in a VLAN Context	308
Figure 11-1	Operation of MVRP	316

Figure 12-1	Relationships among CFM managed objects.....	377
Figure 12-2	Relationship among BEB managed objects.....	394
Figure 12-3	SPB managed objects (MOs).....	449
Figure 12-4	Relationships among EVB Bridge managed objects	465
Figure 12-5	Relationship among EVB station managed objects.....	465
Figure 12-6	Timing points for scheduled traffic	482
Figure 12-7	Timing points for PSFP	489
Figure 13-1	Diagrammatic conventions for spanning tree topologies	506
Figure 13-2	Physical topology and active topology	507
Figure 13-3	Port Roles and Port States.....	507
Figure 13-4	A Backup Port.....	508
Figure 13-5	“Ring Backbone” example.....	508
Figure 13-6	An MST Bridge network	510
Figure 13-7	CIST Priority Vectors, Port Roles, and MST Regions	511
Figure 13-8	MSTI Active Topology in Region 2	512
Figure 13-9	CIST and MSTI active topologies in Region 1 of the example network.....	525
Figure 13-10	Agreements and Proposals.....	529
Figure 13-11	CIST and MSTI Active Topologies in Region 2 of Figure 13-6.....	530
Figure 13-12	Enhanced Agreements	531
Figure 13-13	Spanning tree protocol state machines—overview and relationships	542
Figure 13-14	MSTP overview notation.....	543
Figure 13-15	Port Timers state machine.....	573
Figure 13-16	Port Receive state machine	573
Figure 13-17	Port Protocol Migration state machine	574
Figure 13-18	Bridge Detection state machine	574
Figure 13-19	Port Transmit state machine	575
Figure 13-20	Port Information state machine.....	576
Figure 13-21	Port Role Selection state machine	577
Figure 13-22	Disabled Port role transitions.....	578
Figure 13-23	Port Role Transitions state machine—MasterPort.....	579
Figure 13-24	Port Role Transitions state machine—RootPort.....	580
Figure 13-25	Port Role Transitions state machine—DesignatedPort.....	581
Figure 13-26	Port Role Transitions state machine—AlternatePort and BackupPort	582
Figure 13-27	Port State Transition state machine	582
Figure 13-28	Topology Change state machine.....	584
Figure 13-29	L2 Gateway Port Receive state machine	585
Figure 14-1	RST, MST, SPT, and STP Configuration BPDU format.....	589
Figure 14-2	STP TCN BPDU format	589
Figure 14-3	MSTI Configuration Message parameters and format	594
Figure 15-1	Internal organization of the MAC sublayer in a PBN	597
Figure 15-2	Port-based service interface to a PBN	598
Figure 15-3	Port-based service interface to a PBN	599
Figure 15-4	C-tagged service interface to a PBN	599
Figure 15-5	C-tagged service interface to a PBN.....	599
Figure 15-6	Customer Edge Ports (CEPs).....	600
Figure 15-7	S-tagged service interface to a PBN	600
Figure 15-8	S-tagged interface to a PBN.....	601
Figure 15-9	RCSIs to a PBN	601
Figure 15-10	Remote Customer Access Ports (RCAPs)	602
Figure 15-11	C-tagged RCSI to a PBN	603
Figure 15-12	Port-based RCSI to a PBN.....	603
Figure 15-13	Provider Network Port (PNP) interface	604
Figure 16-1	PBN with interface examples	607
Figure 16-2	Examples of remote customer service access via a second PBN	609

Figure 16-3	Access service separation and “Hairpin Switching”	610
Figure 16-3	Access service separation and “Hairpin Switching”	610
Figure 17-1	C-VLAN component internal LAN managed system	675
Figure 17-2	I/B-component internal LAN managed system	680
Figure 18-1	One Maintenance Domain: operator’s view	1184
Figure 18-2	One service instance: operator’s view	1185
Figure 18-3	One service instance: customer’s view	1185
Figure 18-4	MEP and MIP Symbols	1186
Figure 18-5	MAs: one service instance in a provider network	1187
Figure 18-6	MAs: Expansion of Figure 18-5	1188
Figure 18-7	MEPs, MIPs, and MD Levels	1189
Figure 19-1	CFM Protocol shims	1190
Figure 19-2	MA Endpoint (MEP)	1193
Figure 19-3	MIP Half Function (MHF)	1198
Figure 19-4	LOM shim	1200
Figure 19-5	LOM architecture	1201
Figure 20-1	MEP state machines—overview and relationships	1214
Figure 20-2	MEP Continuity Check Initiator state machine	1221
Figure 20-3	MHF Continuity Check Receiver state machine	1222
Figure 20-4	MEP Continuity Check Receiver state machine	1226
Figure 20-5	Remote MEP state machine	1228
Figure 20-6	Remote MEP Error state machine	1229
Figure 20-7	MEP Cross Connect state machine	1230
Figure 20-8	MEP Traffic Field Mismatch state machine	1232
Figure 20-9	MEP Local Mismatch state machine	1232
Figure 20-10	MP Loopback Responder state machine	1234
Figure 20-11	MEP Loopback Initiator transmit state machine	1237
Figure 20-12	MEP Loopback Initiator receive state machine	1238
Figure 20-13	MEP Fault Notification Generator state machine	1240
Figure 20-14	MEP Mismatch Fault Notification Generator state machine	1242
Figure 20-15	MEP Linktrace Initiator receive state machine	1246
Figure 20-16	Linktrace Responder, MEPs, MHFs, and LOMs	1248
Figure 20-17	LTM Receiver state machine	1254
Figure 20-18	LTR Transmitter state machine	1255
Figure 22-1	MEPs and MIPs distinguished by VID (incomplete picture)	1284
Figure 22-2	Alternate view of Forwarding process	1285
Figure 22-3	Combining per-VLAN MPs into two shims	1286
Figure 22-4	More complete picture of MP placement in a Bridge Port	1287
Figure 22-5	Service instance spanning two Bridges protected by Up MPs	1289
Figure 22-6	Service instance spanning two Bridges protected by Down MPs	1289
Figure 22-7	MP placement in a non-VLAN-aware Bridge Port	1291
Figure 22-8	MP placement relative to other standards	1292
Figure 22-9	Creating MEPs and MIPs	1295
Figure 22-10	CFM in a Provider Edge Bridge C-tagged service interface	1301
Figure 22-11	CFM in a Provider Edge Bridge C-tagged RCSI	1303
Figure 22-12	Up MEPs in a Management Port	1304
Figure 22-13	CFM in the enterprise environment	1305
Figure 22-14	CFM on a Bridge that implements IEEE Std 802.1Q-2005	1306
Figure 23-1	TPMR connecting two Bridge Ports	1307
Figure 23-2	TPMR chain connecting Bridge Ports	1307
Figure 23-3	MSSs and the MSPE	1309
Figure 23-4	Adding connectivity	1311
Figure 23-5	Losing connectivity	1312
Figure 23-6	TPMR recovery	1313

Figure 23-7	Notification from one end of the link to the other	1314
Figure 23-8	Immediate MAC status notification at the end of a link	1314
Figure 23-9	MSPE state machine overview	1315
Figure 23-10	Status Transition state machine (STM)	1319
Figure 23-11	Status Notification state machine (SNM)	1320
Figure 23-12	MSPDU structure.....	1322
Figure 25-1	Internal organization of the MAC sublayer in a PBBN.....	1326
Figure 25-2	PBB terminology	1327
Figure 25-3	Customer service interface types	1328
Figure 25-4	Port-based service interface	1329
Figure 25-5	Port-based interface equipment	1330
Figure 25-6	Encapsulated service frames at ISS	1331
Figure 25-7	S-tagged service interface.....	1331
Figure 25-8	S-tagged service interface equipment	1332
Figure 25-9	I-tagged service interface.....	1333
Figure 25-10	I-tagged service interface equipment.....	1333
Figure 25-11	S-tagged and Port-based service interface access classifications	1335
Figure 25-12	I-tagged service interface access protection classifications.....	1336
Figure 25-1	Internal organization of the MAC sublayer in a PBB-TE Region.....	1339
Figure 25-14	PBB-TE Region	1341
Figure 25-15	Transparent service interface	1342
Figure 25-16	Transparent service interface equipment	1343
Figure 26-1	PBBN example	1345
Figure 26-2	CFM shim model	1352
Figure 26-3	CFM example applied to a Port-based and S-tagged service interface	1353
Figure 26-4	CFM example applied to an I-tagged Service Interface	1354
Figure 26-5	CFM example applied to a hierarchal E-NNI, CBP-PIP Demarc.....	1355
Figure 26-6	CFM example applied to a peer E-NNI, CBP-PIP	1356
Figure 26-7	Independent ESPs using the same ESP-DAs and ESP-VIDs	1359
Figure 26-8	PBB-TE MEP placement in a CBP.....	1360
Figure 26-9	Independent Infrastructure Segments distinguished by SMP-SA.....	1363
Figure 26-10	Infrastructure Segment MEP placement in a PNP.....	1364
Figure 26-11	Protection switching architecture.....	1365
Figure 26-12	PBB-TE point-to-point protection switching.....	1367
Figure 26-13	Mapping data traffic to the protection entity	1368
Figure 26-14	Relationships of the Protection switching state machines—overview	1369
Figure 26-15	Hold-off state machine.....	1373
Figure 26-16	Clear Manual Switch state machine.....	1373
Figure 26-17	Service Mapping state machine	1374
Figure 26-18	Segment terminology and properties	1375
Figure 26-19	Infrastructure Segment monitoring.....	1376
Figure 26-20	Working Segment and Protection Segment.....	1377
Figure 26-21	Nested IPGs	1378
Figure 26-22	IPS Control entity	1380
Figure 26-23	M:1 IPS	1381
Figure 26-24	M:1 IPS state machines.....	1382
Figure 26-25	M:1 Hold-off state machine	1385
Figure 26-26	Protection Segment Selection state machine	1386
Figure 27-1	Configuring VLAN support in an SPT Region (example)	1393
Figure 27-2	SPBM group MAC address—general format	1404
Figure 27-3	SPBM group MAC addresses—source rooted SPT	1404
Figure 27-4	SPBM group MAC addresses—shared tree.....	1405
Figure 27-5	SPBM MEP placement in a CBP.....	1407
Figure 27-6	SPBV campus network example.....	1410

Figure 27-7	SPT Bridge Network using SPBM example.....	1411
Figure 28-1	Agreement Digest field format	1416
Figure 28-2	MT-Capability TLV	1425
Figure 28-3	SPB MCID sub-TLV	1425
Figure 28-4	SPB Digest sub-TLV	1426
Figure 28-5	SPB Base VLAN-Identifiers sub-TLV	1427
Figure 28-6	SPB Instance sub-TLV	1428
Figure 28-7	SPB Instance Opaque ECT-ALGORITHM sub-TLV	1430
Figure 28-8	ECMP ECT-ALGORITHM sub-TLV	1430
Figure 28-9	SPB Link Metric sub-TLV	1431
Figure 28-10	SPB Adjacency Opaque ECT-ALGORITHM sub-TLV	1432
Figure 28-11	SPBV MAC Address sub-TLV.....	1432
Figure 28-12	SPBM Service Identifier and Unicast Address sub-TLV	1434
Figure 29-1	Forward path test (FPT).....	1437
Figure 29-2	Return path test (RPT)	1438
Figure 29-3	Combination of FPT and RPT	1439
Figure 29-4	Detailed functions of RR	1440
Figure 29-5	RFM Receiver on a non-MP.....	1443
Figure 29-6	Return Path DR.....	1444
Figure 29-7	RR Filter state machine.....	1449
Figure 29-8	RR Encapsulation state machine.....	1450
Figure 29-9	RR Transmit state machine.....	1450
Figure 29-10	RFM Receiver state machine.....	1451
Figure 29-11	Decapsulator Responder state machine	1454
Figure 30-1	Congestion detection in QCN CP	1460
Figure 30-2	Sampling (reflection) probability in QCN CP as a function of Fb	1460
Figure 30-3	QCN RP operation	1461
Figure 30-4	Byte Counter and Timer interaction with Rate Limiter.....	1463
Figure 30-5	CP–RP peering in VLAN Bridged Network.....	1465
Figure 30-6	CP–RP peering in PBBN	1466
Figure 31-1	CPs and congestion-aware queues in a Bridge	1467
Figure 31-2	Congestion-aware queue functions in an end station.....	1469
Figure 31-3	Per-CNPV station function	1471
Figure 32-1	CND defense state machine	1484
Figure 32-2	RP rate control state machine	1496
Figure 32-3	CP–RP peering in any hierarchical Bridged Network	1497
Figure 34-1	Queuing model for a Talker station	1509
Figure 35-1	Operation of MSRP	1514
Figure 35-2	Format of the components of the reservation FirstValue fields.....	1525
Figure 35-3	Format of the components of the Domain FirstValue	1530
Figure 35-4	Value of StreamID TLV	1535
Figure 35-5	Value of StreamRank TLV	1535
Figure 35-6	Value of InterfaceID TLV	1535
Figure 35-7	Value of IEEE802-MacAddresses TLV	1536
Figure 35-8	Value of IEEE802-VlanTag TLV.....	1536
Figure 35-9	Value of IPv4-tuple TLV	1537
Figure 35-10	Value of IPv6-tuple TLV	1537
Figure 35-11	Value of TrafficSpecification TLV.....	1540
Figure 35-12	Value of TSpecTimeAware TLV	1540
Figure 35-13	Value of UserToNetworkRequirements TLV.....	1541
Figure 35-14	Value of InterfaceCapabilities TLV	1542
Figure 35-15	Value of StatusInfo TLV	1542
Figure 35-16	Value of AccumulatedLatency TLV.....	1543
Figure 35-17	Value of TimeAwareOffset TLV.....	1544

Figure 36-1	PFC peering	1560
Figure 36-2	PFC Receiver state diagram for priority n	1562
Figure 36-3	PFC-aware system queue functions	1564
Figure 36-4	PFC-aware system queue functions with Link Aggregation	1565
Figure 38-1	DCBX Asymmetric state machine	1570
Figure 38-2	Symmetric state machine	1571
Figure 39-1	Operation of MIRP in an I-component	1573
Figure 39-2	Operation of MIRP in a B-component	1573
Figure 39-3	Alternate model for MIRP in a B-component	1578
Figure 40-1	EVB architecture overview	1580
Figure 40-2	EVB architecture without S-channels	1582
Figure 40-3	EVB architecture with S-channel	1582
Figure 40-4	EVB components and internal LANs with S-channels	1583
Figure 40-5	EVB architecture without S-channels, with EVB Bridge S-VLAN component	1585
Figure 40-6	EVB architecture without S-channels, with EVB station S-VLAN component	1585
Figure 41-1	VSI manager ID TLV	1588
Figure 41-2	VDP association TLV	1589
Figure 41-3	VID Filter Info format	1594
Figure 41-4	MAC/VID filter format	1594
Figure 41-5	GroupID/VID filter format	1595
Figure 41-6	GroupID/MAC/VID filter format	1595
Figure 41-7	GroupID/VID/IPv4 filter format	1595
Figure 41-8	GroupID/MAC/VID/IPv4 filter format	1596
Figure 41-9	GroupID/VID/IPv6 filter format	1596
Figure 41-10	GroupID/MAC/VID/IPv6 filter format	1597
Figure 41-11	Organizationally defined TLV	1598
Figure 41-12	Bridge VDP state machine	1600
Figure 41-13	Station VDP state machine	1601
Figure 42-1	CDCP state machine—Station role	1608
Figure 42-2	CDCP state machine—Bridge role	1609
Figure 43-1	Example ECP exchange	1613
Figure 43-2	ECPDU structure	1615
Figure 43-3	ECP transmit state machine	1616
Figure 43-4	ECP receive state machine	1617
Figure 44-1	Flow Filtering TCI format	1624
Figure 44-2	SPBM VID MEP and ECMP path MEP placement in a CBP	1628
Figure 45-1	An SPT Region controlled by a single PCE	1631
Figure 45-2	An SPT Region controlled by multiple PCEs	1632
Figure 45-3	The use of the SPB Instance sub-TLV for MRT	1640
Figure 45-4	Shared Risk Link Group (SRLG) TLV	1644
Figure 45-5	Topology sub-TLV	1645
Figure 45-6	A strict tree and its descriptor Topology sub-TLV	1646
Figure 45-7	Topology sub-TLV of a loose tree	1647
Figure 45-8	Hop sub-TLV	1649
Figure 45-9	Administrative Group sub-TLV	1652
Figure 45-10	Bandwidth Constraint sub-TLV	1652
Figure 45-11	Bandwidth Assignment sub-TLV	1653
Figure 45-12	Timestamp sub-TLV	1654
Figure 45-13	A GADAG and its descriptor Topology sub-TLV	1660
Figure 45-14	MRT-Blue and MRT-Red for MRT Root 55	1661
Figure 45-15	A GADAG for a topology with multiple blocks	1662
Figure 46-1	Fully distributed model	1665
Figure 46-2	Centralized network/distributed user model	1666
Figure 46-3	Fully centralized model	1668

Figure 46-4	Example of Stream transformation in Talker end station	1669
Figure 46-5	Example of IEEE 802.1CB functions in Talker end station	1670
Figure 46-6	Example of IEEE 802.1CB functions in Listener end station	1670
Figure 48-1	General YANG hierarchy	1696
Figure 48-2	YANG root hierarchy with IEEE 802.1Q YANG modules.....	1696
Figure 48-3	Interface YANG model.....	1697
Figure 48-4	VLAN Bridge components model (MAC Relay Entities).....	1699
Figure 48-5	Bridge Port model.....	1700
Figure 48-6	TPMR model (MAC Relay Entity).....	1701
Figure 48-7	TPMR port model	1702
Figure 48-8	Provider Bridge model.....	1703
Figure 48-9	Provider Edge Bridge C-VLAN Interface model	1704
Figure 48-10	Provider Edge Bridge S-VLAN interface model	1705
Figure 48-11	Bridge to CFM YANG model	1707
Figure 48-12	CFM CFM MEP model relationships model relationships	1708
Figure 48-13	CFM MEP model.....	1709
Figure 48-14	CFM operations structure	1709
Figure 48-15	Stream filters and stream gates model MEP model.....	1710
Figure 48-16	Asynchronous Traffic Shaping model	1711
Figure C-1	CSN backbone	1937
Figure C-2	Bridge’s CSN model for bandwidth reservation.....	1938
Figure C-3	Talker MSRPDU flow	1939
Figure C-4	Listener MSRPDU flow.....	1939
Figure C-5	IEEE DMN Device Attribute IE.....	1941
Figure C-6	DMN Confirmation Transaction.....	1943
Figure C-7	Bandwidth reservation—bridge model for IEEE 802.11 BSS (STA downstream Port)	1945
Figure C-8	Bandwidth reservation—bridge model for IEEE 802.11 BSS (STA upstream Port).....	1946
Figure C-9	Bandwidth reservation—bridge model for IEEE 802.11 BSS (direct link setup)	1946
Figure C-10	MSRP/IEEE 802.11 query flows	1947
Figure C-11	MSRP/802.11 Talker STA to Listener STA reservation flows	1947
Figure C-12	MSRP/802.11 “Bridged” Listener to Talker STA reservation flows	1948
Figure C-13	MSRP/802.11 Listener STA to “Bridged” Talker reservation flows	1948
Figure D-1	Port VLAN ID TLV format	1954
Figure D-2	Port And Protocol VLAN ID TLV format.....	1954
Figure D-3	VLAN Name TLV format	1955
Figure D-4	Protocol Identity TLV format.....	1956
Figure D-5	VID Usage Digest TLV format	1957
Figure D-6	Management VID TLV format.....	1957
Figure D-7	Congestion Notification TLV format	1958
Figure D-8	ETS Configuration TLV format	1959
Figure D-9	ETS Recommendation TLV format.....	1961
Figure D-10	Priority-based Flow Control Configuration TLV format	1962
Figure D-11	Application Priority TLV format.....	1963
Figure D-12	EVB TLV format	1965
Figure D-13	CDCP TLV structure	1969
Figure D-14	Application VLAN TLV format.....	1971
Figure F-1	Connecting independent VLANs—1	2057
Figure F-2	Connecting independent VLANs—2.....	2058
Figure F-3	Duplicate MAC addresses	2058
Figure F-4	Asymmetric VID use: “multi-netted server”	2059
Figure F-5	Asymmetric VLAN use: “Rooted-Multipoint”.....	2061

Figure F-6	Rooted-Multipoint with tagged interfaces	2062
Figure F-7	SPBV VLAN Shared Learning and VID Translation.....	2063
Figure G-1	Example of IEEE 802.3 MAC frame format	2065
Figure G-2	Methods for Bridge access to IEEE 802.11 and PMPN media: example.....	2068
Figure H-1	Static filtering inconsistency.....	2071
Figure H-2	Interoperability with MAC Bridges: example 1	2072
Figure H-3	Interoperability with MAC Bridges: example 2	2073
Figure H-4	Interoperability between Port-based and Port-and-Protocol-based classification	2074
Figure J-1	Up MPs in a CFM Port	2088
Figure K-1	TPMR as UNI demarcation device	2090
Figure K-2	TPMRs with aggregated links.....	2091
Figure K-3	Multiple TPMRs	2091
Figure K-4	Recovery at the end of a chain.....	2092
Figure K-5	Near simultaneous recoveries	2093
Figure K-6	Near simultaneous failure and recovery	2093
Figure K-7	Loss with quick recovery	2094
Figure L-1	Credit-based shaper operation—no conflicting traffic	2097
Figure L-2	Credit-based shaper operation—conflicting traffic	2098
Figure L-3	Credit-based shaper operation—burst traffic.....	2099
Figure L-4	Interference and latency	2103
Figure L-5	Burst behavior and credit.....	2103
Figure L-6	Fan-in scenario.....	2107
Figure L-7	Permanent delay scenario	2108
Figure L-8	Building up buffer occupancy—1.....	2109
Figure L-9	Building up buffer occupancy—2.....	2109
Figure L-10	Building up buffer occupancy—3.....	2109
Figure L-11	Building up buffer occupancy—4.....	2110
Figure M-1	PFC PDU format.....	2112
Figure N-1	PFC delays	2113
Figure N-2	Delay model.....	2114
Figure N-3	Worst-case delay	2115
Figure O-1	Converting a CRC to an FCS.....	2120
Figure O-2	Detection Lossless Circuit	2120
Figure O-3	Field change adjustment	2122
Figure O-4	Field insertion adjustment.....	2123
Figure P-1	Frame duplication scenario	2126
Figure P-2	Frame misordering scenario.....	2127
Figure Q-1	Establishing a guard band.....	2129
Figure Q-2	Using gate operations.....	2130
Figure T-1	Example Stream Filter and Stream Gate configuration for CQF.....	2139
Figure T-2	Traffic scheduling example for CQF	2140
Figure T-3	Example Stream Filter and Stream Gate configuration with two values of T	2141
Figure T-4	Traffic scheduling example with two values of T	2141
Figure T-5	Interleaving example—factor of 2	2142
Figure U-1	Example of enhancements for scheduled traffic.....	2146
Figure V-1	Path of frames along a single hop with index k with two Bridges	2153

Tables

Table 6-1	Bridge transit delay	151
Table 6-2	Priority Code Point encoding.....	159
Table 6-3	Priority Code Point decoding.....	159
Table 6-4	Priority regeneration	160
Table 6-5	Default SRP domain boundary port priority regeneration override values	161
Table 6-6	Service Access Priority	172
Table 6-7	Encapsulated Addresses EtherType.....	179
Table 8-1	C-VLAN and MAC Bridge component Reserved addresses.....	206
Table 8-2	S-VLAN component Reserved addresses.....	207
Table 8-3	TPMR component Reserved addresses.....	207
Table 8-4	Stream gate control operations	214
Table 8-5	Recommended priority to traffic class mappings	217
Table 8-6	Transmission selection algorithm identifiers	220
Table 8-7	Gate operations	223
Table 8-8	Scheduled Traffic and Stream Gate procedures/variables.....	232
Table 8-9	Ageing time parameter value.....	239
Table 8-10	Combining Static and Dynamic Filtering Entries for an individual MAC address	249
Table 8-11	Combining Static Filtering Entry and MAC Address Registration Entry for “All Group Addresses” and “All Unregistered Group Addresses”	250
Table 8-12	Forwarding or Filtering for specific group MAC addresses	250
Table 8-13	Forwarding or Filtering with Dynamic Reservation Entries	251
Table 8-14	Determination of whether a Port is in a VID’s member set.....	252
Table 8-15	Standard LLC address assignment.....	257
Table 8-17	ISIS-SPB Recommended Address Usage.....	259
Table 8-16	ISIS-SPB reserved addresses	259
Table 8-18	CCM group destination MAC addresses	266
Table 8-19	LTM group destination MAC addresses.....	266
Table 9-2	Reserved VID values	269
Table 9-1	IEEE 802.1Q™ EtherType allocations.....	269
Table 9-3	Reserved I-SID values	271
Table 10-1	MRP application addresses	279
Table 10-2	MRP EtherType values	279
Table 10-3	Applicant state table.....	293
Table 10-4	Registrar state table.....	294
Table 10-5	LeaveAll state table	294
Table 10-6	PeriodicTransmission state table	295
Table 10-7	MRP timer parameter default values	295
Table 12-1	Component table entry managed object.....	327
Table 12-2	Port table entry.....	329
Table 12-3	ISS Port Number table entry	330
Table 12-4	Bandwidth Availability Parameter Table row elements	433
Table 12-5	Transmission Selection Algorithm Table row elements.....	434
Table 12-6	Priority Regeneration Override Table row elements	434
Table 12-7	SR Class to Priority Mapping Table row elements.....	435
Table 12-9	CN component priority managed object row elements	436
Table 12-8	CN component managed object row elements	436
Table 12-10	CN Port priority managed object row elements.....	437
Table 12-11	Congestion Point managed object row elements	438
Table 12-13	Reaction Point group managed object row elements.....	439
Table 12-12	Reaction Point port priority managed object row elements.....	439
Table 12-14	SRP Bridge Base Table row elements	440
Table 12-15	SRP Bridge Port Table row elements	440

Table 12-16	SRP Latency Parameter Table row elements.....	441
Table 12-17	SRP Stream Table row elements	441
Table 12-19	SRP Stream Preload Table row elements	442
Table 12-18	SRP Reservations Table row elements	442
Table 12-20	SRP Reservations Preload Table row elements.....	443
Table 12-21	Priority-based Flow Control objects.....	444
Table 12-22	EVB system base table	468
Table 12-24	SBP table entry	469
Table 12-23	EVB system parameter defaults.....	469
Table 12-25	VSI table entry	470
Table 12-27	UAP table entry parameters.....	471
Table 12-26	VSI MAC/VLAN table entry.....	471
Table 12-28	UAP table entry	472
Table 12-29	S-channel interface table entry	473
Table 12-31	ECP table entry	474
Table 12-30	URP table entry.....	474
Table 12-32	The Gate Parameter Table	479
Table 12-33	Frame Preemption Parameter table.....	482
Table 12-34	The Stream Parameter Table.....	484
Table 12-35	Stream Filter Instance Table	486
Table 12-36	The Stream Gate Instance Table.....	487
Table 12-37	The Flow Meter Instance Table	490
Table 12-39	The Scheduler Group Instance Table.....	491
Table 12-38	The Scheduler Instance Table.....	491
Table 12-40	The Scheduler Port Parameter Table	492
Table 12-41	The Timing Characteristics Table.....	493
Table 12-38	Bridge Delay attributes	494
Table 12-39	Propagation Delay attributes.....	496
Table 12-40	Static Trees attributes.....	496
Table 12-41	MRP External Control attributes	498
Table 13-1	Configuration Digest Signature Key.....	516
Table 13-2	Sample Configuration Digest Signature Keys	517
Table 13-3	Bridge and Port Priority values.....	535
Table 13-4	Port Path Cost values	536
Table 13-5	Timer and related parameter values.....	544
Table 17-1	IEEE 802.1Q MIB modules.....	614
Table 17-2	IEEE8021-TC-MIB structure	615
Table 17-3	IEEE8021-BRIDGE-MIB structure.....	616
Table 17-4	IEEE 802.1D objects not in the IEEE8021-BRIDGE-MIB.....	620
Table 17-5	IEEE8021-SPANNING-TREE MIB structure	621
Table 17-6	Clause 12 objects not in the IEEE8021-SPANNING-TREE MIB	622
Table 17-7	IEEE8021-Q-BRIDGE MIB structure.....	623
Table 17-8	Clause 12 management not in IEEE8021-Q-BRIDGE-MIB	628
Table 17-9	IEEE8021-PB-MIB structure.....	628
Table 17-10	IEEE8021-MSTP-MIB structure	630
Table 17-11	IEEE8021-CFM-MIB structure	633
Table 17-12	IEEE8021-CFM-V2-MIB structure.....	637
Table 17-13	IEEE8021-PBB-MIB structure	639
Table 17-14	IEEE8021-DDCFM-MIB structure	642
Table 17-15	IEEE8021-PBBTE-MIB structure	644
Table 17-16	Example of ieee8021PbbTeTeSiEspTable	646
Table 17-17	IEEE8021-TPMR-MIB structure.....	647
Table 17-18	IEEE8021-FQTSS-MIB structure.....	649
Table 17-19	IEEE8021-CN-MIB structure	650

Table 17-20	IEEE8021-SRP-MIB structure	652
Table 17-21	IEEE8021-MVRPX-MIB structure	654
Table 17-22	IEEE8021-MIRP-MIB structure.....	654
Table 17-23	PFC-MIB structure	655
Table 17-24	IEEE8021-TEIPS MIB structure	655
Table 17-25	IEEE8021-SPB-MIB structure	657
Table 17-26	IEEE8021-EVB-MIB structure.....	662
Table 17-27	IEEE8021-ECMP-MIB structure.....	666
Table 17-28	IEEE8021-ST-MIB structure	667
Table 17-29	IEEE8021-Preemption-MIB structure	668
Table 17-30	IEEE8021-PSFP-MIB structure.....	668
Table 17-31	IEEE8021-TSN-REMOTE-MANAGEMENT-MIB structure	671
Table 17-31	PBB-TE required MIB compliances.....	681
Table 17-32	Sensitive managed objects: tables and notifications	689
Table 17-33	Sensitive managed objects: variables in dot1agCfmMdTable.....	690
Table 17-34	Sensitive managed objects (of DDCFM): tables and notifications.....	691
Table 17-35	Sensitive managed objects (of DDCFM) for read	691
Table 17-36	Sensitive managed objects (of EVB): tables and notifications.....	698
Table 17-37	Sensitive managed objects (of EVB) for read	699
Table 17-38	Provider Bridge service interface parameters	715
Table 17-39	PBB service interface parameters	719
Table 19-1	Actions taken by MP OpCode Demultiplexers.....	1195
Table 19-2	SAP use for LTMs and LTRs	1202
Table 20-1	Fault Alarm defects and priorities	1207
Table 20-2	Deriving enableRmepDefect and Port Status TLV in a Bridge.....	1217
Table 21-1	CFM PDU Encapsulation EtherType	1260
Table 21-3	OpCode Field range assignments	1262
Table 21-2	Common CFM Header format	1262
Table 21-4	TLV format.....	1263
Table 21-5	Type Field values	1264
Table 21-6	Organization-Specific TLV format.....	1264
Table 21-7	Sender ID TLV format.....	1265
Table 21-8	Port Status TLV format.....	1266
Table 21-10	Interface Status TLV format	1267
Table 21-11	Interface Status TLV values	1267
Table 21-9	Port Status TLV values	1267
Table 21-12	Data TLV format	1268
Table 21-13	End TLV format.....	1268
Table 21-14	CCM format.....	1269
Table 21-15	CCM Interval field encoding.....	1270
Table 21-16	CCM Maintenance Association Identifier field format: Maintenance Domain present	1271
Table 21-17	CCM Maintenance Association Identifier field format: Maintenance Domain not present	1271
Table 21-19	Short MA Name Format	1272
Table 21-18	Maintenance Domain Name Format.....	1272
Table 21-20	LBM and LBR formats	1273
Table 21-21	PBB-TE MIP TLV format	1274
Table 21-22	LTM format	1275
Table 21-23	LTM Flags field.....	1276
Table 21-24	LTM Egress Identifier TLV format.....	1277
Table 21-25	LTR format	1278
Table 21-26	LTR Flags field.....	1278
Table 21-27	Relay Action field values.....	1279

Table 21-28	LTR Egress Identifier TLV format	1279
Table 21-29	Reply Ingress TLV format	1280
Table 21-30	Ingress Action field values	1281
Table 21-31	Reply Egress TLV format	1282
Table 21-32	Egress Action field values	1282
Table 22-1	MEP creation	1295
Table 22-2	MIP creation	1296
Table 22-3	Bandwidth required for CCMs for 1 MA	1299
Table 22-4	Bandwidth required for CCMs for 1000 MAs	1300
Table 23-1	Time sequence diagram symbols	1311
Table 23-2	MSP performance parameters	1316
Table 23-3	MSP EtherType assignment	1321
Table 23-4	MSP Packet Types	1322
Table 24-1	Transmission and reception delays	1325
Table 26-1	Backbone Service Instance Group address OUI	1348
Table 26-2	Protection Requests Hierarchy	1370
Table 27-1	Allocation of VIDs to FIDs and FIDs to MSTIDs in an SPT Region (example)	1393
Table 28-1	Bridge Priority Masking	1421
Table 29-1	RFM format	1455
Table 29-2	SFM format	1456
Table 32-1	LLDP instance selection managed object overrides	1477
Table 32-2	CND defense mode selection managed object overrides	1477
Table 32-3	Determining cnpdIsAdminDefMode and cnpdDefenseMode	1483
Table 32-4	Correspondence of QCN and CCF message fields	1485
Table 32-5	NewCpSampleBase() return value as a function of cpFb	1488
Table 33-2	CNM Encapsulation	1500
Table 33-1	CN-TAG Encapsulation	1500
Table 33-3	Congestion Notification Message PDU	1501
Table 34-1	Default priority to traffic class mappings for SR classes A and B	1507
Table 34-2	Default priority to traffic class mappings for SR class B only	1508
Table 35-1	AttributeType Values	1522
Table 35-2	AttributeLength Values	1522
Table 35-3	FourPackedEvent Values	1523
Table 35-4	MSRP FirstValue NumberOfValues example	1524
Table 35-5	TSpec components examples	1527
Table 35-6	SR class ID	1530
Table 35-7	TLV types	1533
Table 35-8	Summary of Talker primitives	1546
Table 35-9	Summary of Listener primitives	1546
Table 35-10	Talker attribute propagation per port	1550
Table 35-11	Translation of Talker attributes	1551
Table 35-12	Incoming Listener attribute propagation per port	1554
Table 35-15	Listener Declaration Type Summation	1555
Table 35-13	Updating Dynamic Reservation Entries	1555
Table 35-14	Updating operIdleSlope(N)	1555
Table 35-16	Translation of Listener attributes	1556
Table 41-1	VDP TLV types	1589
Table 41-2	Flag values in VDP requests	1590
Table 41-3	Error types in VDP responses	1591
Table 41-4	Flag values in VDP responses	1591
Table 41-6	Filter Info format values	1592
Table 41-5	VSIID format values	1592
Table 43-1	ECP subtypes	1615
Table 44-1	ECMP ECT-ALGORITHM values	1623

Table 44-2	F-TAG EtherType.....	1624
Table 45-1	ECT-ALGORITHM values for explicit trees	1635
Table 45-2	Bridge Priority Masking for the LT and LTS ECT Algorithms	1636
Table 45-3	Hop sub-TLV flags	1650
Table 46-1	StreamID elements.....	1674
Table 46-2	StreamRank elements	1674
Table 46-3	InterfaceID elements.....	1675
Table 46-4	IEEE802-MacAddresses elements.....	1677
Table 46-5	IEEE802-VlanTag elements	1677
Table 46-6	IPv4-tuple elements	1678
Table 46-7	IPv6-tuple elements	1679
Table 46-8	TrafficSpecification elements.....	1680
Table 46-9	TSpecTimeAware elements.....	1680
Table 46-10	UserToNetworkRequirements elements.....	1682
Table 46-11	InterfaceCapabilities elements.....	1684
Table 46-12	StatusInfo elements.....	1687
Table 46-13	TalkerStatus enumeration	1687
Table 46-14	ListenerStatus enumeration.....	1688
Table 46-15	TSN Failure Codes.....	1689
Table 46-16	AccumulatedLatency elements	1690
Table 48-1	Summary of the YANG modules.....	1712
Table 48-2	VLAN Bridge component model YANG modules.....	1713
Table 48-3	Two-Port MAC Relay (TPMR) model YANG modules	1713
Table 48-4	Customer VLAN Bridge model YANG modules.....	1713
Table 48-6	CFM model YANG modules.....	1714
Table 48-7	Stream filters and stream gates model YANG modules	1714
Table 48-5	Provider Bridge model YANG modules.....	1714
Table 48-8	ATS model YANG modules.....	1715
Table C-1	SRP to MoCA PQoS Transaction mapping.....	1944
Table C-2	SRP TSpec to MoCA TSPEC mapping.....	1944
Table C-3	SRP StreamID to MoCA PQoS Flow transaction mapping	1945
Table C-4	SRP to MLME QoS Services mapping.....	1950
Table C-5	EDCA-AC for AV Streams	1951
Table C-6	HCCA for AV Streams	1952
Table D-1	IEEE 802.1 Organizationally Specific TLVs	1953
Table D-2	Port and protocol capability/status.....	1955
Table D-3	Priority assignment table	1959
Table D-4	Traffic class bandwidth assignment table.....	1960
Table D-5	TSA Assignment Table.....	1960
Table D-6	PFC Enable bit vector.....	1963
Table D-7	Application Priority Table Entry format.....	1964
Table D-8	Sel field values.....	1964
Table D-9	RRSAT flag values and meanings	1967
Table D-10	EVB Mode values.....	1968
Table D-11	NVE Role values	1969
Table D-12	Application VLAN Table Entry format.....	1971
Table D-13	Sel field values.....	1972
Table D-14	IEEE 802.1 extension MIB object group conformance requirements	1977
Table D-15	IEEE 802.1/LLDP extension MIB object cross reference	1978
Table E-1	State machine symbols.....	2055
Table I-1	Traffic type to traffic class mapping.....	2077
Table I-2	Traffic type acronyms.....	2078
Table I-3	Defining traffic types.....	2078
Table I-4	Defining traffic types—Credit-based shaper support of SR class B only	2079

ISO/IEC/IEEE 8802-1Q:2024(en)

Table I-5	Defining traffic types—Credit-based shaper support of SR classes A and B	2080
Table I-6	Priority Code Point encoding.....	2082
Table I-7	Priority Code Point decoding.....	2082
Table J-1	Provider MD Level allocation	2084
Table J-2	IEEE / ITU-T terminology differences.....	2084
Table N-1	IEEE 802.3 Interface Delays	2116