

# ISO/IEC 8208:2000-11 (E)

## Information technology - Data communications - X.25\_Packet Layer Protocol for Data Terminal Equipment

---

### CONTENTS

	Page
<b>Foreword</b> .....	vi
<b>1 Scope</b> .....	1
<b>2 Normative references</b> .....	1
2.1 Identical Recommendations   International Standards .....	1
2.2 Paired Recommendations   International Standards equivalent in technical content.....	2
2.3 Additional references .....	2
<b>3 General considerations</b> .....	2
3.1 Compatibility with versions of Recommendation X.25 .....	3
3.2 Environments .....	5
3.3 Differences in DTE/DTE and DTE/DCE operation .....	5
3.4 Operation over circuit-switched connections .....	6
3.5 Provision of the OSI Network Service .....	7
3.6 External Packet Layer interactions.....	7
3.7 Logical channels .....	7
3.8 Packet Layer entity.....	8
3.9 Packet types .....	9
3.10 Procedures for initialization.....	9
<b>4 Procedures for restart</b> .....	9
4.1 Originating a restart request .....	10
4.2 Receiving a restart indication.....	12
4.3 Restart collision .....	12
4.4 Restart confirmation.....	12
4.5 Determining “DTE” or “DCE” characteristics.....	12
<b>5 Procedures for Virtual Call setup and clearing</b> .....	13
5.1 Ready state.....	13
5.2 Procedures for Virtual Call setup.....	13
5.3 Rejecting a call.....	15
5.4 Aborting a call request .....	15
5.5 Procedures for Virtual Call clearing .....	15
<b>6 Procedures for data and interrupt transfer</b> .....	16
6.1 States for data and interrupt transfer .....	17
6.2 Maximum User Data Field length of DATA packets .....	17
6.3 Delivery Confirmation bit .....	17
6.4 More Data mark .....	18
6.5 Complete packet sequence .....	18
6.6 Qualifier bit.....	18
6.7 Fragmentation and reassembly of messages.....	19
6.8 Procedures for interrupt .....	20
6.9 Transit delay of DATA packets.....	21
<b>7 Procedures for flow control</b> .....	21
7.1 Flow control.....	22
7.2 Throughput characteristics and throughput classes.....	25

<b>8 Procedures for reset .....</b>	<b>25</b>
8.1 Originating a reset request .....	27
8.2 Receiving a reset indication .....	27
8.3 Reset collision.....	27
8.4 Reset confirmation .....	27
<b>9 Effects of clear, reset, and restart procedures on the transfer of packets .....</b>	<b>27</b>
<b>10 Effects of Layers 1 and 2 on the Packet Layer.....</b>	<b>28</b>
<b>11 Error handling .....</b>	<b>28</b>
11.1 The DIAGNOSTIC packet.....	29
11.2 Nonreceipt of window-rotation information .....	29
11.3 Receipt of erroneous DATA packets .....	30
<b>12 Packet formats.....</b>	<b>31</b>
12.1 General.....	31
12.2 Call setup and call clearing packets .....	33
12.3 DATA and interrupt packets.....	42
12.4 Flow control packets.....	44
12.5 Reset packets .....	45
12.6 Restart packets .....	47
12.7 DIAGNOSTIC packet.....	48
12.8 REJECT packet.....	49
12.9 Registration packets.....	50
<b>13 Procedures for optional user facilities .....</b>	<b>52</b>
13.1 On-line Facility Registration.....	52
13.2 Extended and Super Extended Packet Sequence Numbering .....	59
13.3 D-bit Modification .....	60
13.4 Packet Retransmission .....	60
13.5 Incoming Calls Barred .....	61
13.6 Outgoing Calls Barred .....	61
13.7 One-way Logical Channel Outgoing.....	61
13.8 One-way Logical Channel Incoming .....	61
13.9 Nonstandard Default Packet Sizes .....	61
13.10 Nonstandard Default Window Sizes .....	61
13.11 Default Throughput Classes Assignment.....	62
13.12 Flow Control Parameter Negotiation .....	62
13.13 Throughput Class Negotiation Facilities.....	63
13.14 Closed User Group related facilities .....	64
13.15 Bilateral Closed User Group related facilities.....	68
13.16 Fast Select.....	69
13.17 Fast Select Acceptance .....	70
13.18 Reverse Charging.....	70
13.19 Reverse Charging Acceptance .....	70
13.20 Local Charging Prevention .....	70
13.21 Network User Identification (NUI) related facilities.....	71
13.22 Charging Information.....	71
13.23 ROA related facilities .....	73
13.24 Hunt Group.....	73
13.25 Call Redirection and Call Deflection related facilities.....	73
13.26 Called Line Address Modified Notification.....	76
13.27 Transit Delay Selection and Indication .....	76
13.28 Alternative Addressing Related Facilities .....	76
13.29 TOA/NPI address subscription .....	78
13.30 Reference Number .....	78
<b>14 Procedures for optional ITU-T specified DTE facilities.....</b>	<b>80</b>
14.1 Calling Address Extension.....	80
14.2 Called Address Extension.....	80
14.3 Minimum Throughput Class Negotiation .....	80
14.4 End-to-End Transit Delay Negotiation .....	81

14.5 Priority .....	81
14.6 Protection.....	81
14.7 Expedited Data Negotiation.....	81
<b>15 Format for Facility Field in call setup/clearing packets .....</b>	<b>82</b>
15.1 General.....	82
15.2 Coding of the Facility Field for optional user facilities .....	83
15.3 Coding of the Facility Field for ITU-T specified DTE facilities .....	89
<b>16 Format for Registration Field in registration packets.....</b>	<b>92</b>
16.1 General.....	92
16.2 Coding of the Registration Field for registration-facilities .....	93
<b>17 Diagnostic codes .....</b>	<b>95</b>
<b>18 Timers and retransmission counts .....</b>	<b>101</b>
<b>19 State diagrams .....</b>	<b>105</b>
<b>20 State tables.....</b>	<b>111</b>
<b>21 Conformance .....</b>	<b>120</b>
21.1 Static conformance.....	120
21.2 Protocol Implementation Conformance Statement .....	120
21.3 Dynamic conformance .....	120
 <b>Annexes</b>	
<b>A Private networks.....</b>	<b>123</b>
<b>B PICS Proforma .....</b>	<b>131</b>
<b>C Differences between various editions of ISO/IEC 8208.....</b>	<b>159</b>
<b>D Abbreviations.....</b>	<b>169</b>