ISO/IEC 30181:2024-12 (E)

Internet of Things (IoT) - Functional architecture for resource identifier interoperability

Contents

Page

FOREWORD 4
INTRODUCTION 6
1 Scope 7
2 Normative references 7
3 Terms and definitions 7
4 Abbreviated terms 9
5 IoT resource name system 10
5.1 Requirements for the interoperability of the resource ID in an IoT platform 10
5.1.1 General 10
5.1.2 Uniqueness 10
5.1.3 Equality 11
5.1.4 Persistency 11
5.1.5 Scalability 11
5.1.6 Security 11
5.2 IoT RNS architecture 11
5.2.1 Assumption 11
5.2.2 Architecture 12
5.2.3 Metamodel 14
5.2.4 Sequence and algorithms 15
Annex A (informative) Resource identifier format of various IoT platforms 18
A.1 Overview 18
A.2 oneM2M 18
A.3 GS1 Oliot 20
A.4 IBM Watson IoT 21
A.5 OCF IoTivity 22
A.6 FIWARE 22
A.7 Identification Link 23
Annex B (informative) Resource interoperability scenario and implementation examples between heterogeneous IoT platforms in a smart city 24
B.1 Overview 24
B.2 Resource registration and deletion 25
B.3 Discovery service and path conversion 26
B.4 Resource request 29
Bibliography 30

Figure 1 – The IoT metamodel 10
Figure 2 – Overview of system structure and components 13
Figure 3 – The IoT RNS architecture 14
Figure 4 – The metamodel of IoT RNS 15
Figure 5 – Resource registration and deletion of IoT RNS 16
Figure 6 – Discovery service and path conversion in the local IoT RNS 16

Figure A.1 – International OID tree 19
Figure A.2 – oneM2M standard object identifiers 19
Figure A.3 – oneM2M resource structure 20
Figure A.4 – GS1 ID key value 21
Figure A.5 – FIWARE IoT device management architecture based on IoT agents 22
Figure A.6 – Example of Identification Link with QR-Code in Identification Link frame 23
Figure A.7 – Example of RFID emblem with Identification Link frame 23
Figure B.1 – IoT RNS interoperability scenario in a smart city 24
Figure B.2 – Scenario-based sequence diagram that converts the resource path among heterogeneous IoT platforms 25
Figure B.3 – Resource registration example of IoT RNS 26
Figure B.4 – Resource deletion example of IoT RNS 26
Figure B.5 – Discovery service example of IoT RNS 27
Figure B.6 – Path conversion example in the local IoT RNS: phases 1 and 2 27
Figure B.7 – Path conversion example in the local IoT RNS: phases 3 and 4 27
Figure B.8 – Results of path conversion in each local IoT RNS 28
Figure B.9 – Resource request example of IoT RNS 29

Table A.1 – Comparison of five IoT platforms' resource ID formats 18
Table A.2 – GS1 identification key type 20
Table A.3 – Type of Watson IoT client ID 21
Table A.4 – Request identifier parameter 21
Table B.1 – Mapping table example of IoT RNS 28