

ISO/IEC 30181:2024-12 (E)

Internet of Things (IoT) - Functional architecture for resource identifier interoperability

| Contents | Page |
|---|-------------|
| FOREWORD..... | 4 |
| INTRODUCTION..... | 6 |
| 1 Scope..... | 7 |
| 2 Normative references..... | 7 |
| 3 Terms and definitions..... | 7 |
| 4 Abbreviated terms..... | 9 |
| 5 IoT resource name system..... | 10 |
| 5.1 Requirements for the interoperability of the resource ID in an IoT platform..... | 10 |
| 5.1.1 General..... | 10 |
| 5.1.2 Uniqueness..... | 10 |
| 5.1.3 Equality..... | 11 |
| 5.1.4 Persistency..... | 11 |
| 5.1.5 Scalability..... | 11 |
| 5.1.6 Security..... | 11 |
| 5.2 IoT RNS architecture..... | 11 |
| 5.2.1 Assumption..... | 11 |
| 5.2.2 Architecture..... | 12 |
| 5.2.3 Metamodel..... | 14 |
| 5.2.4 Sequence and algorithms..... | 15 |
| Annex A (informative) Resource identifier format of various IoT platforms..... | 18 |
| A.1 Overview..... | 18 |
| A.2 oneM2M..... | 18 |
| A.3 GS1 OIiot..... | 20 |
| A.4 IBM Watson IoT..... | 21 |
| A.5 OCF IoTivity..... | 22 |
| A.6 FIWARE..... | 22 |
| A.7 Identification Link..... | 23 |
| Annex B (informative) Resource interoperability scenario and implementation examples between heterogeneous IoT platforms in a smart city..... | 24 |
| B.1 Overview..... | 24 |
| B.2 Resource registration and deletion..... | 25 |
| B.3 Discovery service and path conversion..... | 26 |
| B.4 Resource request..... | 29 |
| Bibliography..... | 30 |
| | |
| Figure 1 – The IoT metamodel..... | 10 |
| Figure 2 – Overview of system structure and components..... | 13 |
| Figure 3 – The IoT RNS architecture..... | 14 |
| Figure 4 – The metamodel of IoT RNS..... | 15 |
| Figure 5 – Resource registration and deletion of IoT RNS..... | 16 |
| Figure 6 – Discovery service and path conversion in the local IoT RNS..... | 16 |

| | |
|---|----|
| Figure A.1 – International OID tree | 19 |
| Figure A.2 – oneM2M standard object identifiers..... | 19 |
| Figure A.3 – oneM2M resource structure | 20 |
| Figure A.4 – GS1 ID key value | 21 |
| Figure A.5 – FIWARE IoT device management architecture based on IoT agents | 22 |
| Figure A.6 – Example of Identification Link with QR-Code in Identification Link frame..... | 23 |
| Figure A.7 – Example of RFID emblem with Identification Link frame | 23 |
| Figure B.1 – IoT RNS interoperability scenario in a smart city | 24 |
| Figure B.2 – Scenario-based sequence diagram that converts the resource path among heterogeneous IoT platforms | 25 |
| Figure B.3 – Resource registration example of IoT RNS | 26 |
| Figure B.4 – Resource deletion example of IoT RNS..... | 26 |
| Figure B.5 – Discovery service example of IoT RNS | 27 |
| Figure B.6 – Path conversion example in the local IoT RNS: phases 1 and 2 | 27 |
| Figure B.7 – Path conversion example in the local IoT RNS: phases 3 and 4 | 27 |
| Figure B.8 – Results of path conversion in each local IoT RNS | 28 |
| Figure B.9 – Resource request example of IoT RNS | 29 |
| | |
| Table A.1 – Comparison of five IoT platforms' resource ID formats | 18 |
| Table A.2 – GS1 identification key type..... | 20 |
| Table A.3 – Type of Watson IoT client ID | 21 |
| Table A.4 – Request identifier parameter | 21 |
| Table B.1 – Mapping table example of IoT RNS | 28 |