

ISO/IEC/IEEE 8802-15-7:2025-09 (E)

Information technology - Telecommunications and information exchange between systems - Local and metropolitan area networks - Specific requirements - Part 15-7: Short-range optical wireless communications

Contents	Page
1. Overview.....	16
1.1 Scope.....	16
1.2 Purpose.....	16
2. Normative references.....	17
3. Definitions, acronyms, and abbreviations.....	17
3.1 Definitions.....	17
3.2 Acronyms and abbreviations.....	18
4. General description.....	21
4.1 Introduction.....	21
4.2 Network topologies.....	21
4.2.1 Peer-to-peer topology.....	22
4.2.2 Star topology.....	22
4.2.3 Broadcast topology.....	23
4.3 Modulation-domain spectrum.....	23
4.4 Architecture.....	23
4.4.1 PHY types.....	24
4.4.2 MAC sublayer.....	26
4.4.3 Dimming and flicker-mitigation support.....	26
4.5 Functional overview.....	31
4.5.1 Superframe structure.....	32
4.5.2 Data transfer model.....	32
4.5.3 Clock-rate selection.....	34
4.5.4 Frame structure.....	34
4.5.5 Improving probability of successful delivery.....	34
4.6 Security.....	35
4.7 Concept of primitives.....	36
4.8 Some media access mechanisms by PHY types.....	37
4.9 Decoding.....	37
5. MAC protocol specifications.....	38
5.1 MAC functional description.....	38
5.1.1 Channel access.....	39
5.1.2 Starting a OWPAN.....	45
5.1.3 Maintaining OWPANs.....	51
5.1.4 Association and disassociation.....	53
5.1.5 Synchronization.....	55
5.1.6 Transaction handling.....	57
5.1.7 Transmission, reception, and acknowledgment.....	58
5.1.8 GTS allocation and management.....	65
5.1.9 Fast link recovery.....	70
5.1.10 Multiple channel resource assignment.....	73
5.1.11 OWC cell design and mobility support.....	75
5.1.12 Color function support.....	78
5.1.13 Color stabilization.....	81
5.1.14 Visibility and dimming support.....	82
5.2 MAC frame formats.....	87

5.2.1	General MAC frame formats	88
5.2.2	Format of individual frame types	96
5.3	MAC command frames.....	103
5.3.1	Association request command	104
5.3.2	Association response command	105
5.3.3	Disassociation notification command	107
5.3.4	Data request command	108
5.3.5	OWPAN ID conflict notification command	109
5.3.6	Beacon request command	109
5.3.7	Coordinator realignment command	110
5.3.8	GTS request command	111
5.3.9	Blinking notification command	112
5.3.10	Dimming notification command	113
5.3.11	Fast link recovery command	113
5.3.12	Mobility notification command	114
5.3.13	GTS response command	114
5.3.14	Clock rate change notification command	115
5.3.15	Multiple channel assignment command	115
5.3.16	Color stabilization timer notification command	116
5.3.17	Color stabilization information command	116
5.3.18	CVD disable command	116
5.3.19	Information element command	117
6.	MAC sublayer service specification	124
6.1	Overview.....	124
6.2	MAC data service	124
6.2.1	MCPS-DATA.request	125
6.2.2	MCPS-DATA.confirm	128
6.2.3	MCPS-DATA.indication	130
6.2.4	MCPS-PURGE.request	132
6.2.5	MCPS-PURGE.confirm	133
6.2.6	Data service message sequence chart	134
6.3	MAC management service.....	134
6.3.1	Association primitives	135
6.3.2	Disassociation primitives	143
6.3.3	Beacon notification primitive	149
6.3.4	Primitives for reading PIB attributes	151
6.3.5	GTS management primitives	153
6.3.6	Primitives for resetting the MAC sublayer	160
6.3.7	Primitives for specifying the receiver enable time	161
6.3.8	Primitives for channel scanning	165
6.3.9	Communication status primitive	168
6.3.10	Primitives for writing PIB attributes	172
6.3.11	Primitives for updating the superframe configuration	174
6.3.12	Primitive for synchronizing with a coordinator	179
6.3.13	Primitive for synchronization loss with a coordinator	180
6.3.14	Primitives for requesting data from a coordinator	183
6.4	MAC constants and PIB attributes.....	186
6.4.1	MAC constants	186
6.4.2	MAC PIB attributes	188
6.5	Optical clock-rate selection	199
6.5.1	Optical-clock-rate selection for peer-to-peer topology	199
6.5.2	Optical-clock-rate selection for star topology	202

6.5.3	Clock-rate selection for multicast topology	204
6.6	Message sequence charts illustrating MAC-PHY interaction	206
7.	Security suite specifications.....	214
7.1	Overview.....	214
7.2	Functional description.....	214
7.2.1	Outgoing frame security procedure	214
7.2.2	Outgoing frame key retrieval procedure	215
7.2.3	Incoming frame security procedure	216
7.2.4	Incoming frame security material retrieval procedure	218
7.2.5	Key descriptor lookup procedure	219
7.2.6	Blacklist checking procedure	219
7.2.7	Device descriptor lookup procedure	220
7.2.8	Incoming security level checking procedure	220
7.2.9	Incoming key usage policy checking procedure	220
7.3	Security operations	221
7.3.1	Integer and octet representation	221
7.3.2	CCM* nonce	221
7.3.3	CCM* prerequisites	221
7.3.4	CCM* transformation data representation	222
7.3.5	CCM* inverse transformation data representation	223
7.4	Auxiliary Security header	224
7.4.1	Integer and octet representation	224
7.4.2	Security Control field	224
7.4.3	Frame Counter field	226
7.4.4	Key Identifier field	226
7.5	Security-related MAC PIB attributes.....	227
7.5.1	PIB security material	227
7.5.2	Key table	230
7.5.3	Device table	231
7.5.4	Minimum security level table	231
7.5.5	Frame counter	231
7.5.6	Automatic request attributes	231
7.5.7	Default key source	231
7.5.8	Coordinator address	231
8.	PHY specification.....	232
8.1	Overview.....	232
8.2	Operating modes.....	232
8.3	General requirements.....	235
8.3.1	Wavelength band plan	235
8.3.2	Optical mapping	235
8.3.3	Maximum error tolerance for multiple optical sources	236
8.3.4	Minimum LIFS, SIFS, and RIFS periods	237
8.3.5	TX-to-RX turnaround time	237
8.3.6	RX-to-TX turnaround time	237
8.3.7	Transmit data clock frequency tolerance	237
8.3.8	Wavelength quality indicator (WQI)	238
8.3.9	Clear channel assessment (CCA)	238
8.4	Data modes	239
8.5	Dimming and flicker mitigation	239
8.5.1	Dimming during idle time	240
8.5.2	Dimming during data transmission time	241

8.5.3	Flicker mitigation	245
8.5.4	CSK color stabilization at the transmitter	246
8.6	PPDU format.....	247
8.6.1	Preamble field	247
8.6.2	PHY Header field	252
8.6.3	HCS field	256
8.6.4	Optional fields	256
8.6.5	PSDU field	259
9.	PHY service specifications	265
9.1	Overview.....	265
9.2	PHY management service.....	265
9.2.1	PLME-CCA.request	266
9.2.2	PLME-CCA.confirm	266
9.2.3	PLME-GET.request	267
9.2.4	PLME-GET.confirm	267
9.2.5	PLME-SET.request	268
9.2.6	PLME-SET.confirm	269
9.2.7	PLME-SET-TRX-STATE.request	270
9.2.8	PLME-SET-TRX-STATE.confirm	270
9.2.9	PLME-SWITCH.request	271
9.2.10	PLME-SWITCH.confirm	272
9.3	PHY data service	272
9.3.1	PD-DATA.request	273
9.3.2	PD-DATA.confirm	273
9.3.3	PD-DATA.indication	274
9.4	PHY enumeration description.....	275
9.5	PHY constants and PIB attributes.....	275
9.5.1	PHY constants	275
9.5.2	PHY PIB attributes	276
10.	PHY I specifications	290
10.1	Reference modulator diagram.....	290
10.2	Outer FEC encoder	290
10.3	Interleaving and puncturing block	291
10.4	Inner FEC encoder	292
10.4.1	Rate-1/4 code	293
10.4.2	Rate-1/3 code	293
10.4.3	Rate-2/3 code	293
10.5	RLL encoder	294
10.5.1	4B6B encoding for VPPM modes	294
10.5.2	Manchester encoding for OOK mode	295
10.6	Data mapping for VPPM	295
11.	PHY II specifications.....	296
11.1	Reference modulator diagram.....	296
11.2	FEC encoder	296
11.3	RLL encoder	297
11.4	Data mapping for VPPM	297
12.	PHY III specifications	298
12.1	Reference modulator diagram.....	298

12.2	Scrambler	298
12.3	Channel encoder	299
12.4	CSK constellation overview	300
12.5	CSK constellation design rules	301
	12.5.1 Design rule for 4-CSK	301
	12.5.2 Design rule for 8-CSK	301
	12.5.3 Design rule for 16-CSK	302
12.6	Data mapping for CSK	303
12.7	Valid color band combinations	304
12.8	CSK color mapping	306
12.9	CSK calibration at the receiver	307
13.	PHY IV specifications	309
13.1	UFSOOK	309
	13.1.1 Reference modulator diagram	309
	13.1.2 UFSOOK encoder	309
	13.1.3 UFSOOK spatial FEC	309
	13.1.4 UFSOOK temporal FEC	310
	13.1.5 UFSOOK MIMO protocol	311
13.2	Twinkle VPPM	316
	13.2.1 Reference modulator diagram	316
	13.2.2 VPPM encoder	316
	13.2.3 Twinkle generation	317
13.3	S2-PSK.....	318
	13.3.1 Reference architecture	318
	13.3.2 S2-PSK bit-to-symbol mapping	318
	13.3.3 S2-PSK 1/2-rate line coding	319
	13.3.4 S2-PSK FEC encoder	319
13.4	HS-PSK.....	319
	13.4.1 Reference architecture	319
	13.4.2 DS8-PSK modulator	320
	13.4.3 HS-PSK encoder	321
	13.4.4 HS-PSK FEC encoder	322
13.5	Offset-VPWM.....	322
	13.5.1 Reference architecture	322
	13.5.2 Offset-VPWM PHY encoder	322
14.	PHY V specifications.....	325
14.1	RS-FSK.....	325
	14.1.1 Transmitted signal frequency	325
	14.1.2 Symbol duration	325
14.2	CM-FSK modulation	325
	14.2.1 Reference architecture	325
	14.2.2 Asynchronous bit(s) insertion	325
	14.2.3 CM-FSK encoder	326
14.3	C-OOK.....	328
	14.3.1 Reference architecture	328
	14.3.2 C-OOK encoder	328
	14.3.3 Packet structure specification modes	330
14.4	MPM	330
	14.4.1 Sequence Number subfield	331
	14.4.2 Last Sequence Flag subfield	331
	14.4.3 PLCP Header/Center/Footer subfields	331

14.4.4	Front Payload subfield and Back Payload subfield	332
14.4.5	MPWM/MPPM waveform	332
15.	PHY VI specifications	334
15.1	A-QL	334
15.1.1	Reference architecture	334
15.1.2	Channel encoder	335
15.1.3	Bits-to-intensity mapping	337
15.1.4	Channel estimation and color calibration	337
15.2	VTASC specifications	338
15.2.1	VTASC reference architecture	338
15.2.2	Synchronization sequence	339
15.2.3	VTASC code design	340
15.2.4	VTASC encoder	342
15.2.5	Asynchronous communication mode	345
15.2.6	Scalable bitrate controller	346
15.3	SS2DC specification	347
15.3.1	SS2DC reference architecture	347
15.3.2	SS2DC code design	347
15.3.3	SS2DC encoder	348
15.4	IDE specification	349
15.4.1	IDE reference architecture	349
15.4.2	Synchronization sequence	350
15.4.3	IDE encoder	350
15.5	Hidden A-QL (HA-QL)	353
15.5.1	Reference architecture	353
15.5.2	Channel encoder	354
15.5.3	Bits-to-intensity mapping	355
Annex A	(informative) Bibliography	356
A.1	General	356
A.2	Regulatory documents	357
Annex B	(normative) Service-specific convergence sublayer (SSCS)	360
B.1	IEEE 802.2 convergence sublayer	360
Annex C	(normative) Cyclic redundancy check (CRC)	364
Annex D	(normative) Channel assignment	365
Annex E	(informative) Considerations for OWC using LED displays	371
E.1	Introduction—Dynamic displays vs. addressed displays	371
E.2	Dynamic displays	371
E.3	Addressed displays	375
Annex F	(informative) Receiver performance variation on multi-color channels	376
Annex G	(informative) RS-FSK tutorial	380
G.1	RS-FSK transmitted waveform	380
G.2	Transmitted signal frequency	380
G.3	Symbol duration	381

G.4	Relation between signal frequency and the observed strip width in the captured image	381
G.5	Survey of parameters of commercially available image sensors.....	382
Annex H (informative)	PHY modes TX and RX profile	383
H.1	PHY modes TX profiles	383
H.2	PHY modes RX profile.....	384
Annex I (informative)	PHY IV, PHY V, and PHY VI OCC waveforms decoding guide	386
I.1	S2-PSK decoding method.....	386
I.2	DS8-PSK decoding method	386
I.3	HS-PSK decoding method	388
I.4	C-OOK decoding method	388
I.5	A-QL decoding method	392
I.6	HA-QL decoding method	393
I.7	Offset-VPWM decoding method.....	394
I.8	VTASC decoding method.....	395
I.9	SS2DC decoder.....	396
I.10	IDE decoder	396
Annex J (normative)	Hamming code and majority bit voting	398
J.1	Generation of Hamming code.....	398
J.2	Temporal error correction using majority bit voting	400
Annex K (informative)	PHY mode-specific characteristics	401
K.1	VTASC	401
K.2	SS2DC	401
K.3	IDE.....	401
Annex L (normative)	Frequency-based invisible watermarking	402
Annex M (informative)	UFSOOK MIMO decoder protocol	403
Annex N (informative)	Receiver details on Twinkle VPPM processing	405