

ISO/IEC 18809:2000-12 (E)

Information technology - 8 mm wide magnetic tape cartridge for information interchange - Helical scan recording AIT-1 with MIC format

| Contents | | Page |
|---------------------------|---|------|
| Section 1 - General | | 1 |
| 1 | Scope | 1 |
| 2 | Conformance | 1 |
| 2.1 | Magnetic tape cartridge | 1 |
| 2.2 | Generating drive | 1 |
| 2.3 | Receiving drive | 1 |
| 3 | Normative references | 2 |
| 4 | Terms and definitions | 2 |
| 4.1 | Absolute Frame Number (AFN) | 2 |
| 4.2 | a.c. erase | 2 |
| 4.3 | Access | 2 |
| 4.4 | algorithm | 2 |
| 4.5 | Area ID | 2 |
| 4.6 | Automatic Track Finding (ATF) | 2 |
| 4.7 | Average Signal Amplitude | 2 |
| 4.8 | azimuth | 2 |
| 4.9 | back surface | 2 |
| 4.10 | byte | 2 |
| 4.11 | cartridge | 2 |
| 4.12 | Channel bit | 2 |
| 4.13 | Codeword | 2 |
| 4.14 | Early Warning Point (EWP) | 2 |
| 4.15 | End of Data (EOD) | 2 |
| 4.16 | Entity | 2 |
| 4.17 | Error Correcting Code (ECC) | 2 |
| 4.18 | flux transition position | 2 |
| 4.19 | flux transition spacing | 2 |
| 4.20 | Frame | 3 |
| 4.21 | Housekeeping Frame | 3 |
| 4.22 | Logical Beginning of Tape (LBOT) | 3 |
| 4.23 | magnetic tape | 3 |
| 4.24 | Master Standard Amplitude Calibration Tape | 3 |
| 4.25 | Master Standard Reference Tape | 3 |
| 4.26 | Memory In Cartridge (MIC) | 3 |
| 4.27 | Partition Boundary | 3 |
| 4.28 | Physical Beginning of Tape (PBOT) | 3 |
| 4.29 | Physical End of Tape (PEOT) | 3 |
| 4.30 | physical recording density | 3 |
| 4.31 | pre-recording condition | 3 |
| 4.32 | processing | 3 |
| 4.33 | processed data | 3 |
| 4.34 | Processed Record | 3 |
| 4.35 | record | 3 |
| 4.36 | Reference Field | 3 |
| 4.37 | Secondary Standard Amplitude Calibration Tape | 3 |
| 4.38 | Secondary Standard Reference Tape | 3 |
| 4.39 | Separator Mark | 3 |

| | | |
|--|--|----|
| 4.40 | Standard Reference Amplitude (SRA) | 3 |
| 4.41 | Tape Reference Edge | 4 |
| 4.42 | Typical Field | 4 |
| 4.43 | Standard Reference Current | 4 |
| 4.44 | Test Recording Current | 4 |
| 4.45 | track | 4 |
| 4.46 | unprocessed data | 4 |
| 4.47 | Unprocessed Record | 4 |
| 5 | Conventions and Notations | 4 |
| 5.1 | Representation of numbers | 4 |
| 5.2 | Names | 4 |
| 6 | Acronyms | 4 |
| 7 | Environment and safety | 4 |
| 7.1 | Test environment | 4 |
| 7.2 | Operating environment | 5 |
| 7.3 | Storage environment | 5 |
| 7.4 | Transportation | 5 |
| 7.5 | Safety | 5 |
| 7.6 | Flammability | 5 |
| Section 2 - Requirements for the case | | 6 |
| 8 | Dimensional and mechanical characteristics of the case | 6 |
| 8.1 | General | 6 |
| 8.2 | Overall dimension (figures 5 and 6) | 6 |
| 8.3 | Holding areas | 7 |
| 8.4 | Cartridge insertion | 7 |
| 8.5 | Window (figure 1) | 8 |
| 8.6 | Loading grips (figures 5 and 7) | 8 |
| 8.7 | Label areas (figures 6 and 8) | 8 |
| 8.8 | Datum areas and Datum holes | 8 |
| 8.9 | Support areas (figure 9) | 9 |
| 8.10 | Recognition holes (figures 10, 11 and 12) | 10 |
| 8.11 | Write-inhibit hole (figure 11) | 10 |
| 8.12 | Pre-positioning surfaces (figures 4 and 10) | 11 |
| 8.13 | Cartridge lid (figures 6, 13 and 15) | 11 |
| 8.14 | Cartridge reel lock (figures 10 and 16) | 12 |
| 8.15 | Reel access holes (figure 10) | 13 |
| 8.16 | Interface between the reels and the drive spindles | 13 |
| 8.17 | Light path (figures 10, 12, 20 and 21) | 14 |
| 8.18 | Position of the tape in the case (figure 21) | 15 |
| 8.19 | Tape path zone | 15 |
| 8.20 | Tape access cavity (figure 10) | 16 |
| 8.21 | Tape access cavity clearance (figure 24) | 16 |
| 8.22 | Requirements for the MIC (figures 25 and 26) | 16 |
| 8.23 | Recognition recesses (figures 8 and 10) | 17 |
| Section 3 - Requirements for the unrecorded tape | | 38 |
| 9 | Mechanical, physical and dimensional characteristics of the tape | 38 |
| 9.1 | Materials | 38 |
| 9.2 | Tape length | 38 |
| 9.2.1 | Length of the magnetic tape | 38 |
| 9.2.2 | Length of the leader and trailer tapes | 38 |
| 9.2.3 | Length of the splicing tapes | 38 |
| 9.3 | Tape width | 38 |
| 9.3.1 | Width of the magnetic, leader and trailer tapes | 38 |
| 9.3.2 | Width and position of the splicing tape | 38 |
| 9.4 | Discontinuities | 39 |

| | | |
|---|---|----|
| 9.5 | Tape thickness | 39 |
| 9.5.1 | Thickness of the magnetic tape | 39 |
| 9.5.2 | Thickness of the leader and trailer tapes | 39 |
| 9.5.3 | Thickness of the splicing tape | 39 |
| 9.6 | Longitudinal curvature | 39 |
| 9.7 | Cupping | 39 |
| 9.8 | Coating adhesion | 39 |
| 9.9 | Layer-to-layer adhesion | 40 |
| 9.10 | Tensile strength | 40 |
| 9.10.1 | Breaking strength | 40 |
| 9.10.2 | Yield strength | 40 |
| 9.11 | Residual elongation | 40 |
| 9.12 | Electrical resistance of the recording surface | 40 |
| 9.13 | Tape winding | 41 |
| 9.14 | Light transmittance of the tape | 41 |
| 10 | Magnetic recording characteristics | 41 |
| 10.1 | Typical Field | 42 |
| 10.2 | Signal Amplitude | 42 |
| 10.3 | Resolution | 42 |
| 10.4 | Overwrite | 42 |
| 10.5 | Ease of erasure | 42 |
| 10.6 | Tape quality | 42 |
| 10.6.1 | Missing pulses | 42 |
| 10.6.2 | Missing pulse zone | 43 |
| 10.7 | Signal-to-Noise Ratio (SNR) characteristic | 43 |
| Section 4 - Requirements for an interchanged tape | | 43 |
| 11 | Format | 43 |
| 11.1 | General | 43 |
| 11.2 | Basic Groups | 43 |
| 11.2.1 | Entity | 44 |
| 11.2.2 | Group Information Table | 45 |
| 11.2.3 | Block Access Table (BAT) | 47 |
| 11.3 | Sub-Groups | 50 |
| 11.3.1 | G1 Sub-Group | 50 |
| 11.3.2 | G2 Sub-Group - Randomizing | 51 |
| 11.3.3 | G3 Sub-Group | 52 |
| 11.4 | Data Block | 53 |
| 11.4.1 | ID information | 54 |
| 11.4.2 | Recording of the ID Information in the Data Block Headers | 56 |
| 12 | Method of recording | 62 |
| 12.1 | Physical recording density | 62 |
| 12.2 | Long-term average bit cell length | 62 |
| 12.3 | Short-term average bit cell length | 62 |
| 12.4 | Rate of change | 62 |
| 12.5 | Bit shift | 63 |
| 12.6 | Read signal amplitude | 63 |
| 12.7 | Maximum recorded levels | 63 |
| 13 | Track geometry | 63 |
| 13.1 | Track configuration | 63 |
| 13.2 | Average track pitch | 63 |
| 13.3 | Variations of the track pitch | 64 |
| 13.4 | Track width | 64 |
| 13.5 | Track angle | 64 |
| 13.6 | Track edge straightness | 64 |
| 13.7 | Track length | 64 |
| 13.8 | Azimuth angles | 64 |

| | | |
|--|--|-----|
| 14 | Recorded patterns | 64 |
| 14.1 | Recorded Data Block | 64 |
| 14.2 | Margin blocks | 64 |
| 15 | Format of a track | 64 |
| 15.1 | Track structure | 64 |
| 15.2 | Positioning accuracy | 65 |
| 15.3 | Tracking scheme | 66 |
| 16 | Layout of the tape | 66 |
| 16.1 | Device Area | 67 |
| 16.2 | Reference Area | 67 |
| 16.3 | Position Tolerance Band No. 1 | 68 |
| 16.4 | System Area | 68 |
| 16.4.1 | System Preamble | 68 |
| 16.4.2 | System Log | 68 |
| 16.4.3 | System Postamble | 72 |
| 16.4.4 | Position Tolerance Band No. 2 | 72 |
| 16.4.5 | Vendor Group Preamble | 72 |
| 16.5 | Data Area | 72 |
| 16.5.1 | Vendor Group | 72 |
| 16.5.2 | Recorded Data Group | 72 |
| 16.5.3 | ECC3 | 72 |
| 16.5.4 | Multiple Recorded Instances | 73 |
| 16.5.5 | Repeated Frames | 73 |
| 16.5.6 | Appending and overwriting | 74 |
| 16.6 | EOD Area | 75 |
| 16.7 | Optional Device Area | 75 |
| 16.8 | Logical End Of Tape (LEOT) | 76 |
| 16.9 | Logical Beginning of Tape (LBOT) | 76 |
| 16.10 | Early Warning Point - EWP | 76 |
| 16.11 | Empty Partition | 76 |
| 16.12 | Initialization | 76 |
| 17 | Housekeeping Frames | 77 |
| 17.1 | Amble Frames | 77 |
| 17.2 | System Amble Frames | 77 |
| 18 | Content of the MIC | 77 |
| Annexes A - Measurement of light transmittance | | 79 |
| B | - Measurement of Signal-to-Noise Ratio | 82 |
| C | - Method for determining the nominal and the maximum allowable recorded levels | 83 |
| D | - Representation of 8-bit bytes by 10-bit patterns | 84 |
| E | - Measurement of bit shift | 96 |
| F | - Method of measuring the straightness of track edges | 98 |
| G | - ECC calculation | 99 |
| H | - Recommendations for transportation | 102 |
| J | - Read-After-Write | 103 |
| K | - Example of the content of a Basic Group No. 0 | 104 |
| L | - Examples of MIC chip | 105 |