

ISO/IEC 14496-6:2000-12 (E)

Information technology - Coding of audio-visual objects - Part 6: Delivery Multimedia Integration Framework (DMIF)

| Contents | | Page |
|-----------------|---|-------------|
| 1 | Scope | 1 |
| 2 | Conformance | 1 |
| 2.1 | Requirements for conformance | 1 |
| 2.2 | DMIF-Application Interface | 1 |
| 2.3 | DMIF signalling messages | 2 |
| 3 | Normative references | 2 |
| 4 | Terms and definitions | 2 |
| 5 | Abbreviations | 3 |
| 7 | Compliance terms | 5 |
| 8 | DMIF overview | 5 |
| 8.2 | The objectives of DMIF | 6 |
| 8.3 | The DMIF communications architecture | 6 |
| 8.4 | DMIF computational model | 8 |
| 8.5 | DMIF QoS model | 9 |
| 8.6 | The User Plane in the Delivery Layer | 9 |
| 9 | Remote interactive scenario | 10 |
| 9.1 | Additional requirements | 10 |
| 9.1.1 | Introduction | 10 |
| 9.1.2 | Billing policies | 11 |
| 9.1.3 | Possible evolution to Heterogeneous Networks | 11 |
| 9.2 | DMIF within the context of the ISO/OSI layers | 11 |
| 10 | The DMIF-Application Interface | 12 |
| 10.1 | The DMIF-Application Interface key concepts | 12 |
| 10.2 | Common semantic elements | 13 |
| 10.2.1 | channelDescriptor | 13 |
| 10.3 | DMIF-Application Interface primitives | 15 |
| 10.4 | DMIF-Application Interface semantics | 17 |
| 10.4.1 | DA_ServiceAttach () | 17 |
| 10.4.2 | DA_ServiceAttachCallback () | 18 |
| 10.4.3 | DA_ServiceDetach () | 18 |
| 10.4.4 | DA_ServiceDetachCallback () | 18 |
| 10.4.5 | DA_ChannelAdd () | 18 |
| 10.4.6 | DA_ChannelAddCallback () | 19 |
| 10.4.7 | DA_ChannelDelete () | 19 |
| 10.4.8 | DA_ChannelDeleteCallback () | 19 |
| 10.4.9 | DA_UserCommand () | 19 |
| 10.4.10 | DA_UserCommandCallback () | 19 |
| 10.4.11 | DA_Data () | 19 |
| 10.4.12 | DA_DataCallback () | 20 |
| 10.4.13 | DA_UserCommandAck() | 20 |
| 10.4.14 | DA_UserCommandAckCallback() | 20 |
| 10.4.15 | DA_ChannelMonitor() | 20 |
| 10.4.16 | DA_ChannelEvent() | 20 |

| | | |
|---------|---|----|
| 10.5 | QoS Monitoring | 21 |
| 10.5.1 | Monitoring events | 21 |
| 10.5.2 | qosMode | 21 |
| 10.5.3 | qosReport | 23 |
| 11 | The DMIF-Network Interface | 23 |
| 11.1 | The DMIF-Network Interface key concepts | 23 |
| 11.2 | Common syntax elements | 24 |
| 11.2.1 | DMIF Descriptors | 24 |
| 11.2.2 | DMIF to DMIF data | 26 |
| 11.2.3 | Resource Descriptors | 26 |
| 11.2.4 | Direction parameter | 28 |
| 11.2.5 | Reason parameter | 28 |
| 11.2.6 | Response parameter | 28 |
| 11.2.7 | channelDescriptor and qosDescriptors | 29 |
| 11.3 | DMIF-Network Interface primitives | 34 |
| 11.4 | DMIF-Network Interface semantics | 36 |
| 11.4.1 | DN_SessionSetup () | 36 |
| 11.4.2 | DN_SessionRelease () | 36 |
| 11.4.3 | DN_ServiceAttach () | 36 |
| 11.4.4 | DN_ServiceDetach () | 37 |
| 11.4.5 | DN_TransMuxSetup () | 37 |
| 11.4.6 | DN_TransMuxRelease () | 37 |
| 11.4.7 | DN_ChannelAdd() | 37 |
| 11.4.8 | DN_ChannelAdded() | 38 |
| 11.4.9 | DN_ChannelDelete () | 38 |
| 11.4.10 | DN_TransMuxConfig () | 39 |
| 11.4.11 | DN_UserCommand () | 39 |
| 11.4.12 | DN_UserCommandAck () | 39 |
| 12 | Control Plane mappings | 40 |
| 12.1 | Default syntax | 40 |
| 12.1.1 | Syntax elements | 40 |
| 12.1.2 | DNI mapping to DMIF signalling messages | 46 |
| 12.2 | Syntax for IP networks with (or without) RSVP signalling, using TCP for DMIF signalling | 56 |
| 12.2.1 | Approach overview | 56 |
| 12.2.2 | DSM-CC Resource Descriptors used | 56 |
| 12.2.3 | Usage of networkSessionIds | 56 |
| 12.2.4 | Usage of transactionIds | 57 |
| 12.2.5 | DNI mapping to socket actions and RSVP signalling | 57 |
| 12.3 | Syntax for IP networks with (or without) RSVP Signalling, using UDP for DMIF signalling | 59 |
| 12.3.1 | Approach overview | 60 |
| 12.3.2 | DSM-CC Resource Descriptors used | 60 |
| 12.3.3 | Usage of networkSessionIds | 60 |
| 12.3.4 | Usage of transactionIds | 60 |
| 12.3.5 | DNI mapping to socket actions and RSVP signalling | 60 |
| 12.4 | Syntax for ATM networks with Q.2931 signalling | 61 |
| 12.4.1 | Approach overview | 61 |
| 12.4.2 | DSM-CC Resource Descriptors used | 61 |
| 12.4.3 | Usage of networkSessionIds | 61 |
| 12.4.4 | Usage of transactionIds | 61 |
| 12.4.5 | DNI mapping to Q.2931 signalling messages | 62 |
| 12.5 | Syntax for Networks with ITU-T H.245 Signaling | 66 |
| 12.5.1 | Approach overview | 66 |
| 12.5.2 | DSM-CC Resource Descriptors used | 66 |
| 12.5.3 | Usage of networkSessionIds | 66 |
| 12.5.4 | Usage of transactionIds | 67 |
| 12.5.5 | DNI mapping to H.245 Signaling messages | 67 |
| 12.5.6 | Data transmission procedures | 68 |
| 13 | Terminal Capability Matching | 68 |
| 13.1 | DMIF Default signalling with Compatibility Descriptors | 68 |

| | |
|---|------------|
| Annex A (informative) Overview of DAI and DNI parameters | 69 |
| A.1 Sessions and services | 69 |
| A.2 Channels | 69 |
| Annex B (informative) Information flows for DMIF | 71 |
| B.1 Information flows for Remote Interactive DMIF | 71 |
| B.1.1 Initiation of a service in a Remote Interactive DMIF | 72 |
| B.1.2 Addition of Channels in a Remote Interactive DMIF | 74 |
| B.1.3 Deletion of Channels in a Remote Interactive DMIF | 80 |
| B.1.4 Termination of a Service in a Remote Interactive DMIF | 82 |
| B.2 Information Flows for Broadcast DMIF | 83 |
| B.2.1 Initiation of a service in a Broadcast DMIF | 84 |
| B.2.2 Addition of Channels in a Broadcast DMIF | 85 |
| B.2.3 Deletion of Channels in a Broadcast DMIF | 86 |
| B.2.4 Termination of a service in a Broadcast DMIF | 87 |
| B.3 Information Flows for Local Storage DMIF | 87 |
| B.3.1 Initiation of a service in a Local Storage DMIF | 88 |
| B.3.2 Addition of Channels in a Local Storage DMIF | 89 |
| B.3.3 Deletion of Channels in a Local Storage DMIF | 90 |
| B.3.4 Termination of a service in a Local Storage DMIF | 91 |
| Annex C (informative) Use of URLs in DMIF | 92 |
| C.1 Introduction | 92 |
| C.2 Generic concepts | 92 |
| C.3 URL schemes allowed in DMIF | 92 |
| C.4 New URL schemes | 92 |
| C.4.1 URL scheme for DMIF signalling over UDP/IP | 93 |
| C.4.2 URL scheme for DMIF signalling over TCP/IP | 93 |
| C.4.3 URL scheme for DMIF signalling over networks using NSAP addresses format | 93 |
| Annex D (informative) Protocol error recovery | 94 |
| D.1 Timeouts and retransmission | 94 |
| D.2 Transaction state variables | 94 |
| D.2.1 Transaction identifier: Tid | 94 |
| D.2.2 Transaction state: Tid.state | 94 |
| D.2.3 Associated session: Tid.Sid | 94 |
| D.2.4 Transaction message timeout: Tid.tMessage | 94 |
| D.2.5 Expired transactionId holding timer: Tid.tHold | 95 |
| D.2.6 Transaction message: Tid.message | 95 |
| D.2.7 Tid.retransBound | 95 |
| D.2.8 Tid.numRetrans | 95 |
| D.3 Transaction Identifier State Machine | 95 |
| D.4 Transaction Identifier State table | 96 |
| E.1 ResourceDescriptor format | 98 |
| E.1.1 ResourceDescriptorDataField | 98 |
| E.1.2 Specifying ranges and lists of values in resource descriptors | 99 |
| E.3 Resource descriptor definitions | 102 |
| E.3.1 AtmSvcConnection resource descriptor definition | 102 |
| E.3.2 IP resource descriptor definition | 102 |
| E.3.3 AtmVcConnection resource descriptor definition | 103 |
| F.1 Introduction | 104 |
| F.2.1 Overview of ETS 300 401 payload transmission | 104 |
| F.2.2 Object descriptor encapsulation | 105 |
| F.2.3 Scene description stream encapsulation | 109 |
| F.2.3.1 BIFSCCommandDataField | 110 |

| | | |
|--|--|-----|
| F.2.4 | ClockReferenceStream encapsulation | 111 |
| F.2.5 | Audiovisual stream encapsulation | 111 |
| F.3 | Walkthrough of a typical MPEG-4 session carried in an ETS 300 401 system | 112 |
| F.3.1 | General | 112 |
| F.3.2 | Start of a session | 113 |
| F.3.3 | Retrieval of the InitialOD | 113 |
| F.3.4 | Retrieval of the subsequent BIFS and Object Descriptor streams | 113 |
| F.3.5 | Retrieval of the clock reference and the audio-visual streams | 113 |
| F.3.6 | Dynamic changes to the scene | 113 |
| F.4 | Mapping of DAI procedures to ETS 300 401 procedures | 113 |
| F.4.1 | Initiation of an MPEG-4 service in a DAB system | 114 |
| F.4.2 | Addition of channels in an MPEG-4 service in a DAB system | 114 |
| F.4.3 | Deletion of Channels in an MPEG-4 service in a DAB system | 115 |
| F.4.4 | Termination of a service in an MPEG-4 service in a DAB system | 115 |
| Annex G (informative) Patent statement | | 116 |
| G.1 | Patent statement | 116 |
| H.1 | Introduction | 118 |
| H.2 | Walkthrough of a typical MPEG-4 session carried in an H.324 system | 118 |
| H.2.1 | General | 118 |
| H.2.2 | Start of a session | 118 |
| H.2.3 | Retrieval of the InitialOD | 118 |
| H.3 | Mapping of DAI procedures to H.245 procedures | 118 |
| H.3.1 | Initiation of a service in a Remote Interactive DMIF | 119 |
| H.3.2 | Addition of Channels in a Remote Interactive DMIF | 119 |
| H.3.3 | Deletion of Channels in a Remote Interactive DMIF | 121 |
| H.3.4 | Termination of a Service in a Remote Interactive DMIF | 122 |
| Annex I (informative) DMIF Application Programming Interface - Syntax definition | | 123 |
| I.1 | Objectives of this Annex | 123 |
| I.2 | DAI protocol flow | 123 |
| I.3 | Application Programming Interface | 124 |
| I.3.1 | DMIF primitives | 124 |
| I.4 | DMIF Application Programming Interface - ANSI C/C++ | 126 |
| I.4.1 | Reference Implementation | 126 |