ISO/IEC 30188:2026-07 (E)

Digital twin - Reference architecture

Contents

Page

FOREWORD 3
INTRODUCTION 4
1 Scope 7
2 Normative references 7
3 Terms and definitions 7
4 Abbreviated terms 9
5 Specifying an architecture for digital twins 10
6 Foundational viewpoint 10
6.1 Stakeholders and concerns 10
6.1.1 General 10
6.1.2 Stakeholders 10
6.1.3 Concerns 10
6.2 Views and models 11
6.2.1 General 11
6.2.2 Conceptual models 11
6.2.3 Physical target entity 13
6.2.4 Digital target entity 13
6.2.5 Combined physical and digital target entity 14
6.2.6 Lifecycle model 14
7 Functional viewpoint 16
7.1 Stakeholders and concerns 16
7.1.1 General 16
7.1.2 Stakeholders 16
7.1.3 Concerns 16
7.2 Views and models 16
7.2.1 General 16
7.2.2 Design and development stage 17
7.2.3 Deployment stage 18
7.2.4 Operation stage 18
7.2.5 Retirement stage 19
8 Implementation viewpoint 19
8.1 Stakeholders and concerns 19
8.1.1 General 19
8.1.2 Stakeholders 19
8.1.3 Concerns 19
8.2 Views and models 19
8.2.1 General 19
8.2.2 Implementation of interfaces 20
8.2.3 Implementation of interoperability 21
8.2.4 Implementation of models 22
Annex A (normative) Architecture pattern viewpoint 24
A.1 Stakeholders and concerns 24

A.1.1 General 24
A.1.2 Stakeholders 24
A.1.3 Concerns 24
A.2 Views and models 24
A.2.1 General 24
A.2.2 Construction model 25
A.2.3 Using views and models from other reference architectures 26
A.3 Examples of patterns 27
A.3.1 Template 27
A.3.2 Sensing and actuating pattern 28
A.3.3 Smart manufacturing RAMI reference model pattern 30
A.3.4 Maturity pattern 31
A.3.5 Framework for manufacturing pattern 32
Bibliography 34

Figure 1 – How to use this document 5
Figure 2 – Used architecture views 6
Figure 3 – Twinning model 12
Figure 4 – Synchronization model 12
Figure 5 – Digital twin for a physical target entity 13
Figure 6 – Digital twin for a digital target entity 13
Figure 7 – Digital twin for a combined physical and digital target entity 14
Figure 8 – Full lifecycle twinning 15
Figure 9 – Example of partial lifecycle twinning 16
Figure 10 – Business and usage interface model 20
Figure 11 – Inner and outer interoperability 21
Figure 12 – Transversal interoperability 21
Figure 13 – Model construction processes 23
Figure A.1 – Digital twin architecture construction model 25
Figure A.2 – Relationship between IoT component, IoT system and IoT environment 28
Figure A.3 – IoT component capability 29
Figure A.4 – RAMI architecture model 30
Figure A.5 – ISO/IEC 30186 [11] maturity model 31
Figure A.6 – ISO 23247-2:2021 [17] architecture 32
Figure A.7 – ISO 23247 series [19] 33

Table 1 – Capabilities in the design and development stage 17
Table 2 – Capabilities in the deployment stage 18
Table 3 – Capabilities in the operation stage 18
Table 4 – Capabilities in the retirement stage 19
Table A.1 – Example of additional views for IoT-related digital twins 26
Table A.2 – Architecture pattern template 27
Table A.3 – Sensing and actuating pattern legend 28
Table A.4 – Smart manufacturing RAMI reference model pattern 30
Table A.5 – Digital twin maturity pattern 31
Table A.6 – Framework from manufacturing pattern 32