

ISO/IEC 7811-2:2001-02 (E)

Identification cards - Recording technique - Part 2: Magnetic stripe; Low coercivity

Contents		Page
1	Scope	1
2	Conformance	1
3	Normative references	1
4	Terms and definitions	2
5	Physical characteristics of the identification card	3
5.1	Magnetic stripe area warpage	3
5.2	Surface distortions	3
6	Physical characteristics of the magnetic stripe	4
6.1	Height and surface profile of the magnetic stripe area	4
6.1.1	Surface profile of the magnetic stripe area	5
6.1.2	Height of the magnetic stripe area	6
6.2	Surface roughness	7
6.3	Adhesion of stripe to card	7
6.4	Wear of magnetic stripe from read/write head	7
6.5	Resistance to chemicals	7
7	Performance characteristics for the magnetic material	7
7.1	General	7
7.2	Testing and operating environment	7
7.3	Signal amplitude requirements for magnetic media	7
8	Encoding technique	9
9	Encoding specification, general	10
9.1	Angle of recording	10
9.2	Nominal bit density	11
9.3	Signal amplitude requirements for tracks 1, 2 and 3	11
9.4	Bit configuration	11
9.5	Direction of recording	11
9.6	Leading and trailing zeroes	11
10	Encoding specifications	12
10.1	Alphanumeric track, track 1	12
10.1.1	Average bit density	12
10.1.2	Flux transition spacing variation	12
10.1.3	Coded character set	13
10.1.4	Maximum number of characters for ID-1 type card	14
10.2	Numeric track, Track 2	15
10.2.1	Average bit density	15
10.2.2	Flux transition spacing variation	15
10.2.3	Coded character set	15
10.2.4	Maximum number of characters for ID-1 type card	16
10.3	Numeric track, Track 3	16
10.3.1	Average bit density	16
10.3.2	Flux transition spacing variation	16
10.3.3	Coded character set	16
10.3.4	Maximum number of characters for ID-1 type card	17

11	Error detection	17
11.1	Parity	17
11.2	Longitudinal redundancy check (LRC)	17
12	Location of encoded tracks	18
Annex B (normative) Signal amplitude measurements		20
Annex C (informative) Magnetic stripe abrasivity		21