ISO/IEC 30178:2026-08 (E)

Internet of Things (IoT) - Data format, value and coding for interoperability

Contents

Page

FOREWORD 5
INTRODUCTION 6
1 Scope 7
2 Normative references 7
3 Terms and definitions 7
4 Abbreviated terms 10
5 Background 11
5.1 Overview 11
5.1.1 General 11
5.1.2 Sensor-related data 12
5.1.3 Source data collection 13
5.1.4 Time-resolution and sample rate 14
5.1.5 Signal-processing implications 14
5.1.6 Low-power sensors 14
5.1.7 Measurement data 15
5.1.8 Numerical component 15
5.1.9 Semantic component 15
5.1.10 Unit 15
5.1.11 Prefix 16
5.2 Sensor value metadata 17
5.2.1 General 17
5.2.2 Resolution 18
5.2.3 Precision (measurement) 18
5.2.4 Sampling time (time resolution) 18
5.2.5 Sample rate 19
5.2.6 Range 19
5.2.7 Accuracy 20
5.2.8 Unit 20
5.2.9 Data type 20
5.2.10 Physical quantity 20
5.3 Physical quantities 20
5.3.1 Overview 20
5.3.2 Occurrences 21
5.4 Examples of data models 22
5.4.1 Overview 22
5.4.2 Exchange formats 22
5.4.3 File formats 22
5.4.4 Information modelling formats 23
5.5 Interoperability challenges 23
5.5.1 System integration 23
5.5.2 Maximizing the economic value of data through reusability 24

5.5.3 Sensor lifecycle cost 25
5.5.4 Sensor data capital value 26
5.5.5 Scalability 26
5.5.6 Semantics 29
5.5.7 Symbol mapping 29
5.5.8 Sensor semantics 29
5.5.9 Representation versus presentation 31
5.5.10 Human readability 31
5.5.11 Resolving data points 32
5.5.12 Type inference and casting 33
5.5.13 Hard coupling 34
5.5.14 Machine-to-machine exchange 34
5.5.15 Representation 34
5.5.16 Presentation 34
5.5.17 Data translation 35
5.5.18 Errors and quality 37
5.5.19 Semantic mismatch 37
6 Core profile 37
6.1 Overview 37
6.2 Sensor data parameters 38
6.2.1 Unit 38
6.2.2 The "unit-word" 38
6.2.3 Dimensionless units 39
6.2.4 Range 39
6.3 Physical quantity 40
6.3.1 Overview 40
6.3.2 Canonical representation 41
6.3.3 Operations 41
6.3.4 Significance-based comparison 42
7 High-level system design 42
7.1 Overview 42
7.2 Type safety 44
7.3 Conversion mechanics 44
7.3.1 Overview 44
7.3.2 Single-step conversion 44
7.3.3 Unit resolver 44
7.3.4 Magnitude resolver 45
7.3.5 Precision estimation 45
7.3.6 Time-resolution and oversampling 45
7.4 Sanity-check mechanisms 46
7.5 Component manufacture 46
7.6 Digitized specification 46
7.6.1 General 46
7.6.2 Measurement range 46
7.6.3 Accuracy 46
7.6.4 Precision 46

Annex A (informative) Single-step conversion 47
A.1 Overview 47
A.2 Example 1: Forward temperature conversion (Kelvin to base SI units) 47
A.3 Example 2: Forward energy conversion (nanojoules to joules) 48
A.4 List of unit-word value examples 49
A.5 Floating-point format 51
A.6 Examples on data point expression 53
Annex B (informative) Unifying sensor data and mapping with standards 54
B.1 Unifying sensor data value metadata: the type of sensor, the measurement type, and the unit 54
B.2 Mapping with IEC 61360-4 [3] Common Data Dictionary (CDD) 55
B.3 Mapping with ETSI SmartM2M SAREF [4] 56
Annex C (informative) Contextualizing sensor characteristics 58
C.1 Concerns in metrology 58
C.2 Context 58
C.3 Preserving data integrity 59
C.4 Example of contextual data conversion 59
Bibliography 60

Figure 1 – Discrimination and reduction of uncertainty of each bit within the range of an 8-bit ADC 13
Figure 2 – Sampling resolution of a signal within a given range 18
Figure 3 – Hypothetical physical entity possessing three physical quantities 20
Figure 4 – Sensors measuring a physical quantity 20
Figure 5 – Sensor attached to, and measuring, some aspect of a physical entity 21
Figure 6 – Integration of sensor (data source) and data consumer is necessary for a data stream to be possible 23
Figure 7 – Sensor and consumer interfaces not compatible 23
Figure 8 – Sensor and consumer interfaces are not compatible, but achieve compatibility through a format adapter 23
Figure 9 – Sensor and consumer already sharing the same exchange format and do not require any further adaptation 24
Figure 10 – Complete product lifecycle, from initial development to end-of-life 25
Figure 11 – Two separate integrations are made to accommodate full availability of interface A from interfaces B and C 26
Figure 12 – Three and five interfaces being integrated, requiring 6 and 20 (one-way) mappings, respectively 27
Figure 13 – 16 individual interfaces require 240 one-way mappings 27
Figure 14 – With half-step intermediary translations, the number of necessary mappings grows linearly instead of exponentially – Here 16 individual interfaces only require 32 one-way mappings 28
Figure 15 – The text-based value of 100 µm (or 0,1mm) can be represented with a big variation in both data type, value structure and scaling 30
Figure 16 – Example of consequences from change in representation 31
Figure 17 – Example of sensor measurement sample serialized as senML/JSON 32
Figure 18 – Essential properties of a physical quantity 38

Figure 19 – Sensor system overview, from electric measurement to pre-processing and transmission over typical IoT protocols 43
Figure A.1 – Breakdown and conversion of data points in a forward temperature conversion 47
Figure A.2 – Magnitude resolver parameters 48
Figure A.3 – Breakdown and conversion of data points in a forward energy conversion 48
Figure A.4 – Magnitude resolver parameters 49
Figure A.5 – Combination of base units into derived units 51
Figure A.6 – Floating-point format binary encoding 52
Figure C.1 – When applied on contextual data, QUDT schema definitions can map to a canonical representation of measurement/sensor data 59

Table 1 – Data source characteristics of a sensor 12
Table 2 – Examples of historical units 16
Table 3 – Prefixes of the Metric System 16
Table 4 – Costs of sensor lifecycle 25
Table 5 – Intermediary-representation design goals for physical quantities 28
Table 6 – JSON payload broken down into first-level objects 32
Table 7 – Data point breakdown 33
Table 8 – Semantic data points 36
Table 9 – Normalized data points 36
Table 10 – The "unit-word" is a compact way to store base SI unit exponents 38
Table 11 – Basic data types of a physical quantity 42
Table A.1 – List of unit-word value examples 49
Table A.2 – Examples on different representations of the physical quantity 0,000 1 m 53
Table B.1 – Subset of the sensor dictionary for energy (classification of sensor name, sensor measurement name, and unit) 54
Table B.2 – Sensor dictionary for energy mapped to IEC 61360 Common Data Dictionary 55
Table B.3 – Subset of the sensor dictionary for energy mapped with ETSI SmartM2M SAREF-Core and its extensions (SAREF4BLDG, SAREF4ENER) 57