

# ISO/IEC 18810:2001-02 (E)

## Information technology\_ - 8 mm wide magnetic tape cartridge for information interchange\_ - Helical scan recording AIT-2 with MIC format

---

### Contents

<b>Section 1 – General</b>	<b>1</b>
1 Scope	1
2 Conformance	1
2.1 Magnetic tape cartridge	1
2.2 Generating drive	1
2.3 Receiving drive	1
3 Normative references	2
4 Definitions	2
4.1 Absolute Frame Number (AFN)	2
4.2 a.c. erase	2
4.3 Access	2
4.4 algorithm	2
4.5 Area ID	2
4.6 Automatic Track Finding (ATF)	2
4.7 Average Signal Amplitude	2
4.8 azimuth	2
4.9 back surface	2
4.10 byte	2
4.11 cartridge	2
4.12 Channel bit	2
4.13 Codeword	2
4.14 Early Warning Point (EWP)	2
4.15 End of Data (EOD)	2
4.16 Entity	2
4.17 Error Correcting Code (ECC)	2
4.18 flux transition position	2
4.19 flux transition spacing	2
4.20 Frame	3
4.21 Housekeeping Frame	3
4.22 Logical Beginning of Tape (LBOT)	3
4.23 magnetic tape	3
4.24 Master Standard Amplitude Calibration Tape	3
4.25 Master Standard Reference Tape	3
4.26 Memory In Cartridge (MIC)	3
4.27 Partition Boundary	3
4.28 Physical Beginning of Tape (PBOT)	3
4.29 Physical End of Tape (PEOT)	3
4.30 physical recording density	3
4.31 pre-recording condition	3
4.32 processing	3
4.33 processed data	3
4.34 Processed Record	3
4.35 record	3
4.36 Reference Field	3
4.37 Secondary Standard Amplitude Calibration Tape	3
4.38 Secondary Standard Reference Tape	3
4.39 Separator Mark	4

4.40	Standard Reference Amplitude (SRA)	4
4.41	Tape Reference Edge	4
4.42	Typical Field	4
4.43	Standard Reference Current	4
4.44	Test Recording Current	4
4.45	track	4
4.46	unprocessed data	4
4.47	Unprocessed Record	4
5	Conventions and Notations	4
5.1	Representation of numbers	4
5.2	Names	4
6	Acronyms	4
7	Environment and safety	5
7.1	Test environment	5
7.2	Operating environment	5
7.3	Storage environment	5
7.4	Transportation	5
7.5	Safety	5
7.6	Flammability	5
<b>Section 2 - Requirements for the case</b>		<b>6</b>
8	Dimensional and mechanical characteristics of the case	6
8.1	General	6
8.2	Overall dimension	6
8.3	Holding areas	7
8.4	Cartridge insertion	7
8.5	Window	8
8.6	Loading grips	8
8.7	Label areas	8
8.8	Datum areas and Datum holes	8
8.9	Support areas	9
8.10	Recognition holes	10
8.11	Write-inhibit hole	10
8.12	Pre-positioning surfaces	11
8.13	Cartridge lid	11
8.14	Cartridge reel lock	13
8.15	Reel access holes	13
8.16	Interface between the reels and the drive spindles	14
8.17	Light path	15
8.18	Position of the tape in the case	15
8.19	Tape path zone	16
8.20	Tape access cavity	16
8.21	Tape access cavity clearance	16
8.22	Requirements for the MIC	16
8.23	Recognition recesses	18
<b>Section 3 - Requirements for the unrecorded tape</b>		<b>38</b>
9	Mechanical, physical and dimensional characteristics of the tape	38
9.1	Materials	38
9.2	Tape length	38
9.2.1	Length of magnetic tape	38
9.2.2	Length of leader and trailer tapes	38
9.2.3	Length of the splicing tapes	38
9.3	Tape width	38
9.3.1	Width of magnetic, leader and trailer tapes	38

9.3.2	Width and position of the splicing tape	38
9.4	Discontinuities	39
9.5	Tape thickness	39
9.5.1	Thickness of the magnetic tape	39
9.5.2	Thickness of the leader and trailer tape	39
9.5.3	Thickness of the splicing tape	39
9.6	Longitudinal curvature	39
9.7	Cupping	39
9.8	Coating adhesion	39
9.9	Layer-to-layer adhesion	40
9.10	Tensile strength	40
9.10.1	Breaking strength	40
9.10.2	Yield strength	40
9.11	Residual elongation	40
9.12	Electrical resistance of the recording surface	40
9.13	Tape winding	41
9.14	Light transmittance of the tape	41
9.15	Recognition stripe	41
10	Magnetic recording characteristics	42
10.1	Typical Field	42
10.2	Signal Amplitude	42
10.3	Resolution	42
10.4	Overwrite	42
10.5	Ease of erasure	43
10.6	Tape quality	43
10.6.1	Missing pulses	43
10.6.2	Missing pulse zone	43
10.7	Signal-to-Noise Ratio (SNR) characteristic	43
<b>Section 4 - Requirements for an interchanged tape</b>		<b>44</b>
11	Format	44
11.1	General	44
11.2	Basic Groups	44
11.2.1	Entity	45
11.2.2	Group Information Table	45
11.2.3	Block Access Table (BAT)	47
11.3	Sub-Groups	50
11.3.1	G1 Sub-Group	50
11.3.2	G2 Sub-Group - Randomizing	51
11.3.3	G3 Sub-Group	52
11.4	Data Block	52
11.4.1	ID information	53
11.4.2	Recording of the ID Information in the Data Block Headers	55
12	Method of recording	61
12.1	Physical recording density	62
12.2	Long-term average bit cell length	62
12.3	Short-term average bit cell length	62
12.4	Rate of change	62
12.5	Bit shift	62
12.6	Read signal amplitude	62
12.7	Maximum recorded levels	62

<b>13</b>	Track geometry	<b>62</b>
<b>13.1</b>	Track configuration	<b>62</b>
<b>13.2</b>	Average track pitch	<b>63</b>
<b>13.3</b>	Variations of the track pitch	<b>63</b>
<b>13.4</b>	Track width	<b>63</b>
<b>13.5</b>	Track angle	<b>63</b>
<b>13.6</b>	Track edge straightness	<b>63</b>
<b>13.7</b>	Track length	<b>63</b>
<b>13.8</b>	Azimuth angles	<b>63</b>
<b>14</b>	Recorded patterns	<b>64</b>
<b>14.1</b>	Recorded Data Block	<b>64</b>
<b>14.2</b>	Margin blocks	<b>64</b>
<b>15</b>	Format of a track	<b>64</b>
<b>15.1</b>	Track structure	<b>64</b>
<b>15.2</b>	Positioning accuracy	<b>65</b>
<b>15.3</b>	Tracking scheme	<b>66</b>
<b>16</b>	Layout of the tape	<b>66</b>
<b>16.1</b>	Device Area	<b>67</b>
<b>16.2</b>	Reference Area	<b>67</b>
<b>16.3</b>	Position Tolerance Band No. 1	<b>68</b>
<b>16.4</b>	System Area	<b>68</b>
<b>16.4.1</b>	System Preamble	<b>68</b>
<b>16.4.2</b>	System Log	<b>68</b>
<b>16.4.3</b>	System Postamble	<b>72</b>
<b>16.4.4</b>	Position Tolerance Band No. 2	<b>72</b>
<b>16.4.5</b>	Vendor Group Preamble	<b>72</b>
<b>16.5</b>	Data Area	<b>72</b>
<b>16.5.1</b>	Vendor Group	<b>72</b>
<b>16.5.2</b>	Recorded Data Group	<b>72</b>
<b>16.5.3</b>	ECC3	<b>72</b>
<b>16.5.4</b>	Multiple Recorded Instances	<b>73</b>
<b>16.5.5</b>	Repeated Frames	<b>73</b>
<b>16.5.6</b>	Appending and overwriting	<b>74</b>
<b>16.6</b>	EOD Area	<b>75</b>
<b>16.7</b>	Optional Device Area	<b>75</b>
<b>16.8</b>	Logical End Of Tape (LEOT)	<b>76</b>
<b>16.9</b>	Logical Beginning of Tape (LBOT)	<b>76</b>
<b>16.10</b>	Early Warning Point - EWP	<b>76</b>
<b>16.11</b>	Empty Partition	<b>76</b>
<b>16.12</b>	Initialization	<b>76</b>
<b>17</b>	Housekeeping Frames	<b>77</b>
<b>17.1</b>	Amble Frames	<b>77</b>
<b>17.2</b>	System Amble Frames	<b>77</b>
<b>18</b>	Content of the MIC	<b>78</b>
<b>Annexes</b>		
<b>A</b>	- Measurement of light transmittance	<b>79</b>
<b>B</b>	- Measurement of Signal-to-Noise Ratio	<b>82</b>
<b>C</b>	- Method for determining the nominal and the maximum allowable recorded levels (pre-recording condition)	<b>83</b>
<b>D</b>	- Representation of 16-bit words by 20-Channel bits patterns	<b>84</b>
<b>E</b>	- Measurement of bit shift	<b>86</b>

<b>F</b> - Method of measuring the straightness of track edges	<b>88</b>
<b>G</b> - ECC calculation	<b>89</b>
<b>H</b> - Recommendations for transportation	<b>92</b>
<b>J</b> - Read-After-Write	<b>93</b>
<b>K</b> - Example of the content of a Basic Group No. 0	<b>94</b>
<b>L</b> - Examples of chip	<b>95</b>