

ISO/IEC TR 14475:2001-07 (E)

Information technology_ - Telecommunications and information exchange between systems_ - Private Integrated Service Network_ - Architecture and scenarios for Private Integrated Services Networking

Contents		Page
1	Scope	1
2	References	1
3	Terms and definitions	1
3.1	External Definitions	2
3.2	Special Definitions	2
4	Symbols and Abbreviations	4
5	Introduction	5
5.1	PINX Reference Configuration	5
5.2	Additional Descriptions	6
5.2.1	Inter-PINX Connection (IPC)	6
5.2.2	Inter-PINX Link (IPL)	6
5.2.3	Relationship between IPLs and IPCs	7
6	Details of the Functional Groupings as Relevant for Scenario Handling	7
6.1	Mapping Unit (MP)	7
6.1.1	Physical Adaptation	8
6.1.2	Mapping Matrix	8
6.2	Inter-PINX Connection Control (ICC)	9
6.2.1	IPC Control	9
6.2.2	IPL Control	9
6.3	Scenario Management	9
6.3.1	Link Resource Management	10
6.3.2	Mapping Management	10
6.3.3	IPC Management	10
6.4	Complete PINX Model	10
7	Configuration Variants	11
7.1	PINX with Multiple IPLs	11
7.2	More than One Type of IVN	12
7.3	Different Spread of IPCs among the Interfaces at the Two PINXs	12
8	IPL Establishment and administration procedures	13
8.1	IPL Establishment using ScenSIG	13
8.1.1	Static Pre-Conditions	14
8.1.2	Establishment of a First IPC	14
8.1.3	IPL Initialisation Process	14

8.1.4	Establishment of the D _Q -Channel	15
8.1.5	Establishment of U _Q -Channels	15
8.1.6	Channel Mapping	15
8.2	IPL Establishment Procedures without using ScenSIG	16
8.3	IPL Administration Procedures	16
9	Items for Future Standardisation	16
9.1	Mapping Function	17
9.1.1	Physical Adoption	17
9.1.2	Mapping Matrix	17
9.1.3	Static Pre-Conditions	17
9.2	ScenSIG	17
9.2.1	IPL Establishment and Administration Procedures	17
9.2.2	Bearer Modification Procedures	18
9.3	Bearer Conditioning	18
10	Scenarios	18
10.1	Scenarios: Dedicated Transmission Systems	18
10.1.1	Scenario 1.1 - Unstructured Transmission Link	18
10.1.2	Scenario 1.2 - Structured Transmission Link	19
10.2	Scenarios: Semi-Permanent IVN Connections	19
10.2.1	Scenario 2.1 - Semi-permanent Circuit Switched	19
10.2.2	Scenario 2.2 - Permanent Virtual Call	20
10.3	Scenarios: On-Demand Public Network Connections	21
10.3.1	Scenario 3.1 - On-demand Circuit Switched	21
10.3.2	Scenario 3.2 - ISDN Call with User-to-User Signalling	21
10.3.3	Scenario 3.3 - On Demand Virtual Call	22
10.4	Scenarios: Virtual Private Network	23
10.4.1	Introduction	23
10.4.2	Access Arrangements	23
10.4.3	Scenario 4.1 -Transit PINX	26
10.4.2	Scenario 4.2 -Centrex	26
10.4.3	Scenario 4.3 -Gateway to another network	27
Annexes		
A - Attribute Values		28
B - Scenario 4.4 - Relay Node		30