

# ISO/IEC 21411:2001-08 (E)

## Information technology\_ - Telecommunications and information exchange between systems\_ - Corporate telecommunication networks; Signalling interworking between QSIG and H.323; Call diversion supplementary services

---

### Contents

Foreword	v
Introduction	vi
<b>1</b> Scope	<b>1</b>
<b>2</b> Conformance	<b>1</b>
<b>3</b> Normative references	<b>1</b>
<b>4</b> Definitions	<b>2</b>
<b>4.1</b> External definitions	<b>2</b>
<b>4.2</b> Other definitions	<b>2</b>
<b>4.2.1</b> Association D	<b>2</b>
<b>4.2.2</b> Association E	<b>2</b>
<b>4.2.3</b> Association F	<b>2</b>
<b>4.2.4</b> Association G	<b>2</b>
<b>4.2.5</b> Entity A	<b>2</b>
<b>4.2.6</b> Entity B	<b>2</b>
<b>4.2.7</b> Entity B'	<b>2</b>
<b>4.2.8</b> Entity C	<b>2</b>
<b>4.2.9</b> Entity D	<b>2</b>
<b>4.2.10</b> Entity E	<b>3</b>
<b>4.2.11</b> Entity F	<b>3</b>
<b>4.2.12</b> Entity G	<b>3</b>
<b>4.2.13</b> Entity H	<b>3</b>
<b>4.2.14</b> Gateway	<b>3</b>
<b>4.2.15</b> Leg A	<b>3</b>
<b>4.2.16</b> Leg B	<b>3</b>
<b>4.2.17</b> Leg B'	<b>3</b>
<b>4.2.18</b> Leg C	<b>3</b>
<b>4.2.19</b> Rerouting entity	<b>3</b>
<b>4.2.20</b> Scenario A1	<b>3</b>
<b>4.2.21</b> Scenario A2	<b>3</b>
<b>4.2.22</b> Scenario B1	<b>3</b>
<b>4.2.23</b> Scenario B2	<b>3</b>
<b>4.2.24</b> Scenario C1	<b>3</b>
<b>4.2.25</b> Scenario C2	<b>3</b>
<b>4.2.26</b> Scenario D1	<b>3</b>
<b>4.2.27</b> Scenario D2	<b>3</b>
<b>4.2.28</b> Scenario E1	<b>3</b>
<b>4.2.29</b> Scenario E2	<b>3</b>
<b>4.2.30</b> Scenario F1	<b>3</b>
<b>4.2.31</b> Scenario F2	<b>3</b>
<b>4.2.32</b> Scenario G1	<b>3</b>
<b>4.2.33</b> Scenario G2	<b>3</b>
<b>5</b> Acronyms	<b>4</b>
<b>6</b> Service architecture	<b>4</b>
<b>6.1</b> Service architecture for invocation and operation	<b>4</b>
<b>6.1.1</b> ISO/IEC 13873 service architecture	<b>4</b>

<b>6.1.2</b>	H.450.3 service architecture	<b>5</b>
<b>6.1.3</b>	Scenarios for interworking	<b>5</b>
<b>6.1.4</b>	Determination of the location of the rerouting entity when interworking	<b>6</b>
<b>6.2</b>	Service architecture for activation, deactivation and interrogation	<b>6</b>
<b>6.2.1</b>	ISO/IEC 13873 service architecture	<b>6</b>
<b>6.2.2</b>	H.450.3 service architecture	<b>7</b>
<b>6.2.3</b>	Scenarios for interworking	<b>7</b>
<b>7</b>	Protocol interworking – General requirements	<b>8</b>
<b>8</b>	Protocol interworking – Messages and APDUs	<b>8</b>
<b>8.1</b>	Scenario A1	<b>8</b>
<b>8.2</b>	Scenario A2	<b>10</b>
<b>8.3</b>	Scenario B1	<b>11</b>
<b>8.4</b>	Scenario B2	<b>12</b>
<b>8.5</b>	Scenario C1	<b>12</b>
<b>8.6</b>	Scenario C2	<b>13</b>
<b>8.7</b>	Scenario D1	<b>13</b>
<b>8.8</b>	Scenario D2	<b>14</b>
<b>8.9</b>	Scenario E1	<b>14</b>
<b>8.10</b>	Scenario E2	<b>15</b>
<b>8.11</b>	Scenario F1	<b>15</b>
<b>8.12</b>	Scenario F2	<b>16</b>
<b>8.13</b>	Scenario G1	<b>16</b>
<b>8.14</b>	Scenario G2	<b>17</b>
 <b>Annexes</b>		
<b>A</b>	Implementation Conformance Statement (ICS) proforma	<b>18</b>
<b>B</b>	Example message sequence diagrams	<b>28</b>