

ISO/IEC 21411:2001-08 (E)

Information technology_ - Telecommunications and information exchange between systems_ - Corporate telecommunication networks; Signalling interworking between QSIG and H.323; Call diversion supplementary services

Contents

Foreword	v
Introduction	vi
1 Scope	1
2 Conformance	1
3 Normative references	1
4 Definitions	2
4.1 External definitions	2
4.2 Other definitions	2
4.2.1 Association D	2
4.2.2 Association E	2
4.2.3 Association F	2
4.2.4 Association G	2
4.2.5 Entity A	2
4.2.6 Entity B	2
4.2.7 Entity B'	2
4.2.8 Entity C	2
4.2.9 Entity D	2
4.2.10 Entity E	3
4.2.11 Entity F	3
4.2.12 Entity G	3
4.2.13 Entity H	3
4.2.14 Gateway	3
4.2.15 Leg A	3
4.2.16 Leg B	3
4.2.17 Leg B'	3
4.2.18 Leg C	3
4.2.19 Rerouting entity	3
4.2.20 Scenario A1	3
4.2.21 Scenario A2	3
4.2.22 Scenario B1	3
4.2.23 Scenario B2	3
4.2.24 Scenario C1	3
4.2.25 Scenario C2	3
4.2.26 Scenario D1	3
4.2.27 Scenario D2	3
4.2.28 Scenario E1	3
4.2.29 Scenario E2	3
4.2.30 Scenario F1	3
4.2.31 Scenario F2	3
4.2.32 Scenario G1	3
4.2.33 Scenario G2	3
5 Acronyms	4
6 Service architecture	4
6.1 Service architecture for invocation and operation	4
6.1.1 ISO/IEC 13873 service architecture	4

6.1.2	H.450.3 service architecture	5
6.1.3	Scenarios for interworking	5
6.1.4	Determination of the location of the rerouting entity when interworking	6
6.2	Service architecture for activation, deactivation and interrogation	6
6.2.1	ISO/IEC 13873 service architecture	6
6.2.2	H.450.3 service architecture	7
6.2.3	Scenarios for interworking	7
7	Protocol interworking – General requirements	8
8	Protocol interworking – Messages and APDUs	8
8.1	Scenario A1	8
8.2	Scenario A2	10
8.3	Scenario B1	11
8.4	Scenario B2	12
8.5	Scenario C1	12
8.6	Scenario C2	13
8.7	Scenario D1	13
8.8	Scenario D2	14
8.9	Scenario E1	14
8.10	Scenario E2	15
8.11	Scenario F1	15
8.12	Scenario F2	16
8.13	Scenario G1	16
8.14	Scenario G2	17
Annexes		
A	Implementation Conformance Statement (ICS) proforma	18
B	Example message sequence diagrams	28