

ISO/IEC 20061:2001-12 (E)

Information technology_ - 12,65_mm wide magnetic tape cassette for information interchange_ - Helical scan recording; DTF-2

Contents		Page
Section 1 - General		1
1	Scope	1
2	Conformance	1
2.1	Magnetic tape cassette	1
2.2	Generating system	1
2.3	Receiving system	1
3	Normative references	1
4	Terms and definitions	2
4.1	Absolute block number	2
4.2	a.c. erase	2
4.3	algorithm	2
4.4	Append file	2
4.5	Append volume	2
4.6	Average Signal Amplitude (ASA)	2
4.7	azimuth	2
4.8	back surface	2
4.9	bit cell	2
4.10	block	2
4.11	Block Management Table (BMT)	2
4.12	byte	2
4.13	cassette	2
4.14	compressed data	2
4.15	Control Track	2
4.16	flux transition position	2
4.17	flux transition spacing	2
4.18	Logical track set ID	2
4.19	Logical volume	2
4.20	magnetic tape	2
4.21	Master Standard Reference Tape (MSRT)	2
4.22	physical recording density	2
4.23	Reference Field (RF)	2
4.24	Secondary Standard Reference Tape (SSRT)	2
4.25	Standard Reference Amplitude (SRA)	3
4.26	Standard Reference Current (Ir)	3
4.27	Tape Reference Edge	3
4.28	Test Recording Current (TRC)	3
4.29	track	3
4.30	track angle	3
4.31	Track Set	3
4.32	Typical Field (TF)	3
4.33	word	3
5	Conventions and notations	3
5.1	Representation of numbers	3
5.2	Names	3
6	Acronyms	4
7	Environment and safety	4

7.1	Testing environment	4
7.2	Operating environment	4
7.3	Storage environment	5
7.4	Transportation	5
7.5	Safety	5
7.6	Flammability	5
Section 2 - Requirements for the case		5
8	Dimensional and mechanical characteristics of the case	5
8.1	General	5
8.2	Type S cassette	5
8.2.1	Overall dimensions (Figure 3)	6
8.2.2	Holding areas (Figure 4)	6
8.2.3	Window	6
8.2.4	Label areas (Figure 4)	7
8.2.5	Datum areas and datum holes (Figures 5 and 6)	7
8.2.6	Support areas (Figure 5)	7
8.2.7	Guiding grooves (Figures 3 and 6)	8
8.2.8	Recognition holes (Figures 6 and 7)	9
8.2.9	Write-inhibit plug (Figure 8)	10
8.2.10	Pre-positioning surface (Figures 3 and 5)	11
8.2.11	Cassette lid (Figures 9, 10, 11, 12 and 13)	11
8.2.12	Cassette reel lock (Figure 13)	12
8.2.13	Reel access holes (Figure 6)	13
8.2.14	Reels (Figure 14)	13
8.2.15	Position of the tape in the case (Figure 16)	14
8.2.16	Tape path zone (Figures 16 to 18)	14
8.2.17	Tape access cavity (Figure 19)	15
8.3	Type L cassette	30
8.3.1	Overall dimensions (Figure 22)	30
8.3.2	Holding areas (Figure 23)	30
8.3.3	Window	31
8.3.4	Label areas (Figure 23)	31
8.3.5	Datum areas and datum holes (Figures 24 and 25)	31
8.3.6	Support areas (Figure 24)	32
8.3.7	Guiding grooves (Figure 25)	32
8.3.8	Recognition holes (Figure 26)	33
8.3.9	Write-inhibit plug (Figure 27)	34
8.3.10	Pre-positioning surface (Figures 24 and 25)	35
8.3.11	Cassette lid (Figures 28, 29, 30, 31 and 32)	35
8.3.12	Cassette reel lock (Figure 32)	36
8.3.13	Reel access holes (Figure 25)	36
8.3.14	Reels (Figure 33)	37
8.3.15	Position of the tape in the case (Figure 35)	38
8.3.16	Tape path zone (Figures 35 to 37)	38
8.3.17	Tape access cavity (Figure 38)	39
8.3.18	Cavity for compatibility with Type S cassette (Figure 39)	40
Section 3 - Requirements for the unrecorded tape		55
9	Mechanical, physical and dimensional characteristics of the tape	55
9.1	Materials	55
9.2	Tape length	55
9.3	Tape width	55
9.4	Width and position of splicing tape	55
9.5	Discontinuity	55
9.6	Tape thickness	55
9.7	Longitudinal curvature	55
9.8	Out-of-plane distortions	56

9.9	Coating adhesion	56
9.10	Layer-to-layer adhesion	57
9.11	Tensile strength	57
9.11.1	Breaking strength	57
9.11.2	Yield strength	57
9.11.3	Strength of splice	57
9.12	Residual elongation	57
9.13	Electrical resistance of the coated surfaces	57
9.14	Tape wind	58
10	Magnetic recording characteristics	58
10.1	Typical Field (TF1)	58
10.2	Average Signal Amplitude(ASA)	59
10.3	Resolution	59
10.4	Signal-to-noise ratio (S/N)	59
10.5	Ease of erasure	59
10.6	Tape quality	59
10.6.1	Missing pulses	59
10.6.2	Missing pulse zone	59
10.7	Inhibitor tape	59
11	Format for helical tracks	60
11.1	General description of the write data path (see Figure 42)	60
11.2	Formation of a Logical Track Set	60
11.2.1	Types of information track sets	60
11.2.2	Generation of a Logical Track Set	62
11.2.3	Subcode data field	62
11.2.4	Block Management Table (BMT)	66
11.2.5	Data and information field definitions	66
11.3	Track Set information	70
11.3.1	Loading the Product Code Arrays	70
11.4	Product code array processing	72
11.4.1	Error correction method	72
11.4.2	Error correction coding for C1 Parity	72
11.5	Track assignments	73
11.5.1	Segments/Sectors (Figure 46)	73
11.5.2	Sync Blocks (Figure 47)	74
11.5.3	Track interleave (Figure 48)	74
11.5.4	Byte interleave across Sync Blocks (Figure 49)	77
11.5.5	Randomization	77
11.6	Formation of the contents of a helical track (Figure 50)	78
11.6.1	Segment/Sector details (Figure 47)	78
11.6.2	Channel bit coding	79
11.6.3	Interleaved-NRZ1 (Figure 51)	79
11.6.4	Tracking Pilot Signals (TPS)	79
12	Track geometry	79
12.1	General	79
12.2	Helically recorded tracks	80
12.2.1	Location of the tracks	80
12.2.2	Track width	81
12.2.3	Track angle	81
12.2.4	Track pitch	81
12.2.5	Location of elements in the helical track	82

12.2.6	Location of the Data Area Reference Point	82
12.2.7	Straightness of tracks	82
12.2.8	Azimuth angles	82
12.2.9	Tracking Pilot Signals (TPS)	82
12.2.10	Amplitude of servo signals	82
12.3	Longitudinal tracks geometry	82
12.3.1	Control Track	82
12.3.2	Time Code Track signals recording position	83
13	Method of recording helical tracks	83
13.1	Physical recording density	83
13.2	Record current optimization	83
13.3	Efficiency of erasure	83
14	Method of recording longitudinal tracks	83
14.1	Overview	83
14.2	Control Track	83
14.2.1	Signal	83
14.2.2	Polarity of magnetisation (Figure 54)	83
14.2.3	Alignment	83
14.2.4	Read signal amplitude	84
14.2.5	Quality of the Control Track	84
14.3	Time Code Track	84
14.3.1	Method of recording the Time Code Track	84
14.3.2	Physical recording density	84
14.3.3	Bit shift	84
14.3.4	Read signal amplitude	84
14.3.5	Quality of the Time Code Track	85
14.4	Format for the Time Code Track	85
14.4.1	Count bits	85
14.4.2	Phase bit	85
14.4.3	Synchronizing pattern	85
14.4.4	Supplemental Data	85
14.4.5	Extent of Time Code	85
Section 5 - Requirements for recorded information		85
15	Recorded information	85
15.1	Recording area (Figure 55)	85
15.2	Magnetic tape layout (Figure 56)	85
15.2.1	Valid data areas	85
15.2.2	Invalid data areas	86
15.3	Physical TSID	86
15.3.1	Structure surrounding the VSIT area	88
15.3.2	Structure of the DIT area	88
15.3.3	Structure of the User Data Area	89
Section 6 - Write operations		89
16	Write retry sequence (Figure 58)	89
17	Append file operation (Figure 59)	90
17.1	Append volume	90
17.2	Append write (Figure 60)	90
17.3	Overwrite (Figure 61)	91

17.4	File extension (Figure 62)	92
Annexes		
A	- Measurement of Signal-to-Noise Ratio	94
B	- Representation 8/9 coding patterns	95
C	- Recommendations for transportation	99
D	- Inhibitor tape	100