

ISO/IEC 16448 :2002-04 (E)

Information technology_ - 120_mm DVD_ - Read-only disk

Contents

Section 1 - General	1
1 Scope	1
2 Conformance	1
2.1 Optical Disk	1
2.2 Generating system	1
2.3 Receiving system	1
3 Normative reference	1
4 Terms and definitions	1
4.1 Adhesive layer	2
4.2 Channel bit	2
4.3 Clamping Zone	2
4.4 Digital Sum Value (DSV)	2
4.5 Disk Reference Plane	2
4.6 Dual Layer disk	2
4.7 Dummy substrate	2
4.8 Entrance surface	2
4.9 Optical disk	2
4.10 Physical sector number	2
4.11 Read-only disk	2
4.12 Recorded layer	2
4.13 Reed-Solomon code	2
4.14 Reserved field	2
4.15 Sector	2
4.16 Single Layer disk	2
4.17 Spacer	2
4.18 Substrate	2
4.19 Track	3
4.20 Track pitch	3
4.21 Zone	3
5 Conventions and notations	3
5.1 Representation of numbers	3
5.2 Names	3
6 List of acronyms	3
7 General description of the disk	4
8 General requirements	5
8.1 Environments	5
8.1.1 Test environment	5
8.1.2 Operating environment	6
8.1.3 Storage environment	6
8.1.4 Transportation	6
8.2 Safety requirements	6
8.3 Flammability	6

9	Reference measurement devices	6
9.1	Pick Up Head (PUH)	6
9.2	Measurement conditions	7
9.3	Normalized servo transfer function	8
9.4	Reference Servo for axial tracking	8
9.5	Reference Servo for radial tracking	9
Section 2 - Dimensional, mechanical and physical characteristics of the disk		10
10	Dimensional characteristics	10
10.1	Overall dimensions	10
10.2	First transition area	10
10.3	Second transition area	10
10.4	Clamping Zone	10
10.5	Third transition area	11
10.6	Information Zone	11
10.6.1	Sub-divisions of the Information Zone	11
10.6.2	Track geometry	12
10.6.3	Track modes	12
10.6.4	Channel bit length	12
10.7	Rim area	12
10.8	Remark on tolerances	13
10.9	Runout	13
10.9.1	Axial runout	13
10.9.2	Radial runout	13
10.10	Label	13
11	Mechanical parameters	14
11.1	Mass	14
11.2	Moment of inertia	14
11.3	Dynamic imbalance	14
11.4	Sense of rotation	14
12	Optical parameters	14
12.1	Index of refraction	14
12.2	Thickness of the transparent substrate	14
12.3	Thickness of the spacer of Types C and D	14
12.4	Angular deviation	14
12.5	Birefringence of the transparent substrate	14
12.6	Reflectivity	14
Section 3 - Operational Signals		18
13	High frequency signals (HF)	18
13.1	Modulated amplitude	18
13.2	Signal asymmetry	19
13.3	Cross-track signal	19
13.4	Quality of signals	19
13.4.1	Jitter	19
13.4.2	Random errors	19
13.4.3	Defects	19
14	Servo signals	19
14.1	Differential phase tracking error signal	19
14.2	Tangential push-pull signal	20

Section 4 - Data Format	22
15 General	22
16 Data Frames	22
16.1 Identification Data (ID)	22
16.2 ID Error Detection Code (IED)	23
16.3 Copyright Management Information (CPR_MAI)	24
16.4 Error Detection Code (EDC)	24
17 Scrambled Frames	24
18 ECC Blocks	25
19 Recording Frames	26
20 Modulation	27
21 Physical Sectors	27
22 Suppress control of the d.c. component	29
Section 5 - Format of the Information Zone(s)	30
23 General description of an Information Zone	30
24 Layout of the Information Zone	30
25 Physical Sector numbering	30
26 Lead-in Zone	32
26.1 Initial Zone	33
26.2 Reference Code Zone	33
26.3 Buffer Zone 1	33
26.4 Buffer Zone 2	33
26.5 Control Data Zone	33
26.5.1 Physical format information	34
26.5.2 Disk manufacturing information	35
26.5.3 Content provider information	36
27 Middle Zone	36
28 Lead-out Zone	36
Annexes	
A (normative) - Measurement of the angular deviation α	37
B (normative) - Measurement of birefringence	39
C (normative) - Measurement of the differential phase tracking error	41
D (normative) - Measurement of light reflectance	45
E (normative) - Tapered cone for disk clamping	47
F (normative) - Measurement of jitter	48
G (normative) - 8-to-16 Modulation with RLL (2,10) requirements	51
H (normative) - Burst Cutting Area (BCA)	61
J (normative) - Source Identification Code (SID)	66
K (informative) - Measurement of the thickness of the spacer of Dual Layer disks	69
L (informative) - Note on the Reference Code	71
M (informative) - Maximum transfer rate	72
N (informative) - Disk bonding	73
P (informative) - Transportation	75