

# ISO/IEC 11801:2002-09 (E)

## Information technology\_ - Generic cabling for customer premises

---

### CONTENTS

- FOREWORD ..... 10
- INTRODUCTION ..... 11
- 1 Scope ..... 13
- 2 Normative references..... 13
- 3 Definitions, abbreviations and symbols ..... 17
  - 3.1 Definitions ..... 17
  - 3.2 Abbreviations..... 23
  - 3.3 Symbols ..... 24
    - 3.3.1 Variables ..... 24
    - 3.3.2 Indices ..... 25
- 4 Conformance ..... 25
- 5 Structure of the generic cabling system ..... 26
  - 5.1 General ..... 26
  - 5.2 Functional elements..... 26
  - 5.3 Cabling subsystems..... 27
    - 5.3.1 General..... 27
    - 5.3.2 Campus backbone cabling subsystem..... 27
    - 5.3.3 Building backbone cabling subsystem ..... 28
    - 5.3.4 Horizontal cabling subsystem..... 28
    - 5.3.5 Design objectives..... 28
  - 5.4 Interconnection of subsystems..... 29
    - 5.4.1 General..... 29
    - 5.4.2 Centralised cabling architecture ..... 30
  - 5.5 Accommodation of functional elements ..... 30
  - 5.6 Interfaces ..... 30
    - 5.6.1 Equipment interfaces and test interfaces..... 30
    - 5.6.2 Channel and permanent link ..... 32
    - 5.6.3 External network interface..... 32
  - 5.7 Dimensioning and configuring..... 32
    - 5.7.1 Distributors ..... 32
    - 5.7.2 Cables ..... 34
    - 5.7.3 Work area cords and equipment cords ..... 34
    - 5.7.4 Patch cords and jumpers ..... 34
    - 5.7.5 Telecommunications outlet (TO) ..... 35
    - 5.7.6 Consolidation point ..... 36
    - 5.7.7 Telecommunications rooms and equipment rooms ..... 36
    - 5.7.8 Building entrance facilities ..... 36
    - 5.7.9 External services cabling ..... 36
- 6 Performance of balanced cabling ..... 37
  - 6.1 General ..... 37
  - 6.2 Layout ..... 38
  - 6.3 Classification of balanced cabling ..... 39
  - 6.4 Balanced cabling performance..... 39
    - 6.4.1 General..... 39

6.4.2	Return loss .....	39
6.4.3	Insertion loss/attenuation .....	40
6.4.4	NEXT .....	41
6.4.5	Attenuation to crosstalk ratio (ACR) .....	44
6.4.6	ELFEXT .....	45
6.4.7	Direct current (d.c.) loop resistance .....	47
6.4.8	Direct current (d.c.) resistance unbalance .....	48
6.4.9	Current carrying capacity .....	48
6.4.10	Operating voltage .....	48
6.4.11	Power capacity .....	48
6.4.12	Propagation delay .....	48
6.4.13	Delay skew .....	49
6.4.14	Unbalance attenuation .....	49
6.4.15	Coupling attenuation .....	50
7	Reference implementations for balanced cabling .....	50
7.1	General .....	50
7.2	Balanced cabling .....	50
7.2.1	General.....	50
7.2.2	Horizontal cabling .....	50
7.2.3	Backbone cabling.....	54
8	Performance of optical fibre cabling .....	55
8.1	General .....	55
8.2	Component choice .....	55
8.3	Channel attenuation.....	56
8.4	Channel topology.....	56
8.5	Propagation delay.....	58
9	Cable requirements.....	58
9.1	General .....	58
9.2	Balanced cables .....	58
9.2.1	Basic performance requirements.....	58
9.2.2	Additional requirements .....	59
9.2.3	Additional performance requirements for flexible cables.....	60
9.3	Additional crosstalk considerations for cable sharing in balanced cables .....	60
9.3.1	General.....	60
9.3.2	Power summation in backbone cables.....	60
9.3.3	Hybrid, multi-unit and cables connected to more than one TO.....	60
9.4	Optical fibre cables .....	61
9.4.1	Optical fibre types .....	61
9.4.2	Generic performance requirements .....	61
9.4.3	Multimode optical fibre cable.....	61
9.4.4	Single-mode optical fibre cables .....	62
10	Connecting hardware requirements.....	62
10.1	General requirements .....	62
10.1.1	Applicability .....	62
10.1.2	Location.....	63
10.1.3	Design .....	63
10.1.4	Operating environment.....	63
10.1.5	Mounting.....	63

10.1.6	Installation practices .....	63
10.1.7	Marking and colour coding .....	64
10.2	Connecting hardware for balanced cabling .....	64
10.2.1	General requirements .....	64
10.2.2	Performance marking .....	64
10.2.3	Mechanical characteristics .....	64
10.2.4	Electrical characteristics .....	66
10.2.5	Telecommunications outlet requirements .....	72
10.2.6	Design considerations for installation .....	73
10.3	Optical fibre connecting hardware .....	74
10.3.1	General requirements .....	74
10.3.2	Marking and colour coding .....	74
10.3.3	Mechanical and optical characteristics .....	74
10.3.4	Telecommunications outlet requirements .....	75
10.3.5	Connection schemes for optical fibre cabling .....	75
11	Screening practices .....	77
11.1	General .....	77
11.2	Electromagnetic performance .....	77
11.3	Earthing .....	78
12	Administration .....	78
13	Balanced cords .....	78
13.1	Introduction .....	78
13.2	Insertion loss .....	78
13.3	Return loss .....	79
13.4	NEXT .....	79
Annex A (normative)	Balanced permanent link and CP link performance .....	82
A.1	General .....	82
A.2	Performance .....	82
A.2.1	General .....	82
A.2.2	Return loss .....	83
A.2.3	Insertion loss/attenuation .....	84
A.2.4	NEXT .....	85
A.2.5	Attenuation to crosstalk ratio (ACR) .....	88
A.2.6	ELFEXT .....	89
A.2.7	Direct current (d.c.) loop resistance .....	92
A.2.8	Direct current (d.c.) resistance unbalance .....	93
A.2.9	Propagation delay .....	93
A.2.10	Delay skew .....	94
Annex B (normative)	Test procedures .....	96
B.1	General .....	96
B.2	Channel and link performance testing .....	96
B.2.1	Testing balanced cabling channels, permanent links and CP links .....	96
B.2.2	Testing optical fibre cabling channels .....	96
B.2.3	Channel and link test schedules .....	96
B.3	Transmission testing of cords for balanced cabling .....	97
B.4	Transmission testing of components for cabling .....	98
B.4.1	Transmission testing of copper cables for balanced cabling .....	98

B.4.2	Transmission testing of connecting hardware for balanced cabling .....	98
B.4.3	Transmission testing of cables for optical cabling.....	98
B.4.4	Transmission testing of connectors for optical cabling.....	98
Annex C (normative)	Mechanical and environmental performance testing of connecting hardware for balanced cabling .....	99
C.1	Introduction.....	99
C.2	Test requirements.....	99
C.2.1	General.....	99
C.2.2	Initial test measurements .....	99
C.2.3	Environmental and mechanical performance .....	100
Annex D (informative)	Electromagnetic characteristics .....	104
Annex E (informative)	Acronyms for balanced cables .....	105
Annex F (informative)	Supported applications .....	107
F.1	Supported applications for balanced cabling .....	107
F.2	Supported applications for optical fibre cabling .....	109
Annex G (informative)	Channel and permanent link models for balanced cabling .....	113
G.1	General .....	113
G.2	Insertion loss .....	113
G.2.1	Insertion loss of the channel configuration .....	113
G.2.2	Insertion loss of the permanent link configurations.....	114
G.2.3	Assumptions for insertion loss .....	114
G.3	NEXT .....	115
G.3.1	NEXT of the channel configuration.....	115
G.3.2	NEXT of the permanent link configurations .....	115
G.3.3	Assumptions for NEXT .....	116
G.4	ELFEXT .....	119
G.4.1	ELFEXT of the channel configuration.....	119
G.4.2	ELFEXT for the permanent link configurations .....	119
G.4.3	Assumptions for ELFEXT .....	120
G.5	Return loss .....	120
G.5.1	Return loss of the channel and permanent link configurations .....	120
G.5.2	Assumptions for the return loss circuit analysis method .....	121
Annex H (informative)	Class F channel and permanent link with two connections.....	124
Annex I (informative)	Significant changes to balanced cabling requirements with respect to earlier editions of this International Standard.....	125
I.1	General .....	125
I.2	References .....	125
I.3	Structural elements.....	125
I.4	Product designation .....	125
I.5	Component requirements.....	125
I.6	Installed cabling requirements .....	126
Bibliography	.....	132

Figure 1 – Structure of generic cabling.....	27
Figure 2 – Hierarchical structure of generic cabling.....	29
Figure 3 – Structures for centralised generic cabling.....	29
Figure 4 – Accommodation of functional elements.....	30
Figure 5 – Interconnect models.....	31
Figure 6 – Cross-connect models.....	31
Figure 7 – Equipment and test interfaces.....	31
Figure 8 – Example of a generic cabling system with combined BD and FD.....	33
Figure 9 – Inter-relationship of functional elements in an installation with redundancy.....	34
Figure 10 – Channel, permanent link and CP link of a balanced cabling.....	37
Figure 11 – Example of a system showing the location of cabling interfaces and extent of associated channels.....	38
Figure 12 – Horizontal cabling models.....	52
Figure 13 – Backbone cabling model.....	54
Figure 14 – Combined backbone/horizontal channels.....	57
Figure 15 – Eight-position outlet pin and pair grouping assignments (front view of connector).....	73
Figure 16 – Duplex SC connectivity configuration.....	76
Figure 17 – Optical fibre patch cord.....	77
Figure A.1 – Link options.....	82
Figure E.1 – Cable naming schema.....	105
Figure E.2 – Cable types.....	106
Figure G.1 – Example of computation of NEXT with higher precision.....	116
Figure H.1 – Two connection channel and permanent link.....	124
Figure I.1 – Horizontal cabling model.....	127
Figure I.2 – Backbone cabling model.....	127

Table 1 – Maximum channel lengths .....	32
Table 2 – Return loss for channel.....	40
Table 3 – Informative return loss values for channel at key frequencies .....	40
Table 4 – Insertion loss for channel.....	41
Table 5 – Informative insertion loss values for channel at key frequencies .....	41
Table 6 – NEXT for channel .....	42
Table 7 – Informative NEXT values for channel at key frequencies.....	42
Table 8 – PS NEXT for channel.....	43
Table 9 – Informative PS NEXT values for channel at key frequencies .....	43
Table 10 – Informative ACR values for channel at key frequencies.....	44
Table 11 – Informative PS ACR values for channel at key frequencies .....	45
Table 12 – ELFEXT for channel.....	46
Table 13 – Informative ELFEXT values for channel at key frequencies .....	46
Table 14 – PS ELFEXT for channel .....	47
Table 15 – Informative PS ELFEXT values for channel at key frequencies .....	47
Table 16 – Direct current (d.c.) loop resistance for channel.....	47
Table 17 – Propagation delay for channel .....	48
Table 18 – Informative propagation delay values for channel at key frequencies .....	49
Table 19 – Delay skew for channel.....	49
Table 20 – Unbalance attenuation for channel.....	50
Table 21 – Horizontal link length equations .....	53
Table 22 – Backbone link length equations .....	55
Table 23 – Channel attenuation.....	56
Table 24 – Basic requirements of balanced cables .....	58
Table 25 – Mechanical characteristics of balanced cables.....	59
Table 26 – Optical fibre cable attenuation .....	61
Table 27 – Multimode optical fibre modal bandwidth.....	62
Table 28 – Mechanical characteristics of connecting hardware for use with balanced cabling .....	65
Table 29 – Electrical characteristics of telecommunications outlets intended for use with balanced cabling .....	67
Table 30 – Return loss .....	68
Table 31 – Insertion loss .....	68
Table 32 – Near end crosstalk (NEXT) .....	68
Table 33 – Power sum near end crosstalk (PS NEXT).....	69
Table 34 – Far end crosstalk (FEXT).....	69
Table 35 – Power sum far end crosstalk (PS FEXT .....	70
Table 36 – Input to output resistance .....	70
Table 37 – Input to output resistance unbalance .....	70
Table 38 – Current carrying capacity.....	71
Table 39 – Propagation delay.....	71
Table 40 – Delay skew .....	71

Table 41 – Transverse conversion loss (TCL) f.f.s.....	71
Table 42 – Transfer impedance (screened connectors only).....	72
Table 43 – Insulation resistance.....	72
Table 44 – Voltage proof.....	72
Table 45 – Matrix of backward compatible mated modular connector performance.....	73
Table 46 – Mechanical and optical characteristics of optical fibre connecting hardware.....	75
Table 47 – Minimum return loss for balanced cords.....	79
Table 48 – Informative values of return loss at key frequencies for Category 5, 6 and 7 cords.....	79
Table 49 – Informative values of NEXT at key frequencies for Category 5, 6 and 7 cords.....	81
Table A.1 – Return loss for permanent link or CP link.....	83
Table A.2 – Informative return loss values for permanent link with maximum implementation at key frequencies.....	83
Table A.3 – Insertion loss for permanent link or CP link.....	84
Table A.4 – Informative insertion loss values for permanent link with maximum implementation at key frequencies.....	85
Table A.5 – NEXT for permanent link or CP link.....	86
Table A.6 – Informative NEXT values for permanent link with maximum implementation at key frequencies.....	86
Table A.7 – PS NEXT for permanent link or CP link.....	87
Table A.8 – Informative PS NEXT values for permanent link with maximum implementation at key frequencies.....	88
Table A.9 – Informative ACR values for permanent link with maximum implementation at key frequencies.....	89
Table A.10 – Informative PS ACR values for permanent link with maximum implementation at key frequencies.....	89
Table A.11 – ELFEXT for permanent link or CP link.....	90
Table A.12 – Informative ELFEXT values for permanent link with maximum implementation at key frequencies.....	91
Table A.13 – PS ELFEXT for permanent link or CP link.....	92
Table A.14 – Informative PS ELFEXT values for permanent link with maximum implementation at key frequencies.....	92
Table A.15 – Direct current (d.c.) loop resistance for permanent link or CP link.....	93
Table A.16 – Informative d.c. loop resistance for permanent link with maximum implementation.....	93
Table A.17 – Propagation delay for permanent link or CP link.....	94
Table A.18 – Informative propagation delay values for permanent link with maximum implementation at key frequencies.....	94
Table A.19 – Delay skew for permanent link or CP link.....	95
Table A.20 – Informative delay skew for permanent link with maximum implementation.....	95
Table B.1 – Cabling characteristics of copper and optical fibre cabling for acceptance, compliance and reference testing.....	97
Table C.1 – Group P.....	100
Table C.2 – Group A.....	101
Table C.3 – Group B.....	102
Table C.4 – Group C.....	103

Table C.5 – Group D .....	103
Table F.1 – Applications using balanced cabling .....	108
Table F.2 – Modular connector pin assignment for applications.....	109
Table F.3 – Supported applications using optical fibre cabling.....	110
Table F.4 – Maximum channel lengths supported by optical fibre applications for multimode fibre .....	111
Table F.5 – Maximum channel length supported by optical fibre applications for single-mode fibres .....	112
Table G.1 – Insertion loss deviation. ....	114
Table H.1 – ACR and PS ACR values for 2 connection class F channels and permanent links at key frequencies .....	124
Table I.1 – Principal transmission performance requirements of 150 $\Omega$ connecting hardware.....	126
Table I.2 – Minimum return loss limits for links, permanent links and channels for the different cabling classes.....	128
Table I.3 – Maximum attenuation limits for links, permanent links and channels for the different cabling classes.....	128
Table I.4 – Minimum NEXT limits for links, permanent links and channels for the different cabling classes.....	129
Table I.5 – Minimum ACR limits for links, permanent links and channels for the different cabling classes.....	129
Table I.6 – Maximum propagation delay limits for links, permanent links and channels for the different cabling classes.....	130
Table I.7 – Maximum d.c. loop resistance limits for links, permanent links and channels for the different cabling classes.....	130
Table I.8 – Minimum unbalance attenuation (LCL/LCTL) limits for links, permanent links and channels for the different cabling classes .....	130
Table I.9 – Minimum PS NEXT, PS ACR, ELFEXT and PS ELFEXT limits for permanent links and channels for the different cabling classes.....	131
Table I.10 – Maximum delay skew limits for permanent links and channels for the different cabling classes.....	131