

ISO/IEC 10589:2002-11 (E)

Information technology - Telecommunications and information exchange between systems -
Intermediate system to intermediate system intra-domain routing information exchange protocol for
use in conjunction with the protocol for providing the connectionless-mode network service
(ISO_8473)

Contents

1	Scope	1
2	Normative references	1
3	Definitions	3
3.1	Reference model definitions	3
3.2	Network layer architecture definitions	3
3.3	Network layer addressing definitions	3
3.4	Local area network definitions	3
3.5	Routing framework definitions	3
3.6	Additional definitions	3
4	Symbols and abbreviations	5
4.1	Data units	5
4.2	Protocol data units	5
4.3	Addresses	5
4.4	Miscellaneous	5
5	Typographical conventions	6
6	Overview of the protocol	6
6.1	System types	6
6.2	Subnetwork types	7
6.3	Topologies	7
6.4	Addresses	8
6.5	Functional organisation	8
6.6	Design goals and non-goals	9
6.7	Environmental requirements	11
6.8	Functional organisation of subnetwork independent components	12
7	Subnetwork independent functions	14
7.1	Addresses	15
7.2	Decision process	18
7.3	Update process	26
7.4	Forwarding process	45
7.5	Routing constants and parameters	48
8	Subnetwork dependent functions	49
8.1	Multi-destination circuits on ISs at a domain boundary	49
8.2	Point-to-point subnetworks	50
8.3	ISO 8208 subnetworks	54
8.4	Broadcast subnetworks	59

9	<i>Structure and encoding of PDUs</i>	65
9.1	General encoding rules	65
9.2	Encoding of network layer addresses	65
9.3	Encoding of SNPA addresses	65
9.4	PDU types	66
9.5	Level 1 LAN IS to IS hello PDU	66
9.6	Level 2 LAN IS to IS hello PDU	69
9.7	Point-to-point IS to IS hello PDU	72
9.8	Level 1 link state PDU	75
9.9	Level 2 link state PDU	79
9.10	Level 1 complete sequence numbers PDU	84
9.11	Level 2 complete sequence numbers PDU	86
9.12	Level 1 partial sequence numbers PDU	88
9.13	Level 2 partial sequence numbers PDU	90
10	<i>System environment</i>	91
10.1	Generating jitter on timers	91
10.2	Resolution of timers	92
10.3	Requirements on the operation of ISO 9542	93
10.4	Requirements on the operation of ISO 8473	93
11	<i>System management</i>	93
11.1	General	93
--11.2	-- <i>GDMO definition</i>	94
--11.2.1	Common GDMO definitions	94
--11.3	ASN1 modules	127
12	<i>Conformance</i>	129
12.1	Conformance for protocol implementation	129
12.1.2	Dynamic conformance	131
12.2	Conformance for management information implementation	133
Annex A		135
A.1	Introduction	135
A.2	Abbreviations and special symbols	135
A.3	Instructions for completing the pics pro formas	135
A.4	Identification	138
A.5	Protocol summary: ISO 10589 general	139
A.6	Protocol summary: ISO 10589 level 1 specific functions	143
A.7	Protocol summary: ISO 10589 level 2 specific functions	144

<i>Annex B</i>	146
B.1 Addressing and routing	146
B.2 Use of the area address field in intra-domain routing	148
<i>Annex C</i>	150
C.1 Routing databases	150
C.3 Forwarding process	156
<i>Annex D</i>	158
D.1 Congestion control	158
D.2 Congestion avoidance	159
<i>Annex E</i>	160
--E.1 Generic managed object class definitions	160
--E.2 ASN.1 definitions	167
<i>Annex F</i>	169
<i>Annex G</i>	170
G.1 Introduction	170
G.2 Identification of the implementation	171
G.3 Identification of the International Standard in which the management information is defined	171
<i>Annex H</i>	175
H.1 Introduction	175
H.2 Instructions for completing the MICS proforma to produce a MICS	175
H.3 Symbols, abbreviates and terms	175
H.4 Statement of Conformance to the management information	175
<i>Annex I</i>	182
I.1 Introduction	182
I.2 Adjacency managed object	182
I.3 Virtual adjacency managed object	185
I.4 Destination system managed object	187
I.5 Destination area managed object	188
I.6 reachableAddress [“ISO/IEC 10589”]	190
<i>Annex J</i>	195
J.1 Introduction	195
J.2 Instructions for completing the MRCS proforma for name binding to produce a MRCS	195
J.3 Statement of conformance to the name binding	195
<i>Index</i>	197