

# ISO/IEC 13873:2003-04 (E)

Information technology — Telecommunications and information exchange between systems —  
Private Integrated Services Network — Inter-exchange signalling protocol —  
Call Diversion supplementary services

---

## Contents

|   |    |
|---|----|
| Foreword  | v  |
| Introduction                                    | vi |
| 1 Scope   | 1  |
| 2 Conformance                                   | 1  |
| 3 Normative references                          | 1  |
| 4 Terms and definitions                         | 2  |
| 4.1 External definitions                        | 2  |
| 4.2 Other definitions                           | 3  |
| 4.2.1 Activating PINX                           | 3  |
| 4.2.2 Busy                                      | 3  |
| 4.2.3 Connected number                          | 3  |
| 4.2.4 Deactivating PINX                         | 3  |
| 4.2.5 Diversion                                 | 3  |
| 4.2.6 Diverted-to number                        | 3  |
| 4.2.7 Diverted-to PINX                          | 3  |
| 4.2.8 Diverted-to user                          | 3  |
| 4.2.9 Diverting cause                           | 3  |
| 4.2.10 Diverting number                         | 3  |
| 4.2.11 Forwarding                               | 3  |
| 4.2.12 Forward switching                        | 3  |
| 4.2.13 Interrogating PINX                       | 3  |
| 4.2.14 Last diverting user                      | 3  |
| 4.2.15 Original called number                   | 3  |
| 4.2.16 Original called user                     | 3  |
| 4.2.17 Partial rerouteing                       | 4  |
| 4.2.18 Presentation indicator                   | 4  |
| 4.2.19 Rerouteing                               | 4  |
| 4.2.20 Rerouteing PINX                          | 4  |
| 4.2.21 Served user                              | 4  |
| 4.2.22 User A                                   | 4  |
| 4.2.23 User B                                   | 4  |
| 4.2.24 User B1, user B2, user B3, etc.          | 4  |
| 4.2.25 User C                                   | 4  |
| 5 Acronyms                                      | 4  |
| 6 Signalling protocol for the support of SS-DIV | 5  |
| 6.1 SS-DIV description                          | 5  |
| 6.2 SS-DIV operational requirements             | 5  |
| 6.2.1 Provision/withdrawal                      | 5  |
| 6.2.2 Requirements on the Originating PINX      | 6  |
| 6.2.3 Requirements on the Served User PINX      | 6  |
| 6.2.4 Requirements on the Diverted-to PINX      | 6  |
| 6.2.5 Requirements on the Rerouteing PINX       | 6  |
| 6.2.6 Requirements on a Transit PINX            | 6  |
| 6.2.7 Requirements on the Activating PINX       | 7  |
| 6.2.8 Requirements on the Deactivating PINX     | 7  |
| 6.2.9 Requirements on the Interrogating PINX    | 7  |

|                |  |           |
|----------------|--|-----------|
| <b>6.3</b>     | <b>SS-DIV coding requirements</b>  |           |
| <b>6.3.1</b>   | <b>Operations</b>  |           |
| <b>6.3.2</b>   | <b>Information elements</b>  | <b>14</b> |
| <b>6.3.3</b>   | <b>Messages</b>  | <b>14</b> |
| <b>6.4</b>     | <b>SS-DIV state definitions</b>  | <b>14</b> |
| <b>6.4.1</b>   | <b>States at the Originating PINX</b>  | <b>14</b> |
| <b>6.4.2</b>   | <b>States at the Served User PINX</b>  | <b>14</b> |
| <b>6.4.3</b>   | <b>States at the Diverted-to PINX</b>  | <b>15</b> |
| <b>6.4.4</b>   | <b>States at the Rerouteing PINX</b>   | <b>15</b> |
| <b>6.4.5</b>   | <b>States at the Activating PINX</b>   | <b>15</b> |
| <b>6.4.6</b>   | <b>States at the Deactivating PINX</b>   | <b>15</b> |
| <b>6.4.7</b>   | <b>States at the Interrogating PINX</b>  | <b>15</b> |
| <b>6.5</b>     | <b>SS-DIV Signalling procedures</b>  | <b>15</b> |
| <b>6.5.1</b>   | <b>Actions at the Originating PINX</b>   | <b>15</b> |
| <b>6.5.2</b>   | <b>Actions at a Transit PINX</b>   | <b>16</b> |
| <b>6.5.3</b>   | <b>Actions at the Served User PINX</b>   | <b>16</b> |
| <b>6.5.4</b>   | <b>Actions at the Rerouteing PINX</b>  | <b>19</b> |
| <b>6.5.5</b>   | <b>Actions at the Diverted-to PINX</b>   | <b>21</b> |
| <b>6.5.6</b>   | <b>Actions at the Activating PINX</b>  | <b>21</b> |
| <b>6.5.7</b>   | <b>Actions at the Deactivating PINX</b>  | <b>22</b> |
| <b>6.5.8</b>   | <b>Actions at the Interrogating PINX</b>   | <b>22</b> |
| <b>6.6</b>     | <b>SS-DIV Impact of interworking with public ISDNs</b>                           | <b>22</b> |
| <b>6.6.1</b>   | <b>Impact of interworking on incoming calls</b>                                  | <b>23</b> |
| <b>6.6.2</b>   | <b>Impact of interworking on outgoing calls</b>                                  | <b>23</b> |
| <b>6.7</b>     | <b>SS-DIV Impact of interworking with non-ISDNs</b>                              | <b>23</b> |
| <b>6.7.1</b>   | <b>Impact of interworking on incoming calls</b>                                  | <b>23</b> |
| <b>6.7.2</b>   | <b>Impact of interworking on outgoing calls</b>                                  | <b>24</b> |
| <b>6.8</b>     | <b>Protocol interactions between SS-DIV and other SSs and ANFs</b>               | <b>24</b> |
| <b>6.8.1</b>   | <b>Protocol interactions of Call Forwarding Unconditional (SS-CFU)</b>           | <b>24</b> |
| <b>6.8.2</b>   | <b>Protocol interactions of Call Forwarding Busy (SS-CFB)</b>                    | <b>25</b> |
| <b>6.8.3</b>   | <b>Protocol interactions of Call Forwarding No Reply (SS-CFNR)</b>               | <b>26</b> |
| <b>6.8.4</b>   | <b>Protocol interactions of Call Deflection (SS-CD)</b>                          | <b>28</b> |
| <b>6.9</b>     | <b>SS-DIV parameter values (timers)</b>  | <b>28</b> |
| <b>6.9.1</b>   | <b>Timer T1</b>  | <b>28</b> |
| <b>6.9.2</b>   | <b>Timer T2</b>  | <b>28</b> |
| <b>6.9.3</b>   | <b>Timer T3</b>  | <b>28</b> |
| <b>6.9.4</b>   | <b>Timer T4</b>  | <b>28</b> |
| <b>6.9.5</b>   | <b>Timer T5</b>  | <b>28</b> |
| <b>Annexes</b> |  |           |
| <b>A</b>       | <b>Protocol Implementation Conformance Statement (PICS) proforma</b>             | <b>29</b> |
| <b>B</b>       | <b>Imported ASN.1 definitions</b>  | <b>40</b> |
| <b>C</b>       | <b>Specification and Description Language (SDL) representation of procedures</b> | <b>41</b> |
| <b>D</b>       | <b>Examples of message sequences</b>   | <b>55</b> |
| <b>E</b>       | <b>Bibliography</b>  | <b>67</b> |
| <b>F</b>       | <b>ASN.1 definitions according to ITU-T Recs. X.208 / X.209</b>                  | <b>68</b> |