

# ISO/IEC 14846:2003-04 (E)

Information technology — Telecommunications and information exchange between systems —  
Private Integrated Services Network — Inter-exchange signalling protocol —  
Call Intrusion supplementary service

---

## Contents

Foreword	v
Introduction	vi
<b>1</b> Scope	<b>1</b>
<b>2</b> Conformance	<b>1</b>
<b>3</b> Normative references	<b>1</b>
<b>4</b> Terms and definitions	<b>2</b>
<b>4.1</b> External definitions	<b>2</b>
<b>4.2</b> Other definitions	<b>3</b>
<b>4.2.1</b> Busy	<b>3</b>
<b>4.2.2</b> Conference type connection	<b>3</b>
<b>4.2.3</b> Impending intrusion warning notification	<b>3</b>
<b>4.2.4</b> Isolation	<b>3</b>
<b>4.2.5</b> Path retention	<b>3</b>
<b>4.2.6</b> Served User PINX	<b>3</b>
<b>4.2.7</b> Wanted user	<b>3</b>
<b>4.2.8</b> Unwanted user	<b>3</b>
<b>4.2.9</b> Unwanted User PINX	<b>3</b>
<b>4.2.10</b> Wait on busy	<b>3</b>
<b>5</b> Acronyms	<b>3</b>
<b>6</b> Signalling protocol for the support of SS-CI	<b>4</b>
<b>6.1</b> SS-CI description	<b>4</b>
<b>6.2</b> SS-CI operational requirements	<b>4</b>
<b>6.2.1</b> Requirements on an Originating PINX	<b>4</b>
<b>6.2.2</b> Requirements on a Terminating PINX	<b>4</b>
<b>6.2.3</b> Requirements on a Transit PINX	<b>4</b>
<b>6.2.4</b> Requirements on an Unwanted User PINX	<b>4</b>
<b>6.3</b> SS-CI coding requirements	<b>5</b>
<b>6.3.1</b> Operations	<b>5</b>
<b>6.3.2</b> Notifications	<b>8</b>
<b>6.3.3</b> Information elements	<b>8</b>
<b>6.3.4</b> Messages	<b>9</b>
<b>6.4</b> SS-CI state definitions	<b>9</b>
<b>6.4.1</b> States at the Originating PINX	<b>9</b>
<b>6.4.2</b> States at the Terminating PINX	<b>9</b>
<b>6.5</b> SS-CI signalling procedures for activation, deactivation and registration	<b>10</b>
<b>6.6</b> SS-CI signalling procedures for invocation and operation	<b>10</b>
<b>6.6.1</b> Actions at the Originating PINX	<b>10</b>
<b>6.6.2</b> Actions at the Terminating PINX	<b>12</b>
<b>6.6.3</b> Actions at the Unwanted User PINX	<b>16</b>
<b>6.6.4</b> Actions at a Transit PINX	<b>16</b>
<b>6.7</b> SS-CI impact of interworking with public ISDNs	<b>16</b>
<b>6.8</b> SS-CI impact of interworking with non-ISDNs	<b>16</b>
<b>6.9</b> Protocol interactions between SS-CI and other supplementary services and ANFs	<b>16</b>

<b>6.9.1</b>	Interaction with Calling Name Identification Presentation (SS-CNIP)	<b>16</b>
<b>6.9.2</b>	Interaction with Connected Name Identification Presentation (SS-CONP)	<b>16</b>
<b>6.9.3</b>	Interaction with Call Completion to Busy Subscriber (SS-CCBS)	<b>17</b>
<b>6.9.4</b>	Interaction with Call Completion on No Reply (SS-CCNR)	<b>17</b>
<b>6.9.5</b>	Interaction with Call Transfer (SS-CT)	<b>17</b>
<b>6.9.6</b>	Interaction with Call Forwarding Unconditional (SS-CFU)	<b>17</b>
<b>6.9.7</b>	Interaction with Call Forwarding Busy (SS-CFB)	<b>17</b>
<b>6.9.8</b>	Interaction with Call Forwarding No Reply (SS-CFNR)	<b>18</b>
<b>6.9.9</b>	Interaction with Call Deflection (SS-CD)	<b>18</b>
<b>6.9.10</b>	Interaction with Path Replacement (ANF-PR)	<b>18</b>
<b>6.9.11</b>	Interaction with Call Offer (SS-CO)	<b>19</b>
<b>6.9.12</b>	Interaction with Do Not Disturb (SS-DND)	<b>19</b>
<b>6.9.13</b>	Interaction with Do Not Disturb Override (SS-DNDO)	<b>19</b>
<b>6.10</b>	SS-CI parameter values (timers)	<b>19</b>
<b>6.10.1</b>	Timer T1	<b>19</b>
<b>6.10.2</b>	Timer T2	<b>20</b>
<b>6.10.3</b>	Timer T3	<b>20</b>
<b>6.10.4</b>	Timer T4	<b>20</b>
<b>6.10.5</b>	Timer T5	<b>20</b>
<b>6.10.6</b>	Timer T6	<b>20</b>
<b>Annexes</b>		
<b>A</b>	- Signalling protocol for the support of Path Retention	<b>21</b>
<b>B</b>	- Protocol Implementation Conformance Statement (PICS) proforma	<b>30</b>
<b>C</b>	- Examples of message sequences	<b>39</b>
<b>D</b>	- Specification and Description Language (SDL) representation of procedures	<b>47</b>
<b>E</b>	- Imported ASN.1 definitions	<b>60</b>
<b>F</b>	- ASN.1 definitions according to ITU-T Recs. X.208 / X.209	<b>61</b>