

# ISO/IEC 15992:2003-04 (E)

Information technology — Telecommunications and information exchange between systems —  
Private Integrated Services Network — Inter-exchange signalling protocol —  
Call Priority Interruption and Call Priority Interruption Protection supplementary services

---

## Contents

Foreword	v
Introduction	vi
1 Scope	1
2 Conformance	1
3 Normative references	1
4 Terms and definitions	2
4.1 External definitions	2
4.2 Called user	3
4.3 Calling user	3
4.4 Call interruption	3
4.5 Call Priority Interruption Capability Level (CPICL)	3
4.6 Call Priority Interruption Protection Level (CPIPL)	3
4.7 Call protection	3
4.8 Established call	3
4.9 Established call user	3
4.10 Established call user's PINX	3
4.11 Forced release	3
4.12 Inter-PINX link	3
4.13 Interrupting PINX	3
4.14 Non-priority call	3
4.15 Priority call	3
4.16 Protected call	3
5 List of acronyms	3
6 Signalling protocol for the support of SS-CPI(P)	4
6.1 SS-CPI(P) description	4
6.2 SS-CPI(P) operational requirements	4
6.2.1 Requirements on the Originating PINX	4
6.2.2 Requirements on the Terminating PINX	4
6.2.3 Requirements on a Transit PINX	4
6.2.4 Requirements on the Interrupting PINX	4
6.2.5 Requirements on the Established call user's PINX	4
6.3 SS-CPI(P) coding requirements	5
6.3.1 Operations	5
6.3.2 Notifications	6
6.3.3 Information elements	6
6.3.4 Messages	7
6.4 SS-CPI state definitions	7
6.4.1 States at the Originating PINX	7
6.4.2 States at the Transit PINX	7
6.4.3 States at the Interrupting PINX	7
6.5 SS-CPIP state definitions	7
6.5.1 States at the Originating PINX	7
6.5.2 States at the Transit PINX	7
6.5.3 States at the Terminating PINX	7

<b>6.6</b>	SS-CPI signalling procedures for activation, deactivation and registration	<b>8</b>
<b>6.7</b>	SS-CPIP signalling procedures for activation, deactivation and registration	<b>8</b>
<b>6.8</b>	SS-CPI signalling procedures for invocation and operation	<b>8</b>
<b>6.8.1</b>	Actions at the Originating PINX	<b>8</b>
<b>6.8.2</b>	Actions at a Transit PINX	<b>8</b>
<b>6.8.3</b>	Actions at the Interrupting PINX	<b>9</b>
<b>6.8.4</b>	Actions at the Terminating PINX	<b>10</b>
<b>6.8.5</b>	Actions at the Established call user's PINX	<b>10</b>
<b>6.9</b>	SS-CPIP signalling procedures for invocation and operation	<b>10</b>
<b>6.9.1</b>	Actions at the Originating PINX	<b>10</b>
<b>6.9.2</b>	Actions at a Transit PINX	<b>10</b>
<b>6.9.3</b>	Actions at the Terminating PINX	<b>11</b>
<b>6.10</b>	SS-CPI impact of interworking with public ISDNs	<b>11</b>
<b>6.11</b>	SS-CPIP impact of interworking with public ISDNs	<b>11</b>
<b>6.12</b>	SS-CPI impact of interworking with non-ISDNs	<b>11</b>
<b>6.13</b>	SS-CPIP impact of interworking with non-ISDNs	<b>12</b>
<b>6.14</b>	Protocol interactions between SS-CPI(P) and other supplementary services and ANFs	<b>12</b>
<b>6.14.1</b>	Interaction with Calling Name Identification Presentation (SS-CNIP)	<b>12</b>
<b>6.14.2</b>	Interaction with Connected Name Identification Presentation (SS-CONP)	<b>12</b>
<b>6.14.3</b>	Interaction with Completion of Call to Busy Subscriber (SS-CCBS)	<b>12</b>
<b>6.14.4</b>	Interaction with Completion of Call on No Reply (SS-CCNR)	<b>12</b>
<b>6.14.5</b>	Interaction with Call Transfer (SS-CT)	<b>12</b>
<b>6.14.6</b>	Interaction with Call Forwarding Unconditional (SS-CFU)	<b>12</b>
<b>6.14.7</b>	Interaction with Call Forwarding Busy (SS-CFB)	<b>13</b>
<b>6.14.8</b>	Interaction with Call Forwarding No Reply (SS-CFNR)	<b>13</b>
<b>6.14.9</b>	Interaction with Call Deflection (SS-CD)	<b>13</b>
<b>6.14.10</b>	Interaction with Path Replacement (ANF-PR)	<b>13</b>
<b>6.14.11</b>	Interaction with Call Offer (SS-CO)	<b>13</b>
<b>6.14.12</b>	Interaction with Call Intrusion (SS-CI)	<b>13</b>
<b>6.14.13</b>	Interaction with Do not Disturb (SS-DND)	<b>13</b>
<b>6.14.14</b>	Interaction with Do not Disturb Override (SS-DNDO)	<b>13</b>
<b>6.14.15</b>	Interaction with Advice of Charge (SS-AOC)	<b>13</b>
<b>6.14.16</b>	Interaction with Recall (SS-RE)	<b>13</b>
<b>6.14.17</b>	Interaction with Call Interception (ANF-CINT)	<b>13</b>
<b>6.14.18</b>	Interaction with Transit Counter (ANF-TC)	<b>13</b>
<b>6.14.19</b>	Interaction with Wireless Terminal Location Registration (SS-WTLR)	<b>14</b>
<b>6.14.20</b>	Interaction with Wireless Terminal Incoming Call (ANF-WTMI)	<b>14</b>
<b>6.14.21</b>	Interaction with Wireless Terminal Outgoing Call (ANF-WTMO)	<b>14</b>
<b>6.14.22</b>	Interaction with Wireless Terminal Authentication of a WTM user (SS-WTAT)	<b>14</b>
<b>6.14.23</b>	Interaction with Wireless Terminal Authentication of a PISN (SS-WTAN)	<b>14</b>
<b>6.14.24</b>	Interaction with Message Waiting Indication (SS-MWI)	<b>14</b>
<b>6.14.25</b>	Interaction with Common Information (ANF-CMN)	<b>14</b>
<b>6.15</b>	SS-CPI parameter values (timers)	<b>14</b>
<b>6.15.1</b>	Timer T1	<b>14</b>
<b>Annexes</b>		
<b>A</b>	Protocol Implementation Conformance Statement (PICS) proforma	<b>15</b>
<b>B</b>	Examples of message sequences	<b>23</b>
<b>C</b>	Specification and Description Language (SDL) representation of procedures	<b>28</b>
<b>D</b>	ASN.1 definitions according to ITU-T Recs. X.208 / X.209	<b>36</b>