ISO/IEC 23651:2003-08 (E)

Information technology — 8 mm wide magnetic tape cartridge for information interchange — Helical scan recording — AIT-3 format

Contents

Section 1 - General **1**

1 Scope **1**

2 Conformance **1**
2.1 Magnetic tape cartridge **1**
2.2 Generating drive **1**
2.3 Receiving drive **1**

3 Normative references **2**

4 Terms and definitions **2**
4.1 Absolute Frame Number (AFN) **2**
4.2 a.c. erase **2**
4.3 Access **2**
4.4 algorithm **2**
4.5 Area ID **2**
4.6 Automatic Track Finding (ATF) **2**
4.7 Average Signal Amplitude **2**
4.8 azimuth **2**
4.9 back surface **2**
4.10 byte **2**
4.11 cartridge **2**
4.12 Channel bit **3**
4.13 Codeword **3**
4.14 Early Warning Point (EWP) **3**
4.15 End of Data (EOD) **3**
4.16 Entity **3**
4.17 Error Correcting Code (ECC) **3**
4.18 flux transition position **3**
4.19 flux transition spacing **3**
4.20 Frame **3**
4.21 Housekeeping Frame **3**
4.22 Logical Beginning of Tape (LBOT) **3**
4.23 magnetic tape **3**
4.24 Master Standard Amplitude Calibration Tape **3**
4.25 Master Standard Reference Tape **3**
4.26 Partition Boundary **3**
4.27 Physical Beginning of Tape (PBOT) **3**
4.28 Physical End of Tape (PEOT) **4**
4.29 physical recording density **4**
4.30 pre-recording condition **4**
4.31 processing **4**
4.32 processed data **4**
4.33 Processed Record **4**
4.34 record **4**
4.35 Reference Field **4**
4.36 Remote Memory In Cartridge (RMIC) **4**
4.37 Secondary Standard Amplitude Calibration Tape **4**
4.38 Secondary Standard Reference Tape **4**

4.39 Separator Mark **4**
4.40 Standard Reference Amplitude (SRA) **4**
4.41 Standard Reference Current **4**
4.42 Tape Reference Edge **4**
4.43 Test Recording Current **4**
4.44 track **5**
4.45 Typical Field **5**
4.46 unprocessed data **5**
4.47 Unprocessed Record **5**

5 Conventions and Notations **5**
5.1 Representation of numbers **5**
5.2 Names **5**

6 Acronyms **5**

7 Environment and safety **6**
7.1 Test environment **6**
7.2 Operating environment **6**
7.3 Storage environment **6**
7.4 Transportation **6**
7.5 Safety **6**
7.6 Flammability **6**

Section 2 - Requirements for the case **6**

8 Dimensional and mechanical characteristics of the case **6**
8.1 General **6**
8.2 Overall dimension **7**
8.3 Holding areas **7**
8.4 Cartridge insertion **8**
8.5 Window **8**
8.6 Loading grips **9**
8.7 Label areas **9**
8.8 Datum areas and Datum holes **9**
8.9 Support areas **10**
8.10 Recognition holes **10**
8.11 Write-inhibit hole **11**
8.12 Pre-positioning surfaces **12**
8.13 Cartridge lid **12**
8.14 Cartridge reel lock **13**
8.15 Reel access holes **14**
8.16 Interface between the reels and the drive spindles **14**
8.17 Light path **15**
8.18 Position of the tape in the case **16**
8.19 Tape path zone **16**
8.20 Tape access cavity **16**
8.21 Tape access cavity clearance **17**
8.22 Requirements for the RMIC **17**
8.23 Recognition recesses **18**

Section 3 - Requirements for the unrecorded tape **38**

9 Mechanical, physical and dimensional characteristics of the tape **38**
9.1 Materials **38**
9.2 Tape length **38**

9.2.1 Length of magnetic tape **38**
9.2.2 Length of leader and trailer tapes **38**
9.2.3 Length of the splicing tapes **38**
9.3 Tape width **38**
9.3.1 Width of magnetic, leader and trailer tapes **38**
9.3.2 Width and position of the splicing tape **38**
9.4 Discontinuities **39**
9.5 Tape thickness **39**
9.5.1 Thickness of the magnetic tape **39**
9.5.2 Thickness of the leader and trailer tape **39**
9.5.3 Thickness of the splicing tape **39**
9.6 Longitudinal curvature **39**
9.7 Cupping **39**
9.8 Coating adhesion **39**
9.9 Layer-to-layer adhesion **40**
9.10 Tensile strength **40**
9.10.1 Breaking strength **40**
9.10.2 Yield strength **40**
9.11 Residual elongation **40**
9.12 Electrical resistance of the recording surface **40**
9.13 Tape winding **41**
9.14 Light transmittance of the tape **41**
9.15 Recognition stripe **41**

10 Magnetic recording characteristics **42**
10.1 Typical Field **42**
10.2 Signal Amplitude **42**
10.3 Resolution **43**
10.4 Overwrite **43**
10.5 Ease of erasure **43**
10.6 Tape quality **43**
10.6.1 Missing pulses **43**
10.6.2 Missing pulse zone **43**
10.7 Signal-to-Noise Ratio (SNR) characteristic **43**

Section 4 - Requirements for an interchanged tape **44**

11 Format **44**
11.1 General **44**
11.2 Basic Groups **44**
11.2.1 Entity **45**
11.2.2 Group Information Table **45**
11.2.3 Block Access Table (BAT) **48**
11.3 Sub-Groups **50**
11.3.1 G1 Sub-Group **50**
11.3.2 G2 Sub-Group - Randomizing **51**
11.3.3 G3 Sub-Group **52**
11.4 Data Block **53**
11.4.1 ID information **53**
11.4.2 Recording of the ID Information in the Data Block Headers **56**

12 Method of recording **61**
12.1 Physical recording density **62**
12.2 Long-term average bit cell length **62**
12.3 Short-term average bit cell length **62**
12.4 Rate of change **62**

12.5 Bit shift **62**
12.6 Read signal amplitude **62**
12.7 Maximum recorded levels **62**

13 Track geometry **62**
13.1 Track configuration **62**
13.2 Average track pitch **63**
13.3 Variations of the track pitch **63**
13.4 Track width **63**
13.5 Track angle **63**
13.6 Track edge straightness **63**
13.7 Track length **63**
13.8 Azimuth angles **63**

14 Recorded patterns **64**
14.1 Recorded Data Block **64**

15 Format of tracks **64**
15.1 Track structure **64**
15.2 Positioning accuracy **64**
15.3 Tracking scheme **64**
15.4 Generation of Margin Blocks **65**

16 Layout of the tape **66**
16.1 Device Area **66**
16.2 Reference Area **67**
16.3 Position Tolerance Band No. 1 **67**
16.4 System Area **67**
16.4.1 System Preamble **67**
16.4.2 System Log **67**
16.4.3 System Postamble **72**
16.4.4 Position Tolerance Band No. 2 **72**
16.4.5 Vendor Group Preamble **72**
16.5 Data Area **72**
16.5.1 Vendor Group **72**
16.5.2 Recorded Data Group **72**
16.5.3 ECC3 **73**
16.5.4 Multiple Recorded Instances **74**
16.5.5 Repeated Frames **74**
16.5.6 Appending and overwriting **75**
16.6 EOD Area **76**
16.7 Optional Device Area **76**
16.8 Logical End Of Tape (LEOT) **77**
16.9 Logical Beginning of Tape (LBOT) **77**
16.10 Early Warning Point - EWP **77**
16.11 Empty Partition **77**
16.12 Initialization **77**

17 Housekeeping Frames **78**
17.1 Amble Frames **78**
17.2 System Amble Frames **78**

18 AIT Remote Memory In Cartridge (AIT RMIC) **78**
18.1 General **78**
18.2 Content of the AIT RMIC **78**
18.2.1 Manufacturer's Information Section **79**

18.2.2 Communication Information Section **82**
18.2.3 Mechanism Error Log Information Section **82**
18.2.4 Memory Management Information Section **83**
18.2.5 Volume Information Section **84**
18.2.6 Volume Use History Information Section **85**
18.3 Memory Heap Management **85**
18.3.1 Cell **85**
18.3.2 Cell Header **85**
18.3.3 Partition Information Cell **87**
18.3.4 Physical Tape Directory Information Cell **87**
18.3.5 User Volume Information Cell **88**
18.3.6 User Partition Information Cell **88**
18.3.7 Application Information Cell **89**
18.3.8 Date and Time Stamp Information Cell **90**
18.3.9 Media Identification Information Cell **91**
18.3.10 Tape Alert Information Cell **91**
18.4 Electrical interface **92**
18.5 Environment **92**
18.5.1 Electromagnetic Compatibility **92**
18.5.2 Magnetic fields **92**
18.5.3 X-rays **92**
18.6 Operating Field **92**
18.7 Message from AIT RMIC reader-writer to AIT RMIC **92**
18.8 Message from AIT RMIC to AIT RMIC reader-writer **93**
18.8.1 Load modulation **94**
18.9 EDC **95**
18.10 AIT RMIC states **95**
18.11 Command and Response **96**
18.11.1 Attention Command and Response **97**
18.11.2 Attention Command and Response Type 1 **97**
18.11.3 Attention Command and Response Type 2 **97**
18.11.4 Read Command and Response **98**
18.11.5 Write Command and Response **98**
18.11.6 Status Command and Response **98**
18.11.7 Reset Command and Response **99**
18.12 Dialogue **99**
18.12.1 Read data from AIT RMIC **99**
18.12.2 Write data to AIT RMIC **100**
18.12.3 Read and Write with Session ID **101**

Annexes

A (normative) - Measurement of light transmittance 105

B (normative) - Measurement of Signal-to-Noise Ratio 108

C (normative) - Method for determining the nominal and the maximum allowable recorded levels (pre-recording condition) 109

D (normative) - Representation of 16-bit words by 18-Channel bits patterns 110

E (normative) - Measurement of bit shift 111

F (normative) - Method of measuring the straightness of track edges 113

G (normative) - ECC calculation 114

H (informative) - Recommendations for transportation 117

J (informative) - Read-After-Write 118

K (informative) - Basic Group No. 0 119

L (informative) - Chip for the AIT-3 format 120

M (informative) - Generation of EDC bytes for the Error Detecting Code for G2 Sub-Groups 121