ISO/IEC TR 20943-3:2004-03 (E)

Information technology - Procedures for achieving metadata registry content consistency - Part 3: Value domains

Contents

Page

Foreword iv

Introduction v

1 Scope 1
1.1 Background 1
1.2 Purpose 1
1.3 Limits of this Technical Report 1
1.4 Registration approach -- value domains and data elements 1

2 Normative references 1

3 Terms and definitions 2

4 Understanding value domains 2
4.1 Introduction 2
4.2 General principles 3
4.2.1 Introduction 3
4.2.2 Choice of codes 4
4.2.3 Number of permissible values 4
4.2.4 Conceptual domain hierarchies 4
4.2.5 Sharing value meanings across permissible values 5
4.2.6 Sharing value domains across data elements 5
4.2.7 Associating value domains with concepts (data element concepts and conceptual domains) 5
4.2.8 Value domains not associated with data elements 6
4.2.9 Contrasting conceptual domains and data element concepts 6
4.2.10 Non-enumerated value domains 6
4.2.11 Value domains with enumerated and non-enumerated components 7
4.2.12 Semantic restriction of use of value domains 8
4.2.13 Rapidly changing enumerated value domains (UPC example) 8
4.3 Structure in value domains 9
4.3.1 Introduction 9
4.3.2 International Standard Industrial Classification (ISIC) 9
4.3.3 Logical Observation Identifiers Names and Codes (LOINC) 11
4.4 Code sets as value domains 12
4.5 Classification schemes as value domains 13
4.6 Data types and value domains 15
4.6.1 Basics 15
4.6.2 Value domains with more than one data type -- limitations of value meaning 15
4.7 Units of measure 16
4.8 Dimensionality 18
4.9 Classifying value domains 19

5 Registering value domains 20
5.1 Introduction 20
5.2 Rules for registering value domains 20
5.3 Strategies 23
5.4 Examples 23
5.4.1 Enumerated value domain 24
5.4.2 Non-enumerated value domain 30

Annex A Metamodel for value domains and conceptual domains 33

Bibliography 35